

Products				
PlotID	Length	Product	Plies	Net Qty
J1	10-00-00	9 1/2" NI-40x	1	6
J2	18-00-00	11 7/8" NI-40x	1	15
J3DJ	18-00-00	11 7/8" NI-40x	2	2
J3	14-00-00	11 7/8" NI-40x	1	3
J4	12-00-00	11 7/8" NI-40x	1	4
J5	10-00-00	11 7/8" NI-40x	1	5
J6	6-00-00	11 7/8" NI-40x	1	3
J7	2-00-00	11 7/8" NI-40x	1	4
B1	18-00-00	1-3/4" x 11-7/8" VERSA-LAM@ 2.0 3100 SP	2	2
B2	12-00-00	1-3/4" x 11-7/8" VERSA-LAM@ 2.0 3100 SP	1	1
B4	10-00-00	1-3/4" x 11-7/8" VERSA-LAM@ 2.0 3100 SP	1	1
B3	6-00-00	1-3/4" x 11-7/8" VERSA-LAM@ 2.0 3100 SP	1	1
B5	4-00-00	1-3/4" x 11-7/8" VERSA-LAM@ 2.0 3100 SP	1	1


Connector Summary		
Qty	Manuf	Product
10	H1	IUS2.56/11.88
4	H1	IUS2.56/11.88
2	H2	HUS1.81/10
1	H2	HUS1.81/10

TOWN OF BRADFORD WEST GWILLIMBURY
BUILDING DEPARTMENT
PLANS EXAMINED
ONTARIO BUILDING CODE APPLIES
DATE: 04/19/2024
INSPECTOR: BG

REVIEWED

DATE: 2021-11-09

1st FLOOR




FROM PLAN DATED: 2021/10
BUILDER: BAYVIEW WELLINGTON
SITE: GREEN VALLEY EAST
MODEL: TH-1 NAPA 1
ELEVATION: A
LOT:
CITY: BRADFORD
SALESMAN: RICK DICIANO
DESIGNER: AJ
REVISION:

NOTES:
REFER TO THE **NORDIC INSTALLATION** GUIDE FOR PROPER STORAGE AND INSTALLATION.
SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F REQ'D UNDER INTERIOR UNIFORM LOAD BEARING WALLS. **MULTIPLE SQUASH BLOCKS** REQ'D UNDER CONCENTRATED LOADS. SEE FIGURE 1. **CANTILEVERED JOISTS** INCLUDING CANT' OVER BRICK REQ. I-JOIST BLOCKING ALONG BEARING AND RIMBOARD CLOSURE AT ENDS. SEE FIGURES 4 & 5 FOR REINFORCEMENT REQUIREMENTS. FOR **HOLES** INCLUDING **DUCT CHASE** AND **FIELD CUT OPENINGS** SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE** APPLICATION AS PER O.B.C 9.30.6.

LOADING:
DESIGN LOADS: L/480.000
LIVE LOAD: 40.0 lb/ft²
DEAD LOAD: 15.0 lb/ft²
TILE LOAD: 20.0 lb/ft²

SUBFLOOR: 3/4" GLUED AND NAILED




Products				
PlotID	Length	Product	Plies	Net Qty
J1	10-00-00	9 1/2" NI-40x	1	6
J2	8-00-00	9 1/2" NI-40x	1	4
J3	18-00-00	11 7/8" NI-40x	1	20
J3DJ	18-00-00	11 7/8" NI-40x	2	2
J4	16-00-00	11 7/8" NI-40x	1	3
J5	10-00-00	11 7/8" NI-40x	1	5
J6	8-00-00	11 7/8" NI-40x	1	1
J7	6-00-00	11 7/8" NI-40x	1	7
J8	2-00-00	11 7/8" NI-40x	1	4
B7L	8-00-00	1-3/4" x 9-1/2" VERSA-LAM® 2.0 3100 SP	1	1
B8L	6-00-00	1-3/4" x 9-1/2" VERSA-LAM® 2.0 3100 SP	1	1
B1	18-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B2	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B4	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B3	6-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B6	6-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B5	4-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1

Connector Summary		
Qty	Manuf	Product
14	H1	IUS2.56/11.88
4	H1	IUS2.56/11.88
2	H2	HUS1.81/10
1	H2	HUS1.81/10
3	H9	IUS2.56/9.5

REVIEWED

DATE: 2021-11-17

1st FLOOR SUNKEN



FROM PLAN DATED: 2021/10

BUILDER: BAYVIEW WELLINGTON

SITE: GREEN VALLEY EAST

MODEL: TH-1 NAPA 1

ELEVATION: A

LOT:

CITY: BRADFORD

SALESMAN: RICK DICIANO


DESIGNER: AJ

REVISION:

NOTES:
REFER TO THE **NORDIC INSTALLATION** GUIDE FOR PROPER STORAGE AND INSTALLATION.
SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F REQ'D UNDER INTERIOR UNIFORM LOAD BEARING WALLS. **MULTIPLE SQUASH BLOCKS** REQ'D UNDER CONCENTRATED LOADS. SEE FIGURE 1. **CANTILEVERED JOISTS** INCLUDING **CANT' OVER BRICK** REQ. I-JOIST BLOCKING ALONG BEARING AND RIMBOARD CLOSURE AT ENDS. SEE FIGURES 4 & 5 FOR REINFORCEMENT REQUIREMENTS. FOR **HOLES** INCLUDING **DUCT CHASE** AND **FIELD CUT OPENINGS** SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE** APPLICATION AS PER O.B.C 9.30.6.

LOADING:
DESIGN LOADS: L/480.000
LIVE LOAD: 40.0 lb/ft²
DEAD LOAD: 15.0 lb/ft²
TILE LOAD: 20.0 lb/ft²

SUBFLOOR: 3/4" GLUED AND NAILED




Products				
PlotID	Length	Product	Plies	Net Qty
J1	10-00-00	9 1/2" NI-40x	1	6
J2	18-00-00	11 7/8" NI-40x	1	20
J3DJ	18-00-00	11 7/8" NI-40x	2	2
J3	16-00-00	11 7/8" NI-40x	1	3
J4	12-00-00	11 7/8" NI-40x	1	4
J5	10-00-00	11 7/8" NI-40x	1	5
J6	6-00-00	11 7/8" NI-40x	1	3
J7	2-00-00	11 7/8" NI-40x	1	4
B1	18-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B2	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B4	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B3	6-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B5	4-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1

Connector Summary		
Qty	Manuf	Product
10	H1	IUS2.56/11.88
4	H1	IUS2.56/11.88
2	H2	HUS1.81/10
1	H2	HUS1.81/10

REVIEWED

DATE: 2021-11-17


1st FLOOR



FROM PLAN DATED: 2021/10
BUILDER: BAYVIEW WELLINGTON
SITE: GREEN VALLEY EAST
MODEL: TH-1 NAPA 1
ELEVATION: B
LOT:
CITY: BRADFORD
SALESMAN: RICK DICIANO
DESIGNER: AJ
REVISION:

NOTES:
REFER TO THE **NORDIC INSTALLATION** GUIDE FOR PROPER STORAGE AND INSTALLATION.
SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F REQ'D UNDER INTERIOR UNIFORM LOAD BEARING WALLS. **MULTIPLE SQUASH BLOCKS** REQ'D UNDER CONCENTRATED LOADS. SEE FIGURE 1. **CANTILEVERED JOISTS** INCLUDING **CANT' OVER BRICK** REQ. I-JOIST BLOCKING ALONG BEARING AND RIMBOARD CLOSURE AT ENDS. SEE FIGURES 4 & 5 FOR REINFORCEMENT REQUIREMENTS. FOR **HOLES** INCLUDING **DUCT CHASE** AND **FIELD CUT OPENINGS** SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE** APPLICATION AS PER O.B.C 9.30.6.

LOADING:
DESIGN LOADS: L/480.000
LIVE LOAD: 40.0 lb/ft²
DEAD LOAD: 15.0 lb/ft²
TILE LOAD: 20.0 lb/ft²
SUBFLOOR: 3/4" GLUED AND NAILED




Products				
PlotID	Length	Product	Plies	Net Qty
J1	10-00-00	9 1/2" NI-40x	1	6
J2	8-00-00	9 1/2" NI-40x	1	4
J3	18-00-00	11 7/8" NI-40x	1	20
J3DJ	18-00-00	11 7/8" NI-40x	2	2
J4	16-00-00	11 7/8" NI-40x	1	3
J5	10-00-00	11 7/8" NI-40x	1	5
J6	8-00-00	11 7/8" NI-40x	1	1
J7	6-00-00	11 7/8" NI-40x	1	7
J8	2-00-00	11 7/8" NI-40x	1	4
B7L	8-00-00	1-3/4" x 9-1/2" VERSA-LAM® 2.0 3100 SP	1	1
B8L	6-00-00	1-3/4" x 9-1/2" VERSA-LAM® 2.0 3100 SP	1	1
B1	18-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B2	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B4	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B3	6-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B6	6-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B5	4-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1

Connector Summary		
Qty	Manuf	Product
14	H1	IUS2.56/11.88
4	H1	IUS2.56/11.88
2	H2	HUS1.81/10
1	H2	HUS1.81/10
3	H9	IUS2.56/9.5

REVIEWED

DATE: 2021-11-17

1st FLOOR SUNKEN



FROM PLAN DATED: 2021/10

BUILDER: BAYVIEW WELLINGTON

SITE: GREEN VALLEY EAST

MODEL: TH-1 NAPA 1

ELEVATION: B

LOT:

CITY: BRADFORD

SALESMAN: RICK DICIANO

DESIGNER: AJ

REVISION:

NOTES:

REFER TO THE **NORDIC INSTALLATION**
GUIDE FOR PROPER STORAGE AND
INSTALLATION.

SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F. REQ'D UNDER INTERIOR UNIFORM LOAD BEARING WALLS. **MULTIPLE SQUASH BLOCKS** REQ'D UNDER CONCENTRATED LOADS. SEE FIGURE 1. **CANTILEVERED JOISTS** INCLUDING **CANT' OVER BRICK** REQ. I-JOIST BLOCKING ALONG BEARING AND RIMBOARD CLOSURE AT ENDS. SEE FIGURES 4 & 5 FOR REINFORCEMENT REQUIREMENTS. FOR **HOLES** INCLUDING **DUCT CHASE** AND **FIELD CUT OPENINGS** SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE** APPLICATION AS PER O.B.C 9.30.6.


LOADING:

DESIGN LOADS: L/480.000

LIVE LOAD: 40.0 lb/ft²

DEAD LOAD: 15.0 lb/ft²TILE LOAD: 20.0 lb/ft²

SUBFLOOR: 3/4" GLUED AND NAILED




Products				
PlotID	Length	Product	Plies	Net Qty
J1	20-00-00	11 7/8" NI-40x	1	21
J2	14-00-00	11 7/8" NI-40x	1	6
J3	12-00-00	11 7/8" NI-40x	1	11
J4	10-00-00	11 7/8" NI-40x	1	11
J5	4-00-00	11 7/8" NI-40x	1	4
B11	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B12	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B9	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B17	14-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B16	14-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B13	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B14	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B10	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B15	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2

Connector Summary		
Qty	Manuf	Product
10	H1	IUS2.56/11.88
2	H2	HUS1.81/10
7	H4C	HUC412
1	H2.5A	H2.5A*

REVIEWED

DATE: 2021-12-02

2ND FLOOR




FROM PLAN DATED: 2021/10
BUILDER: BAYVIEW WELLINGTON
SITE: GREEN VALLEY EAST
MODEL: TH-1 NAPA 1
ELEVATION: A
LOT:
CITY: BRADFORD
SALESMAN: RICK DICIANO
DESIGNER: AJ
REVISION:

NOTES:
REFER TO THE **NORDIC INSTALLATION** GUIDE FOR PROPER STORAGE AND INSTALLATION.
SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F REQ'D UNDER INTERIOR UNIFORM LOAD BEARING WALLS. **MULTIPLE SQUASH BLOCKS** REQ'D UNDER CONCENTRATED LOADS. SEE FIGURE 1. **CANTILEVERED JOISTS** INCLUDING CANT' OVER BRICK REQ. I-JOIST BLOCKING ALONG BEARING AND RIMBOARD CLOSURE AT ENDS. SEE FIGURES 4 & 5 FOR REINFORCEMENT REQUIREMENTS. FOR **HOLES** INCLUDING **DUCT CHASE** AND **FIELD CUT OPENINGS** SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE** APPLICATION AS PER O.B.C 9.30.6.

LOADING:
DESIGN LOADS: L/480.000
LIVE LOAD: 40.0 lb/ft²
DEAD LOAD: 15.0 lb/ft²
TILE LOAD: 20.0 lb/ft²

SUBFLOOR: 3/4" GLUED AND NAILED




Products				
PlotID	Length	Product	Plies	Net Qty
J1	20-00-00	11 7/8" NI-40x	1	21
J2	14-00-00	11 7/8" NI-40x	1	6
J3	12-00-00	11 7/8" NI-40x	1	11
J4	10-00-00	11 7/8" NI-40x	1	10
J5	8-00-00	11 7/8" NI-40x	1	2
J6	4-00-00	11 7/8" NI-40x	1	5
B11	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B12	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B9	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B17	14-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B16	14-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B13	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B14	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B10	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B15	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B21	2-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2

Connector Summary		
Qty	Manuf	Product
10	H1	IUS2.56/11.88
1	H1	IUS2.56/11.88
2	H2	HUS1.81/10
7	H4C	HUC412
1	H2.5A	H2.5A*

REVIEWED

DATE: 2021-12-02

2ND FLOOR




FROM PLAN DATED: 2021/10
BUILDER: BAYVIEW WELLINGTON
SITE: GREEN VALLEY EAST
MODEL: TH-1 NAPA 1
ELEVATION: B
LOT:
CITY: BRADFORD
SALESMAN: RICK DICIANO
DESIGNER: AJ
REVISION:

NOTES:
REFER TO THE **NORDIC INSTALLATION**
GUIDE FOR PROPER STORAGE AND
INSTALLATION.
SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F
REQ'D UNDER INTERIOR UNIFORM LOAD
BEARING WALLS. **MULTIPLE SQUASH**
BLOCKS REQ'D UNDER CONCENTRATED
LOADS. SEE FIGURE 1. **CANTILEVERED**
JOISTS INCLUDING **CANT' OVER BRICK** REQ.
I-JOIST BLOCKING ALONG BEARING AND
RIMBOARD CLOSURE AT ENDS. SEE
FIGURES 4 & 5 FOR REINFORCEMENT
REQUIREMENTS. FOR **HOLES** INCLUDING
DUCT CHASE AND **FIELD CUT OPENINGS**
SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE**
APPLICATION AS PER O.B.C 9.30.6.


LOADING:
DESIGN LOADS: L/480.000
LIVE LOAD: 40.0 lb/ft²
DEAD LOAD: 15.0 lb/ft²
TILE LOAD: 20.0 lb/ft²

SUBFLOOR: 3/4" GLUED AND NAILED



Products				
PlotID	Length	Product	Plies	Net Qty
J1	20-00-00	11 7/8" NI-40x	1	21
J2	14-00-00	11 7/8" NI-40x	1	6
J3	12-00-00	11 7/8" NI-40x	1	11
J4	10-00-00	11 7/8" NI-40x	1	11
J5	4-00-00	11 7/8" NI-40x	1	4
B11	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B12	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B9	20-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B17	14-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	1	1
B16	14-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B13	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B14	12-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B10	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2
B15	10-00-00	1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP	2	2

Connector Summary		
Qty	Manuf	Product
10	H1	IUS2.56/11.88
2	H2	HUS1.81/10
7	H4C	HUC412
1	H2.5A	H2.5A*



FROM PLAN DATED: 2021/10
BUILDER: BAYVIEW WELLINGTON
SITE: GREEN VALLEY EAST
MODEL: TH-1 NAPA 1
ELEVATION: B MOD
LOT:
CITY: BRADFORD
SALESMAN: RICK DICIANO
DESIGNER: AJ
REVISION:

NOTES:
REFER TO THE **NORDIC INSTALLATION** GUIDE FOR PROPER STORAGE AND INSTALLATION.
SQUASH BLOCKS OF 2x4, 2x6, 2x8 #2 S.P.F REQ'D UNDER INTERIOR UNIFORM LOAD BEARING WALLS. **MULTIPLE SQUASH BLOCKS** REQ'D UNDER CONCENTRATED LOADS. SEE FIGURE 1. **CANTILEVERED JOISTS** INCLUDING **CANT' OVER BRICK** REQ. I-JOIST BLOCKING ALONG BEARING AND RIMBOARD CLOSURE AT ENDS. SEE FIGURES 4 & 5 FOR REINFORCEMENT REQUIREMENTS. FOR **HOLES** INCLUDING **DUCT CHASE** AND **FIELD CUT OPENINGS** SEE FIGURE 7, TABLES 1 & 2. **CERAMIC TILE** APPLICATION AS PER O.B.C 9.30.6.

LOADING:
DESIGN LOADS: L/480.000
LIVE LOAD: 40.0 lb/ft²
DEAD LOAD: 15.0 lb/ft²
TILE LOAD: 20.0 lb/ft²

REVIEWED

DATE: 2021-12-02

2ND FLOOR

SUBFLOOR: 3/4" G11FD AND NAILFD


Design Check Calculation Sheet

Nordic Sizer – Canada 8.0

Loads:

Load	Type	Distribution	Pat-tern	Location [ft] Start End	Magnitude Start End	Unit
Load1	Dead	Full Area			15.00	psf
Load2	Live	Full Area			40.00	psf

Maximum Reactions (lbs) and Support Bearing (in):



Unfactored:			
Dead	170		170
Live	454		454
Factored:			
Total	895		895
Bearing:			
Capacity			
Joist	2336		2102
Support	7735		3981
Des ratio			
Joist	0.38		0.43
Support	0.12		0.22
Load case	#2		#2
Length	4-3/8		2-3/8
Min req'd	1-1/2		1-1/2
Stiffener	No		No
KD	1.00		1.00
KB support	1.00		1.00
fcp sup	769		769
Kzcp sup	1.15		1.09


*Minimum bearing length for joists is 1-1/2" for exterior supports

Nordic Joist 11-7/8" NI-40x Floor joist @ 16" o.c.

Supports: All - Lumber Sill plate, No.1/No.2

Total length: 17' 5-3/4"; Clear span: 16' 11"; 3/4" nailed and glued OSB sheathing

This section **PASSES** the design code check.



106 NO. TAM25900-21

REVIEWED

Limit States Design using CSA O86-14 and Vibration Criterion:

Criterion	Analysis Value	Design Value	Unit	Analysis/Design
Shear	$V_f = 895$	$V_r = 2336$	lbs	$V_f/V_r = 0.38$
Moment(+)	$M_f = 3811$	$M_r = 6255$	lbs-ft	$M_f/M_r = 0.61$
Perm. Defl'n	$0.09 = < L/999$	$0.57 = L/360$	in	0.17
Live Defl'n	$0.25 = L/817$	$0.43 = L/480$	in	0.59
Total Defl'n	$0.34 = L/594$	$0.85 = L/240$	in	0.40
Bare Defl'n	$0.31 = L/659$	$0.57 = L/360$	in	0.55
Vibration	$L_{max} = 17'-0.5$	$L_v = 18'-1.3$	ft	0.94
Defl'n	$= 0.031$	$= 0.037$	in	0.83

Additional Data:

FACTORS:	f/E	KD	KH	KZ	KL	KT	KS	KN	LC#
Vr	2336	1.00	1.00	-	-	-	-	-	#2
Mr+	6255	1.00	1.00	-	1.000	-	-	-	#2
EI	371.1 million	-	-	-	-	-	-	-	#2

CRITICAL LOAD COMBINATIONS:

Shear : LC #2 = 1.25D + 1.5L
 Moment(+) : LC #2 = 1.25D + 1.5L
 Deflection: LC #1 = 1.0D (permanent)
 LC #2 = 1.0D + 1.0L (live)
 LC #2 = 1.0D + 1.0L (total)
 LC #2 = 1.0D + 1.0L (bare joist)

Bearing : Support 1 - LC #2 = 1.25D + 1.5L
 Support 2 - LC #2 = 1.25D + 1.5L

Load Types: D=dead L=live(use, occupancy)

Load Patterns: s=S/2 L=L+Ls _=no pattern load in this span

All Load Combinations (LCs) are listed in the Analysis output

CALCULATIONS:

$EI_{eff} = 459.76 \text{ lb-in}^2$ $K = 6.18e06 \text{ lbs}$ $GA = 0.77e06 \text{ lb}$

"Live" deflection is due to all non-dead loads (live, wind, snow...) **CONFORMS TO CBC 2012**

Design Notes:**AMENDED 2020**

- WoodWorks analysis and design are in accordance with the 2015 National Building Code of Canada (NBC), Division B, Part 4, and the CSA O86-14 Engineering Design in Wood standard, Update No. 2 (June 2017).
- Please verify that the default deflection limits are appropriate for your application.
- Refer to Nordic Structures technical documentation for installation guidelines and construction details.
- Nordic I-joists are listed in CCMC evaluation report 13032-R.
- Joists shall be laterally supported at supports and continuously along the compression edge.
- Allowable vibration-controlled span as per the Concluding Report, Development of Design Procedures for Vibration Controlled Spans using Engineered Wood Members, CWC et al for CCMC, 1997.
- Floor vibration design from the CCMC Concluding Report (1997) on vibration controlled spans for engineered wood products.
- The design assumptions and specifications have been provided by the client. Any damages resulting from faulty or incorrect information, specifications, and/or designs furnished, and the correctness or accuracy of this information is their responsibility. This analysis does not constitute a record of the structural integrity of the building nor suitability of the design assumptions made. Nordic Structures is responsible only for the structural adequacy of this component based on the design criteria and loadings shown.



DWG NO. TAM25900-21

REVIEWED
 STRUCTURAL COMPONENT ONLY

1ST FLR FRAMING\Flush Beams\B1(i452) (Flush Beam)


BC CALC® Member Report
Build 7773
Job name:
Address:
City, Province, Postal Code:
Customer:
Code reports:

Dry | 1 span | No cant.

November 9, 2021 11:10:31

File name: TH-1 EL A.mmdl
Description: 1ST FLR FRAMING\Flush Beams\B1(i452)
Specifier:
Designer:
Company:

CCMC 12472-R



Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 2-3/8"	1160 / 0	709 / 0		
B2, 4-3/8"	492 / 0	359 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	17-05-12	Top		12			00-00-00
1	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	17-05-12	Top	9	5			n/a
2	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	03-07-08	Top	6	3			n/a
3	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	03-07-08	17-05-12	Top	18	9			n/a
4	B2(i449)	Conc. Pt. (lbs)	L	03-08-06	03-08-06	Top	1192	627			n/a
5	B2(i449)	Conc. Pt. (lbs)	L	03-08-06	03-08-06	Top	0				n/a
6	STAIR	Conc. Pt. (lbs)	L	05-05-04	05-05-04	Top	37	18			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	9047 ft-lbs	35392 ft-lbs	25.6%	1	03-08-07
End Shear	2571 lbs	14464 lbs	17.8%	1	01-02-04
Total Load Deflection	L/672 (0.304")	n/a	35.7%	6	07-11-05
Live Load Deflection	L/1104 (0.185")	n/a	32.6%	8	07-11-05
Max Defl.	0.304"	n/a	n/a	6	07-11-05
Span / Depth	17.2				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 2-3/8" x 3-1/2"	2627 lbs	51.4%	25.9%	Spruce-Pine-Fir
B2	Wall/Plate 4-3/8" x 3-1/2"	1186 lbs	12.6%	6.3%	Spruce-Pine-Fir

Notes

Design meets Code minimum (L/240) Total load deflection criteria.
Design meets Code minimum (L/360) Live load deflection criteria.
Resistance Factor phi has been applied to all presented results per CSA O86.
BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.
Design based on Dry Service Condition.
Importance Factor : Normal Part code : Part 9
Calculations assume unbraced length of Top: 00-00-00, Bottom: 13-04-02.

CONFORMS TO OBC 2012

AMENDED 2020



NO. TAM25901-21
STRUCTURAL
COMPONENT ONLY

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports:

CCMC 12472-R

File name: TH-1 EL A.mmdl


Description: 1ST FLR FRAMING\Flush Beams\B1(i452)

Specifier:

Designer:

Company:

Connection Diagram: Full Length of Member



a minimum = 2"
b minimum = 3"


c = 7-7/8"
d = 8"

Connectors are: 1 Nails

3 1/2" ARDOX SPIRAL

Connection Diagrams: Concentrated Side Loads


Connection Tag: A Applies to load tag(s): 4+5



a minimum = 2"
b minimum = 4"
c minimum = 4"
d maximum = 12"
e minimum = 4"

Connectors are: 16d Nails

3 1/2" ARDOX SPIRAL



DWG NO. TAM 25901-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED



BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B2(i449)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:


Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 1-3/4"	675 / 0	369 / 0		
B2, 2"	1198 / 0	630 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	10-03-06	Top		6			00-00-00
1	Smoothed Load	Unf. Lin. (lb/ft)	L	02-02-10	06-02-10	Top	110	55			n/a
2	J7(i447)	Conc. Pt. (lbs)	L	00-04-10	00-04-10	Top	86	43			n/a
3	J7(i460)	Conc. Pt. (lbs)	L	01-06-10	01-06-10	Top	131	66			n/a
4	J5(i307)	Conc. Pt. (lbs)	L	06-11-03	06-11-03	Top	300	150			n/a
5	J5(i307)	Conc. Pt. (lbs)	L	06-11-03	06-11-03	Top	0				n/a
6	J5(i317)	Conc. Pt. (lbs)	L	08-02-10	08-02-10	Top	497	248			n/a
7	J5(i329)	Conc. Pt. (lbs)	L	09-06-10	09-06-10	Top	418	209			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/ Resistance	Case	Location
Pos. Moment	4669 ft-lbs	17696 ft-lbs	26.4%	1	06-11-03
End Shear	2195 lbs	7232 lbs	30.4%	1	09-01-08
Total Load Deflection	L/999 (0.124")	n/a	n/a	6	05-04-09
Live Load Deflection	L/999 (0.081")	n/a	n/a	8	05-04-09
Max Defl.	0.124"	n/a	n/a	6	05-04-09
Span / Depth	10.2				

Bearing Supports

B1	Column	1-3/4" x 1-3/4"	1473 lbs	59.2%	39.4%	Unspecified
B2	Hanger	2" x 1-3/4"	2585 lbs	n/a	60.5%	HUS1.81/10

Cautions

Header for the hanger HUS1.81/10 is a Double 1-3/4" x 11-7/8" LVL Beam.

Hanger model HUS1.81/10 and seat length were input by the user. Hanger has not been analyzed for adequate capacity.


 OWG NO. TAM 25902-21
 STRUCTURAL
 COMPONENT ONLY

REVIEWED



1ST FLR FRAMING\Flush Beams\B2(i449) (Flush Beam)

Dry | 1 span | No cant.

November 9, 2021 11:10:31

BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports: CCMC 12472-R

File name: TH-1 EL A.mmdl

Description: 1ST FLR FRAMING\Flush Beams\B2(i449)

Specifier:

Designer:

Company:

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Hanger Manufacturer: Unassigned

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.


Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 01-02-01.

CONFORMS TO OBC 2012

AMENDED 2020

DWG NO. TAM25902-21
STRUCTURAL
COMPONENT ONLY**Disclosure**

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED

1ST FLR FRAMING\Flush Beams\B3(i461) (Flush Beam)

Dry | 1 span | No cant.

November 9, 2021 11:10:31

BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B3(i461)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



Total Horizontal Product Length = 05-04-12

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 3-1/2"	321 / 0	185 / 0		
B2, 4-3/8"	135 / 0	86 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	05-04-12	Top	1.00	0.65	1.00	1.15	00-00-00
1	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	01-00-00	Top	11	5			n/a
2	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	01-00-00	05-04-12	Top	30	15			n/a
3	B5(i458)	Conc. Pt. (lbs)	L	01-00-14	01-00-14	Top	314	167			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	583 ft-lbs	17696 ft-lbs	3.3%	1	01-00-13
End Shear	553 lbs	7232 lbs	7.6%	1	01-03-06
Total Load Deflection	L/999 (0.003")	n/a	n/a	4	02-05-14
Live Load Deflection	L/999 (0.002")	n/a	n/a	5	02-05-14
Max Defl.	0.003"	n/a	n/a	4	02-05-14
Span / Depth	4.9				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Column 3-1/2" x 1-3/4"	713 lbs	14.3%	9.5%	Unspecified
B2	Wall/Plate 4-3/8" x 1-3/4"	310 lbs	6.6%	3.3%	Spruce-Pine-Fir

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 03-10-10.

CONFORMS TO CBC 2012

AMENDED 2020


 DWG NO. TAM 25903-21
STRUCTURAL COMPONENT ONLY
Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®

REVIEWED

1ST FLR FRAMING\Flush Beams\B4(i456) (Flush Beam)

Dry | 1 span | No cant.

November 9, 2021 11:10:31

BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B4(i456)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:


Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 2-3/8"	264 / 0	163 / 0		
B2, 4-3/8"	338 / 0	202 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	09-00-04	Top	1.00	0.65	1.00	1.15	00-00-00
1	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	09-00-04	Top	20	10			n/a
2	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	04-07-08	Top	3	2			n/a
3	FC1 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	04-07-08	09-00-04	Top	24	12			n/a
4	B5(i458)	Conc. Pt. (lbs)	L	04-08-06	04-08-06	Top	307	164			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	2128 ft-lbs	17696 ft-lbs	12.0%	1	04-08-06
End Shear	625 lbs	7232 lbs	8.6%	1	07-08-00
Total Load Deflection	L/999 (0.035")	n/a	n/a	4	04-06-03
Live Load Deflection	L/999 (0.022")	n/a	n/a	5	04-06-03
Max Defl.	0.035"	n/a	n/a	4	04-06-03
Span / Depth	8.7				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 2-3/8" x 1-3/4"	600 lbs	23.5%	11.8%	Spruce-Pine-Fir
B2	Wall/Plate 4-3/8" x 1-3/4"	760 lbs	16.2%	8.2%	Spruce-Pine-Fir

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.


Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 04-05-02.

CONFORMS TO OBC 2012
AMENDED 2020

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCi®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B5(i458)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



B1

03-05-03

B2

Total Horizontal Product Length = 03-05-03

Reaction Summary (Down / Uplift) (lbs)


Bearing	Live	Dead	Snow	Wind
B1, 2"	307 / 0	164 / 0		
B2, 2"	314 / 0	167 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	03-05-03	Top		6			00-00-00
1	STAIR	Unf. Lin. (lb/ft)	L	00-00-00	03-05-03	Top	120	60			n/a
2	J7(i457)	Conc. Pt. (lbs)	L	01-01-09	01-01-09	Top	108	54			n/a
3	J7(i455)	Conc. Pt. (lbs)	L	02-05-09	02-05-09	Top	101	50			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	553 ft-lbs	17696 ft-lbs	3.1%	1	01-07-12
End Shear	355 lbs	7232 lbs	4.9%	1	01-01-14
Total Load Deflection	L/999 (0.002")	n/a	n/a	4	01-08-10
Live Load Deflection	L/999 (0.001")	n/a	n/a	5	01-08-10
Max Defl.	0.002"	n/a	n/a	4	01-08-10
Span / Depth	3.3				


 DWG NO. TAM 25905-21
STRUCTURAL
COMPONENT ONLY
Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Hanger 2" x 1-3/4"	665 lbs	n/a	15.6%	HUS1.81/10
B2	Hanger 2" x 1-3/4"	680 lbs	n/a	15.9%	HUS1.81/10

Cautions

Header for the hanger HUS1.81/10 is a Single 1-3/4" x 11-7/8" LVL Beam.

Hanger model HUS1.81/10 and seat length were input by the user. Hanger has not been analyzed for adequate capacity.

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Hanger Manufacturer: Unassigned

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 01-01-08.

CONFORMS TO OBC 2012

AMENDED 2020

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

1ST FLR FRAMING\Flush Beams\B6(i451) (Flush Beam)

BC CALC® Member Report

Dry | 1 span | No cant.

November 9, 2021 11:10:31

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B6(i451)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:


Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 10"	350 / 0	230 / 0		
B2, 3-1/2"	250 / 0	140 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	05-03-08	Top	6				00-00-00
1	Smoothed Load	Unf. Lin. (lb/ft)	L	00-10-08	04-10-08	Top	110	55			n/a
2	J7(i429)	Conc. Pt. (lbs)	L	05-01-04	05-01-04	Top	33	17			n/a
3	2(i128)	Conc. Pt. (lbs)	L	00-02-12	00-02-12	Top	126	100			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	605 ft-lbs	17696 ft-lbs	3.4%	1	02-10-08
End Shear	407 lbs	7232 lbs	5.6%	1	04-00-02
Total Load Deflection	L/999 (0.003")	n/a	n/a	4	02-10-15
Live Load Deflection	L/999 (0.002")	n/a	n/a	5	02-10-15
Max Defl.	0.003"	n/a	n/a	4	02-10-15
Span / Depth	4.3				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 10" x 1-3/4"	812 lbs	7.5%	3.8%	Spruce-Pine-Fir
B2	Column 3-1/2" x 1-3/4"	551 lbs	11.1%	7.4%	Unspecified

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.


Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 01-01-08.

CONFORMS TO OBC 2012
AMENDED 2020

UWG NO. TAM 25906-21
STRUCTURAL
COMPONENT ONLY
Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B7L(i426)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



Total Horizontal Product Length = 05-11-06

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 3-1/2"	78 / 0	53 / 0		
B2, 4-3/8"	80 / 0	55 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	05-11-06	Top	1.00	0.65	1.00	1.15	00-00-00
1	FC3 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	05-11-06	Top	27	13			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	230 ft-lbs	11610 ft-lbs	2.0%	1	02-11-04
End Shear	116 lbs	5785 lbs	2.0%	1	01-01-00
Total Load Deflection	L/999 (0.003")	n/a	n/a	4	02-11-04
Live Load Deflection	L/999 (0.002")	n/a	n/a	5	02-11-04
Max Defl.	0.003"	n/a	n/a	4	02-11-04
Span / Depth	6.8				

Bearing Supports

			Demand/ Resistance Support	Demand/ Resistance Member	Material	
Bearing Supports	Dim. (LxW)	Demand				
B1	Column	3-1/2" x 1-3/4"	184 lbs	3.7%	2.5%	Unspecified
B2	Wall/Plate	4-3/8" x 1-3/4"	189 lbs	4.0%	2.0%	Spruce-Pine-Fir

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 05-05-04.

CONFORMS TO OBC 2012

AMENDED 2020

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED

BC CALC® Member Report

Dry | 1 span | No cant.

November 9, 2021 11:10:31

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 1ST FLR FRAMING\Flush Beams\B8L(i436)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



Total Horizontal Product Length = 04-09-02

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 4-3/8"	232 / 0	128 / 0		
B2, 1-3/4"	202 / 0	111 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	04-09-02	Top	1.00	0.65	1.00	1.15	00-00-00
1	J2(i425)	Conc. Pt. (lbs)	L	00-10-14	00-10-14	Top	124	62			n/a
2	J2(i423)	Conc. Pt. (lbs)	L	02-02-14	02-02-14	Top	155	77			n/a
3	J2(i418)	Conc. Pt. (lbs)	L	03-06-14	03-06-14	Top	155	77			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	618 ft-lbs	11610 ft-lbs	5.3%	1	02-02-14
End Shear	436 lbs	5785 lbs	7.5%	1	03-09-14
Total Load Deflection	L/999 (0.006")	n/a	n/a	4	02-05-14
Live Load Deflection	L/999 (0.004")	n/a	n/a	5	02-05-14
Max Defl.	0.006"	n/a	n/a	4	02-05-14
Span / Depth	5.5				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 4-3/8" x 1-3/4"	508 lbs	10.8%	5.4%	Spruce-Pine-Fir
B2	Column 1-3/4" x 1-3/4"	442 lbs	17.8%	11.8%	Unspecified

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.


Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 01-01-08.

CONFORMS TO OBC 2012
AMENDED 2020

**DWG NO. TAM 25908-21
STRUCTURAL
COMPONENT ONLY**
Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED



BC CALC® Member Report

Dry | 1 span | No cant.

November 9, 2021 11:10:31

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B10(i342)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:


Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 3-1/2"	478 / 37	536 / 0		
B2, 5-1/2"	848 / 70	583 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	09-02-08	Top		12			00-00-00
1	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	05-09-00	Top	17	8			n/a
2	WALL	Unf. Lin. (lb/ft)	L	00-03-08	05-10-01	Top		60			n/a
3	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	05-09-00	08-11-12	Top	29	14			n/a
4	B17(i395)	Conc. Pt. (lbs)	L	05-09-14	05-09-14	Top	1138	557			n/a
5	B17(i395)	Conc. Pt. (lbs)	L	05-09-14	05-09-14	Top	-107				n/a
6	E24(i294)	Conc. Pt. (lbs)	L	00-02-12	00-02-12	Top		24			n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	5593 ft-lbs	35392 ft-lbs	15.8%	1	05-09-14
End Shear	1904 lbs	14464 lbs	13.2%	1	07-09-02
Total Load Deflection	L/999 (0.046")	n/a	n/a	6	04-09-04
Live Load Deflection	L/999 (0.026")	n/a	n/a	8	04-10-15
Max Defl.	0.046"	n/a	n/a	6	04-09-04
Span / Depth	8.7				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 3-1/2" x 3-1/2"	1388 lbs	18.4%	9.3%	Spruce-Pine-Fir
B2	Wall/Plate 5-1/2" x 3-1/2"	2000 lbs	16.9%	8.5%	Spruce-Pine-Fir

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 05-05-08.

CONFORMS TO CBC 2012

AMENDED 2020


 STRUCTURAL
 COMPONENT ONLY

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports: CCMC 12472-R

File name: TH-1 EL A.mmdl


Description: 2ND FLR FRAMING\Flush Beams\B10(i342)

Specifier:

Designer:

Company:

Connection Diagram: Full Length of Member



a minimum = 2"

b minimum = 3"

c = 7-7/8"


d = 8"

Connectors are: 1 Nails

3 1/2" ARDOX SPIRAL

Connection Diagrams: Concentrated Side Loads

Connection Tag: A Applies to load tag(s): 5+6



a minimum = 2"

b minimum = 4"

c minimum = 4"

d maximum = 12"

e minimum = 4"

Connectors are: 16d 1 Nails

3 1/2" ARDOX SPIRAL



UWG NO. TAM 25909-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B11(i373)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



Total Horizontal Product Length = 19-05-14

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 2-3/8"	175 / 3	39 / 0	0 / 82	
B2, 5-1/2"	218 / 0	1684 / 0	789 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	19-05-14	Top		12			00-00-00
1	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	19-05-14	Top	20	10			n/a
2	-	Conc. Pt. (lbs)	L	19-04-02	19-04-02	Top		1294	707		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/ Resistance	Case	Location
Pos. Moment	848 ft-lbs	35392 ft-lbs	2.4%	35	05-10-04
Neg. Moment	-5463 ft-lbs	-11766 ft-lbs	46.4%	37	17-04-02
End Shear	243 lbs	14464 lbs	1.7%	32	01-02-04
Cont. Shear	1840 lbs	9401 lbs	19.6%	0	18-06-12
Total Load Deflection	2xL/1998 (0.082")	n/a	n/a	83	19-05-14
Live Load Deflection	L/999 (-0.049")	n/a	n/a	121	10-00-11
Total Neg. Defl.	L/999 (-0.095")	n/a	n/a	83	10-09-01
Max Defl.	-0.095"	n/a	n/a	83	10-09-01
Span / Depth	17.4				

Bearing Supports

	Dim. (LxW)	Demand	Demand/ Resistance Support	Demand/ Resistance Member	Material
B1	Wall/Plate 2-3/8" x 3-1/2"	311 lbs	6.1%	3.1%	Spruce-Pine-Fir
B1	Uplift	91 lbs			
B2	Wall/Plate 5-1/2" x 3-1/2"	2358 lbs	30.6%	15.4%	Spruce-Pine-Fir

Cautions

Uplift of 90 lbs found at bearing B1.

Concentrated side load(s) 7,12 are closer than 18" from end of member. Please consult a technical representative or Professional of Record.


 DWG NO. TAM 25910-21
 STRUCTURAL
 COMPONENT ONLY

REVIEWED



BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports: CCMC 12472-R

File name: TH-1 EL A.mmdl

Description: 2ND FLR FRAMING\Flush Beams\B11(i373)

Specifier:

Designer:

Company:

Notes

Design meets User specified (2xL/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Unbalanced snow loads determined from building geometry were used in selected product's verification.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9


Cantilevers require sheathed bottom flanges, blocking at cantilever support and closure at ends.

Calculations assume unbraced length of Top: 00-00-00, Bottom: 16-11-00.

CONFIRMS TO DEC 2012

AMENDED 2020

Connection Diagram: Full Length of Member



a minimum = 2"

b minimum = 3"

c = 7-7/8"

d = 6-0"

Connectors are:

3 1/2" ARDOX SPIRAL

Nails



BWG NO. TAM25910-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED



BC CALC® Member Report

Dry | 3 spans | R cant.

November 9, 2021 11:10:31

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B12(i377)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 34-15/16"	101 / 5	2355 / 0	4401 / 0	
B2, 24"	174 / 0	3001 / 0	5609 / 0	
B3, 20"	124 / 0	3246 / 0	5223 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	19-05-14	Top		12			00-00-00
1	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	19-05-14	Top	20	10			n/a
2	E25(i293)	Unf. Lin. (lb/ft)	L	00-04-06	02-09-14	Top		81			n/a
3	E25(i293)	Unf. Lin. (lb/ft)	L	00-04-06	02-05-14	Top		322	759		n/a
4	E33(i302)	Unf. Lin. (lb/ft)	L	02-09-14	09-09-14	Top		61			n/a
5	E34(i303)	Unf. Lin. (lb/ft)	L	09-09-14	13-09-14	Top		81			n/a
6	E34(i303)	Unf. Lin. (lb/ft)	L	10-01-14	13-05-14	Top		322	759		n/a
7	E31(i299)	Unf. Lin. (lb/ft)	L	13-09-14	17-09-14	Top		61			n/a
8	E32(i300)	Unf. Lin. (lb/ft)	L	17-09-14	19-05-14	Top		81			n/a
9	E32(i300)	Unf. Lin. (lb/ft)	L	18-01-14	19-05-14	Top		322	759		n/a
10	B13(i430)	Conc. Pt. (lbs)	L	19-04-02	19-04-02	Top		612	333		n/a
11	E25(i293)	Conc. Pt. (lbs)	L	02-08-14	02-08-14	Top		1261	2918		n/a
12	E34(i303)	Conc. Pt. (lbs)	L	09-10-14	09-10-14	Top		1254	2901		n/a
13	E34(i303)	Conc. Pt. (lbs)	L	13-08-14	13-08-14	Top		772	1786		n/a
14	E32(i300)	Conc. Pt. (lbs)	L	17-10-14	17-10-14	Top		759	1756		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	5156 ft-lbs	35392 ft-lbs	14.6%	105	13-00-14
Neg. Moment	-6279 ft-lbs	-10475 ft-lbs	59.9%	101	17-06-14
End Shear	173 lbs	14464 lbs	1.2%	92	03-10-13
Cont. Shear	4885 lbs	14464 lbs	33.8%	101	10-10-12
Total Load Deflection	L/999 (0.019")	n/a	n/a	249	12-10-06
Live Load Deflection	L/999 (0.013")	n/a	n/a	353	12-10-06
Total Neg. Defl.	L/999 (-0.009")	n/a	n/a	249	07-02-10
Max Defl.	0.019"	n/a	n/a	249	12-10-06
Span / Depth	6.1				
Dist. Load (B1)	1674.71 lb/ft	57645.1 lb/ft	2.9%		
Dist. Load (B2)	127.28 lb/ft	37469.32 lb/ft	0.3%		
Dist. Load (B3)	99.26 lb/ft	37469.32 lb/ft	0.3%		
Conc. Load (B1)	5953 lbs	16813 lbs	35.4%		



DWG NO. TAM 25911 -21
STRUCTURAL
COMPONENT ONLY

REVIEWED

BC CALC® Member Report
 Build 7773

Dry | 3 spans | R cant.

November 9, 2021 11:10:31

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B12(i377)

City, Province, Postal Code:

Specifier:

Customer:

Designer:

Code reports:

CCMC 12472-R

Company:

Bearing Supports	Dim. (LxW)	Demand	Demand/ Resistance Support	Demand/ Resistance Member	Material
B1	Wall/Plate 34-15/16" x 3-1/2"	9716 lbs	12.9%	6.5%	Spruce-Pine-Fir
B2	Wall/Plate 24" x 3-1/2"	11832 lbs	22.9%	11.5%	Spruce-Pine-Fir
B3	Wall/Plate 20" x 3-1/2"	12028 lbs	27.9%	14.1%	Spruce-Pine-Fir

Cautions

Concentrated side load(s) 42 are closer than 18" from end of member. Please consult a technical representative or Professional of Record.

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Unbalanced snow loads determined from building geometry were used in selected product's verification.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9


Cantilevers require sheathed bottom flanges, blocking at cantilever support and closure at ends.

Calculations assume unbraced length of Top: 00-00-00, Bottom: 19-00-00.

CONFORMS TO OBC 2012

AMENDED 2020

Connection Diagram: Full Length of Member


 a minimum = 2"
 b minimum = 3"

 c = 7-7/8"
 d = 8"

Connectors are: 3-1/4" Nails

3 1/2" ARDOX SPIRAL

 ENG NO. TAM 25911-21
 STRUCTURAL
 COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED

2ND FLR FRAMING\Flush Beams\B13(i430) (Flush Beam)

Dry | 1 span | No cant.

November 9, 2021 11:10:31

BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B13(i430)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



B1

10-03-03

B2

Total Horizontal Product Length = 10-03-03

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 2"		621 / 0	339 / 0	
B2, 2"		603 / 0	328 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	10-03-03	Top	1.00	0.65	1.00	1.15	00-00-00
1	E30(i298)	Unf. Lin. (lb/ft)	L	00-00-00	10-01-03	Top		109	66		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	2140 ft-lbs	23005 ft-lbs	9.3%	0	05-01-09
End Shear	673 lbs	9401 lbs	7.2%	0	01-01-14
Total Load Deflection	L/999 (0.044")	n/a	n/a	12	05-01-09
Live Load Deflection	L/999 (0.016")	n/a	n/a	17	05-01-09
Max Defl.	0.044"	n/a	n/a	12	05-01-09
Span / Depth	10.2				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Hanger 2" x 3-1/2"	869 lbs	n/a	15.7%	HUC412
B2	Hanger 2" x 3-1/2"	844 lbs	n/a	15.2%	HUC412

Cautions

Header for the hanger HUC412 is a Double 1-3/4" x 11-7/8" LVL Beam.

Hanger model HUC412 and seat length were input by the user. Hanger has not been analyzed for adequate capacity.) 06/9

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Hanger Manufacturer: Unassigned

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Unbalanced snow loads determined from building geometry were used in selected product's verification.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 00-09-08.

CONFORMS TO CBC 2012

AMENDED 2020



OWG NO. TAM25912-21
STRUCTURAL
COMPONENT ONLY

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports:

CCMC 12472-R

Dry | 1 span | No cant.

November 9, 2021 11:10:31

File name: TH-1 EL A.mmdl


Description: 2ND FLR FRAMING\Flush Beams\B13(i430)

Specifier:

Designer:

Company:

Connection Diagram: Full Length of Member



a minimum = 2"

b minimum = 3"

c = 7-7/8"

d = 8"

Connectors are:

1
3 1/2" ARDOX SPIRAL

Nails



POE
DWG NO. TAM 25912-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED



BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B14(i424)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



B1

10-09-00

B2

Total Horizontal Product Length = 10-09-00

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 2"		650 / 0	355 / 0	
B2, 2"		650 / 0	355 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	10-09-00	Top		12			00-00-00
1	E30(i298)	Unf. Lin. (lb/ft)	L	00-00-00	10-09-00	Top		109	66		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	2351 ft-lbs	23005 ft-lbs	10.2%	0	05-04-08
End Shear	714 lbs	9401 lbs	7.6%	0	01-01-14
Total Load Deflection	L/999 (0.053")	n/a	n/a	12	05-04-08
Live Load Deflection	L/999 (0.019")	n/a	n/a	17	05-04-08
Max Defl.	0.053"	n/a	n/a	12	05-04-08
Span / Depth	10.7				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1 Hanger	2" x 3-1/2"	910 lbs	n/a	16.4%	HUC412
B2 Hanger	2" x 3-1/2"	910 lbs	n/a	16.4%	HUC412

Cautions

Header for the hanger HUC412 is a Double 1-3/4" x 11-7/8" LVL Beam.

Hanger model HUC412 and seat length were input by the user. Hanger has not been analyzed for adequate capacity.

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Hanger Manufacturer: Unassigned

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Unbalanced snow loads determined from building geometry were used in selected product's verification.


Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 00-09-08.

CONFORMS TO OBC 2012

AMENDED 2020


 DWG NO. TAM25913-21
 STRUCTURAL
 COMPONENT ONLY

REVIEWED



BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports:

CCMC 12472-R

File name: TH-1 EL A.mmdl


Description: 2ND FLR FRAMING\Flush Beams\B14(i424)

Specifier:

Designer:

Company:

Connection Diagram: Full Length of Member



a minimum = 2"

b minimum = 3"


c = 7-7/8"

d = 6"

Connectors are:

1 -
3 1/2" ARDOX SPIRAL

Nails




Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED


Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 3-1/2"		551 / 0	301 / 0	
B2, 2"		536 / 0	292 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live 1.00	Dead 0.65	Snow 1.00	Wind 1.15	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	08-11-13	Top		12			00-00-00
1	E30(i298)	Unf. Lin. (lb/ft)	L	00-00-00	08-11-13	Top		109	66		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	1585 ft-lbs	23005 ft-lbs	6.9%	0	04-06-11
End Shear	554 lbs	9401 lbs	5.9%	0	01-03-06
Total Load Deflection	L/999 (0.024")	n/a	n/a	12	04-06-11
Live Load Deflection	L/999 (0.009")	n/a	n/a	17	04-06-11
Max Defl.	0.024"	n/a	n/a	12	04-06-11
Span / Depth	8.7				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 3-1/2" x 3-1/2"	771 lbs	15.7%	7.9%	Spruce-Pine-Fir
B2	Hanger 2" x 3-1/2"	750 lbs	n/a	13.5%	HUC412

Cautions

Header for the hanger HUC412 is a Double 1-3/4" x 11-7/8" LVL Beam.

Hanger model HUC412 and seat length were input by the user. Hanger has not been analyzed for adequate capacity. *OK*

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Hanger Manufacturer: Unassigned

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Unbalanced snow loads determined from building geometry were used in selected product's verification.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 01-02-01.

CONFORMS TO OBC 2012
AMENDED 2020


DWG NO. TAM25914-21
 STRUCTURAL
 COMPONENT ONLY

REVIEWED

BC CALC® Member Report
Build 7773

Dry | 1 span | No cant.

November 9, 2021 11:10:31

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B15(i414)

City, Province, Postal Code:

Specifier:

Customer:


Designer:

Code reports:

CCMC 12472-R

Company:

Connection Diagram: Full Length of Member




a minimum = 2"
b minimum = 3"

c = 7-7/8"
d = 3"

Connectors are:

3 1/2" ARDOX SPIRAL

Nails



ENG NO. TAM 25914-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED

BC CALC® Member Report

Build 0

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B16(i401)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



FULLY SUPPORTED BOTTOM EDGE ALONG FULL WIDTH & FULL SPAN OF BEAM.
Total Horizontal Product Length = 13-10-08

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	13-10-08	Top	1.00	0.65	1.00	1.15	00-00-00
1	E24(i294)	Unf. Lin. (lb/ft)	L	00-00-00	13-10-08	Top		81			n/a

Controls Summary

Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Dist. Load 113.26 lb/ft	37469.32 lb/ft	0.3%		
Conc. Load 0 lbs	16813 lbs	n/a		


CONFORMS TO OBC 2012

AMENDED 2020

Notes

Calculations assume member is fully braced.

Connection Diagram: Full Length of Member



a minimum = 2"

c = 7-7/8"

b minimum = 3"

d = 8"

Connectors are:

Nails

3 1/2" ARDOX SPIRAL



DWG NO. TAM 25915-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED



BC CALC® Member Report

Build 7773

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B17(i395)

City, Province, Postal Code:

Specifier:


Customer:

Designer:

Code reports:

CCMC 12472-R

Company:



B1

13-10-08

B2

Total Horizontal Product Length = 13-10-08

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 2"	1137 / 107	556 / 0		
B2, 2"	1240 / 158	583 / 0		

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	13-10-08	Top	1.00	0.65	1.00	1.15	00-00-00
1	STAIR	Unf. Lin. (lb/ft)	L	00-00-00	03-04-09	Top	120	60			n/a
2	Smoothed Load	Unf. Lin. (lb/ft)	L	01-03-03	05-03-03	Top	65	32			n/a
3	Smoothed Load	Unf. Lin. (lb/ft)	L	05-03-03	10-07-03	Top	188	71			n/a
4	J5(i383)	Conc. Pt. (lbs)	L	00-07-03	00-07-03	Top	67	33			n/a
5	J2(i427)	Conc. Pt. (lbs)	L	05-11-03	05-11-03	Top	-61				n/a
6	J2(i422)	Conc. Pt. (lbs)	L	07-03-03	07-03-03	Top	-61				n/a
7	J2(i420)	Conc. Pt. (lbs)	L	08-07-03	08-07-03	Top	-61				n/a
8	J2(i434)	Conc. Pt. (lbs)	L	09-11-03	09-11-03	Top	-61				n/a
9	J2(i428)	Conc. Pt. (lbs)	L	11-03-03	11-03-03	Top	316	153			n/a
10	J2(i428)	Conc. Pt. (lbs)	L	11-03-03	11-03-03	Top	-10				n/a
11	J2(i419)	Conc. Pt. (lbs)	L	12-07-03	12-07-03	Top	326	158			n/a
12	J2(i419)	Conc. Pt. (lbs)	L	12-07-03	12-07-03	Top	-11				n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	8384 ft-lbs	17696 ft-lbs	47.4%	1	07-03-03
End Shear	2581 lbs	7232 lbs	35.7%	1	12-08-10
Total Load Deflection	L/407 (0.403")	n/a	58.9%	6	07-01-03
Live Load Deflection	L/594 (0.276")	n/a	60.7%	8	07-01-03
Max Defl.	0.403"	n/a	n/a	6	07-01-03
Span / Depth	13.8				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Hanger 2" x 1-3/4"	2400 lbs	n/a	56.2%	HUS1.81/10
B2	Hanger 2" x 1-3/4"	2589 lbs	n/a	60.6%	HUS1.81/10

Cautions

Header for the hanger HUS1.81/10 is a Double 1-3/4" x 11-7/8" LVL Beam.

Hanger model HUS1.81/10 and seat length were input by the user. Hanger has not been analyzed for adequate capacity.


 SWG NO. TAM25916-21
 STRUCTURAL
 COMPONENT ONLY

REVIEWED

**Single 1-3/4" x 11-7/8" VERSA-LAM® 2.0 3100 SP**
2ND FLR FRAMING\Flush Beams\B17(i395) (Flush Beam)**PASSED**BC CALC® Member Report
Build 7773

Dry | 1 span | No cant.

November 9, 2021 11:10:31

Job name:

File name: TH-1 EL A.mmdl

Address:

Description: 2ND FLR FRAMING\Flush Beams\B17(i395)

City, Province, Postal Code:

Specifier:

Customer:

Designer:

Code reports:

CCMC 12472-R

Company:

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Hanger Manufacturer: Unassigned

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 01-02-01.

CONFORMS TO OBC 2012**AMENDED 2020**

pg 2
DWG NO. TAM 25916-21
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports:

CCMC 12472-R


File name: TH-1 EL A.mmdl

Description: 2ND FLR FRAMING\Flush Beams\B9(i327)

Specifier:

Designer:

Company:



Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 3-1/2"	1095 / 112	785 / 0	0 / 77	
B2, 5-1/2"	852 / 51	1954 / 0	741 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	19-07-00	Top	1.00	0.65	1.00	1.15	
1	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	00-00-00	05-09-00	Top	18	9			00-00-00
2	WALL	Unf. Lin. (lb/ft)	L	00-03-08	05-10-00	Top		60			n/a
3	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	05-09-00	19-07-00	Top	43	22			n/a
4	B17(i395)	Conc. Pt. (lbs)	L	05-09-14	05-09-14	Top	1239	583			n/a
5	B17(i395)	Conc. Pt. (lbs)	L	05-09-14	05-09-14	Top	-158				n/a
6	-	Conc. Pt. (lbs)	L	19-05-04	19-05-04	Top		1213	664		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	12465 ft-lbs	35392 ft-lbs	35.2%	43	05-09-14
Neg. Moment	-5219 ft-lbs	-17596 ft-lbs	29.7%	49	17-05-04
End Shear	2452 lbs	14464 lbs	16.9%	43	01-03-06
Cont. Shear	1742 lbs	9401 lbs	18.5%	0	18-07-14
Total Load Deflection	L/549 (0.376")	n/a	43.7%	102	07-11-04
Live Load Deflection	L/760 (0.272")	n/a	47.4%	151	08-03-02
Total Neg. Defl.	2xL/1998 (-0.104")	n/a	n/a	102	19-07-00
Max Defl.	0.376"	n/a	n/a	102	07-11-04
Span / Depth	17.4				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Wall/Plate 3-1/2" x 3-1/2"	2623 lbs	34.8%	17.6%	Spruce-Pine-Fir
B2	Wall/Plate 5-1/2" x 3-1/2"	4461 lbs	37.7%	19.0%	Spruce-Pine-Fir

Cautions

Concentrated side load(s) 12,17 are closer than 18" from end of member. Please consult a technical representative or Professional of Record.



BWB NO. TAM 25917-26
STRUCTURAL
COMPONENT ONLY

REVIEWED

BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code:

Customer:

Code reports:

CCMC 12472-R

Dry | 2 spans | R cant.

November 9, 2021 11:10:31

File name: TH-1 EL A.mmdl

Description: 2ND FLR FRAMING\Flush Beams\B9(i327)

Specifier:

Designer:

Company:

Notes

Design meets Code minimum (L/240) Total load deflection criteria.

Design meets Code minimum (L/360) Live load deflection criteria.

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86.

Unbalanced snow loads determined from building geometry were used in selected product's verification.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9


Cantilevers require sheathed bottom flanges, blocking at cantilever support and closure at ends.

Calculations assume unbraced length of Top: 00-00-00, Bottom: 11-03-12.

CONFORMS TO CBC 2012

AMENDED 2020

Connection Diagram: Full Length of Member



a minimum = 2"

b minimum = 3"

c = 7-7/8"


d = 8"

Connectors are: 1 : Nails

3 1/2" ARDOX SPIRAL

Connection Diagrams: Concentrated Side Loads

Connection Tag: A Applies to load tag(s): 5+6



a minimum = 2"

b minimum = 4"

c minimum = 4"

d maximum = 12"

e minimum = 4"

Connectors are: 16d : 1 : Nails

3 1/2" ARDOX SPIRAL




DOB NO. TAM 25917 = 2L
**STRUCTURAL
COMPONENT ONLY**

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJS™, ALLJOIST®, BC RIM BOARD™, BCi®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED



Total Horizontal Product Length = 01-10-08

Reaction Summary (Down / Uplift) (lbs)

Bearing	Live	Dead	Snow	Wind
B1, 3"	42 / 0	115 / 0	55 / 0	
B2, 5-1/2"	109 / 0	177 / 0	69 / 0	

Load Summary

Tag	Description	Load Type	Ref.	Start	End	Loc.	Live	Dead	Snow	Wind	Tributary
0	Self-Weight	Unf. Lin. (lb/ft)	L	00-00-00	01-10-08	Top	1.00	0.65	1.00	1.15	00-00-00
1	E36(i720)	Unf. Lin. (lb/ft)	L	00-00-00	01-05-00	Top		12			n/a
2	FC4 Floor Decking (Plan View Fill)	Unf. Lin. (lb/ft)	L	01-01-06	01-07-06	Top	6	100	66		n/a
3	J5(i546)	Conc. Pt. (lbs)	L	01-01-06	01-01-06	Top	148	74			n/a
4	E29(i296)	Conc. Pt. (lbs)	L	01-07-12	01-07-12	Top		48	30		n/a

Controls Summary

	Factored Demand	Factored Resistance	Demand/Resistance	Case	Location
Pos. Moment	118 ft-lbs	35392 ft-lbs	0.3%	1	01-01-06
End Shear	63 lbs	9401 lbs	0.7%	0	00-05-02
Span / Depth	1.3				

Bearing Supports

	Dim. (LxW)	Demand	Demand/Resistance Support	Demand/Resistance Member	Material
B1	Beam 3" x 3-1/2"	268 lbs	4.1%	2.1%	Spruce-Pine-Fir
B2	Wall/Plate 5-1/2" x 3-1/2"	453 lbs	3.8%	1.9%	Spruce-Pine-Fir

Notes

Resistance Factor phi has been applied to all presented results per CSA O86.

BC CALC® analysis is based on Canadian Limit States Design, as per NBCC 2015 and CSA O86. CONFORMS TO OBC 2012


Unbalanced snow loads determined from building geometry were used in selected product's verification.

Design based on Dry Service Condition.

Importance Factor : Normal Part code : Part 9

Calculations assume unbraced length of Top: 00-00-00, Bottom: 00-08-08.

AMENDED 2020



SW & NO. TAM2591B.21
STRUCTURAL
COMPONENT ONLY

REVIEWED



BC CALC® Member Report

Build 7773

Job name:

Address:

City, Province, Postal Code: BRADFORD

Customer:

Code reports: CCMC 12472-R

Dry | 1 span | No cant.

November 9, 2021 12:36:39

File name: TH-1 EL B SUNKEN.mmdl


Description: 2ND FLR FRAMING\Flush Beams\B21(i565)

Specifier:

Designer: AJ

Company:

Connection Diagram: Full Length of Member



a minimum = 2"

b minimum = 3"

c = 7-7/8"

d = 8"

Calculated Side Load = 157.3 lb/ft

Connectors are:

3 1/2" ARDOX SPIRAL

Nails



NO. TAM 2591821
STRUCTURAL
COMPONENT ONLY

Disclosure

Use of the Boise Cascade Software is subject to the terms of the End User License Agreement (EULA). Completeness and accuracy of input must be reviewed and verified by a qualified engineer or other appropriate expert to assure its adequacy, prior to anyone relying on such output as evidence of suitability for a particular application. The output here is based on building code-accepted design properties and analysis methods. Installation of Boise Cascade engineered wood products must be in accordance with current Installation Guide and applicable building codes. To obtain Installation Guide or ask questions, please call (800)232-0788 before installation.

BC CALC®, BC FRAMER®, AJST™, ALLJOIST®, BC RIM BOARD™, BCI®, BOISE GLULAM™, BC FloorValue®, VERSA-LAM®, VERSA-RIM PLUS®,

REVIEWED

Maximum Floor Spans – S2.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 15 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	5/8 in. nailed-glued oriented strand board (OSB) sheathing

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	15'-1"	14'-3"	13'-10"	-	15'-7"	14'-9"	14'-3"	-
	NI-40x	16'-2"	15'-3"	14'-8"	-	16'-7"	15'-8"	15'-1"	-
	NI-60	16'-4"	15'-4"	14'-10"	-	16'-9"	15'-9"	15'-3"	-
	NI-80	17'-3"	16'-3"	15'-8"	-	17'-8"	16'-7"	16'-0"	-
11-7/8"	NI-20	17'-0"	16'-0"	15'-6"	-	17'-6"	16'-7"	16'-0"	-
	NI-40x	18'-2"	17'-1"	16'-6"	-	18'-9"	17'-6"	16'-11"	-
	NI-60	18'-5"	17'-3"	16'-8"	-	19'-0"	17'-8"	17'-1"	-
	NI-80	19'-9"	18'-3"	17'-7"	-	20'-4"	18'-10"	18'-0"	-
	NI-90	20'-2"	18'-8"	17'-10"	-	20'-9"	19'-2"	18'-4"	-
14"	NI-40x	20'-1"	18'-8"	17'-10"	-	20'-10"	19'-4"	18'-6"	-
	NI-60	20'-6"	18'-11"	18'-2"	-	21'-2"	19'-8"	18'-9"	-
	NI-80	21'-11"	20'-3"	19'-4"	-	22'-7"	20'-11"	20'-0"	-
	NI-90	22'-5"	20'-8"	19'-9"	-	23'-0"	21'-4"	20'-4"	-
16"	NI-60	22'-4"	20'-8"	19'-9"	-	23'-1"	21'-5"	20'-6"	-
	NI-80	23'-11"	22'-1"	21'-1"	-	24'-8"	22'-10"	21'-9"	-
	NI-90	24'-5"	22'-6"	21'-6"	-	25'-1"	23'-2"	22'-2"	-

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-8"	15'-3"	14'-5"	-	16'-8"	15'-3"	14'-5"	-
	NI-40x	17'-11"	17'-0"	16'-1"	-	18'-5"	17'-1"	16'-1"	-
	NI-60	18'-2"	17'-1"	16'-4"	-	18'-8"	17'-4"	16'-4"	-
	NI-80	19'-5"	18'-0"	17'-5"	-	19'-10"	18'-5"	17'-8"	-
11-7/8"	NI-20	19'-7"	18'-2"	17'-3"	-	19'-11"	18'-3"	17'-3"	-
	NI-40x	21'-1"	19'-7"	18'-8"	-	21'-8"	20'-2"	19'-2"	-
	NI-60	21'-4"	19'-9"	18'-11"	-	21'-11"	20'-5"	19'-6"	-
	NI-80	22'-9"	21'-1"	20'-2"	-	23'-3"	21'-8"	20'-8"	-
	NI-90	23'-3"	21'-6"	20'-6"	-	23'-9"	22'-0"	21'-0"	-
14"	NI-40x	23'-8"	21'-11"	20'-11"	-	24'-4"	22'-8"	21'-8"	-
	NI-60	24'-0"	22'-3"	21'-3"	-	24'-8"	22'-11"	21'-11"	-
	NI-80	25'-7"	23'-9"	22'-7"	-	26'-2"	24'-4"	23'-3"	-
	NI-90	26'-1"	24'-2"	23'-0"	-	26'-8"	24'-9"	23'-7"	-
16"	NI-60	26'-5"	24'-6"	23'-5"	-	27'-2"	25'-3"	24'-2"	-
	NI-80	28'-2"	26'-1"	24'-10"	-	28'-10"	26'-9"	25'-6"	-
	NI-90	28'-8"	26'-6"	25'-3"	-	29'-3"	27'-2"	25'-11"	-

Notes:

1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

NORDIC STRUCTURES

Maximum Floor Spans – S4.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 15 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	3/4 in. nailed-glued oriented strand board (OSB) sheathing

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	15'-11"	15'-0"	14'-6"	13'-5"	16'-5"	15'-5"	14'-6"	13'-5"
	NI-40x	17'-0"	16'-0"	15'-5"	14'-10"	17'-5"	16'-5"	15'-10"	15'-2"
	NI-60	17'-2"	16'-2"	15'-7"	14'-11"	17'-7"	16'-7"	16'-0"	15'-4"
	NI-80	18'-3"	17'-1"	16'-5"	15'-9"	18'-8"	17'-5"	16'-9"	16'-1"
11-7/8"	NI-20	17'-11"	16'-11"	16'-3"	15'-8"	18'-7"	17'-5"	16'-10"	16'-2"
	NI-40x	19'-4"	17'-11"	17'-3"	16'-7"	19'-11"	18'-6"	17'-9"	17'-0"
	NI-60	19'-7"	18'-2"	17'-6"	16'-9"	20'-2"	18'-9"	17'-11"	17'-2"
	NI-80	21'-1"	19'-6"	18'-6"	17'-7"	21'-7"	20'-0"	19'-0"	18'-0"
	NI-90	21'-6"	19'-10"	18'-11"	17'-11"	22'-0"	20'-4"	19'-5"	18'-4"
14"	NI-40x	21'-5"	19'-11"	18'-11"	18'-0"	22'-1"	20'-7"	19'-7"	18'-7"
	NI-60	21'-10"	20'-2"	19'-3"	18'-3"	22'-6"	20'-10"	19'-11"	18'-10"
	NI-80	23'-5"	21'-7"	20'-7"	19'-5"	24'-0"	22'-3"	21'-2"	20'-0"
	NI-90	23'-10"	22'-1"	21'-0"	19'-10"	24'-5"	22'-7"	21'-6"	20'-4"
16"	NI-60	23'-9"	22'-0"	21'-0"	19'-10"	24'-6"	22'-9"	21'-8"	20'-7"
	NI-80	25'-6"	23'-7"	22'-5"	21'-2"	26'-2"	24'-3"	23'-1"	21'-10"
	NI-90	26'-0"	24'-0"	22'-10"	21'-6"	26'-7"	24'-8"	23'-5"	22'-2"

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-10"	15'-5"	14'-6"	13'-5"	16'-10"	15'-5"	14'-6"	13'-5"
	NI-40x	18'-8"	17'-2"	16'-3"	15'-2"	18'-10"	17'-2"	16'-3"	15'-2"
	NI-60	18'-11"	17'-6"	16'-6"	15'-5"	19'-2"	17'-6"	16'-6"	15'-5"
	NI-80	20'-3"	18'-10"	17'-11"	16'-10"	20'-8"	19'-3"	18'-2"	16'-10"
11-7/8"	NI-20	20'-1"	18'-5"	17'-5"	16'-2"	20'-1"	18'-5"	17'-5"	16'-2"
	NI-40x	21'-10"	20'-4"	19'-4"	17'-8"	22'-5"	20'-6"	19'-4"	17'-8"
	NI-60	22'-1"	20'-7"	19'-8"	18'-4"	22'-8"	20'-10"	19'-8"	18'-4"
	NI-80	23'-8"	22'-0"	20'-11"	19'-10"	24'-1"	22'-6"	21'-6"	20'-0"
	NI-90	24'-1"	22'-5"	21'-4"	20'-2"	24'-7"	22'-11"	21'-10"	20'-7"
14"	NI-40x	24'-5"	22'-9"	21'-9"	19'-5"	25'-1"	23'-2"	21'-9"	19'-5"
	NI-60	24'-10"	23'-2"	22'-1"	20'-10"	25'-6"	23'-8"	22'-4"	20'-10"
	NI-80	26'-6"	24'-8"	23'-6"	22'-2"	27'-1"	25'-3"	24'-1"	22'-9"
	NI-90	27'-0"	25'-1"	23'-11"	22'-7"	27'-6"	25'-8"	24'-6"	23'-2"
16"	NI-60	27'-3"	25'-5"	24'-3"	22'-11"	28'-0"	26'-2"	24'-9"	23'-1"
	NI-80	29'-1"	27'-1"	25'-9"	24'-4"	29'-8"	27'-9"	26'-5"	25'-0"
	NI-90	29'-7"	27'-6"	26'-2"	24'-9"	30'-2"	28'-2"	26'-10"	25'-5"

Notes:

1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

NORDIC STRUCTURES

Maximum Floor Spans – S6.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 15 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	5/8 in. nailed-glued Canadian softwood plywood

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	14'-11"	14'-1"	13'-7"	-	15'-4"	14'-6"	14'-1"	-
	NI-40x	15'-11"	15'-0"	14'-6"	-	16'-4"	15'-5"	14'-11"	-
	NI-60	16'-1"	15'-2"	14'-8"	-	16'-6"	15'-7"	15'-1"	-
	NI-80	17'-1"	16'-1"	15'-6"	-	17'-5"	16'-5"	15'-10"	-
11-7/8"	NI-20	16'-9"	15'-10"	15'-4"	-	17'-4"	16'-4"	15'-10"	-
	NI-40x	17'-10"	16'-10"	16'-3"	-	18'-6"	17'-4"	16'-9"	-
	NI-60	18'-1"	17'-0"	16'-5"	-	18'-9"	17'-6"	16'-11"	-
	NI-80	19'-6"	18'-0"	17'-4"	-	20'-1"	18'-7"	17'-9"	-
	NI-90	19'-11"	18'-4"	17'-8"	-	20'-5"	18'-11"	18'-1"	-
14"	NI-40x	19'-10"	18'-4"	17'-8"	-	20'-6"	19'-1"	18'-3"	-
	NI-60	20'-2"	18'-8"	17'-11"	-	20'-10"	19'-4"	18'-6"	-
	NI-80	21'-8"	20'-0"	19'-1"	-	22'-4"	20'-8"	19'-9"	-
	NI-90	22'-1"	20'-5"	19'-6"	-	22'-9"	21'-0"	20'-1"	-
16"	NI-60	22'-0"	20'-4"	19'-6"	-	22'-9"	21'-1"	20'-2"	-
	NI-80	23'-7"	21'-10"	20'-10"	-	24'-4"	22'-6"	21'-6"	-
	NI-90	24'-1"	22'-2"	21'-2"	-	24'-9"	22'-11"	21'-10"	-

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-6"	15'-1"	14'-3"	-	16'-6"	15'-1"	14'-3"	-
	NI-40x	17'-9"	16'-10"	15'-11"	-	18'-2"	16'-11"	15'-11"	-
	NI-60	17'-11"	16'-11"	16'-2"	-	18'-5"	17'-2"	16'-2"	-
	NI-80	19'-3"	17'-10"	17'-3"	-	19'-8"	18'-3"	17'-7"	-
11-7/8"	NI-20	19'-4"	18'-0"	17'-1"	-	19'-9"	18'-1"	17'-1"	-
	NI-40x	20'-10"	19'-4"	18'-6"	-	21'-5"	19'-11"	19'-0"	-
	NI-60	21'-1"	19'-7"	18'-8"	-	21'-8"	20'-2"	19'-3"	-
	NI-80	22'-6"	20'-10"	19'-11"	-	23'-1"	21'-5"	20'-5"	-
	NI-90	23'-0"	21'-3"	20'-4"	-	23'-6"	21'-10"	20'-10"	-
14"	NI-40x	23'-5"	21'-8"	20'-9"	-	24'-0"	22'-5"	21'-5"	-
	NI-60	23'-9"	22'-0"	21'-0"	-	24'-5"	22'-8"	21'-8"	-
	NI-80	25'-4"	23'-6"	22'-5"	-	25'-11"	24'-1"	23'-0"	-
	NI-90	25'-10"	23'-11"	22'-9"	-	26'-5"	24'-6"	23'-4"	-
16"	NI-60	26'-2"	24'-3"	23'-2"	-	26'-11"	25'-0"	23'-11"	-
	NI-80	27'-11"	25'-10"	24'-7"	-	28'-7"	26'-6"	25'-3"	-
	NI-90	28'-5"	26'-3"	25'-0"	-	29'-0"	26'-11"	25'-8"	-

Notes:

1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

Maximum Floor Spans – S7.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 15 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	3/4 in. nailed-glued Canadian softwood plywood

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	15'-10"	15'-0"	14'-5"	13'-5"	16'-4"	15'-5"	14'-6"	13'-5"
	NI-40x	16'-11"	15'-11"	15'-4"	14'-9"	17'-4"	16'-4"	15'-9"	15'-1"
	NI-60	17'-1"	16'-1"	15'-6"	14'-10"	17'-6"	16'-6"	15'-11"	15'-3"
	NI-80	18'-1"	17'-0"	16'-4"	15'-8"	18'-7"	17'-4"	16'-8"	16'-0"
11-7/8"	NI-20	17'-10"	16'-10"	16'-2"	15'-7"	18'-5"	17'-4"	16'-9"	16'-1"
	NI-40x	19'-3"	17'-10"	17'-2"	16'-6"	19'-10"	18'-5"	17'-8"	16'-11"
	NI-60	19'-6"	18'-1"	17'-4"	16'-8"	20'-1"	18'-8"	17'-10"	17'-1"
	NI-80	20'-11"	19'-4"	18'-5"	17'-7"	21'-5"	19'-10"	18'-11"	17'-11"
	NI-90	21'-4"	19'-9"	18'-9"	17'-10"	21'-10"	20'-3"	19'-3"	18'-3"
14"	NI-40x	21'-4"	19'-9"	18'-10"	17'-11"	22'-0"	20'-5"	19'-6"	18'-6"
	NI-60	21'-8"	20'-1"	19'-2"	18'-2"	22'-4"	20'-9"	19'-9"	18'-9"
	NI-80	23'-3"	21'-6"	20'-5"	19'-4"	23'-10"	22'-1"	21'-0"	19'-11"
	NI-90	23'-9"	21'-11"	20'-10"	19'-8"	24'-3"	22'-6"	21'-5"	20'-3"
16"	NI-60	23'-7"	21'-10"	20'-10"	19'-9"	24'-4"	22'-7"	21'-7"	20'-5"
	NI-80	25'-4"	23'-5"	22'-3"	21'-1"	26'-0"	24'-1"	22'-11"	21'-8"
	NI-90	25'-10"	23'-10"	22'-8"	21'-5"	26'-5"	24'-6"	23'-4"	22'-0"

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-10"	15'-5"	14'-6"	13'-5"	16'-10"	15'-5"	14'-6"	13'-5"
	NI-40x	18'-7"	17'-2"	16'-3"	15'-2"	18'-10"	17'-2"	16'-3"	15'-2"
	NI-60	18'-10"	17'-6"	16'-6"	15'-5"	19'-1"	17'-6"	16'-6"	15'-5"
	NI-80	20'-2"	18'-9"	17'-11"	16'-10"	20'-7"	19'-2"	18'-2"	16'-10"
11-7/8"	NI-20	20'-1"	18'-5"	17'-5"	16'-2"	20'-1"	18'-5"	17'-5"	16'-2"
	NI-40x	21'-9"	20'-3"	19'-4"	17'-8"	22'-4"	20'-5"	19'-4"	17'-8"
	NI-60	22'-0"	20'-6"	19'-7"	18'-4"	22'-7"	20'-10"	19'-8"	18'-4"
	NI-80	23'-6"	21'-10"	20'-10"	19'-9"	24'-0"	22'-5"	21'-4"	20'-0"
	NI-90	24'-0"	22'-4"	21'-3"	20'-1"	24'-6"	22'-10"	21'-9"	20'-7"
14"	NI-40x	24'-4"	22'-8"	21'-8"	19'-5"	25'-0"	23'-2"	21'-9"	19'-5"
	NI-60	24'-9"	23'-0"	22'-0"	20'-9"	25'-5"	23'-8"	22'-4"	20'-10"
	NI-80	26'-5"	24'-6"	23'-4"	22'-1"	27'-0"	25'-2"	24'-0"	22'-8"
	NI-90	26'-11"	25'-0"	23'-10"	22'-6"	27'-5"	25'-7"	24'-5"	23'-1"
16"	NI-60	27'-2"	25'-4"	24'-2"	22'-10"	27'-11"	26'-1"	24'-9"	23'-1"
	NI-80	29'-0"	26'-11"	25'-8"	24'-3"	29'-7"	27'-7"	26'-4"	24'-11"
	NI-90	29'-6"	27'-5"	26'-1"	24'-8"	30'-1"	28'-1"	26'-9"	25'-4"

Notes:

1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

NORDIC STRUCTURES

Maximum Floor Spans – M2.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 20 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	5/8 in. nailed-glued oriented strand board (OSB) sheathing

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9'-1/2"	NI-20	15'-1"	14'-3"	13'-10"	-	15'-7"	14'-9"	14'-3"	-
	NI-40x	16'-2"	15'-3"	14'-8"	-	16'-7"	15'-8"	15'-1"	-
	NI-60	16'-4"	15'-4"	14'-10"	-	16'-9"	15'-9"	15'-3"	-
	NI-80	17'-3"	16'-3"	15'-8"	-	17'-8"	16'-7"	16'-0"	-
11'-7/8"	NI-20	17'-0"	16'-0"	15'-6"	-	17'-6"	16'-7"	16'-0"	-
	NI-40x	18'-2"	17'-1"	16'-6"	-	18'-9"	17'-6"	16'-11"	-
	NI-60	18'-5"	17'-3"	16'-8"	-	19'-0"	17'-8"	17'-1"	-
	NI-80	19'-9"	18'-3"	17'-7"	-	20'-4"	18'-10"	18'-0"	-
	NI-90	20'-2"	18'-8"	17'-10"	-	20'-9"	19'-2"	18'-4"	-
14"	NI-40x	20'-1"	18'-8"	17'-10"	-	20'-10"	19'-4"	18'-6"	-
	NI-60	20'-6"	18'-11"	18'-2"	-	21'-2"	19'-8"	18'-9"	-
	NI-80	21'-11"	20'-3"	19'-4"	-	22'-7"	20'-11"	20'-0"	-
	NI-90	22'-5"	20'-8"	19'-9"	-	23'-0"	21'-4"	20'-4"	-
16"	NI-60	22'-4"	20'-8"	19'-9"	-	23'-1"	21'-5"	20'-6"	-
	NI-80	23'-11"	22'-1"	21'-1"	-	24'-8"	22'-10"	21'-9"	-
	NI-90	24'-5"	22'-6"	21'-6"	-	25'-1"	23'-2"	22'-2"	-

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9'-1/2"	NI-20	16'-8"	15'-3"	14'-5"	-	16'-8"	15'-3"	14'-5"	-
	NI-40x	17'-11"	17'-0"	16'-1"	-	18'-5"	17'-1"	16'-1"	-
	NI-60	18'-2"	17'-1"	16'-4"	-	18'-8"	17'-4"	16'-4"	-
	NI-80	19'-5"	18'-0"	17'-5"	-	19'-10"	18'-5"	17'-8"	-
11'-7/8"	NI-20	19'-7"	18'-2"	17'-3"	-	19'-11"	18'-3"	17'-3"	-
	NI-40x	21'-1"	19'-7"	18'-8"	-	21'-8"	20'-2"	19'-0"	-
	NI-60	21'-4"	19'-9"	18'-11"	-	21'-11"	20'-5"	19'-6"	-
	NI-80	22'-9"	21'-1"	20'-2"	-	23'-3"	21'-8"	20'-8"	-
	NI-90	23'-3"	21'-6"	20'-6"	-	23'-9"	22'-0"	21'-0"	-
14"	NI-40x	23'-8"	21'-11"	20'-11"	-	24'-4"	22'-8"	20'-11"	-
	NI-60	24'-0"	22'-3"	21'-3"	-	24'-8"	22'-11"	21'-11"	-
	NI-80	25'-7"	23'-9"	22'-7"	-	26'-2"	24'-4"	23'-3"	-
	NI-90	26'-1"	24'-2"	23'-0"	-	26'-8"	24'-9"	23'-7"	-
16"	NI-60	26'-5"	24'-6"	23'-5"	-	27'-2"	25'-3"	24'-2"	-
	NI-80	28'-2"	26'-1"	24'-10"	-	28'-10"	26'-9"	25'-6"	-
	NI-90	28'-8"	26'-6"	25'-3"	-	29'-3"	27'-2"	25'-11"	-

Notes:

1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

Maximum Floor Spans – M4.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 20 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	3/4 in. nailed-glued oriented strand board (OSB) sheathing

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	15'-11"	15'-0"	14'-6"	13'-5"	16'-5"	15'-5"	14'-6"	13'-5"
	NI-40x	17'-0"	16'-0"	15'-5"	14'-10"	17'-5"	16'-5"	15'-10"	14'-11"
	NI-60	17'-2"	16'-2"	15'-7"	14'-11"	17'-7"	16'-7"	16'-0"	15'-4"
	NI-80	18'-3"	17'-1"	16'-5"	15'-9"	18'-8"	17'-5"	16'-9"	16'-1"
11-7/8"	NI-20	17'-11"	16'-11"	16'-3"	15'-8"	18'-7"	17'-5"	16'-10"	16'-1"
	NI-40x	19'-4"	17'-11"	17'-3"	16'-7"	19'-11"	18'-6"	17'-9"	17'-0"
	NI-60	19'-7"	18'-2"	17'-6"	16'-9"	20'-2"	18'-9"	17'-11"	17'-2"
	NI-80	21'-1"	19'-6"	18'-6"	17'-7"	21'-7"	20'-0"	19'-0"	18'-0"
	NI-90	21'-6"	19'-10"	18'-11"	17'-11"	22'-0"	20'-4"	19'-5"	18'-4"
14"	NI-40x	21'-5"	19'-11"	18'-11"	18'-0"	22'-1"	20'-7"	19'-7"	18'-7"
	NI-60	21'-10"	20'-2"	19'-3"	18'-3"	22'-6"	20'-10"	19'-11"	18'-10"
	NI-80	23'-5"	21'-7"	20'-7"	19'-5"	24'-0"	22'-3"	21'-2"	20'-0"
	NI-90	23'-10"	22'-1"	21'-0"	19'-10"	24'-5"	22'-7"	21'-6"	20'-4"
16"	NI-60	23'-9"	22'-0"	21'-0"	19'-10"	24'-6"	22'-9"	21'-8"	20'-7"
	NI-80	25'-6"	23'-7"	22'-5"	21'-2"	26'-2"	24'-3"	23'-1"	21'-10"
	NI-90	26'-0"	24'-0"	22'-10"	21'-6"	26'-7"	24'-8"	23'-5"	22'-2"

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-10"	15'-5"	14'-6"	13'-5"	16'-10"	15'-5"	14'-6"	13'-5"
	NI-40x	18'-8"	17'-2"	16'-3"	14'-11"	18'-10"	17'-2"	16'-3"	14'-11"
	NI-60	18'-11"	17'-6"	16'-6"	15'-5"	19'-2"	17'-6"	16'-6"	15'-5"
	NI-80	20'-3"	18'-10"	17'-11"	16'-10"	20'-8"	19'-3"	18'-2"	16'-10"
11-7/8"	NI-20	20'-1"	18'-5"	17'-5"	16'-1"	20'-1"	18'-5"	17'-5"	16'-1"
	NI-40x	21'-10"	20'-4"	19'-0"	17'-0"	22'-5"	20'-6"	19'-0"	17'-0"
	NI-60	22'-1"	20'-7"	19'-8"	18'-4"	22'-8"	20'-10"	19'-8"	18'-4"
	NI-80	23'-8"	22'-0"	20'-11"	19'-10"	24'-1"	22'-6"	21'-6"	20'-0"
	NI-90	24'-1"	22'-5"	21'-4"	20'-2"	24'-7"	22'-11"	21'-10"	20'-7"
14"	NI-40x	24'-5"	22'-9"	20'-11"	18'-8"	25'-1"	22'-11"	20'-11"	18'-8"
	NI-60	24'-10"	23'-2"	22'-1"	20'-10"	25'-6"	23'-8"	22'-4"	20'-10"
	NI-80	26'-6"	24'-8"	23'-6"	22'-2"	27'-1"	25'-3"	24'-1"	22'-9"
	NI-90	27'-0"	25'-1"	23'-11"	22'-7"	27'-6"	25'-8"	24'-6"	23'-2"
16"	NI-60	27'-3"	25'-5"	24'-3"	22'-11"	28'-0"	26'-2"	24'-9"	23'-1"
	NI-80	29'-1"	27'-1"	25'-9"	24'-4"	29'-8"	27'-9"	26'-5"	25'-0"
	NI-90	29'-7"	27'-6"	26'-2"	24'-9"	30'-2"	28'-2"	26'-10"	25'-5"

Notes:

1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

Maximum Floor Spans – M6.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 20 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	5/8 in. nailed-glued Canadian softwood plywood

Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	14'-11"	14'-1"	13'-7"	-	15'-4"	14'-6"	14'-1"	-
	NI-40x	15'-11"	15'-0"	14'-6"	-	16'-4"	15'-5"	14'-11"	-
	NI-60	16'-1"	15'-2"	14'-8"	-	16'-6"	15'-7"	15'-1"	-
	NI-80	17'-1"	16'-1"	15'-6"	-	17'-5"	16'-5"	15'-10"	-
11-7/8"	NI-20	16'-9"	15'-10"	15'-4"	-	17'-4"	16'-4"	15'-10"	-
	NI-40x	17'-10"	16'-10"	16'-3"	-	18'-6"	17'-4"	16'-9"	-
	NI-60	18'-1"	17'-0"	16'-5"	-	18'-9"	17'-6"	16'-11"	-
	NI-80	19'-6"	18'-0"	17'-4"	-	20'-1"	18'-7"	17'-9"	-
	NI-90	19'-11"	18'-4"	17'-8"	-	20'-5"	18'-11"	18'-1"	-
14"	NI-40x	19'-10"	18'-4"	17'-8"	-	20'-6"	19'-1"	18'-3"	-
	NI-60	20'-2"	18'-8"	17'-11"	-	20'-10"	19'-4"	18'-6"	-
	NI-80	21'-8"	20'-0"	19'-1"	-	22'-4"	20'-8"	19'-9"	-
	NI-90	22'-1"	20'-5"	19'-6"	-	22'-9"	21'-0"	20'-1"	-
16"	NI-60	22'-0"	20'-4"	19'-6"	-	22'-9"	21'-1"	20'-2"	-
	NI-80	23'-7"	21'-10"	20'-10"	-	24'-4"	22'-6"	21'-6"	-
	NI-90	24'-1"	22'-2"	21'-2"	-	24'-9"	22'-11"	21'-10"	-

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-6"	15'-1"	14'-3"	-	16'-6"	15'-1"	14'-3"	-
	NI-40x	17'-9"	16'-10"	15'-11"	-	18'-2"	16'-11"	15'-11"	-
	NI-60	17'-11"	16'-11"	16'-2"	-	18'-5"	17'-2"	16'-2"	-
	NI-80	19'-3"	17'-10"	17'-3"	-	19'-8"	18'-3"	17'-7"	-
11-7/8"	NI-20	19'-4"	18'-0"	17'-1"	-	19'-9"	18'-1"	17'-1"	-
	NI-40x	20'-10"	19'-4"	18'-6"	-	21'-5"	19'-11"	19'-0"	-
	NI-60	21'-1"	19'-7"	18'-8"	-	21'-8"	20'-2"	19'-3"	-
	NI-80	22'-6"	20'-10"	19'-11"	-	23'-1"	21'-5"	20'-5"	-
	NI-90	23'-0"	21'-3"	20'-4"	-	23'-6"	21'-10"	20'-10"	-
14"	NI-40x	23'-5"	21'-8"	20'-9"	-	24'-0"	22'-5"	20'-11"	-
	NI-60	23'-9"	22'-0"	21'-0"	-	24'-5"	22'-8"	21'-8"	-
	NI-80	25'-4"	23'-6"	22'-5"	-	25'-11"	24'-1"	23'-0"	-
	NI-90	25'-10"	23'-11"	22'-9"	-	26'-5"	24'-6"	23'-4"	-
16"	NI-60	26'-2"	24'-3"	23'-2"	-	26'-11"	25'-0"	23'-11"	-
	NI-80	27'-11"	25'-10"	24'-7"	-	28'-7"	26'-6"	25'-3"	-
	NI-90	28'-5"	26'-3"	25'-0"	-	29'-0"	26'-11"	25'-8"	-

Notes:

- The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
- For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
- Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
- Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
- Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.

NORDIC STRUCTURES

Maximum Floor Spans – M7.1

Design Criteria

Spans:	Simple span
Loads:	Live load = 40 psf and dead load = 20 psf
Deflection limits:	L/480 under live load and L/240 under total load
Sheathing:	3/4 in. nailed-glued Canadian softwood plywood


Maximum Floor Spans

Joist depth	Joist series	Bare				1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	15'-10"	15'-0"	14'-5"	13'-5"	16'-4"	15'-5"	14'-6"	13'-5"
	NI-40x	16'-11"	15'-11"	15'-4"	14'-9"	17'-4"	16'-4"	15'-9"	14'-11"
	NI-60	17'-1"	16'-1"	15'-6"	14'-10"	17'-6"	16'-6"	15'-11"	15'-3"
	NI-80	18'-1"	17'-0"	16'-4"	15'-8"	18'-7"	17'-4"	16'-8"	16'-0"
11-7/8"	NI-20	17'-10"	16'-10"	16'-2"	15'-7"	18'-5"	17'-4"	16'-9"	16'-1"
	NI-40x	19'-3"	17'-10"	17'-2"	16'-6"	19'-10"	18'-5"	17'-8"	16'-11"
	NI-60	19'-6"	18'-1"	17'-4"	16'-8"	20'-1"	18'-8"	17'-10"	17'-1"
	NI-80	20'-11"	19'-4"	18'-5"	17'-7"	21'-5"	19'-10"	18'-11"	17'-11"
	NI-90	21'-4"	19'-9"	18'-9"	17'-10"	21'-10"	20'-3"	19'-3"	18'-3"
14"	NI-40x	21'-4"	19'-9"	18'-10"	17'-11"	22'-0"	20'-5"	19'-6"	18'-6"
	NI-60	21'-8"	20'-1"	19'-2"	18'-2"	22'-4"	20'-9"	19'-9"	18'-9"
	NI-80	23'-3"	21'-6"	20'-5"	19'-4"	23'-10"	22'-1"	21'-0"	19'-11"
	NI-90	23'-9"	21'-11"	20'-10"	19'-8"	24'-3"	22'-6"	21'-5"	20'-3"
16"	NI-60	23'-7"	21'-10"	20'-10"	19'-9"	24'-4"	22'-7"	21'-7"	20'-5"
	NI-80	25'-4"	23'-5"	22'-3"	21'-1"	26'-0"	24'-1"	22'-11"	21'-8"
	NI-90	25'-10"	23'-10"	22'-8"	21'-5"	26'-5"	24'-6"	23'-4"	22'-0"

Joist depth	Joist series	Mid-span blocking with 1x4 inch strap				Mid-span blocking and 1/2 in. gypsum ceiling			
		On centre spacing				On centre spacing			
		12"	16"	19.2"	24"	12"	16"	19.2"	24"
9-1/2"	NI-20	16'-10"	15'-5"	14'-6"	13'-5"	16'-10"	15'-5"	14'-6"	13'-5"
	NI-40x	18'-7"	17'-2"	16'-3"	14'-11"	18'-10"	17'-2"	16'-3"	14'-11"
	NI-60	18'-10"	17'-6"	16'-6"	15'-5"	19'-1"	17'-6"	16'-6"	15'-5"
	NI-80	20'-2"	18'-9"	17'-11"	16'-10"	20'-7"	19'-2"	18'-2"	16'-10"
11-7/8"	NI-20	20'-1"	18'-5"	17'-5"	16'-1"	20'-1"	18'-5"	17'-5"	16'-1"
	NI-40x	21'-9"	20'-3"	19'-0"	17'-0"	22'-4"	20'-5"	19'-0"	17'-0"
	NI-60	22'-0"	20'-6"	19'-7"	18'-4"	22'-7"	20'-10"	19'-8"	18'-4"
	NI-80	23'-6"	21'-10"	20'-10"	19'-9"	24'-0"	22'-5"	21'-4"	20'-0"
	NI-90	24'-0"	22'-4"	21'-3"	20'-1"	24'-6"	22'-10"	21'-9"	20'-7"
14"	NI-40x	24'-4"	22'-8"	20'-11"	18'-8"	25'-0"	22'-11"	20'-11"	18'-8"
	NI-60	24'-9"	23'-0"	22'-0"	20'-9"	25'-5"	23'-8"	22'-4"	20'-10"
	NI-80	26'-5"	24'-6"	23'-4"	22'-1"	27'-0"	25'-2"	24'-0"	22'-8"
	NI-90	26'-11"	25'-0"	23'-10"	22'-6"	27'-5"	25'-7"	24'-5"	23'-1"
16"	NI-60	27'-2"	25'-4"	24'-2"	22'-10"	27'-11"	26'-1"	24'-9"	23'-1"
	NI-80	29'-0"	26'-11"	25'-8"	24'-3"	29'-7"	27'-7"	26'-4"	24'-11"
	NI-90	29'-6"	27'-5"	26'-1"	24'-8"	30'-1"	28'-1"	26'-9"	25'-4"

Notes:



1. The tabulated clear spans are based on CSA O86-14 and NBC 2015, and are applicable to residential floor construction meeting the above design criteria.
2. For multiple-span applications, the end spans shall be 40% or more of the adjacent span.
3. Minimum bearing length shall be 1-3/4 inch for end bearings, and 3-1/2 inches for intermediate bearings.
4. Bearing stiffeners are not required when I-joists are used in accordance with this table, except as required for hangers.
5. Nordic I-joists are listed in CCMC Evaluation Report 13032-R and APA Product Report PR-L274C.



- Notes:**
- 1. To prevent interference with plumbing, a joist may be shifted up to 3 inches if the edge of the floor panel is supported, and the span rating is not exceeded.
 - 2. In all other cases, an additional joist is required.

All nails shown in the details are assumed to be common nails unless otherwise noted. Nails shall have a diameter not less than 0.128 inch for 2-1/2-inch nails, or 0.144 inch for 3-inch nails. Individual components not shown to scale for clarity.

TITLE		DRAWING	
Allowance for Piping		7c	
CATEGORY	SCALE	DATE	PAGE
Openings for Vertical Elements	-	2020-10-01	3.10



- Notes:**
1. Blocking required at bearing for lateral support, not shown for clarity.
 2. The maximum dimensions for a notch on the side of the top flange are 4-inch length by 1/2-inch depth for flange width of 2-1/2 inches, and 4-inch length by 1-inch depth for flange width of 3-1/2 inches.
 3. This detail applies to simple-span joists and multiple-span joists where the notch is located at the end half-span.
 4. For other applications, contact Nordic Structures.

All nails shown in the details are assumed to be common nails unless otherwise noted. Nails shall have a diameter not less than 0.128 inch for 2-1/2-inch nails, or 0.144 inch for 3-inch nails. Individual components not shown to scale for clarity.