

STEEL QUEEN FABRICATED SINKS - DUAL MOUNT







QDLF2233/8

COPC®

20 gauge, 18-8 stainless steel Topmount or undermount model

Outside sink dimensions 22" FB x 33 1/4" LR

Equal size bowl dimensions 17" FB x 15" LR x 8" DP


36" cabinet - recommended minimum for Kindred topmount method


39" cabinet - recommended minimum for Kindred undermount method

33" cabinet - minimum to accept sink bowls (refer to Table of Contents page)



cUPC®





20 gauge, 10-8 stainless steel Topmount or undermount model

Outside sink dimensions 20 9/16" FB x 31 1/4" LR


Equal size bowl dimensions 16" FB x 14" LR x 8" DP

33" cabinet - recommended minimum for Kindred topmount method

36" cabinet - recommended minimum for Kindred undermount method

33" cabinet - minimum to accept sink bowls (refer to Table of Contents page)





QCLF2031R/8

cUPC®


20 gauge, 18-8 stainless steel Topmount or undermount model


Outside sink dimensions 20 9/16" FB x 31 1/4" LR Large bowl dimensions 16" FB x 18" LRx 8" DP Small bowl dimensions 16" FB x 10" LR x 8" DP

33" cabinet - recommended minimum for Kindred topmount method

36" cabinet - recommended minimum for Kindred undermount method

33" cabinet - minimum to accept sink bowls (refer to Table of Contents page)





OCLF2027R/8

cUPC

Е

OF

В


20 gauge, 18-8 stainless steel Topmount or undermount model


Outside sink dimensions 20 9/16" FB x 27 1/4" LR

Large bowl dimensions 16" FB x 14" LR x 8" DP Small bowl dimensions 16" FB x 10" LR x 8" DP

30" cabinet - recommended minimum for Kindred topmount method

33" cabinet - recommended minimum for Kindred undermount method 27" cabinet - minimum to accept sink bowls (refer to Table of Contents page)





QCLF2039DBR/8 cUPC®

20 gauge, 18-8 stainless steel Topmount or undermount model

Outside sink dimensions 20 9/16" FB x 39 3/8" LR

Large bowl dimensions 16" FB x 14" LR x 8" DP Small bowl dimensions 16" FB x 10" LR x 8" DP

30" cabinet - recommended minimum for Kindred topmount method 45" cabinet - recommended minimum for Kindred undermount method 27" cabinet - minimum to accept sink bowls (refer to Table of Contents page)