

CSA F280-12 Residential Heat Loss and Heat Gain Calculations																																																												
Formula Sheet (For Air Leakage / Ventilation Calculation)																																																												
LO#: 66855	Model: 25-2	Builder: GOLD PARK HOMES	Date: 2016-08-08																																																									
Volume Calculation			Air Change & Delta T Data																																																									
House Volume <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Level</th> <th>Floor Area (ft²)</th> <th>Floor Height (ft)</th> <th>Volume (ft³)</th> </tr> </thead> <tbody> <tr> <td>Bsmt</td> <td>850</td> <td>9</td> <td>7650</td> </tr> <tr> <td>First</td> <td>850</td> <td>10</td> <td>8500</td> </tr> <tr> <td>Second</td> <td>1014</td> <td>9</td> <td>9126</td> </tr> <tr> <td>Third</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td>Fourth</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>25,276.0 ft³</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>715.7 m³</td> </tr> </tbody> </table>			Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)	Bsmt	850	9	7650	First	850	10	8500	Second	1014	9	9126	Third	0	9	0	Fourth	0	9	0	Total:			25,276.0 ft³	Total:			715.7 m³	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">WINTER NATURAL AIR CHANGE RATE</td> <td style="width: 30%;">0.322</td> </tr> <tr> <td>SUMMER NATURAL AIR CHANGE RATE</td> <td>0.095</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="5" style="text-align: center;">Design Temperature Difference</th> </tr> <tr> <th></th> <th>Tin °C</th> <th>Tout °C</th> <th>ΔT °C</th> <th>ΔT °F</th> </tr> </thead> <tbody> <tr> <td>Winter DTDh</td> <td>22</td> <td>-20</td> <td>42</td> <td>76</td> </tr> <tr> <td>Summer DTDc</td> <td>22</td> <td>31</td> <td>9</td> <td>16</td> </tr> </tbody> </table>		WINTER NATURAL AIR CHANGE RATE	0.322	SUMMER NATURAL AIR CHANGE RATE	0.095	Design Temperature Difference						Tin °C	Tout °C	ΔT °C	ΔT °F	Winter DTDh	22	-20	42	76	Summer DTDc	22	31	9	16
Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)																																																									
Bsmt	850	9	7650																																																									
First	850	10	8500																																																									
Second	1014	9	9126																																																									
Third	0	9	0																																																									
Fourth	0	9	0																																																									
Total:			25,276.0 ft³																																																									
Total:			715.7 m³																																																									
WINTER NATURAL AIR CHANGE RATE	0.322																																																											
SUMMER NATURAL AIR CHANGE RATE	0.095																																																											
Design Temperature Difference																																																												
	Tin °C	Tout °C	ΔT °C	ΔT °F																																																								
Winter DTDh	22	-20	42	76																																																								
Summer DTDc	22	31	9	16																																																								
5.2.3.1 Heat Loss due to Air Leakage			6.2.6 Sensible Gain due to Air Leakage																																																									
$HL_{airb} = LR_{airh} \times \frac{V_b}{3.6} \times DTD_h \times 1.2$ 0.322 x 198.82 x 42 °C x 1.2 = 3244 W = 11067 Btu/h			$HG_{salb} = LR_{airc} \times \frac{V_b}{3.6} \times DTD_c \times 1.2$ = 0.095 x 198.82 x 9 °C x 1.2 = 201 W = 687 Btu/h																																																									
5.2.3.2 Heat Loss due to Mechanical Ventilation			6.2.7 Sensible heat Gain due to Ventilation																																																									
$HL_{vairb} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 77 CFM x 76 °F x 1.08 x 0.34 = 2149 Btu/h			$HL_{vairb} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 77 CFM x 16 °F x 1.08 x 0.34 = 452 Btu/h																																																									
5.2.3.3 Calculation of Air Change Heat Loss for Each Room (Floor Multiplier Section)																																																												
$HL_{airr} = Level\ Factor \times HL_{airbv} \times \{(HL_{agcr} + HL_{bgcr}) \div (HL_{agclevel} + HL_{bgclevel})\}$																																																												
Level	Level Factor (LF)	HLairve Air Leakage + Ventilation Heat Loss (Btu/h)	Level Conductive Heat Loss: (HL _{clevel})	Air Leakage Heat Loss Multiplier (LF x HLairbv / HLlevel)																																																								
1	0.5	11,067	7,944	0.697																																																								
2	0.3		9,015	0.368																																																								
3	0.2		9,283	0.238																																																								
4	0		0	0.000																																																								
5	0		0	0.000																																																								
*HLairbv = Air leakage heat loss + ventilation heat loss *For a balanced or supply only ventilation system HLairve = 0																																																												

CSA F280-12 Residential Heat Loss and Heat Gain Calculations																																																												
Formula Sheet (For Air Leakage / Ventilation Calculation)																																																												
LO#: 66856	Model: 25-2	Builder: GOLD PARK HOMES	Date: 2016-08-08																																																									
Volume Calculation			Air Change & Delta T Data																																																									
House Volume <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Level</th> <th>Floor Area (ft²)</th> <th>Floor Height (ft)</th> <th>Volume (ft³)</th> </tr> </thead> <tbody> <tr> <td>Bsmt</td> <td>850</td> <td>9</td> <td>7650</td> </tr> <tr> <td>First</td> <td>850</td> <td>10</td> <td>8075</td> </tr> <tr> <td>Second</td> <td>1014</td> <td>9</td> <td>9126</td> </tr> <tr> <td>Third</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td>Fourth</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>24,851.0 ft³</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>703.7 m³</td> </tr> </tbody> </table>			Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)	Bsmt	850	9	7650	First	850	10	8075	Second	1014	9	9126	Third	0	9	0	Fourth	0	9	0	Total:			24,851.0 ft³	Total:			703.7 m³	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 70%;">WINTER NATURAL AIR CHANGE RATE</td> <td style="width: 30%;">0.322</td> </tr> <tr> <td>SUMMER NATURAL AIR CHANGE RATE</td> <td>0.095</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="5" style="text-align: center;">Design Temperature Difference</th> </tr> <tr> <th></th> <th>Tin °C</th> <th>Tout °C</th> <th>ΔT °C</th> <th>ΔT °F</th> </tr> <tr> <td>Winter DTDh</td> <td>22</td> <td>-20</td> <td>42</td> <td>76</td> </tr> <tr> <td>Summer DTDc</td> <td>22</td> <td>31</td> <td>9</td> <td>16</td> </tr> </table>		WINTER NATURAL AIR CHANGE RATE	0.322	SUMMER NATURAL AIR CHANGE RATE	0.095	Design Temperature Difference						Tin °C	Tout °C	ΔT °C	ΔT °F	Winter DTDh	22	-20	42	76	Summer DTDc	22	31	9	16
Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)																																																									
Bsmt	850	9	7650																																																									
First	850	10	8075																																																									
Second	1014	9	9126																																																									
Third	0	9	0																																																									
Fourth	0	9	0																																																									
Total:			24,851.0 ft³																																																									
Total:			703.7 m³																																																									
WINTER NATURAL AIR CHANGE RATE	0.322																																																											
SUMMER NATURAL AIR CHANGE RATE	0.095																																																											
Design Temperature Difference																																																												
	Tin °C	Tout °C	ΔT °C	ΔT °F																																																								
Winter DTDh	22	-20	42	76																																																								
Summer DTDc	22	31	9	16																																																								
5.2.3.1 Heat Loss due to Air Leakage			6.2.6 Sensible Gain due to Air Leakage																																																									
$HL_{airb} = LR_{airh} \times \frac{V_b}{3.6} \times DTD_h \times 1.2$ 0.322 x 195.47 x 42 °C x 1.2 = 3189 W = 10881 Btu/h			$HG_{salb} = LR_{airc} \times \frac{V_b}{3.6} \times DTD_c \times 1.2$ = 0.095 x 195.47 x 9 °C x 1.2 = 198 W = 676 Btu/h																																																									
5.2.3.2 Heat Loss due to Mechanical Ventilation			6.2.7 Sensible heat Gain due to Ventilation																																																									
$HL_{vairb} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 77 CFM x 76 °F x 1.08 x 0.34 = 2149 Btu/h			$HL_{vairb} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 77 CFM x 16 °F x 1.08 x 0.34 = 452 Btu/h																																																									
5.2.3.3 Calculation of Air Change Heat Loss for Each Room (Floor Multiplier Section)																																																												
$HL_{airr} = Level\ Factor \times HL_{airbv} \times \{(HL_{agcr} + HL_{bgcr}) \div (HL_{agclevel} + HL_{bgclevel})\}$																																																												
Level	Level Factor (LF)	HLairve Air Leakage + Ventilation Heat Loss (Btu/h)	Level Conductive Heat Loss: (HL _{clevel})	Air Leakage Heat Loss Multiplier (LF x HLairbv / HLlevel)																																																								
1	0.5	10,881	7,944	0.685																																																								
2	0.3		9,224	0.354																																																								
3	0.2		9,283	0.234																																																								
4	0		0	0.000																																																								
5	0		0	0.000																																																								
*HLairbv = Air leakage heat loss + ventilation heat loss *For a balanced or supply only ventilation system HLairve = 0																																																												

CSA F280-12 Residential Heat Loss and Heat Gain Calculations																																																												
Formula Sheet (For Air Leakage / Ventilation Calculation)																																																												
LO#: 66857	Model: 25-3	Builder: GOLD PARK HOMES	Date: 2016-08-08																																																									
Volume Calculation			Air Change & Delta T Data																																																									
House Volume <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Level</th> <th>Floor Area (ft²)</th> <th>Floor Height (ft)</th> <th>Volume (ft³)</th> </tr> </thead> <tbody> <tr> <td>Bsmt</td> <td>917</td> <td>9</td> <td>8253</td> </tr> <tr> <td>First</td> <td>917</td> <td>9</td> <td>8253</td> </tr> <tr> <td>Second</td> <td>1100</td> <td>9</td> <td>9900</td> </tr> <tr> <td>Third</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td>Fourth</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>26,406.0 ft³</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>747.7 m³</td> </tr> </tbody> </table>			Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)	Bsmt	917	9	8253	First	917	9	8253	Second	1100	9	9900	Third	0	9	0	Fourth	0	9	0	Total:			26,406.0 ft³	Total:			747.7 m³	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">WINTER NATURAL AIR CHANGE RATE</td> <td style="width: 20%;">0.300</td> </tr> <tr> <td>SUMMER NATURAL AIR CHANGE RATE</td> <td>0.091</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th colspan="5" style="text-align: center;">Design Temperature Difference</th> </tr> <tr> <th></th> <th>Tin °C</th> <th>Tout °C</th> <th>ΔT °C</th> <th>ΔT °F</th> </tr> </thead> <tbody> <tr> <td>Winter DTDh</td> <td>22</td> <td>-20</td> <td>42</td> <td>76</td> </tr> <tr> <td>Summer DTDc</td> <td>23</td> <td>31</td> <td>8</td> <td>15</td> </tr> </tbody> </table>		WINTER NATURAL AIR CHANGE RATE	0.300	SUMMER NATURAL AIR CHANGE RATE	0.091	Design Temperature Difference						Tin °C	Tout °C	ΔT °C	ΔT °F	Winter DTDh	22	-20	42	76	Summer DTDc	23	31	8	15
Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)																																																									
Bsmt	917	9	8253																																																									
First	917	9	8253																																																									
Second	1100	9	9900																																																									
Third	0	9	0																																																									
Fourth	0	9	0																																																									
Total:			26,406.0 ft³																																																									
Total:			747.7 m³																																																									
WINTER NATURAL AIR CHANGE RATE	0.300																																																											
SUMMER NATURAL AIR CHANGE RATE	0.091																																																											
Design Temperature Difference																																																												
	Tin °C	Tout °C	ΔT °C	ΔT °F																																																								
Winter DTDh	22	-20	42	76																																																								
Summer DTDc	23	31	8	15																																																								
5.2.3.1 Heat Loss due to Air Leakage			6.2.6 Sensible Gain due to Air Leakage																																																									
$HL_{airb} = LR_{airh} \times \frac{V_b}{3.6} \times DTD_h \times 1.2$ 0.300 x 207.70 x 42 °C x 1.2 = 3157 W = 10772 Btu/h			$HG_{salb} = LR_{airc} \times \frac{V_b}{3.6} \times DTD_c \times 1.2$ = 0.091 x 207.70 x 8 °C x 1.2 = 189 W = 645 Btu/h																																																									
5.2.3.2 Heat Loss due to Mechanical Ventilation			6.2.7 Sensible heat Gain due to Ventilation																																																									
$HL_{vaib} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 77 CFM x 76 °F x 1.08 x 0.34 = 2149 Btu/h			$HL_{vaib} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 77 CFM x 15 °F x 1.08 x 0.34 = 424 Btu/h																																																									
5.2.3.3 Calculation of Air Change Heat Loss for Each Room (Floor Multiplier Section)																																																												
$HL_{airr} = Level\ Factor \times HL_{airbv} \times \{(HL_{agcr} + HL_{bgcr}) \div (HL_{agclevel} + HL_{bgclevel})\}$ <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Level</th> <th>Level Factor (LF)</th> <th>HLairve Air Leakage + Ventilation Heat Loss (Btu/h)</th> <th>Level Conductive Heat Loss: (HL_{clevel})</th> <th>Air Leakage Heat Loss Multiplier (LF x HLairbv / HLlevel)</th> </tr> </thead> <tbody> <tr> <td>1</td> <td>0.5</td> <td rowspan="5" style="text-align: center; vertical-align: middle;">10,772</td> <td>7,961</td> <td>0.677</td> </tr> <tr> <td>2</td> <td>0.3</td> <td>9,350</td> <td>0.346</td> </tr> <tr> <td>3</td> <td>0.2</td> <td>9,678</td> <td>0.223</td> </tr> <tr> <td>4</td> <td>0</td> <td>0</td> <td>0.000</td> </tr> <tr> <td>5</td> <td>0</td> <td>0</td> <td>0.000</td> </tr> </tbody> </table> *HLairbv = Air leakage heat loss + ventilation heat loss *For a balanced or supply only ventilation system HLairve = 0					Level	Level Factor (LF)	HLairve Air Leakage + Ventilation Heat Loss (Btu/h)	Level Conductive Heat Loss: (HL _{clevel})	Air Leakage Heat Loss Multiplier (LF x HLairbv / HLlevel)	1	0.5	10,772	7,961	0.677	2	0.3	9,350	0.346	3	0.2	9,678	0.223	4	0	0	0.000	5	0	0	0.000																														
Level	Level Factor (LF)	HLairve Air Leakage + Ventilation Heat Loss (Btu/h)	Level Conductive Heat Loss: (HL _{clevel})	Air Leakage Heat Loss Multiplier (LF x HLairbv / HLlevel)																																																								
1	0.5	10,772	7,961	0.677																																																								
2	0.3		9,350	0.346																																																								
3	0.2		9,678	0.223																																																								
4	0		0	0.000																																																								
5	0		0	0.000																																																								

CSA F280-12 Residential Heat Loss and Heat Gain Calculations																																																												
Formula Sheet (For Air Leakage / Ventilation Calculation)																																																												
LO#: 66858	Model: 25-3	Builder: GOLD PARK HOMES	Date: 2016-08-08																																																									
Volume Calculation			Air Change & Delta T Data																																																									
House Volume <table border="1" style="width: 100%; border-collapse: collapse;"> <thead> <tr> <th>Level</th> <th>Floor Area (ft²)</th> <th>Floor Height (ft)</th> <th>Volume (ft³)</th> </tr> </thead> <tbody> <tr> <td>Bsmt</td> <td>917</td> <td>9</td> <td>8253</td> </tr> <tr> <td>First</td> <td>917</td> <td>9</td> <td>8253</td> </tr> <tr> <td>Second</td> <td>1100</td> <td>9</td> <td>9900</td> </tr> <tr> <td>Third</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td>Fourth</td> <td>0</td> <td>9</td> <td>0</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>26,406.0 ft³</td> </tr> <tr> <td colspan="3" style="text-align: right;">Total:</td> <td>747.7 m³</td> </tr> </tbody> </table>			Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)	Bsmt	917	9	8253	First	917	9	8253	Second	1100	9	9900	Third	0	9	0	Fourth	0	9	0	Total:			26,406.0 ft³	Total:			747.7 m³	<table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <td style="width: 80%;">WINTER NATURAL AIR CHANGE RATE</td> <td style="width: 20%;">0.300</td> </tr> <tr> <td>SUMMER NATURAL AIR CHANGE RATE</td> <td>0.091</td> </tr> </table> <table border="1" style="width: 100%; border-collapse: collapse;"> <tr> <th colspan="5" style="text-align: center;">Design Temperature Difference</th> </tr> <tr> <th></th> <th>Tin °C</th> <th>Tout °C</th> <th>ΔT °C</th> <th>ΔT °F</th> </tr> <tr> <td>Winter DTDh</td> <td>22</td> <td>-20</td> <td>42</td> <td>76</td> </tr> <tr> <td>Summer DTDc</td> <td>23</td> <td>31</td> <td>8</td> <td>15</td> </tr> </table>		WINTER NATURAL AIR CHANGE RATE	0.300	SUMMER NATURAL AIR CHANGE RATE	0.091	Design Temperature Difference						Tin °C	Tout °C	ΔT °C	ΔT °F	Winter DTDh	22	-20	42	76	Summer DTDc	23	31	8	15
Level	Floor Area (ft²)	Floor Height (ft)	Volume (ft³)																																																									
Bsmt	917	9	8253																																																									
First	917	9	8253																																																									
Second	1100	9	9900																																																									
Third	0	9	0																																																									
Fourth	0	9	0																																																									
Total:			26,406.0 ft³																																																									
Total:			747.7 m³																																																									
WINTER NATURAL AIR CHANGE RATE	0.300																																																											
SUMMER NATURAL AIR CHANGE RATE	0.091																																																											
Design Temperature Difference																																																												
	Tin °C	Tout °C	ΔT °C	ΔT °F																																																								
Winter DTDh	22	-20	42	76																																																								
Summer DTDc	23	31	8	15																																																								
5.2.3.1 Heat Loss due to Air Leakage			6.2.6 Sensible Gain due to Air Leakage																																																									
$HL_{airb} = LR_{airh} \times \frac{V_b}{3.6} \times DTD_h \times 1.2$ 0.300 x 207.70 x 42 °C x 1.2 = 3157 W = 10772 Btu/h			$HG_{salb} = LR_{airc} \times \frac{V_b}{3.6} \times DTD_c \times 1.2$ = 0.091 x 207.70 x 8 °C x 1.2 = 189 W = 645 Btu/h																																																									
5.2.3.2 Heat Loss due to Mechanical Ventilation			6.2.7 Sensible heat Gain due to Ventilation																																																									
$HL_{vaib} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 95 CFM x 76 °F x 1.08 x 0.34 = 2651 Btu/h			$HL_{vaib} = PVC \times DTD_h \times 1.08 \times (1 - E)$ 95 CFM x 15 °F x 1.08 x 0.34 = 523 Btu/h																																																									
5.2.3.3 Calculation of Air Change Heat Loss for Each Room (Floor Multiplier Section)																																																												
$HL_{airr} = Level\ Factor \times HL_{airbv} \times \{(HL_{agcr} + HL_{bgcr}) \div (HL_{agclevel} + HL_{bgclevel})\}$																																																												
Level	Level Factor (LF)	HLairve Air Leakage + Ventilation Heat Loss (Btu/h)	Level Conductive Heat Loss: (HL _{clevel})	Air Leakage Heat Loss Multiplier (LF x HLairbv / HLlevel)																																																								
1	0.5	10,772	7,961	0.677																																																								
2	0.3		8,491	0.381																																																								
3	0.2		10,057	0.214																																																								
4	0		0	0.000																																																								
5	0		0	0.000																																																								
*HLairbv = Air leakage heat loss + ventilation heat loss *For a balanced or supply only ventilation system HLairve = 0																																																												