22 114469 EP WHITING | WED MAR 2/22 02:18 PM | K:\PROJECTS\2021\221081.GOLD\SITE\221081WSP01.DWG COMPLETE ROOF (INCLUDING REAR) CONNECTED TO FRONT DOWNSPOUT AND CONNECTED TO RDC SERVICE CONNECTION. AND CONNECTED TO FIDE SERVICE CONNECTED TO. HALF ROOF CONNECTED TO FRONT DOWNSPOUT & DISCHARGE VIA SPASH PAI ROOF DISCHARGE/OVERLAND FLOW TO BE DIRECETED TO FRONT OF THE LOT. HALF ROOF CONNECTED TO FRONT DOWNSPOUT AND CONNECTED TO RDC SERVICE CONNECTION. HALF ROOF CONNECTED TO REAR DOWNSPOUT AND CONNECTED TO INFILTRATION TRENCH. COMPLETE ROOF (INCLUDING REAR) TO DISCHARGE VIA SPASH PAD. ROOF DISCHARGE/OVERLAND FLOW TO BE DIRECTED TO FRONT OF THE LOT 1.1 - ROOF DRAINS TO BE CONNECTED AT THE FRONT TO RDC SERVICE CONNECTION FOR ROOF CONFIGURATIONS RC, RF, & RR (REFER TO SCS DWG, 906 DETAIL B) 1.2 - IF ROOF CONFIGURATION IS RF OR RC, FRONT ROOF DRAINS TO BE CONNECTED TO FRONT DOWNSPOUT & CONNECTED TO RDC SERVICE CONNECTION. (REFER TO SCS DWG, 906 DETAIL B) 1.3 - IF ROOF CONFIGURATION IS RR, REAR ROOF DRAINS TO BE CONNECTED TO REAR ROOF DOWNSPOUT AND CONNECTED TO INFILTRATION TRENCH (REFER TO SCS DWG, 906 DETAIL A) 1.4 - THE CONTRACTOR SHALL CHECK AND VERIFY ALL GIVEN GRADE ELEVATIONS PRIOR TO COMMENCEMENT OF CONSTRUCTION. FOOTINGS TO BEAR ON NATURAL UNDISTURBED SOIL OR ROCK AND TO BE A MINIMUM OF 1.22m BELOW FINISHED GRADE. COMPLETE ROOF (INCLUDING REAR) TO DISCHARGE VIA SPASH PAD, ROOF **FUTURE RESIDENTIAL** 16.2 234,36 18.30 18.30 V TRENCH (SEE DETAIL TRATION TRENCH (SEE DETAIL POR CONTROL INF 1.22III DELOW FINDRED GRADEY 1.5 - ALL FRONT AND REAR YARDS SHALL BE GRADED AT A 2%-5% GRADE WITHIN 6.0m OF THE DWELLING UNIT. 1.6 - MAXIMUM DRIVEWAY SLOPE SHALL BE 8%. PY SCS CONSULT.) 905 BY SCS CONSULT.) DWG. DWG. 905 BY SCS C 1.7 - THE MAXIMUM, ALLOWABLE SLOPE IS 3:1 (HORIZONTAL AND VERTICAL) WITH A MAXIMUM ELEVATION DIFFERENCE OF 600mm. 163 **⊛164** WITH A MAXIMOM ELEVATION DIFFERENCE OF BUOMMN. 18.8 - DRIVEWAYS TO BE SET BACK A MINIMUM OF 1.0m, FROM ABOVE GROUND SERVICES OR OTHER OBSTRUCTION. 1.9 - LOT HIGH POINT (HP) TO BE 2.0m UPSTREAM OF DOWNSPOUTS 1.10 - ROOF LEADER EMERGENCY OVERFLOW TO DISCHARGE VIA SPLASH PAD. (REFER TO SCS DWG. 996 DETAIL A FOR ROOF CONFIGURATION RC & RF) 1.11 - INIVIT DATION TORKINGES NOT TO COOSS BETWEEN LOT UNISS 165 233.95 HP 233.99 233.91 233,82 I.11 - INFILTRATION TRENCHES NOT TO CROSS BETWEEN LOT LINES. REFER TO SCS DWG. 906 DETAIL A) 2.0% 3.0% 1.12 - IF ROOF CONFIGURATION IS RR, REAR ROOF DOWNSPOUTS CONNECTED TO 100mm0 CAP, REMOVE CAP AND CONNECT TO REAR LOT INFILTRATION TRENCH, BUILD THE REAR YARD ROOF LEADER CONNECT TO THE TRENCH SUILD THE REAR YARD ROOF LEADER CONNECTION TO THE CAP AT THE TRENCHES (TYP.) REFER TO SCS DWG. 906 233.91 234.01 233.93 DETAIL A. 1.13 - BUILDER TO REFER TO SCS DWG. 906 DETAILS A & B FOR DETAILS ON THE INFILTRATION TRENCH. A REVERSE VENEER VENEER (RR)(RF) TFW=234.29 TFW=234.25 (RR)(RF)QUEE! KINGSVIEW 164 INGSVIEW SUNK 2R |233.91 0.82 6001 EL 'B' Fi WE HAVE REVIEWED THE SITE AND GRADING PLAN FOR THE PROPOSED BUILDING TO BE CONSTRUCTED, AND HEREBY *902* '. 'A' REV FF F 234.35 FW 233.94 TF' BF TFW 233.90 BF 231.24 1. The proposed grading and appurtenant drainage works comply 233.29 with sound engineering principles. 2. The proposed grading is in conformity with the grading plan approval for this subdivision and will not adversely affect 231.28 233.31 231.01 231.05 adjacent lands. SUNK 4R 233.61 a national ratios. The proposed building is compatible with the proposed grading. The proposed water service curb stop is to be located in the grassed portion of the front yard. 233.23 ¦**4**12R *15.77* 5. The driveway conforms with the City of Vaughan By-Law 1-88 5.84 as amended and is a minimum 1.0 metre clear of all street landscape catch basins. 6. The proposed building is a minimum of 0.6 m side yard setback 12.04 from a drainage swale. SCS CONSULTING GROUP LTD. PROFESSIONAL 5.69 Ş <u><UF_231.86</u>> 233.09 233.08 M. R. CATTO 234.12 234.16 6R 6R MAR. 2/22 POVINCE OF ONT AR 1R f23<u>2.84</u> 232.92 232.96 232.89 232.72 A=6.50 Date: MAR. 2/22 Reviewed By: \$AN 229.51 STM 229.65 CWC/FDC 232.83 232.75 15 25 1.50m CONC SIDEWALK 229.66 CWC/RDC It is the builder's complete responsibility to ensure that all plans submitted for approval fully comply with the Architectural Guidelines and all applicable regulations and requirements including zoning provisions and any provisions in the subdivision agreement. The Control Architect is not responsible in any way for examining or approving site (lotting) plans or working drawings with respect to any zoning or building code or permit matter or that any house can be properly built or located on its lot. $\triangle \Phi$ This is to certify that these plans comply with the applicable Architectural Design Guidelines approved by the City of VAUGHAN. ARBORDALE DRIVE JOHN G. WILLIAMS LTD., ARCHITECT ARCHITECTURAL CONTROL REVIEW AND APPROVAL APPROVED BY: DATE: MAR 04, 2022 s stamp certifies compliance with the applicable Design Guidelines only and bears no further professional responsibility. COVERAGE CALCULATION OT NO. LOT AREA: 690.380000 BLDG, AREA : (INCL. PORCH) 325 800000 OT COVERAGE : 47.19 % GENERAL NOTES: ANDSCAPE AREA: 0.000000 ATION OF UTILITIES AND OTHER SERVICES. IF MIN. DIMENSIONS ARE NOT MAINTAINED, BUILDER IS TO BELOCATE AT BUILDER'S EXPENSE. ANDSCAPE COV.: 0.00 % 2. BUILDER TO VERIFY ELEV. OF STM. AND SAN. LATERALS IN RELATION TO BASEMENT US OF FOOTING ELEVATIONS FOR COMPLIANCE WITH MUNICIPAL STANDARDS PRIOR TO EXCAVATION. **BUILDING HEIGHT** 3. APPROVED PERMIT DRAWINGS & CONSTRUCTION NOTES MUST BE REVIEWED AND FOLLOWED IN CONJUNCTION WITH THE SITING AND GRADING PLAN, BUILDER TO VERIFY BUILDING ENVELOPE ON SITE PLAN MATCHES APPROVED PERMIT DRAWINGS & CONSTRUCTION NOTES PRIOR TO POURING CONCRETE. IF THERE ARE ANY DISCREPANCIES, THEY ARE TO BE BROUGHT TO THE ATTENTION OF MAX BUILDING HEIGHT: 11.000000 OM AVERAGE FIN. GRADE@ FRONT OF BUILDING TO MEAN STABLISHED GRADE: 233.06 HUNT DESIGN ASSOCIATES INC. 1. UNLESS NOTED ON BUILDING ENVELOPE OR APPROVED PERMIT DRAWINGS & CONSTRUCTION NOTES, ALL TOP OF FOUNDATION WALLS INCLUDING GARAGE WALLS TO BE CONSISTENT WITH THE ELEVATION PROVIDED FOR TFW ON SITING AND GRADING PLAN. THE EXTERIOR OF THE FOUNDATION WALL TO BE F. TO TOP OF ROOF: 13.150000 City of Vaughan .F. TO MEAN OF ROOF: 9.420000 **GRADING APPROVED BY** PROVIDED WITH A REDUCTION OF THICKNESS FOR MASONRY VENEER AS REQUIRED. PROPOSED BLDG. HGT: 10.67 m FRONT YARD LANDSCAPE AREA **Justin Au Yeung** FRONT YARD AREA: 67.950000 ANDSCAPE AREA: 44.450000 May 11 2022 COVERAGE (50% MIN.): 65,42 % ISSUED FOR FINAL APPROVAL AW 2022.02.2 40 410000 SOFT LANDSCAPE AREA: ISSUED FOR PRELIMINARY APPROVAL AW 2022.02.1 SOFT COVERAGE (60% MIN.) 90.91 % BELL PEDESTAL A HYDRO TRANSFORMER SANITARY LINE SANITARY MANHOLE DOWNSPOUTS ENGINEERED FILL LOTS ── WATER SERVICE SUMP PUMP AND SURFACE DISCHARGE LOCATION

SITING AND GRADING PLAN

EAR YARD AREA:

HUNT DESIGN ASSOCIATES INC

SOFT LANDSCAPE AREA :

COVERAGE (60% MIN.):

206.880000

206.880000

100.00 %

19695

REAR YARD LANDSCAPE AREA

QUALIFICATION INFORMATION Allan Whiting 23177



→ HYDRO SERVICE

~~~ SHEET DRAINAGE

→ STREET LIGHT

TRAFFIC SIGNA POWER PEDES

STREET LIGHT PEDESTAL

CABLE PEDESTAL

O- HYDRO POLE GUY

COMMUNITY MAILBOX

→ HYDRO POLE

O STREET SIGN

STREET TREE

RETAINING WAL

DOUBLE / SINGL STM & SAN CONN

VALVE & BOX

## ARBORDALE DRIVE 164 **GOLDPARK HOMES - 221081**

PINE VALLEY PH2 - VAUGHAN, ON AW AW 1:250 221081WSP01

-stm - STORM WATER LINE

-w--- WATERLINE

— G— GAS LINE

-c --- CABLE LINE

WINDOWS PERMITTED

EXTERIOR DOOR LOCATION

EXTERIOR DOOR LOCATION IF GRADE PERMITS

45 MINUTE FIRE RATED WALL SIDEYARD DISTANCE IS LESS

UPGRADE ELEVATION

FENCE AND GATE

ACOUSTIC FENCE

PRIVACY FENCE

CHAIN LINK FENCE

UNDERSIDE OF FOOTING

WALKOUT BASEMENT

MODIFIED

PADMOUNTED MOTOR

190.10 PROPOSED GRADES

2.0% SWALE DIRECTION

EMBANKMENT / BERM