

SITE NAME: LECCO RIDGE

BUILDER: GREENPARK HOMES

TYPE: IVY 2

GFA: 1641

DATE: Jan-17

LO# 71713

WINTER NATURAL AIR CHANGE RATE 0.263

SUMMER NATURAL AIR CHANGE RATE 0.091

HEAT LOSS AT °F. 72

HEAT GAIN AT °F. 15

CSA-F280-12

ENERGYSTAR

ROOM USE	EXP. WALL	CLG. HT.	MBR	ENS	WIC	BED-2	BED-3	BATH						
			16	9	0	15	14	0						
			9	9	9	9	9	9						
GRS.WALL AREA	LOSS	GAIN	144	81	0	135	126	0						
GLAZING	LOSS	GAIN												
NORTH	20.4	16.6	0	0	0	0	0	0	0	0	0	0	0	0
EAST	20.4	42.2	0	0	0	0	0	0	28	571	1181	10	204	422
SOUTH	20.4	25.6	0	0	0	0	0	0	0	0	0	0	0	0
WEST	20.4	42.2	30	612	1266	13	265	549	0	0	0	0	0	0
SKYLT.	35.7	102.7	0	0	0	0	0	0	0	0	0	0	0	0
DOORS	24.1	5.0	0	0	0	0	0	0	0	0	0	0	0	0
NET EXPOSED WALL	3.1	0.6	114	350	72	68	209	43	107	328	68	116	356	74
NET EXPOSED BSMT WALL ABOVE GR	3.6	0.8	0	0	0	0	0	0	0	0	0	0	0	0
EXPOSED CLG	1.4	0.7	208	301	154	90	130	67	135	195	100	182	284	135
NO ATTIC EXPOSED CLG	2.3	1.2	0	0	0	0	0	0	30	70	36	0	0	0
EXPOSED FLOOR	2.3	0.5	52	121	25	0	0	0	165	385	80	0	0	0
BASEMENT/CRAWL HEAT LOSS			0	0	0	0	0	0	0	0	0	0	0	0
SLAB ON GRADE HEAT LOSS			0	0	0	0	0	0	0	0	0	0	0	0
SUBTOTAL HT LOSS			1384		604	325	1550	823	130					
SUB TOTAL HT GAIN				1517	658	131	1465	630	67					
LEVEL FACTOR / MULTIPLIER	0.20	0.32		0.20	0.32	0.20	0.32	0.20	0.32					
AIR CHANGE HEAT LOSS			442		193	104	495	263	42					
AIR CHANGE HEAT GAIN			139		60	12	135	58	6					
DUCT LOSS			183		0	43	204	0	0					
DUCT GAIN			252		0	53	222	0	0					
HEAT GAIN PEOPLE	240	2	480	0	0	0	1	240	1	240				
HEAT GAIN APPLIANCES/LIGHTS			385		385	385	385	385	0					
TOTAL HT LOSS BTU/H			2009		797	472	2249	1086	172					
TOTAL HT GAIN x 1.3 BTU/H			3606		1435	754	3181	1707	95					

**TOWN OF MILTON**  
**PLANNING AND DEVELOPMENT**  
**IVY 2 MODEL**

**BUILDING: REVIEWED**  
**SCOTT SHERRIFFS** **APR 7, 2017**

**PLANS EXAMINER** **DATE**

Neither the issuance of a permit nor carrying out of inspections by the Town of Milton relieves the owner from full responsibility for compliance with the provisions of the Ontario Building Code Act and the Ontario Building Code, both as amended, as well as other applicable statutes and regulations of the Province of Ontario, By-laws of the Region of Halton and Town of Milton

**RECEIVED**  
**TOWN OF MILTON**  
**MAR 29, 2017**  
**IVY 2**  
**BUILDING DIVISION**

ROOM USE	EXP. WALL	CLG. HT.	OFF	K/L/D	FOY	MUD	WOD	BAS
			32	46	16	10	28	107
			11	10	10	11	9	9
GRS.WALL AREA	LOSS	GAIN	352	460	160	110	262	885
GLAZING	LOSS	GAIN						
NORTH	20.4	16.6	0	0	0	0	10	204
EAST	20.4	42.2	50	1020	2110	0	0	0
SOUTH	20.4	25.6	0	0	0	0	0	0
WEST	20.4	42.2	0	0	0	0	0	0
SKYLT.	35.7	102.7	0	0	0	0	0	0
DOORS	24.1	5.0	0	0	0	0	0	0
NET EXPOSED WALL	3.1	0.6	302	926	192	372	1141	236
NET EXPOSED BSMT WALL ABOVE GR	3.6	0.8	0	0	0	0	0	0
EXPOSED CLG	1.4	0.7	110	159	81	56	81	41
NO ATTIC EXPOSED CLG	2.3	1.2	0	0	0	0	0	0
EXPOSED FLOOR	2.3	0.5	0	0	0	0	0	0
BASEMENT/CRAWL HEAT LOSS			0	0	0	0	0	0
SLAB ON GRADE HEAT LOSS			0	0	0	0	0	0
SUBTOTAL HT LOSS			2106	3091	1078	757	776	3949
SUB TOTAL HT GAIN			2383	3047	223	157	285	225
LEVEL FACTOR / MULTIPLIER	0.30	0.33		0.30	0.33	0.30	0.33	0.50
AIR CHANGE HEAT LOSS			690	1013	354	248		3842
AIR CHANGE HEAT GAIN			219	280	21	14		47
DUCT LOSS			0	0	0	0		0
DUCT GAIN			0	0	0	0		0
HEAT GAIN PEOPLE	240	0	0	1	240	0	0	0
HEAT GAIN APPLIANCES/LIGHTS			385	385	385	385	0	385
TOTAL HT LOSS BTU/H			2796	4104	1432	1005	776	7791
TOTAL HT GAIN x 1.3 BTU/H			3883	5137	317	223	370	853

TOTAL HEAT GAIN BTU/H: 22001

TONS: 1.83

LOSS DUE TO VENTILATION LOAD BTU/H: 2127

STRUCTURAL HEAT LOSS: 24690

TOTAL COMBINED HEAT LOSS BTU/H: 26816

*Michael O'Rourke*

SITE NAME: LECCO RIDGE  
BUILDER: GREENPARK HOMES

TYPE: IVY 2

DATE: Jan-17

GFA: 1641

LO# 71713

HEATING CFM	895	COOLING CFM	895
TOTAL HEAT LOSS	24,690	TOTAL HEAT GAIN	21,561
AIR FLOW RATE CFM	36.25	AIR FLOW RATE CFM	41.51

furnace pressure	0.6
furnace filter	0.05
a/c coil pressure	0.2
available pressure for s/a & r/a	0.35

AMEC960302BNA #AMANA 30

AFUE = 96 %  
INPUT (BTU/H) = 30,000  
OUTPUT (BTU/H) = 28,800

RUN COUNT	4th	3rd	2nd	1st	Bas
S/A	0	0	8	6	3
R/A	0	0	3	2	1

All S/A diffusers 4"x10" unless noted otherwise on layout.

All S/A runs 5"Ø unless noted otherwise on layout.

plenum pressure s/a	0.18
max s/a dif press. loss	0.03
min adjusted pressure s/a	0.15

r/a pressure	0.17
r/a grille press. Loss	0.02
adjusted pressure r/a	0.15

LOW  
MEDLOW  
MEDIUM  
MEDIUM HIGH  
HIGH

DESIGN CFM = 895  
CFM @ .6" E.S.P.

TEMPERATURE RISE 30 °F

RUN #	1	2	3	4	5	6	7	10	12	13	14	15	19	20	21	22	23
ROOM NAME	MBR	ENS	WIC	BED-2	BED-3	BED-2	BATH	MBR	OFF	OFF	K/L/D	K/L/D	FOY	MUD	BAS	BAS	BAS
RM LOSS MBH.	1.00	0.80	0.47	1.12	1.09	1.12	0.17	1.00	1.40	1.40	2.05	2.05	1.43	1.01	2.86	2.86	2.86
CFM PER RUN HEAT	36	29	17	41	39	41	6	36	51	51	74	74	52	36	104	104	104
RM GAIN MBH.	1.80	1.43	0.75	1.59	1.71	1.59	0.09	1.80	1.94	1.94	2.57	2.57	0.32	0.22	0.41	0.41	0.41
CFM PER RUN COOLING	75	60	31	66	71	66	4	75	81	81	107	107	13	9	17	17	17
ADJUSTED PRESSURE	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.17	0.16	0.16	0.15	0.15	0.17	0.17	0.16	0.16	0.16
ACTUAL DUCT LGH.	36	32	34	36	30	31	31	45	31	36	20	34	21	22	30	13	29
EQUIVALENT LENGTH	170	180	130	125	140	160	130	160	130	110	150	100	110	80	90	140	120
TOTAL EFFECTIVE LENGTH	206	212	164	161	170	191	161	205	161	146	170	134	131	102	120	153	149
ADJUSTED PRESSURE	0.08	0.08	0.1	0.11	0.1	0.09	0.11	0.08	0.1	0.11	0.09	0.11	0.13	0.17	0.14	0.11	0.11
ROUND DUCT SIZE	5	5	4	5	5	5	4	5	5	5	6	6	4	4	6	6	6
HEATING VELOCITY (ft/min)	264	213	195	301	286	301	69	264	374	374	377	377	597	413	530	530	530
COOLING VELOCITY (ft/min)	551	441	356	485	521	485	46	551	595	595	546	546	149	103	87	87	87
OUTLET GRILL SIZE	3X10	3X10	3X10	3X10	3X10	3X10	3X10	3X10	3X10	3X10	4X10	4X10	3X10	3X10	4X10	4X10	4X10
TRUNK	A	C	A	B	C	B	C	A	B	B	A	A	C	A	A	A	B

RUN #
ROOM NAME
RM LOSS MBH.
CFM PER RUN HEAT
RM GAIN MBH.
CFM PER RUN COOLING
ADJUSTED PRESSURE
ACTUAL DUCT LGH.
EQUVALENT LENGTH
TOTAL EFFECTIVE LENGTH
ADJUSTED PRESSURE
ROUND DUCT SIZE
HEATING VELOCITY (ft/min)
COOLING VELOCITY (ft/min)
OUTLET GRILL SIZE
TRUNK

RECEIVED  
TOWN OF MILTON  
MAR 29, 2017  
IVY 2  
BUILDING DIVISION

SUPPLY AIR TRUNK SIZE																RETURN AIR TRUNK SIZE								
	TRUNK CFM	STATIC PRESS.	ROUND DUCT	RECT DUCT			VELOCITY (ft/min)		TRUNK CFM	STATIC PRESS.	ROUND DUCT	RECT DUCT			VELOCITY (ft/min)		TRUNK CFM	STATIC PRESS.	ROUND DUCT	RECT DUCT			VELOCITY (ft/min)	
TRUNK A	481	0.08	10.7	14	x	8	618		TRUNK G	0	0.00	0	0	x	8	0	TRUNK O	0	0.06	0	0	x	8	0
TRUNK B	288	0.09	8.5	8	x	8	648		TRUNK H	0	0.00	0	0	x	8	0	TRUNK P	0	0.06	0	0	x	8	0
TRUNK C	414	0.08	10.1	12	x	8	621		TRUNK I	0	0.00	0	0	x	8	0	TRUNK Q	0	0.06	0	0	x	8	0
TRUNK D	0	0.00	0	0	x	8	0		TRUNK J	0	0.00	0	0	x	8	0	TRUNK R	0	0.06	0	0	x	8	0
TRUNK E	0	0.00	0	0	x	8	0		TRUNK K	0	0.00	0	0	x	8	0	TRUNK S	0	0.06	0	0	x	8	0
TRUNK F	0	0.00	0	0	x	8	0		TRUNK L	0	0.00	0	0	x	8	0	TRUNK T	0	0.06	0	0	x	8	0
																TRUNK U	0	0.06	0	0	x	8	0	
																TRUNK V	0	0.06	0	0	x	8	0	
																TRUNK W	0	0.06	0	0	x	8	0	
																TRUNK X	895	0.06	14.5	24	x	8	671	
																TRUNK Y	360	0.06	10.3	12	x	8	540	
																TRUNK Z	0	0.06	0	0	x	8	0	
																DROP	895	0.06	14.5	24	x	10	537	

RETURN AIR #	1	2	3	4	5										BR
AIR VOLUME	85	170	85	215	190	0	0	0	0	0	0	0	0	0	150
PLENUM PRESSURE	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15	0.15
ACTUAL DUCT LGH.	51	40	66	16	32	1	1	1	1	1	1	1	1	1	14
EQUIVALENT LENGTH	165	175	175	135	150	0	0	0	0	0	0	0	0	0	135
TOTAL EFFECTIVE LH	216	215	241	151	182	1	1	1	1	1	1	1	1	1	149
ADJUSTED PRESSURE	0.07	0.07	0.06	0.10	0.08	14.80	14.80	14.80	14.80	14.80	14.80	14.80	14.80	14.80	0.10
ROUND DUCT SIZE	5.8	7.5	6	7.5	7.5	0	0	0	0	0	0	0	0	0	6.5
INLET GRILL SIZE	8	8	8	8	8	0	0	0	0	0	0	0	0	0	8
	X	X	X	X	X	X	X	X	X	X	X	X	X	X	X
INLET GRILL SIZE	14	14	14	14	14	0	0	0	0	0	0	0	0	0	14

TYPE: IVY 2  
SITE NAME: LECCO RIDGE

LO # 71713

**RESIDENTIAL MECHANICAL VENTILATION DESIGN SUMMARY**

COMBUSTION APPLIANCES		9.32.3.1(1)
a)	<input checked="" type="checkbox"/> Direct vent (sealed combustion) only	
b)	<input type="checkbox"/> Positive venting induced draft (except fireplaces)	
c)	<input type="checkbox"/> Natural draft, B-vent or induced draft gas fireplace	
d)	<input type="checkbox"/> Solid Fuel (Including fireplaces)	
e)	<input type="checkbox"/> No Combustion Appliances	

HEATING SYSTEM	
<input checked="" type="checkbox"/> Forced Air	<input type="checkbox"/> Non Forced Air
<input type="checkbox"/> Electric Space Heat	

HOUSE TYPE		9.32.1(2)
<input checked="" type="checkbox"/> I	Type a) or b) appliance only, no solid fuel	
<input type="checkbox"/> II	Type I except with solid fuel (including fireplaces)	
<input type="checkbox"/> III	Any Type c) appliance	
<input type="checkbox"/> IV	Type I, or II with electric space heat	
<input type="checkbox"/>	Other: Type I, II or IV no forced air	

SYSTEM DESIGN OPTIONS		O.N.H.W.P.
<input type="checkbox"/> 1	Exhaust only/Forced Air System	
<input type="checkbox"/> 2	HRV with Ducting/Forced Air System	
<input checked="" type="checkbox"/> 3	HRV Simplified/connected to forced air system	
<input type="checkbox"/> 4	HRV with Ducting/non forced air system	
<input type="checkbox"/>	Part 6 Design	

TOTAL VENTILATION CAPACITY		9.32.3.3(1)
Basement + Master Bedroom	<u>2</u> @ 21.2 cfm	<u>42.4</u> cfm
Other Bedrooms	<u>2</u> @ 10.6 cfm	<u>21.2</u> cfm
Kitchen & Bathrooms	<u>4</u> @ 10.6 cfm	<u>42.4</u> cfm
Other Rooms	<u>4</u> @ 10.6 cfm	<u>42.4</u> cfm
Table 9.32.3.A.	TOTAL	<u>148.4</u> cfm

PRINCIPAL VENTILATION CAPACITY REQUIRED		9.32.3.4.(1)
1 Bedroom	31.8	cfm
2 Bedroom	47.7	cfm
3 Bedroom	63.6	cfm
4 Bedroom	79.5	cfm
5 Bedroom	95.4	cfm
More than 5 - Part 6	TOTAL	<u>63.6</u> cfm

SUPPLEMENTAL VENTILATION CAPACITY		9.32.3.5.
Total Ventilation Capacity	<u>148.4</u>	cfm
Less Principal Ventil. Capacity	<u>80</u>	cfm
Required Supplemental Capacity	<u>68.4</u>	cfm

PRINCIPAL EXHAUST FAN CAPACITY	
Model: VANEE 40H+	Location: BSMT
<u>80.0</u> cfm	<u>3.0</u> sones <input checked="" type="checkbox"/> HVI Approved

PRINCIPAL EXHAUST HEAT LOSS CALCULATION				
CFM	$\Delta T$ °F	FACTOR	% LOSS	
80.0 CFM	X 72 F	X 1.08	X	0.34

SUPPLEMENTAL FANS		NUTONE		
Location	Model	cfm	HVI	Sones
ENS	QTXEN050C	50	<input checked="" type="checkbox"/>	0.3
BATH	QTXEN050C	50	<input checked="" type="checkbox"/>	0.3

HEAT RECOVERY VENTILATOR		9.32.3.11.
Model: VANEE 40H+		
<u>86</u> cfm high	<u>37</u> cfm low	
<u>66</u> % Sensible Efficiency	<input checked="" type="checkbox"/> HVI Approved	
@ 32 deg F ( 0 deg C)		

LOCATION OF INSTALLATION	
Lot:	Co
Township	PI
Address	
Roll #	

TOWN OF MILTON PLANNING AND DEVELOPMENT	
IVY 2 MODEL	
BUILDER: GR	DATE
Name:	SCOTT SHERRIFFS
Address:	APR 7, 2017
City:	PLANS EXAMINER
Telephone #:	Neither the issuance of a permit nor carrying out of inspections by the Town of Milton relieves the owner from full responsibility for compliance with the provisions of the Ontario Building Code Act and the Ontario Building Code, both as amended, as well as other applicable statutes and regulations of the Province of Ontario, By-laws of the Region of Halton and Town of Milton

INSTALLING CONTRACTOR	
Name:	
Address:	
City:	
Telephone #:	Fax #:

DESIGNER CERTIFICATION	
I hereby certify that this ventilation system has been designed in accordance with the Ontario Building Code.	
Name:	HVAC Designs Ltd.
Signature:	<i>Michael O'Rourke</i>
HRAI #	001820
Date:	January-17

**HEAT LOSS AND GAIN SUMMARY SHEET**

<b>MODEL:</b> IVY 2	<b>BUILDER:</b> GREENPARK HOMES
<b>SFQT:</b> 1641	<b>SITE:</b> LECCO RIDGE
<b>LO#</b> 71713	

**DESIGN ASSUMPTIONS**

HEATING	°F	COOLING	°F
OUTDOOR DESIGN TEMP.	0	OUTDOOR DESIGN TEMP.	86
INDOOR DESIGN TEMP.	72	INDOOR DESIGN TEMP. (MAX 75°F)	71

**BUILDING DATA**

ATTACHMENT:	ATTACHED	# OF STORIES (+BASEMENT):	3
FRONT FACES:	EAST	ASSUMED (Y/N):	Y
AIR CHANGES PER HOUR:	3	ASSUMED (Y/N):	Y
AIR TIGHTNESS CATEGORY:	TIGHT	ASSUMED (Y/N):	Y
WIND EXPOSURE:	SHELTERED	ASSUMED (Y/N):	Y
HOUSE VOLUME (ft³):	22596.0	ASSUMED (Y/N):	Y
INTERNAL SHADING:	BLINDS/CURTAINS	ASSUMED OCCUPANTS:	4
INTERIOR LIGHTING LOAD (Btu/h/ft²):	1.27	DC BRUSHLESS MOTOR (Y/N):	Y
FOUNDATION CONFIGURATION	BCIN_1	DEPTH BELOW GRADE:	6.7 ft
LENGTH: 50.0 ft	WIDTH: 20.0 ft	EXPOSED PERIMETER:	107.0 ft

**2012 OBC - COMPLIANCE PACKAGE****Component****Compliance Package  
ENERGYSTAR****Nominal**

Ceiling with Attic Space Minimum RSI (R)-Value	50
Ceiling Without Attic Space Minimum RSI (R)-Value	31
Exposed Floor Minimum RSI (R)-Value	31
Walls Above Grade Minimum RSI (R)-Value	20+3.6
Basement Walls Minimum RSI (R)-Value	20
Below Grade Slab Entire surface > 600 mm below grade Minimum RSI (R)-Value	-
Edge of Below Grade Slab ≤ 600 mm Below Grade Minimum RSI (R)-Value	10
Heated Slab or Slab ≤ 600 mm below grade Minimum RSI (R)-Value	10
Windows and Sliding Glass Doors Maximum U-Value	ZONE 2
S Skylights Maximum U-Value	ZONE 2
Space Heating Equipment Minimum AFUE	0.95
HRV Minimum Efficiency	65%
Domestic Hot Water Heater Minimum EF	90% TE


RECEIVED  
TOWN OF MILTON  
MAR 29, 2017  
IVY 2  
BUILDING DIVISION

INDIVIDUAL BCIN: 19669  
MICHAEL O'ROURKE

*Michael O'Rourke*

## Residential Foundation Thermal Load Calculator

Supplemental tool for CAN/CSA-F280

Weather Station Description		
Province:	Ontario	
Region:	Milton	
Site Description		
Soil Conductivity:	Normal conductivity: dry sand, loam, clay	
Water Table:	Normal (7-10 m, 23-33 ft)	
Foundation Dimensions		
Floor Length (m):	15.2	 Insulation Configuration
Floor Width (m):	6.1	
Exposed Perimeter (m):	32.6	
Wall Height (m):	2.7	
Depth Below Grade (m):	2.04	
Window Area (m <sup>2</sup> ):	1.3	
Door Area (m <sup>2</sup> ):	1.9	
Radiant Slab		
Heated Fraction of the Slab:	0	
Fluid Temperature (°C):	33	
Design Months		
Heating Month	1	
Foundation Loads		
Heating Load (Watts):		909

TYPE: IVY 2  
LO# 71713RECEIVED  
TOWN OF MILTON  
MAR 29, 2017  
IVY 2  
BUILDING DIVISION


# Air Infiltration Residential Load Calculator

Supplemental tool for CAN/CSA-F280

Weather Station Description				
Province:	Ontario			
Region:	Milton			
Weather Station Location:	Open flat terrain, grass			
Anemometer height (m):	10			
Local Shielding				
Building Site:	Suburban, forest			
Walls:	Heavy			
Flue:	Heavy			
Highest Ceiling Height (m):	6.49			
Building Configuration				
Type:	Semi			
Number of Stories:	Two			
Foundation:	Full			
House Volume (m <sup>3</sup> ):	639.8			
Air Leakage/Ventilation				
Air Tightness Type:	Energy Star Attached (3.0 ACH)			
Custom BDT Data:	ELA @ 10 Pa.	716.8 cm <sup>2</sup>		
	3.00	ACH @ 50 Pa		
Mechanical Ventilation (L/s):	Total Supply	Total Exhaust		
	37.8	37.8		
Flue Size				
Flue #:	#1	#2	#3	#4
Diameter (mm):	0	0	0	0
Natural Infiltration Rates				
Heating Air Leakage Rate (ACH/H):	0.263			
Cooling Air Leakage Rate (ACH/H):	0.091			

TYPE: IVY 2  
LO# 71713RECEIVED  
TOWN OF MILTON  
MAR 29, 2017  
IVY 2  
BUILDING DIVISION





1

MICHAEL O'ROURKE HAVE REVIEW AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.

Michael O'Rourke, BCIN# 19669  
HVAC DESIGNS LTD.

RECEIVED

TOWN OF MILTON

MAR 29, 2017

IVY 2

BUILDING DIVISION

TOWN OF MILTON  
PLANNING AND DEVELOPMENT  
IVY 2 MODEL

BUILDING: REVIEWED  
SCOTT SHERRIFFS  
PLANS EXAMINER

APR 7, 2017  
DATE

Neither the issuance of a permit nor carrying out of inspections by the Town of Milton relieves the owner from full responsibility for compliance with the provisions of the Ontario Building Code Act and the Ontario Building Code, both as amended, as well as other applicable statutes and regulations of the Province of Ontario, By-laws of the Region of Halton and Town of Milton

CSA-F280-12

ENERGY STAR

HVAC LEGEND

SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION
	FLOOR SUPPLY AIR GRILLE		6" SUPPLY AIR BOOT ABOVE		14"x8" RETURN AIR GRILLE		RETURN AIR STACK ABOVE
	FLOOR SUPPLY AIR GRILLE 6" BOOT		SUPPLY AIR STACK FROM 2nd FLOOR		30"x8" RETURN AIR GRILLE		RETURN AIR STACK 2nd FLOOR
	SUPPLY AIR BOOT ABOVE		6" SUPPLY AIR STACK 2nd FLOOR		FRA- FLOOR RETURN AIR GRILLE		REDUCER

3.

2.

1.

No.

Description

Date

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

Client

GREENPARK HOMES

Project Name

LECCO RIDGE  
MILTON, ONTARIO

375 Finley Ave. Suite 202 - Ajax, Ontario  
L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375  
Email: info@hvacdesigns.ca  
Web: www.hvacdesigns.ca  
Specializing in Residential Mechanical Design Services

Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper. Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.

HEAT LOSS 26816 BTU/H  
UNIT DATA

MAKE AMANA

MODEL AMEC960302BNA-30

INPUT 30 MBTU/H

OUTPUT 28.8 MBTU/H

COOLING 2.0 TONS

FAN SPEED 895 cfm @ 0.6" w.c.

# OF RUNS S/A R/A FANS

3RD FLOOR			
2ND FLOOR	8	3	2
1ST FLOOR	6	2	2
BASEMENT	3	1	0

ALL S/A DIFFUSERS 4"x10" UNLESS NOTED OTHERWISE ON LAYOUT. ALL S/A RUNS 5"Ø UNLESS NOTED OTHERWISE ON LAYOUT. UNDERCUT DOORS 1" min. FOR R/A

Sheet Title

BASEMENT  
HEATING  
LAYOUT

Date JAN/2017


Scale 3/16" = 1'-0"

BCIN# 19669


LO# 71713

IVY 2


1641 sqft



GROUND FLOOR PLAN - ELEV. 1



GROUND FLOOR PLAN - ELEV. 2



GROUND FLOOR PLAN - ELEV. 3

I MICHAEL O'ROURKE HAVE REVIEWED AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.  
*Michael O'Rourke*  
Michael O'Rourke, BChE 19669  
HVAC DESIGNS LTD.



TOWN OF MILTON

PLANNING AND DEVELOPMENT

IVY 2 MODEL

BUILDING: REVIEWED

SCOTT SHERRIFFS

PLANS EXAMINER

DATE

APR 7, 2017













Neither the issuance of a permit nor carrying out of inspections by the Town of Milton relieves the owner from full responsibility for compliance with the provisions of the Ontario Building Code Act and the Ontario Building Code, both as amended, as well as other applicable statutes and regulations of the Province of Ontario, By-laws of the Region of Halton and Town of Milton

RECEIVED  
TOWN OF MILTON  
MAR 29, 2017  
IVY 2  
BUILDING DIVISION

CSA-F280-12



ENERGY STAR

HVAC LEGEND								3.		
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	2.		
	FLOOR SUPPLY AIR GRILLE		6" SUPPLY AIR BOOT ABOVE		14"x8" RETURN AIR GRILLE		RETURN AIR STACK ABOVE	1.		
	FLOOR SUPPLY AIR GRILLE 6" BOOT		SUPPLY AIR STACK FROM 2nd FLOOR		30"x8" RETURN AIR GRILLE		RETURN AIR STACK 2nd FLOOR	No.	Description	Date
	SUPPLY AIR BOOT ABOVE		6" SUPPLY AIR STACK 2nd FLOOR		FRA- FLOOR RETURN AIR GRILLE		REDUCER	REVISIONS		

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

Client

GREENPARK HOMES

Project Name

LECCO RIDGE  
MILTON, ONTARIO

IVY 2

1641 sqft



375 Finley Ave. Suite 202 - Ajax, Ontario  
L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375  
Email: info@hvacdsgns.ca  
Web: www.hvacdsgns.ca  
Specializing in Residential Mechanical Design Services

Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper. Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.

Sheet Title

FIRST FLOOR  
HEATING  
LAYOUT

Date

JAN/2017

Scale


3/16" = 1'-0"

BCIN# 19669


LO#

71713






SECOND FLOOR PLAN – ELEV. 1



SECOND FLOOR PLAN – ELEV. 2  
BLOCK 327



SECOND FLOOR PLAN – ELEV. 3

I MICHAEL O'ROURKE HAVE REVIEWED AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.

*Michael O'Rourke*  
Michael O'Rourke, BCIN# 19669  
HVAC DESIGNS LTD.


RECEIVED  
TOWN OF MILTON  
MAR 29, 2017  
IVY 2  
BUILDING DIVISION

 **TOWN OF MILTON**  
PLANNING AND DEVELOPMENT  
IVY 2 MODEL













**BUILDING: REVIEWED**  
**SCOTT SHERRIFFS**      **APR 7, 2017**  
**PLANS EXAMINER**      **DATE**

Neither the issuance of a permit nor carrying out of inspections by the Town of Milton relieves the owner from full responsibility for compliance with the provisions of the Ontario Building Code Act and the Ontario Building Code, both as amended, as well as other applicable statutes and regulations of the Province of Ontario, By-laws of the Region of Halton and Town of Milton

CSA-F280-12



ENERGY STAR

HVAC LEGEND								3.		
SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	SYMBOL	DESCRIPTION	2.		
	FLOOR SUPPLY AIR GRILLE		6" SUPPLY AIR BOOT ABOVE		14"x8" RETURN AIR GRILLE		RETURN AIR STACK ABOVE	1.		
	FLOOR SUPPLY AIR GRILLE 6" BOOT		SUPPLY AIR STACK FROM 2nd FLOOR		30"x8" RETURN AIR GRILLE		RETURN AIR STACK 2nd FLOOR	No.	Description	Date
	SUPPLY AIR BOOT ABOVE		6" SUPPLY AIR STACK 2nd FLOOR		FRA- FLOOR RETURN AIR GRILLE		REDUCER	REVISIONS		

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

Client <b>GREENPARK HOMES</b>		<div><p>375 Finley Ave. Suite 202 - Ajax, Ontario L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375 Email: info@hvacdesigns.ca Web: www.hvacdesigns.ca Specializing in Residential Mechanical Design Services</p><p>Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper. Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.</p></div>	Sheet Title <b>SECOND FLOOR HEATING LAYOUT</b>	
Project Name <b>LECCO RIDGE MILTON, ONTARIO</b>			Date JAN/2017	
IVY 2				