

SITE NAME: RUSSEL GARDENS  
BUILDER: GREENPARK HOMES  
DATE: Jd-17  
LOW 75021  
TYPE: HIGHGROVE 2  
GFA: 1793  
WINTER NATURAL AIR CHANGE RATE 0.409  
SUMMER NATURAL AIR CHANGE RATE 0.166  
HEAT LOSS AT °F 71  
HEAT GAIN AT °F 16  
CSA-F280-12  
SB-12 PACKAGE A1

| ROOM USE<br>EXP. WALL<br>CLG. HT.   | MBR<br>16<br>9   | ENS<br>9<br>9   | WIC<br>0<br>9  | BED-2<br>11<br>9 | BED-3<br>16<br>10 | BATH<br>0<br>9 | FOY<br>12<br>11 | MUD<br>10<br>11 | WOD<br>20<br>9 | BAS<br>102<br>9 |
|-------------------------------------|------------------|-----------------|----------------|------------------|-------------------|----------------|-----------------|-----------------|----------------|-----------------|
| GRS. WALL AREA<br>GLAZING           | 144<br>LOSS GAIN | 81<br>LOSS GAIN | 0<br>LOSS GAIN | 99<br>LOSS GAIN  | 162<br>LOSS GAIN  | 0<br>LOSS GAIN | 0<br>LOSS GAIN  | 0<br>LOSS GAIN  | 0<br>LOSS GAIN | 0<br>LOSS GAIN  |
| NORTH                               | 19.8 16.8        | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| EAST                                | 19.8 42.4        | 0 0             | 0 0            | 30 593           | 45 880            | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| SOUTH                               | 19.8 25.7        | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| WEST                                | 19.8 42.4        | 14 277          | 593 0          | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| SKYLT.                              | 34.6 103.0       | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| DOORS                               | 23.5 6.2         | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| NET EXPOSED WALL                    | 4.1 0.9          | 116 481         | 108 62         | 0 0              | 69 286            | 64 107         | 444 96          | 0 0             | 0 0            | 0 0             |
| NET EXPOSED B.S.M.T. WALL ABOVE GR. | 3.3 0.7          | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| EXPOSED CLG                         | 1.2 0.6          | 320 381         | 204 90         | 107 67           | 81 97             | 62 143         | 170 91          | 76 45           | 0 0            | 0 0             |
| NO A.T.T.C. EXPOSED CLG             | 2.6 1.4          | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 22 58           | 30 0            | 0 0            | 0 0             |
| EXPOSED FLOOR                       | 2.4 0.5          | 0 0             | 36 85          | 19 28            | 66 15             | 143 339        | 76 0            | 0 0             | 0 0            | 0 0             |
| BASEMENT CRAWL HEAT LOSS            | 0 0              | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| SLAB ON GRADE HEAT LOSS             | 0 0              | 0 0             | 0 0            | 0 0              | 0 0               | 0 0            | 0 0             | 0 0             | 0 0            | 0 0             |
| SUBTOTAL HT LOSS                    | 1416             | 747             | 163            | 1388             | 1503              | 2112           | 83              | 45              | 0.20 0.45      | 38              |
| SUB TOTAL HT GAIN                   | 0.20 0.45        | 0.20 0.45       | 0.20 0.45      | 0.20 0.45        | 0.20 0.45         | 0.20 0.45      | 0.20 0.45       | 0.20 0.45       | 0.20 0.45      | 0.20 0.45       |
| LEVEL FACTOR / MULTIPLIER           | 638              | 337             | 73             | 826              | 680               | 290            | 6               | 0               | 0              | 0               |
| AIR CHANGE HEAT LOSS                | 0                | 108             | 83             | 201              | 237               | 240            | 0               | 0               | 0              | 0               |
| AIR CHANGE HEAT GAIN                | 0                | 480             | 0              | 1                | 419               | 419            | 0               | 0               | 0              | 0               |
| DUCT LOSS                           | 0                | 419             | 0              | 2216             | 3387              | 3980           | 121             | 65              | 0              | 0               |
| DUCT GAIN                           | 0                | 1192            | 260            | 108              | 791               | 3980           | 0               | 0               | 0              | 0               |
| HEAT GAIN PEOPLE                    | 240              | 0               | 0              | 0                | 0                 | 0              | 0               | 0               | 0              | 0               |
| HEAT GAIN APPLIANCES/LIGHTS         | 2064             | 1192            | 260            | 108              | 791               | 3980           | 0               | 0               | 0              | 0               |
| TOTAL HT LOSS BTU/H                 | 3385             | 1192            | 260            | 108              | 791               | 3980           | 121             | 65              | 0              | 0               |
| TOTAL HT GAIN x 1.3 BTU/H           | 3385             | 1192            | 260            | 108              | 791               | 3980           | 121             | 65              | 0              | 0               |

| ROOM USE<br>EXP. WALL<br>CLG. HT.   | LVIND<br>25<br>10 | KITCHEN<br>58<br>10 | LAUN<br>0<br>9 | FOY<br>12<br>11  | MUD<br>10<br>11  | WOD<br>20<br>9   | BAS<br>102<br>9  |
|-------------------------------------|-------------------|---------------------|----------------|------------------|------------------|------------------|------------------|
| GRS. WALL AREA<br>GLAZING           | 260<br>LOSS GAIN  | 680<br>LOSS GAIN    | 0<br>LOSS GAIN | 132<br>LOSS GAIN | 110<br>LOSS GAIN | 180<br>LOSS GAIN | 732<br>LOSS GAIN |
| NORTH                               | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| EAST                                | 29 573            | 0 0                 | 0 0            | 5 99             | 0 0              | 0 0              | 0 0              |
| SOUTH                               | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| WEST                                | 0 0               | 69 1165             | 2501           | 0 0              | 0 0              | 0 0              | 0 0              |
| SKYLT.                              | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| DOORS                               | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| NET EXPOSED WALL                    | 231 958           | 214 501             | 2077 465       | 20 469           | 105 20           | 469 105          | 469 105          |
| NET EXPOSED B.S.M.T. WALL ABOVE GR. | 0 0               | 0 0                 | 0 0            | 107 444          | 99 90            | 373 83           | 0 0              |
| EXPOSED CLG                         | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| NO A.T.T.C. EXPOSED CLG             | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| EXPOSED FLOOR                       | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| BASEMENT CRAWL HEAT LOSS            | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| SLAB ON GRADE HEAT LOSS             | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| SUBTOTAL HT LOSS                    | 1531              | 4203                | 3333           | 1012             | 842              | 180              | 4408             |
| SUB TOTAL HT GAIN                   | 0.30 0.60         | 0.30 0.60           | 0.30 0.60      | 0.30 0.60        | 0.30 0.60        | 0.30 0.60        | 0.30 0.60        |
| LEVEL FACTOR / MULTIPLIER           | 770               | 2114                | 458            | 509              | 424              | 25               | 6360             |
| AIR CHANGE HEAT LOSS                | 0 0               | 0 0                 | 0 0            | 0 0              | 0 0              | 0 0              | 0 0              |
| AIR CHANGE HEAT GAIN                | 0 0               | 1 240               | 419            | 0 0              | 0 0              | 0 0              | 0 0              |
| DUCT LOSS                           | 2301              | 6316                | 5786           | 1520             | 1256             | 803              | 10768            |
| DUCT GAIN                           | 0                 | 0                   | 0              | 0                | 0                | 0                | 0                |
| HEAT GAIN PEOPLE                    | 240               | 0                   | 0              | 0                | 0                | 0                | 0                |
| HEAT GAIN APPLIANCES/LIGHTS         | 0                 | 0                   | 0              | 0                | 0                | 0                | 0                |
| TOTAL HT LOSS BTU/H                 | 2580              | 5786                | 791            | 615              | 824              | 234              | 1341             |
| TOTAL HT GAIN x 1.3 BTU/H           | 2580              | 5786                | 791            | 615              | 824              | 234              | 1341             |

TOTAL HEAT GAIN BTU/H: 24982  
TONS: 2.08  
TOTAL COMBINED HEAT LOSS BTU/H: 34191  
STRUCTURAL HEAT LOSS: 31641  
LOSS DUE TO VENTILATION LOAD BTU/H: 2650

SITE NAME: RUSSEL GARDENS  
BUILDER: GREENPARK HOMES

TYPE: HIGHGROVE 2

DATE: Jul-17

GFA: 1793 LO# 75021

HEATING CFM 890 COOLING CFM 890  
TOTAL HEAT LOSS 31,541 TOTAL HEAT GAIN 24,389  
AIR FLOW RATE CFM 28.22 AIR FLOW RATE CFM 36.49furnace pressure 0.6  
furnace filter 0.05  
a/c coil pressure 0.2  
available pressure 0.35  
for s/a & r/a

#GOODMAN

AFUE = 96 %  
INPUT (BTU/H) = 40,000  
OUTPUT (BTU/H) = 38,400

| RUN COUNT | 4th | 3rd | 2nd | 1st | Bas |
|-----------|-----|-----|-----|-----|-----|
| S/A       | 0   | 0   | 10  | 6   | 4   |
| R/A       | 0   | 0   | 3   | 2   | 1   |

All S/A diffusers 4"x10" unless noted otherwise on layout.  
All S/A runs 5'10" unless noted otherwise on layout.

| ROOM NAME                 | MBR  | ENS  | WIC  | BED-2 | BED-3 | BED-3 | BATH | 7    | 8    | 10   | 11   | 12   | 13   | 14   | 17   | 19   | 20   | 21   | 22   | 23   | 24   |
|---------------------------|------|------|------|-------|-------|-------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|------|
| RM LOSS MBH               | 1.03 | 1.19 | 0.26 | 1.11  | 1.11  | 1.11  | 1.11 | 0.12 | 1.11 | 1.03 | 2.11 | 2.11 | 2.30 | 2.11 | 0.50 | 1.52 | 1.27 | 2.89 | 2.89 | 2.89 | BAS  |
| CFM PER RUN HEAT          | 29   | 34   | 7    | 31    | 31    | 31    | 31   | 3    | 31   | 29   | 59   | 59   | 65   | 59   | 14   | 43   | 36   | 82   | 82   | 82   | BAS  |
| RM GAIN MBH               | 1.69 | 1.19 | 0.11 | 1.69  | 1.99  | 1.99  | 1.99 | 0.07 | 1.99 | 1.69 | 1.93 | 1.93 | 2.68 | 1.93 | 29   | 62   | 70   | 98   | 82   | 82   | BAS  |
| CFM PER RUN COOLING       | 62   | 43   | 4    | 62    | 73    | 62    | 73   | 2    | 73   | 62   | 70   | 70   | 98   | 70   | 29   | 22   | 30   | 14   | 14   | 14   | BAS  |
| ADJUSTED PRESSURE         | 0.17 | 0.17 | 0.17 | 0.17  | 0.17  | 0.17  | 0.17 | 0.17 | 0.17 | 0.17 | 0.17 | 0.17 | 0.16 | 0.17 | 0.17 | 0.17 | 0.17 | 0.16 | 0.16 | 0.16 | BAS  |
| EQUIVALENT LENGTH         | 32   | 26   | 22   | 42    | 50    | 46    | 36   | 47   | 47   | 25   | 27   | 20   | 41   | 22   | 28   | 32   | 18   | 18   | 12   | 29   | 16   |
| TOTAL EFFECTIVE LENGTH    | 110  | 210  | 180  | 160   | 180   | 170   | 170  | 170  | 170  | 220  | 100  | 90   | 160  | 100  | 120  | 100  | 160  | 90   | 150  | 120  | 120  |
| ADJUSTED PRESSURE         | 0.12 | 0.07 | 0.09 | 0.09  | 0.07  | 0.08  | 0.08 | 0.08 | 0.08 | 0.07 | 0.14 | 0.16 | 0.08 | 0.14 | 0.12 | 0.13 | 0.1  | 0.15 | 0.1  | 0.11 | 0.12 |
| ROUND DUCT SIZE           | 4    | 4    | 4    | 5     | 5     | 5     | 4    | 5    | 5    | 5    | 5    | 5    | 6    | 5    | 4    | 4    | 4    | 5    | 5    | 5    | 5    |
| HEATING VELOCITY (ft/min) | 333  | 390  | 80   | 228   | 228   | 228   | 34   | 228  | 228  | 213  | 433  | 433  | 331  | 433  | 161  | 493  | 413  | 602  | 602  | 602  | 602  |
| COOLING VELOCITY (ft/min) | 711  | 493  | 46   | 455   | 536   | 455   | 23   | 536  | 514  | 455  | 514  | 500  | 514  | 514  | 333  | 252  | 344  | 103  | 103  | 103  | 103  |
| OUTLET GRILL SIZE         | 3X10 | 3X10 | 3X10 | 3X10  | 3X10  | 3X10  | 3X10 | 3X10 | 3X10 | 3X10 | 3X10 | 3X10 | 4X10 | 3X10 | 3X10 | 3X10 | 3X10 | 3X10 | 3X10 | 3X10 | 3X10 |
| TRUNK                     | A    | C    | C    | C     | B     | B     | C    | C    | B    | C    | A    | D    | B    | A    | C    | B    | C    | D    | C    | B    | A    |

TEMPERATURE RISE 40 °F

DESIGN CFM = 890  
CFM @ 0.5" E.S.P.MEADOW LOW  
MEDIUM HIGH  
MEDIUM HIGHr/a pressure 0.17  
r/a grille press. loss 0.02  
adjusted pressure r/a 0.15

| ROOM NAME | RM LOSS MBH | CFM PER RUN HEAT | RM GAIN MBH | CFM PER RUN COOLING | ADJUSTED PRESSURE | EQUIVALENT LENGTH | TOTAL EFFECTIVE LENGTH | ADJUSTED PRESSURE | ROUND DUCT SIZE | HEATING VELOCITY (ft/min) | COOLING VELOCITY (ft/min) | OUTLET GRILL SIZE | TRUNK |
|-----------|-------------|------------------|-------------|---------------------|-------------------|-------------------|------------------------|-------------------|-----------------|---------------------------|---------------------------|-------------------|-------|
| TRUNK A   |             |                  |             |                     |                   |                   |                        |                   |                 |                           |                           |                   |       |
| TRUNK B   |             |                  |             |                     |                   |                   |                        |                   |                 |                           |                           |                   |       |
| TRUNK C   |             |                  |             |                     |                   |                   |                        |                   |                 |                           |                           |                   |       |
| TRUNK D   |             |                  |             |                     |                   |                   |                        |                   |                 |                           |                           |                   |       |
| TRUNK E   |             |                  |             |                     |                   |                   |                        |                   |                 |                           |                           |                   |       |
| TRUNK F   |             |                  |             |                     |                   |                   |                        |                   |                 |                           |                           |                   |       |

## SUPPLY AIR TRUNK SIZE

| TRUNK   | CFM | RECT DUCT | ROUND DUCT | STATIC PRESS | TRUNK CFM | STATIC PRESS | ROUND DUCT | RECT DUCT | VELOCITY (ft/min) | TRUNK G | TRUNK H | TRUNK I | TRUNK J | TRUNK K | TRUNK L | VELOCITY (ft/min) |
|---------|-----|-----------|------------|--------------|-----------|--------------|------------|-----------|-------------------|---------|---------|---------|---------|---------|---------|-------------------|
| TRUNK A | 229 | 6         | 7.3        | 0.12         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0       | 0       | 0       | 0                 |
| TRUNK B | 252 | 10        | 8.7        | 0.07         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0       | 0       | 0       | 0                 |
| TRUNK C | 519 | 14        | 11.3       | 0.07         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0       | 0       | 0       | 0                 |
| TRUNK D | 889 | 22        | 13.9       | 0.07         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0       | 0       | 0       | 0                 |
| TRUNK E | 0   | 0         | 0          | 0.00         | 0         | 0.00         | 0          | 0         | 0                 | 0       | 0       | 0       | 0       | 0       | 0       | 0                 |
| TRUNK F | 0   | 0         | 0          | 0.00         | 0         | 0.00         | 0          | 0         | 0                 | 0       | 0       | 0       | 0       | 0       | 0       | 0                 |

## RETURN AIR TRUNK SIZE

| TRUNK   | CFM | RECT DUCT | ROUND DUCT | STATIC PRESS | TRUNK CFM | STATIC PRESS | ROUND DUCT | RECT DUCT | VELOCITY (ft/min) | TRUNK X | TRUNK Y | TRUNK Z | DROP | VELOCITY (ft/min) |
|---------|-----|-----------|------------|--------------|-----------|--------------|------------|-----------|-------------------|---------|---------|---------|------|-------------------|
| TRUNK A | 229 | 6         | 7.3        | 0.12         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0    | 0                 |
| TRUNK B | 252 | 10        | 8.7        | 0.07         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0    | 0                 |
| TRUNK C | 519 | 14        | 11.3       | 0.07         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0    | 0                 |
| TRUNK D | 889 | 22        | 13.9       | 0.07         | 0         | 0.00         | 0          | 0         | 887               | 0       | 0       | 0       | 0    | 0                 |
| TRUNK E | 0   | 0         | 0          | 0.00         | 0         | 0.00         | 0          | 0         | 0                 | 0       | 0       | 0       | 0    | 0                 |
| TRUNK F | 0   | 0         | 0          | 0.00         | 0         | 0.00         | 0          | 0         | 0                 | 0       | 0       | 0       | 0    | 0                 |

TYPE: HIGHGROVE 2  
SITE NAME: RUSSEL GARDENS

LO # 75021

**RESIDENTIAL MECHANICAL VENTILATION DESIGN SUMMARY**

| COMBUSTION APPLIANCES                  |                                                      | 9.32.3.1(1) |
|----------------------------------------|------------------------------------------------------|-------------|
| a) <input checked="" type="checkbox"/> | Direct vent (sealed combustion) only                 |             |
| b) <input type="checkbox"/>            | Positive venting induced draft (except fireplaces)   |             |
| c) <input type="checkbox"/>            | Natural draft, B-vent or induced draft gas fireplace |             |
| d) <input type="checkbox"/>            | Solid Fuel (including fireplaces)                    |             |
| e) <input type="checkbox"/>            | No Combustion Appliances                             |             |

| HEATING SYSTEM                      |                     |
|-------------------------------------|---------------------|
| <input checked="" type="checkbox"/> | Forced Air          |
| <input type="checkbox"/>            | Non Forced Air      |
| <input type="checkbox"/>            | Electric Space Heat |

| HOUSE TYPE                          |                                                         | 9.32.1(2) |
|-------------------------------------|---------------------------------------------------------|-----------|
| <input checked="" type="checkbox"/> | I Type a) or b) appliance only, no solid fuel           |           |
| <input type="checkbox"/>            | II Type I except with solid fuel (including fireplaces) |           |
| <input type="checkbox"/>            | III Any Type c) appliance                               |           |
| <input type="checkbox"/>            | IV Type I, or II with electric space heat               |           |
| <input type="checkbox"/>            | Other: Type I, II or IV no forced air                   |           |

| SYSTEM DESIGN OPTIONS               |                                                 | O.N.H.W.P. |
|-------------------------------------|-------------------------------------------------|------------|
| <input type="checkbox"/>            | 1 Exhaust only/Forced Air System                |            |
| <input type="checkbox"/>            | 2 HRV with Ducting/Forced Air System            |            |
| <input checked="" type="checkbox"/> | 3 HRV Simplified/connected to forced air system |            |
| <input type="checkbox"/>            | 4 HRV with Ducting/non forced air system        |            |
| <input type="checkbox"/>            | Part 6 Design                                   |            |

| TOTAL VENTILATION CAPACITY |              | 9.32.3.3(1) |
|----------------------------|--------------|-------------|
| Basement + Master Bedroom  | 2 @ 21.2 cfm | 42.4 cfm    |
| Other Bedrooms             | 2 @ 10.6 cfm | 21.2 cfm    |
| Kitchen & Bathrooms        | 4 @ 10.6 cfm | 42.4 cfm    |
| Other Rooms                | 5 @ 10.6 cfm | 53.0 cfm    |
| Table 9.32.3.A.            | TOTAL        | 159.0 cfm   |

| PRINCIPAL VENTILATION CAPACITY REQUIRED |      | 9.32.3.4.(1) |
|-----------------------------------------|------|--------------|
| 1 Bedroom                               | 31.8 | cfm          |
| 2 Bedroom                               | 47.7 | cfm          |
| 3 Bedroom                               | 63.6 | cfm          |
| 4 Bedroom                               | 79.5 | cfm          |
| 5 Bedroom                               | 95.4 | cfm          |
| TOTAL                                   | 63.6 | cfm          |

| SUPPLEMENTAL VENTILATION CAPACITY |      | 9.32.3.5. |
|-----------------------------------|------|-----------|
| Total Ventilation Capacity        | 159  | cfm       |
| Less Principal Ventil. Capacity   | 139  | cfm       |
| Required Supplemental Capacity    | 20.0 | cfm       |

| PRINCIPAL EXHAUST FAN CAPACITY      |              |
|-------------------------------------|--------------|
| Model:                              | VANEE 60H-V+ |
| Location:                           | BSMT         |
| 139.0 cfm                           | 3.0 sones    |
| <input checked="" type="checkbox"/> | HVI Approved |

| PRINCIPAL EXHAUST HEAT LOSS CALCULATION |        |        |        |      |  |
|-----------------------------------------|--------|--------|--------|------|--|
| CFM                                     | ΔT °F  | FACTOR | % LOSS |      |  |
| 139.0 CFM                               | X 71 F | X 1.08 | X      | 0.25 |  |

| SUPPLEMENTAL FANS |           | NUTONE |                                     |
|-------------------|-----------|--------|-------------------------------------|
| Location          | Model     | cfm    | HVI                                 |
| ENS               | QTXEN050C | 50     | <input checked="" type="checkbox"/> |
| BATH              | QTXEN050C | 50     | <input checked="" type="checkbox"/> |
|                   |           |        |                                     |

| HEAT RECOVERY VENTILATOR |                                     | 9.32.3.11.   |
|--------------------------|-------------------------------------|--------------|
| Model:                   | VANEE 60H-V+                        |              |
| 139 cfm high             | 50 cfm low                          |              |
| 75 % Sensible Efficiency | <input checked="" type="checkbox"/> | HVI Approved |
| @ 32 deg F ( 0 deg C)    |                                     |              |

| LOCATION OF INSTALLATION |                   |
|--------------------------|-------------------|
| Lot:                     | Concession        |
| Township                 | Plan:             |
| Address                  |                   |
| Roll #                   | Building Permit # |

| BUILDER:        |        |
|-----------------|--------|
| GREENPARK HOMES |        |
| Name:           |        |
| Address:        |        |
| City:           |        |
| Telephone #:    | Fax #: |

| INSTALLING CONTRACTOR |        |
|-----------------------|--------|
| Name:                 |        |
| Address:              |        |
| City:                 |        |
| Telephone #:          | Fax #: |

| DESIGNER CERTIFICATION                                                                                        |                         |
|---------------------------------------------------------------------------------------------------------------|-------------------------|
| I hereby certify that this ventilation system has been designed in accordance with the Ontario Building Code. |                         |
| Name:                                                                                                         | HVAC Designs Ltd.       |
| Signature:                                                                                                    | <i>Michael O'Rourke</i> |
| HRAI #                                                                                                        | 001820                  |
| Date:                                                                                                         | July-17                 |


**HEAT LOSS AND GAIN SUMMARY SHEET****MODEL:** HIGHGROVE 2  
**SFQT:** 1793**LO#** 75021**BUILDER:** GREENPARK HOMES  
**SITE:** RUSSEL GARDENS**DESIGN ASSUMPTIONS**

| HEATING              | °F | COOLING                        | °F |
|----------------------|----|--------------------------------|----|
| OUTDOOR DESIGN TEMP. | 1  | OUTDOOR DESIGN TEMP.           | 88 |
| INDOOR DESIGN TEMP.  | 72 | INDOOR DESIGN TEMP. (MAX 75°F) | 72 |

**BUILDING DATA**


|                                                  |                 |                           |          |
|--------------------------------------------------|-----------------|---------------------------|----------|
| ATTACHMENT:                                      | ATTACHED        | # OF STORIES (+BASEMENT): | 3        |
| FRONT FACES:                                     | EAST            | ASSUMED (Y/N):            | Y        |
| AIR CHANGES PER HOUR:                            | 4.55            | ASSUMED (Y/N):            | Y        |
| AIR TIGHTNESS CATEGORY:                          | AVERAGE         | ASSUMED (Y/N):            | Y        |
| WIND EXPOSURE:                                   | SHELTERED       | ASSUMED (Y/N):            | Y        |
| HOUSE VOLUME (ft <sup>3</sup> ):                 | 24617.0         | ASSUMED (Y/N):            | Y        |
| INTERNAL SHADING:                                | BLINDS/CURTAINS | ASSUMED OCCUPANTS:        | 4        |
| INTERIOR LIGHTING LOAD (Btu/h/ft <sup>2</sup> ): | 1.27            | DC BRUSHLESS MOTOR (Y/N): | Y        |
| FOUNDATION CONFIGURATION                         | BCIN_1          | DEPTH BELOW GRADE:        | 6.0 ft   |
| LENGTH: 50.0 ft                                  | WIDTH: 20.0 ft  | EXPOSED PERIMETER:        | 102.0 ft |

| 2012 OBC - COMPLIANCE PACKAGE                                              |                       |           |
|----------------------------------------------------------------------------|-----------------------|-----------|
| Component                                                                  | Compliance Package A1 |           |
|                                                                            | Nominal               | Min. Eff. |
| Ceiling with Attic Space Minimum RSI (R)-Value                             | 60                    | 59.22     |
| Ceiling Without Attic Space Minimum RSI (R)-Value                          | 31                    | 27.65     |
| Exposed Floor Minimum RSI (R)-Value                                        | 31                    | 29.80     |
| Walls Above Grade Minimum RSI (R)-Value                                    | 22                    | 17.03     |
| Basement Walls Minimum RSI (R)-Value                                       | 20 ci                 | 21.12     |
| Below Grade Slab Entire surface > 600 mm below grade Minimum RSI (R)-Value | -                     | -         |
| Edge of Below Grade Slab ≤ 600 mm Below Grade Minimum RSI (R)-Value        | 10                    | 10        |
| Heated Slab or Slab ≤ 600 mm below grade Minimum RSI (R)-Value             | 10                    | 11.13     |
| Windows and Sliding Glass Doors Maximum U-Value                            | 0.28                  | -         |
| Skylights Maximum U-Value                                                  | 0.49                  | -         |
| Space Heating Equipment Minimum AFUE                                       | 0.96                  | -         |
| HRV Minimum Efficiency                                                     | 75%                   | -         |
| Domestic Hot Water Heater Minimum EF                                       | 0.8                   | -         |

INDIVIDUAL BCIN: 19669  
MICHAEL O'ROURKE

## Residential Foundation Thermal Load Calculator

Supplemental tool for CAN/CSA-F280

| Weather Station Description    |                                           |                                                                                                                 |
|--------------------------------|-------------------------------------------|-----------------------------------------------------------------------------------------------------------------|
| Province:                      | Ontario                                   |                                                                                                                 |
| Region:                        | Hamilton                                  |                                                                                                                 |
| Site Description               |                                           |                                                                                                                 |
| Soil Conductivity:             | Normal conductivity: dry sand, loam, clay |                                                                                                                 |
| Water Table:                   | Normal (7-10 m, 23-33 ft)                 |                                                                                                                 |
| Foundation Dimensions          |                                           |                                                                                                                 |
| Floor Length (m):              | 15.2                                      | <br>Insulation Configuration |
| Floor Width (m):               | 6.1                                       |                                                                                                                 |
| Exposed Perimeter (m):         | 31.1                                      |                                                                                                                 |
| Wall Height (m):               | 2.7                                       |                                                                                                                 |
| Depth Below Grade (m):         | 1.83                                      |                                                                                                                 |
| Window Area (m <sup>2</sup> ): | 0.7                                       |                                                                                                                 |
| Door Area (m <sup>2</sup> ):   | 1.9                                       |                                                                                                                 |
| Radiant Slab                   |                                           |                                                                                                                 |
| Heated Fraction of the Slab:   | 0                                         |                                                                                                                 |
| Fluid Temperature (°C):        | 33                                        |                                                                                                                 |
| Design Months                  |                                           |                                                                                                                 |
| Heating Month                  | 1                                         |                                                                                                                 |
| Foundation Loads               |                                           |                                                                                                                 |
| Heating Load (Watts):          | 925                                       |                                                                                                                 |


TYPE: HIGHGROVE 2  
LO# 75021

## Air Infiltration Residential Load Calculator


Supplemental tool for CAN/CSA-F280

| Weather Station Description       |                                |                        |    |    |
|-----------------------------------|--------------------------------|------------------------|----|----|
| Province:                         | Ontario                        |                        |    |    |
| Region:                           | Hamilton                       |                        |    |    |
| Weather Station Location:         | Open flat terrain, grass       |                        |    |    |
| Anemometer height (m):            | 10                             |                        |    |    |
| Local Shielding                   |                                |                        |    |    |
| Building Site:                    | Suburban, forest               |                        |    |    |
| Walls:                            | Heavy                          |                        |    |    |
| Flue:                             | Heavy                          |                        |    |    |
| Highest Ceiling Height (m):       | 6.71                           |                        |    |    |
| Building Configuration            |                                |                        |    |    |
| Type:                             | Semi                           |                        |    |    |
| Number of Stories:                | Two                            |                        |    |    |
| Foundation:                       | Full                           |                        |    |    |
| House Volume (m <sup>3</sup> ):   | 697.1                          |                        |    |    |
| Air Leakage/Ventilation           |                                |                        |    |    |
| Air Tightness Type:               | Average (1946-1960) (4.55 ACH) |                        |    |    |
| Custom BDT Data:                  | ELA @ 10 Pa.                   | 1184.3 cm <sup>2</sup> |    |    |
|                                   | 4.55                           | ACH @ 50 Pa            |    |    |
| Mechanical Ventilation (L/s):     | Total Supply                   | Total Exhaust          |    |    |
|                                   | 65.6                           | 65.6                   |    |    |
| Flue Size                         |                                |                        |    |    |
| Flue #:                           | #1                             | #2                     | #3 | #4 |
| Diameter (mm):                    | 0                              | 0                      | 0  | 0  |
| Natural Infiltration Rates        |                                |                        |    |    |
| Heating Air Leakage Rate (ACH/H): | 0.409                          |                        |    |    |
| Cooling Air Leakage Rate (ACH/H): | 0.155                          |                        |    |    |


TYPE: HIGHGROVE 2  
LO# 75021



BASEMENT PLAN – ELEV. 1



PART. BASEMENT PLAN W.O.D CONDITION (8R OR MORE)



PART. BASEMENT PLAN W.O.D CONDITION (4R TO 7R MAX.)



I MICHAEL O'ROURKE HAVE REVIEW AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.

CSA-F280-12  
PACKAGE A1

| HVAC LEGEND |                           |        |                                 |        |                              |        |                            | 3.        |             |      |
|-------------|---------------------------|--------|---------------------------------|--------|------------------------------|--------|----------------------------|-----------|-------------|------|
| SYMBOL      | DESCRIPTION               | SYMBOL | DESCRIPTION                     | SYMBOL | DESCRIPTION                  | SYMBOL | DESCRIPTION                | 2.        |             |      |
|             | SUPPLY AIR GRILLE         |        | 6" SUPPLY AIR BOOT ABOVE        |        | 14"x8" RETURN AIR GRILLE     |        | RETURN AIR STACK ABOVE     | 1.        |             |      |
|             | SUPPLY AIR GRILLE 6" BOOT |        | SUPPLY AIR STACK FROM 2nd FLOOR |        | 30"x8" RETURN AIR GRILLE     |        | RETURN AIR STACK 2nd FLOOR | No.       | Description | Date |
|             | SUPPLY AIR BOOT ABOVE     |        | 6" SUPPLY AIR STACK 2nd FLOOR   |        | FRA- FLOOR RETURN AIR GRILLE |        | REDUCER                    | REVISIONS |             |      |

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

|                                                             |  |                                                                                                                                                                                                                                                                      |                                    |  |                                                                                                                                                             |  |    |   |                                                       |  |   |
|-------------------------------------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|------------------------------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------|--|----|---|-------------------------------------------------------|--|---|
| Client<br><b>GREENPARK HOMES</b>                            |  | <div><b>HVACDESIGNS LTD.</b><br/>375 Finley Ave. Suite 202 - Ajax, Ontario<br/>L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375<br/>Email: info@hvacdesigns.ca<br/>Web: www.hvacdesigns.ca<br/>Specializing in Residential Mechanical Design Services</div> | HEAT LOSS 34191 BTU/H<br>UNIT DATA |  | # OF RUNS S/A R/A FANS                                                                                                                                      |  |    |   | Sheet Title<br><b>BASEMENT<br/>HEATING<br/>LAYOUT</b> |  |   |
| Project Name<br><b>RUSSEL GARDENS<br/>HAMILTON, ONTARIO</b> |  |                                                                                                                                                                                                                                                                      | MAKE<br>GOODMAN                    |  | 3RD FLOOR                                                                                                                                                   |  |    |   |                                                       |  |   |
|                                                             |  |                                                                                                                                                                                                                                                                      | MODEL<br>GMEC960402BNA-40          |  | 2ND FLOOR                                                                                                                                                   |  | 10 | 3 |                                                       |  | 3 |
|                                                             |  |                                                                                                                                                                                                                                                                      | INPUT<br>40 MBTU/H                 |  | 1ST FLOOR                                                                                                                                                   |  | 6  | 2 | 2                                                     |  |   |
|                                                             |  |                                                                                                                                                                                                                                                                      | OUTPUT<br>38.4 MBTU/H              |  | BASEMENT                                                                                                                                                    |  | 4  | 1 | 0                                                     |  |   |
| HIGHGROVE 2 1793 sqft                                       |  | Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper.<br>Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.           | COOLING<br>2.0 TONS                |  | ALL S/A DIFFUSERS 4"x10"<br>UNLESS NOTED OTHERWISE<br>ON LAYOUT. ALL S/A RUNS 5'Ø<br>UNLESS NOTED OTHERWISE<br>ON LAYOUT. UNDERCUT<br>DOORS 1" min. FOR R/A |  |    |   | Date<br>JULY/2017                                     |  |   |
| FAN SPEED<br>890 cfm @ 0.6" w.c.                            |  |                                                                                                                                                                                                                                                                      | Scale<br>3/16" = 1'-0"             |  |                                                                                                                                                             |  |    |   |                                                       |  |   |
|                                                             |  |                                                                                                                                                                                                                                                                      |                                    |  | BCIN# 19669                                                                                                                                                 |  |    |   | LO# 75021                                             |  |   |



PART. GROUND FLOOR PLAN W.O.D  
CONDITION (4R TO 8R OR MORE)

GROUND FLOOR PLAN – ELEV. 1

I MICHAEL O'ROURKE HAVE REVIEWED AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.

Michael O'Rourke  
Michael O'Rourke, BCIN# 19669  
HVAC DESIGNS LTD.


CSA-F280-12  
PACKAGE A1

| HVAC LEGEND |                           |        |                                 |        |                              |        |                            | 3.        |             |      |
|-------------|---------------------------|--------|---------------------------------|--------|------------------------------|--------|----------------------------|-----------|-------------|------|
| SYMBOL      | DESCRIPTION               | SYMBOL | DESCRIPTION                     | SYMBOL | DESCRIPTION                  | SYMBOL | DESCRIPTION                | 2.        |             |      |
|             | SUPPLY AIR GRILLE         |        | 6" SUPPLY AIR BOOT ABOVE        |        | 14"x8" RETURN AIR GRILLE     |        | RETURN AIR STACK ABOVE     | 1.        |             |      |
|             | SUPPLY AIR GRILLE 6" BOOT |        | SUPPLY AIR STACK FROM 2nd FLOOR |        | 30"x8" RETURN AIR GRILLE     |        | RETURN AIR STACK 2nd FLOOR | No.       | Description | Date |
|             | SUPPLY AIR BOOT ABOVE     |        | 6" SUPPLY AIR STACK 2nd FLOOR   |        | FRA- FLOOR RETURN AIR GRILLE |        | REDUCER                    | REVISIONS |             |      |


ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

|                                                     |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                 |       |
|-----------------------------------------------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|-------------------------------------------------|-------|
| Client<br>GREENPARK HOMES                           |  | <div><p>375 Finley Ave. Suite 202 - Ajax, Ontario<br/>L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375<br/>Email: info@hvacdesigns.ca<br/>Web: www.hvacdesigns.ca<br/>Specializing in Residential Mechanical Design Services</p><p>Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper.<br/>Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.</p></div> | Sheet Title<br>FIRST FLOOR<br>HEATING<br>LAYOUT |       |
| Project Name<br>RUSSEL GARDENS<br>HAMILTON, ONTARIO |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Date<br>JULY/2017                               |       |
| HIGHGROVE 2      1793 sqft                          |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Scale<br>3/16" = 1'-0"                          |       |
|                                                     |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | BCIN# 19669                                     |       |
|                                                     |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | LO#                                             | 75021 |





SECOND FLOOR PLAN – ELEV. 1



SECOND FLOOR PLAN – ELEV. 2

I MICHAEL O'ROURKE HAVE REVIEWED AND TAKE RESPONSIBILITY FOR THE DESIGN WORK AND AM QUALIFIED UNDER DIVISION C, 3.2.5 OF THE BUILDING CODE.  
*Michael O'Rourke*  
Michael O'Rourke, BCIN# 19669  
HVAC DESIGNS LTD.

CSA-F280-12  
PACKAGE A1

| HVAC LEGEND |                           |        |                                 |        |                              |        |                            | 3.        |             |      |
|-------------|---------------------------|--------|---------------------------------|--------|------------------------------|--------|----------------------------|-----------|-------------|------|
| SYMBOL      | DESCRIPTION               | SYMBOL | DESCRIPTION                     | SYMBOL | DESCRIPTION                  | SYMBOL | DESCRIPTION                | 2.        |             |      |
|             | SUPPLY AIR GRILLE         |        | 6" SUPPLY AIR BOOT ABOVE        |        | 14"x8" RETURN AIR GRILLE     |        | RETURN AIR STACK ABOVE     | 1.        |             |      |
|             | SUPPLY AIR GRILLE 6" BOOT |        | SUPPLY AIR STACK FROM 2nd FLOOR |        | 30"x6" RETURN AIR GRILLE     |        | RETURN AIR STACK 2nd FLOOR | No.       | Description | Date |
|             | SUPPLY AIR BOOT ABOVE     |        | 6" SUPPLY AIR STACK 2nd FLOOR   |        | FRA- FLOOR RETURN AIR GRILLE |        | REDUCER                    | REVISIONS |             |      |

ALL DRAWINGS, CALCULATIONS AND SPECIFICATIONS ARE THE PROPERTY OF HVAC DESIGNS LTD.© AND MAY NOT BE REPRODUCED, MODIFIED OR ALTERED WITHOUT EXPRESSED WRITTEN CONSENT. THE DRAWINGS ARE DATED AND USE OF THESE DRAWINGS AFTER ONE YEAR FROM THE DATED NOTED IS NOT AUTHORIZED. CONTRACTOR SHALL CHECK ALL CONDITIONS BEFORE PROCEEDING WITH WORK. LATEST MUNICIPAL APPROVED DRAWINGS ONLY TO BE USED DURING INSTALLATION OF HEATING SYSTEM. HVAC DESIGNS LTD. IS NOT LIABLE FOR ANY CLAIMS ARISING FROM UNAUTHORIZED USE OF THE DRAWINGS OR FROM ANY CHANGES TO ACCEPTED STANDARDS AND/OR THE ONTARIO BUILDING CODE.

|                                                     |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       |                                                  |  |
|-----------------------------------------------------|--|-------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--------------------------------------------------|--|
| Client<br>GREENPARK HOMES                           |  | <div><p>375 Finley Ave. Suite 202 - Ajax, Ontario<br/>L1S 2E2 Tel. 905.619.2300 - 905.420.5300 Fax 905.619.2375<br/>Email: info@hvacdesigns.ca<br/>Web: www.hvacdesigns.ca<br/>Specializing in Residential Mechanical Design Services</p><p>Installation to comply with the latest Ontario Building Code. All supply branch outlets shall be equipped with a manual balancing damper.<br/>Ductwork which passes through the garage or unheated spaces shall be adequately insulated and be gas-proofed.</p></div> | Sheet Title<br>SECOND FLOOR<br>HEATING<br>LAYOUT |  |
| Project Name<br>RUSSEL GARDENS<br>HAMILTON, ONTARIO |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Date<br>JULY/2017                                |  |
| HIGHGROVE 2      1793 sqft                          |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | Scale<br>3/16" = 1'-0"                           |  |
|                                                     |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | BCIN# 19669                                      |  |
|                                                     |  |                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                                       | LO#      75021                                   |  |