## Sales Selection Sheet Checklist

1 of 46

LOT 3186A-5 Model: 20-1456 B The Hampton

PURCHASERS: GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA

VENDOR: Heathwood Homes (Huron) Limited

COFFERED CEILING IN GREAT ROOM
OPTIONAL DOUBLE SINKS IN MASTER ENSUITE BATHROOM

	COLD	CELLAR				
UPGRA	ADED / I	MODIFIED ELEVATION	ON			
	CORNE	R UPGRADE				
	REAR L	JPGRADE				
		RADE - SMOOTH				
	MAIN FI					
	SECON BASEM	D FLOOR				
	DASEIVI	ENI				
ADDITI	ONAL F	ROUGH-INS				
	200 AMI	P SERVICE				
	WET BA	AR ROUGH-IN				
	HUMIDI	FIER				
Y	AIR CO	NDITIONING				
CACD	0110111	NI .				
GAS RO	STOVE	N				
<u> </u>	DRYER					
	BBQ					
	ADDITIO	ONAL FIREPLACE				
KITCHE	EN: HO	ODFAN VENTING SIZ	ZE			
		UND DUCT				
	7 IN RO	UND DUCT				
E	405145	NIT OTAIDO	<b>D</b> 1/0			
		NT STAIRS: MENT STAIRS:	N/A All Oak			
		MENT STAIRS:	Carpet Grade			
MAIN S		VILIVI O I/ (II CO.	All Oak			
		(if applicable):	N/A			
LOFT S	TAIRS (	(if applicable):	N/A			
April 8,	2022	Signature on file		April 8, 2022	TINA LEFUR	
Da	te	Purchaser:		Date	Decor Consultant:	
Da	te	Purchaser:		April 8, 2022	MARILYN ROSEN	
				Date	Heathwood Homes (H	luron) Limited
Locked	Date:			Approved		

Y

FINISHED BASEMENT

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton



Kitchen			
Cabinet Colour/Style	9166	Viking III-CHARLESTON-ORCHID-3DL ***STD***	
Countertop	9121	MSI Quartz GROUP 1 ICED WHITE 3/4 inch with double mitre edge ***1***	I
Countertop Edge	4005	DOUBLE MITRE 1 1/2 INCH ***UPG***	
Cabinet Hardware	2086	9677-HARDWARE ***STD***	ı
Island Cabinet Colour/Style	9166	Viking III-CHARLESTON-ORCHID-3DL ***STD***	l
Island Countertop	9121	MSI Quartz GROUP 1 ICED WHITE 3/4 inch with double mitre edge ***1***	l
Backsplash	8104	OD.ON.TPE.02.HEX.MT-ONTARIO HEXAGON MATTE-TAUPE ***2***	
Backsplash Grout	2226	Grout-(00) White ***STD***	ı
Backsplash Tile Pattern	3110	HORIZONTAL HEX ***STD***	
HoodFan	9393	SCB51930-CYCLONE 30 inch CANOPY CHIMNEY HOODFAN-SS	34-35
HoodFan	9393	Purchasers have been advised: standard fridge opening is a minimum 37 3/8 x 73 3/8". Ice Waterline Rough-In is included.	
Appliances	9393	Standard stove opening is 30" and standard dishwasher opening is 24". Any gas stove will require backsplash or stainless steel backing to avoid fire hazards.	
Appliances	9393	Purchasers acknowledge: Heathwood Homes and its contractors will not be responsible for any kitchen cabinet changes due to appliances dimension changes after	I
Comment			
Kitchen/Breakfast	_		
Flooring	9393	GE.MD.WHT.1818.MT Madison Series White Matte 18	
Floor Tile Grout	2225	Grout-(27) Silver ***STD***	ı
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***	

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton

Page 2 of 8

Locked: Closed:

			Ciosea.
Comment			
Hall		_	
<u>l</u> lali			
Flooring		7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
Comment			
Foyer			
Flooring		7498	GE.MD.WHT.1818.MT Madison Series White Matte 18
Floor Tile G	rout	2225	Grout-(27) Silver ***STD***
Floor Tile Pa	attern	3000	STANDARD SQUARE ***STD***
Comment			
Mud Room			
Flooring		3000	GE.MD.WHT.1818.MT Madison Series White Matte 18
Floor Tile G	rout	2225	Grout-(27) Silver ***STD***
Floor Tile Pa	attern	3000	STANDARD SQUARE ***STD***
Comment			
Powder Room		<b>—</b>	
Flooring		3000	GE.MD.WHT.1818.MT Madison Series White Matte 18

Grout (27) Silver \*\*\*STD\*\*\*

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton

Floor Flie Grout		KKKU	Olout-(21) Olivei Olo
Floor Tile Pattern		3000	STANDARD SQUARE ***STD***
Plumbing Fixture (	Colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment			
Great Room			
Flooring		7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
Comment			
Upper Hall			
Flooring		7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch ***3***
Comment			
Finished Basement (R	ec) Room/Hall		
Flooring		9247	DY 16611-Dynasty Tex-SANDY BEIGE-40 oz Poly***STD***
Comment			
Master Bedroom			
Flooring		9247	DY 16611-Dynasty Tex-SANDY BEIGE-40 oz Poly***STD***
Comment			
Bedroom 2		_	
Flooring		9247	DY 16611-Dynasty Tex-SANDY BEIGE-40 oz Poly***STD***

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton



Comment		
room 3		
Flooring	9247	DY 16611-Dynasty Tex-SANDY BEIGE-40 oz Poly***STD***
Comment		
ter Ensuite		
	0444	VIKING III SIMCOE ORCHID 3DL ***STD***
Cabinet Colour/Style	9111	VIKING III SINICOE ORCHID 3DL STD
Countertop	8801	P-344 LM-Countertop-INUKSHUK GREY-Arborite ***STD***
Countertop Edge	1111	N/A *****
Cabinet Hardware	2086	9677-HARDWARE ***STD***
Floor Tile	2086	GE.MD.WHT.1818.MT Madison Series White Matte 18
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Shower Floor Tile	8661	OD.ON.SWT.0202.MT.N-Ontario Series Mosaic-Snow White Matte-2 x 2 ***STD***
Shower Floor Tile Grout	2226	Grout-(00) White ***STD***
Shower Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Shower Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***
Shower Wall Tile Grout	2226	Grout-(00) White ***STD***
Shower Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton



Shower Jamb(s) and Sill(s)	8923	Shower Jamb / Sill-Thassos White ***STD***
Plumbing Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment		
Main Bathroom		
Cabinet Colour/Style	9111	VIKING III SIMCOE ORCHID 3DL ***STD***
Countertop	8801	P-344 LM-Countertop-INUKSHUK GREY-Arborite ***STD***
Countertop Edge	1111	N/A *****
Cabinet Hardware	2086	9677-HARDWARE ***STD***
Flooring	2086	GE.MD.WHT.1818.MT Madison Series White Matte 18
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Tub Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***
Tub Wall Tile Grout	2226	Grout-(00) White ***STD***
Tub Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***
Plumbing Fixture (Colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment		
Finished Basement Bathroom		
	0444	WIKING III OIMOOF ODOLUD ODL ***CTD***
Cabinet Colour/Style	9111	VIKING III SIMCOE ORCHID 3DL ***STD***
Countertop Page 5 of 8	8801	P-344 LM-Countertop-INUKSHUK GREY-Arborite
	8801	P-344 LM-Countertop-INUKSHUK GREY-Arborite

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton

		***STD***	
Countertop Edge	1111	N/A *****	
Cabinet Hardware	2086	9677-HARDWARE ***STD***	
Flooring	2086	GE.MD.WHT.1818.MT Madison Series White Matte 18	
Floor Tile Grout	2225	Grout-(27) Silver ***STD***	
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***	
Shower Floor Tile	8661	OD.ON.SWT.0202.MT.N-Ontario Series Mosaic-Snow White Matte-2 x 2 ***STD***	
Shower Floor Tile Grout	2226	Grout-(00) White ***STD***	
Shower Floor Tile Pattern	3000	STANDARD SQUARE ***STD***	
Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***	
Wall Tile Grout	2226	Grout-(00) White ***STD***	
Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***	
Shower Jamb(s)	8923	Shower Jamb / Sill-Thassos White ***STD***	
Plumbing Fixture (Colour)	1737	Plumbing Fixtures-WHITE ***STD***	
Comment			
Great Room Fireplace			
Туре	8865	Dimplex-Electric Fireplace-PF3033HL ***STD***	
Mantle	8891	NF-17-Paint Grade Mantle- Cabinet (Per Plan)-WHITE ***STD***	PG 22
Surround Opt.	1111	N/A *****	

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton



Disclaimer	1111	Purchasers have been advised: heat from the FP can damage TV above a FP and items placed on mantle.
Disclaimer	1111	Heathwood and its contractors will not be liable for any damage on items placed/installed above a FP after closing.
Comment		
Basement Stairs		
Туре	1111	Carpet Grade Stairs ***STD BASEMENT STAIRS***
Colour	7912	Irongate (Gryphon) STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING
Carpet Runner	1111	N/A *****
Handrail/Pickets/Post Type	9119	Handrail only on closed walls (one or two sides per building code) ***STD***
Handrail/Pickets/Post Colours	1729	Carpet Grade-Stain handrail, pickets, stringers, nosing _pos
Carpet	9247	DY 16611-Dynasty Tex-SANDY BEIGE-40 oz Poly***STD***
Custom Stain/Paint	1111	N/A *****
Comment		
Basement Stairs Landing(s)		
5( )		
Flooring	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch ***3***
Comment		
Main Stairs		
Туре	1714	Oak Stairs ***STD MAIN STAIRS***
Colour	7912	Irongate (Gryphon) STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING
Carpet Runner	1111	N/A *****
Handrail/Pickets/Posts Type	7652	1 5/16 inch Square pickets with 3 1/2" Square/Cap Post(s)-ALL OAK ***STD***

GURPREET, SINGH CHHABRA/MANPREET, KAUR CHHABRA Project: Wallaceton Unit: 3186A-5, Phase: 3 Model: 20-1456 B The Hampton



Handrail	Pickets/Posts Colour	1728	Oak Grade-Stain handrail,oak pickets,stringers,treads,r		
Custom	Stain/Paint	1111	N/A *****		
Commer	it				
Main Stairs L	anding(s)				
Flooring		7498	Red Oak F	Pearl-Vintage	
1 looning		7490	Engineere	d-GRYPHON/IRONGATE-3/4	inch x 3 1/4 inch
Commer	nt				
Throughout					
Walls - F	aint Colour	1717	22-Wall-W	ARM GREY ***STD***	
Underpa	d	1079	500 Series	s-Underpad ***STD***	
Threshol	ds	2232	Metal Thre	esholds ***STD***	
Switches	and Plug	5796	Decora White Switches and Plugs ***STD***		
Trim Size	e	8705	4 1/4 Baseboard and 2 3/4 Casings ***STD***		
Trim - Pa	nint Colour	1716	Trim-WHI	ΓΕ ***STD***	
Commer	nt				
Purchaser:					
	GURPREET, SINGH CHH	ABR/	Date	Decor Consultant	Date
Purchaser:					
. 410114361.	MANPREET, KAUR CHH	 ABRA	Date	Wallaceton	Date Approved

# 10 of 46



Lot: 3186A-5

Model: 20-1456 B The Hampton Project/Phase: Wallaceton / 3

Offer	Five Appliances: SS Fridge, Stove, Dishwasher: White Front Loader Washer/Dryer - Townhomes
Worksheet	Note:
Offer	The Purchaser(s) acknowledge that they have NOT been referred by an existing Heathwood Homeowner and therefor are not
	entitled to referral fee under Heathwood Homes referral program
Worksheet	Note:

DisciplineMS.rpt 13dec21 Page 1 of 6

# construction summary of 46



Lot: 3186A-5 Model: 20-1456 B The Hampton Project/Phase: Wallaceton / 3

#### **APPLIANCES**

invoice	Qıy.	Description
962	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930
313,484		
12Apr22		
		CABINETRY - delete stove uppers; ELECTRICAL - delete std range hood; HEATING/AIR CONDITIONING - Du
		change to 6"

#### CARINETRY

CABIN	LII	KY
Invoice	Qty.	Description
962 313,624 12Apr22	1	KITCHEN - 04H-66cm deep fridge enclosure (counter depth) with (1) wall ([1] 66cm deep gable and [1] 66cm deep cabinet) (This is not a zero clearance enclosure. Standard heights and widths will be used.) Viking  SKETCH # 3
962 313,768 12Apr22	1	KITCHEN - 11A-Upper angle corner per unit Viking SKETCH # 3
962 314,040 12Apr22	1	KITCHEN - 30H-Wall cabinet with shelf for microwave (finished interior) (opening 24 InchW x 13 3/4 InchH x 17 InchD) Viking SKETCH # 3
962 313,484 12Apr22 **	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930  CABINETRY - delete stove uppers; ELECTRICAL - delete std range hood; HEATING/AIR CONDITIONING - Du change to 6"
962 334,723 12Apr22 **	1	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING  SKETCH # 4  CABINETRY-2D Convert Cabinetry Viking; Eletrical-Additional Vanity Light

CARPI	CARPET		
Invoice	Qty.	Description	
962 311,441	1	UPPER HALL - HARDWOOD - VINTAGE - 3-1/4 INCH RED OAK ENGINEERED - UPPER HALL - UPG	
12Apr22 **		CARPET - delete std CARPET; INTERIOR TRIM - supply and install quarter rounds; PAINTING - paint quarter	

DisciplineMS.rpt 13dec21 Page 2 of 6

# construction summary of 46



Lot: 3186A-5

Model: 20-1456 B The Hampton Project/Phase: Wallaceton / 3

#### **CERAMICS**

Invoice	Qty.	Description
1037 314,179 08Apr22	1	- CERAMICS - ADDITIONAL BACKSPLASH DUE TO INSTALL CHIMENEY HOODFAN IN KITCHEN - KITCHEN - UPGRADE 2
962 308,014 12Apr22	1	KITCHEN/BREAKFAST - CERAMICS - FLOOR - KITCHEN - UPGRADE 1
962 307,978 12Apr22	1	KITCHEN - CERAMICS - BACKSPLASH - KITCHEN - UPGRADE 2
962 307,999 12Apr22	1	FOYER - CERAMICS - FLOOR - FOYER - UPGRADE 1
962 308,042 12Apr22	1	POWDER ROOM - CERAMICS - FLOOR - POWDER ROOM - UPGRADE 1
962 308,028 12Apr22	1	MUD ROOM - CERAMICS - FLOOR - MUD ROOM - UPGRADE 1
962 307,992 12Apr22	1	MASTER ENSUITE - CERAMICS - FLOOR - ENSUITE MASTER - UPGRADE 1
962 308,021 12Apr22	1	MAIN BATHROOM - CERAMICS - FLOOR - MAIN BATHROOM - UPGRADE 1
962 307,985 12Apr22	1	FINISHED BASEMENT BATHROOM - CERAMICS - FLOOR - BASEMENT BATHROOM - UPGRADE 1

#### COFFERED CEILING

COLLE	COFFERED CEILING		
Invoice	Qty.	Description	
962 310,655 12Apr22	1	GREAT ROOM - COFFERED CEILING - OPT. COFFERED CEILING - GREAT ROOM	
•		DRYWALL - notification; PAINTING- notification	

DisciplineMS.rpt 13dec21 Page 3 of 6

# 13 of 46 construction summary



Lot: 3186A-5

Model: 20-1456 B The Hampton Project/Phase: Wallaceton / 3

#### **DRYWALL**

Invoice	Qty.	Description
962	1	- DRYWALL - SMOOTH CEILING IN MAIN FLOOR
310,689		
12Apr22		
		PAINTING - Paint smooth ceiling
962	1	GREAT ROOM - COFFERED CEILING - OPT. COFFERED CEILING - GREAT ROOM
310,655		
12Apr22		
**		DRYWALL - notification; PAINTING- notification

#### ELECTRICAL

ELECTRICAL		
Invoice	Qty.	Description
962 314,223	3	- ELECTRICAL - ADDITIONAL SWITCH
12Apr22		1) 1X IN GREAT ROOM FOR 2 CAPPED ELECTRICAL 2) 1X ON ISLAND WITH CAPPED ELECTRICAL 3) 1X BREAKFAST ROOM ON SEPARATE SWITCH (KEEP STD KITCHEN ON STD 3-WAY) SKETCH # 2
962 314,224	3	- ELECTRICAL - CEILING ROUGH-IN (CAPPED)
12Apr22		1) 2X IN GREAT ROOM ON SEPERATE SWITCH;2) 1X CENTERED +/- ON ISLAND ON SEPERATE SWITCH SKETCH # 2
962 314,232	1	GREAT ROOM - ELECTRICAL - EXTRA WALL INTERIOR OUTLET ON EXISTING CIRCUIT (DOES NOT INCLUDE KITCHEN OUTLETS)
12Apr22		TO BE CENTERED +/- ABOVE FIREPLACE APPROX. 70" +/- FROM FLOOR SKETCH # 2
962 314,340	1	KITCHEN - HEATING/AIR - ROUGH-IN GAS LINE FOR GAS STOVE AT MAIN FLOOR (SEE SPECS) (HOOK-UP NOT INCLUDED) LEAVE STANDARD 120 VOLT ELECTRICAL OUTLET ON A SEPARATE CIRCUIT. * STANDARD 220V WILL STAY
12Apr22 **		SKETCH # 3 ELECTRICAL - notification
962 314,229	1	KITCHEN - ELECTRICAL - EXTRA WALL INTERIOR OUTLET (120V/15A) ON A SEPARATE CIRCUIT (ON ARCFAULT)
12Apr22		FOR MIDROWAVE SHELF SKETCH # 3
962 313,484	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930
12Apr22 **		CABINETRY - delete stove uppers; ELECTRICAL - delete std range hood; HEATING/AIR CONDITIONING - Du change to 6"
962 334,723	1	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING
12Apr22 **		SKETCH # 4 CABINETRY-2D Convert Cabinetry Viking; Eletrical-Additional Vanity Light

#### GLASS PRODUCTS / MIRRORS

Invoice	Qty.	Description
962 310,740 12Apr22	-	MASTER ENSUITE - MIRRORS/GLASS PRODUCTS - UPGRADE TO FRAMELESS CLEAR GLASS WITH D-RING HANDLE IN CHROME - ENSUITE MASTER

DisciplineMS.rpt 13dec21

Page 4 of 6

# 14 of 46 CONSTRUCTION SUMMARY



Lot: 3186A-5 Model: 20-1456 B The Hampton Project/Phase: Wallaceton / 3

#### **GRANITE**

Iı	nvoice	Qty.	Description
	962	1	KITCHEN - GRANITE - COUNTERTOP - 3/4 INCH GROUP 1 WITH MITRE EDGE - KITCHEN / ISLAND - UPG
	310,801		
	12Apr22		
L			

#### **HARDWOOD**

Invoice	Qty.	Description
962	1	UPPER HALL - HARDWOOD - VINTAGE - 3-1/4 INCH RED OAK ENGINEERED - UPPER HALL - UPG
311,441		
12Apr22		
		CARPET - delete std CARPET; INTERIOR TRIM - supply and install quarter rounds; PAINTING - paint quarter

#### **HEATING / AIR CONDITIONING**

IILAII	HEATING / AIR CONDITIONING		
Invoice	Qty.	Description	
962 314,340 12Apr22	1	KITCHEN - HEATING/AIR - ROUGH-IN GAS LINE FOR GAS STOVE AT MAIN FLOOR (SEE SPECS) (HOOK-UP NOT INCLUDED) LEAVE STANDARD 120 VOLT ELECTRICAL OUTLET ON A SEPARATE CIRCUIT. * STANDARD 220V WILL STAY SKETCH # 3 ELECTRICAL - notification	
962 313,484 12Apr22 **	1	KITCHEN - APPLIANCES - CYCLONE 30 INCH WALL MOUNT CHIMNEY HOOD SS - SCB51930  CABINETRY - delete stove uppers; ELECTRICAL - delete std range hood; HEATING/AIR CONDITIONING - Duchange to 6"	

#### **INTERIOR TRIM AND DOORS**

Invoice	Qty.	Description
962	1	UPPER HALL - HARDWOOD - VINTAGE - 3-1/4 INCH RED OAK ENGINEERED - UPPER HALL - UPG
311,441		
12Apr22		
**		CARPET - delete std CARPET; INTERIOR TRIM - supply and install quarter rounds; PAINTING - paint quarter

#### DAINTING

PAINI	PAINTING		
Invoice	Qty.	Description	
962	1	- DRYWALL - SMOOTH CEILING IN MAIN FLOOR	
310,689			
12Apr22			
**		PAINTING - Paint smooth ceiling	
962	1	GREAT ROOM - COFFERED CEILING - OPT. COFFERED CEILING - GREAT ROOM	
310,655			
12Apr22			
**		DRYWALL - notification; PAINTING- notification	
962	1	UPPER HALL - HARDWOOD - VINTAGE - 3-1/4 INCH RED OAK ENGINEERED - UPPER HALL - UPG	
311,441			
12Apr22			
**		CARPET - delete std CARPET: INTERIOR TRIM - supply and install quarter rounds: PAINTING - paint quarter	

DisciplineMS.rpt 13dec21 Page 5 of 6

# 15 of 46 construction summary



Lot: 3186A-5 Model: 20-1456 B The Hampton

Project/Phase: Wallaceton / 3

#### **PLUMBING**

Invoice	Qty.	Description
962 314,479 12Apr22	3	- PLUMBING - MOEN -HANDHELD SHOWER - ENGAGE ECO-PERFORMANCE 6 FUNCTION HAND SHOWER WITH MAGNETIX DOCKING MODEL 26100 EP CHROME ( IN LIEU OF STANDARD SHOWERHEAD ) - MASTER ENSUITE/ MAIN BATHROOM / BASEMENT BATH
962 334,723 12Apr22		MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING  SKETCH # 4  CABINETRY-2D Convert Cabinetry Viking; Eletrical-Additional Vanity Light

#### **SECURITY**

Invoice	Qty.	Description
1066 314,534 26May22		- SECURITY - SECURITY CAMERA ROUGH-IN -V-CAMIP5- IP CAMERA ROUGH-IN (CAT 5e RUN TO HOME ELECTRICAL PANEL SKETCH # 6

STRUC	STRUCTURED WIRING							
Invoice	Qty.	Description						
962 314,543 12Apr22	1	GREAT ROOM - STRUCTURED WIRING - HDMI TO ABOVE FIREPLACE ROUGH-IN  GREAT ROOM - TO BE CENTERED +/- WITH PLUG ABOVE FIREPLACE APPROX. 70" +/- FROM FLOOR SKETCH # 2						
1066 314,550 26May22	2	- STRUCTURED WIRING RELOCATE STANDARD CAT 5¢ TELEPHONE ROUGH-IN AND STANDARD RG6 TV ROUGH-IN IN LOWER LEVEL RECREATION ROOM AND MAIN FLOOR GREAT ROOM- PFIN INSTALLATION CHARGE SKETCH #'S 5 AND 6						

DisciplineMS.rpt 13dec21 Page 6 of 6

16 of 46

### THE HAMPTON


SKETCH #1

20-1456 ELEV. B

ELEVATION B | 1,800 SQ. FT.

Includes 329 sq. ft. of Finished Lower Level

WALLACETON



17 of 46

## THE HAMPTON


SKETCH #2


ELEVATION B | 1,800 SQ. FT.

Includes 329 sq. ft. of Finished Lower Level

WALLACETON

20-1456 ELEV. B





19 of 46

### THE HAMPTON


SKETCH #4

20-1456 ELEV. B

ELEVATION B | 1,800 SQ. FT.

Includes 329 sq. ft. of Finished Lower Level


WALLACETON



Model: 20-1456 B The Hampton

20 of 46

Sketch#5




LOWER LEVEL ELEVATION B

luplut Singh

Mày 21, 2022

Model: 20-1456 B The Hampton

## 21 of 46



22 of 46





NFAS NF17 Mantel

Franke Kindred Canada Limited

Project: Wallaceton Unit: 3186A-5, Phase: 3


Model: 20-1456 B The Hampton


## Reginox

### ND1831UA/9

23 of 46







#### ND1831UA/9 SPECIFICATION

Model ND1831UA/9 is a double (two equal size) bowl undermount sink manufactured by Franke Kindred Canada Limited from 18 gauge stainless steel. Product has silk finished rims and linear brush finished bowls. Sink is fully undercoated. Basket strainer waste fittings (3 1/2", 89 mm) are included. Sink is backed with a limited lifetime warranty.

- O.D. 17 3/4" x 30 7/8" x 8 1/2" (45 x 78 x 22 cm)
- Recommended for minimum 36" cabinet

Franke Kindred Canada Limited

P.O. Box 190, 1000 Franke Kindred Road, Midland, Ontario, Canada, L4R 4K9 Phone: 866-687-7465 Fax: 800-361-8408

Model: 20-1456 B The Hampton

## 24 of 46

## MOEN

#### **FAUCET DESCRIPTION**

Reflex™ pulldown system offers smooth operation, easy movement and secure docking Power Clean™ spray technology Metal construction with various finishes identified by suffix

Quick connect installation

- Pulldown spray with 68" braided hose Flexible supply lines with 3/8" compression fittings
- High arc spout provides height and reach to fill or clean large pots while pulldown wand provides the maneuverability for cleaning or rinsing 360° rotating spout

Faucet designed for handle to be mounted on right side only

**OPERATION** 

- Lever style handle
- Temperature controlled by 100° arc of handle travel

Operates with less than 5 lbs. of force

• Operates in stream or spray mode in the pullout or retracted position **FLOW** 

Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi

CARTRIDGE

• 1255™ Duralast™ cartridge

#### **STANDARDS**


Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9G & 372

- Meets CalGreen and Georgia SB370 requirements Complies with California Proposition 65 and with the Federal Safe Drinking
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA 🖒 for lever handle

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations

## Specifications




ALIGN™ **Single Handle High Arc Pulldown Kitchen Faucet** 

Models: 7565 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA. (OPTIONAL 3-HOLE ESCUTCHEON 141002 AVAILABLE)





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev. 6/20



**b** BARRIER FREE (ABOVE COUNTER OR DROP-IN ONLY)

#### BOULEVARD® PEDESTAL SINK VITREOUS CHINA

#### **BOULEVARD® PEDESTAL SINK**

☐ 0641.800 Faucet holes on 8" (203mm) centers (Illustrated)

STD • 0641.400 Faucet holes on 4" (102mm) centers

#### ☐ 0641.100 Center hole only

- · Classic styled rectangular pedestal lavatory
- Vitreous china
- Rear overflow
- Supplied with mounting kit
- Right Height® for greater comfort during use
- Faucet ledge with large deck area (faucet not included)
- Design coordinates with Boulevard® Toilet
- Basin has flat bottom to also allow use as an **above counter** sink or a **drop-in** sink (with u-shaped cut out)

#### **Nominal Dimensions:**

24" x 19" x 35-1/2" (610 x 483 x 902mm)

- ☐ 0641.008 Pedestal top-8" (203mm) centers
- **0641.004** Pedestal top-4" (102mm) centers
- ☐ 0641.001 Pedestal top-center hole only
- □ **0010.000** Pedestal only

#### Bowl sizes:

17" (432mm) wide, 12-1/2" (318mm) front to back, 5" (127mm) deep

#### **Compliance Certifications -**

#### Meets or Exceeds the Following Specifications:

• ASME A112.19.2 - 2008/CSA B45.1-08

#### To Be Specified:

- ☐ Color: ☐ White ☐ Linen
- ☐ Faucet Finish:
- Supplies:
- ☐ 1-1/4" Trap:
- □ Nipple:



SEE REVERSE FOR ROUGHING-IN DIMENSIONS

<sup>\*</sup> See faucet section for additional models available


26 of 46


4merican

tandard

#### **BOULEVARD®** PEDESTAL SINK VITREOUS CHINA

**barrier free (above counter or drop-in only)** 





ABOVE COUNTER AND DROP-IN SINK CONFIGURATIONS MEET THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES.

Top of sink installed at 34" (864mm) height from finished floor. Sink installed 5" (127mm) minimum from front edge of countertop. Provide 27" (686mm) knee clearance area.

NOTES:

\* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAPS ARE SUGGESTED.

▼ PEDESTAL ANCHORING SCREWS NOT INCLUDED.

■ SUITABLE FOR REINFORCEMENT ONLY. ACTUAL DIMENSIONS MUST BE TAKEN FROM FIXTURE.

FITTING NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL SUPPORTS.

INISTALL ATION INSTRICTIONS SUPPLIED WITH I AWATORY. INSTALLATION INSTRUCTIONS SUPPLIED WITH LAVATORY.

**IMPORTANT:** Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

© 2018 AS America Inc.

27 of 46

### American Standard

### **BARRIER FREE**

#### **COLONY™ COUNTERTOP SINK**

VITREOUS CHINA

#### **COLONY COUNTERTOP SINK**

- · Vitreous china
- Self-rimming
- · Front overflow
- · Supplied with template
- Faucet deck (Faucet shown not included)

☐ 0346 803 → Faucet hotes on 203mm (8"), centres	$\mathcal{L}$
O346 403 (Illustrated) Faucet holes on 102mm (4") centres	3
₩ <u>₽</u> 0346001	~
Contro holo only	


Centre hole only

Nominal Dimensions: 521 x 448mm (20-1/2" x 17-5/8")

Bowl sizes:

422mm (16-5/8") wide, 279mm (11") front to back, 143mm (5-5/8") deep





#### COMPLIANCE CERTIFICATIONS -

Meets or exceeds the following Specifications:

- ASME A112.19.2M for Vitreous China Fixtures.
- · CAN/CSA B45 Series.

To I	Be Specified
	Colour: ☐ White ☐ Bone ☐ Silver Gray
	Linen
	Faucet*:
	Faucet Finish:
	Supplies & Stops:
	Trap 1-1/4" (32 mm):

NOTES:

\* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED. \* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED. FOR COUNTERTOP CUTOUT AND INSTALLATION INSTRUCTIONS USE TEMPLATE SUPPLIED WITH SINK.
FAUCETS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.
IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard ATI2.19.2.
These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

BAS-198

<sup>\*</sup> See faucet section for additional models available

Model: 20-1456 B The Hampton

## 28 of 46



### DEMI™ **Product Specification Sheet**

### Two Piece Freestanding Collection

CF2007 Two Piece Freestanding Soaker


Size: 60" x 32" x 22"

1524 mm x 813 mm x 559 mm




- Vacuum formed acrylic reinforced with fiberglass
- Scratch, stain and fade resistant high gloss finish
- Installation friendly two piece design
- Accepts deck mounted faucet
- Includes integral pop up drain and rectangular overflow
- Includes levelling feet


#### TWO PIECE ASSEMBLY



#### **TOP VIEW**



#### **END VIEW**



#### **GENERAL SPECIFICATIONS**

Average Weight	90 lb	41 kg
Bathing Well at bottom	43"x 20"	1092 x 508 mm
Capacity Drain to Overflow		195 litres
Water Depth Drain to Overflow	16"	406 mm
Drain Opening (dia.)	2"	51 mm
Overflow Opening	2 ¼"x ½"	57 x 13 mm
Drain to Floor Clearance	3 1/4"	83 mm

NOTES: Please confirm measurements on actual product to ensure proper identification. Bathtub to be installed on the floor supported by 5 self levelling feet. Adjust if required to level the bathtub for adequate drainage. Refer to installation instructions for additional information.

**IMPORTANT:** Dimensions of fixtures are nominal and may vary  $\pm$  %" (6 mm). Weight may vary  $\pm$  5 lb ( 2.3 kg). Drawing is not to scale. These measurements are subject to change at manufacturer's discretion.

**Compliance Certifications -**

Meets or Exceeds the following Specifications:

CAN/CSA - B45 Series





Fax: 416.231.0929 www.mirolin.com

*Customer Service:* 416.231.5790 Canada, U.S.A.: 800.**MIROLIN**(647-6546) Fax, Canada: 800.463.2236

R0084162 25 Sep. 2018

Model: 20-1456 B The Hampton

## 29 of 46

## American Standard

Style That Works Better

#### FloWise™ DUAL FLUSH **ELONGATED TOILET**

VITREOUS CHINA


#### FloWise™ DUAL FLUSH ELONGATED TOILET

#### **2476 216**

- Vitreous china
- · Low-consumption Dual Flush Full flush 6.0 Lpf/1.3 gpf, Partial flush 3.0 Lpf/0.66 gpf.
- · Elongated wash down bowl
- · Internal trapway fully-glazed, 2-1/4" (57mm) ballpass
- · Concealed trapway bowl
- · Chrome-plated top mounted push button actuator
- Easy to clean sanitary dam on bowl
- Includes Elongated Slow Close Seat
- 100% factory flush tested
- · 2 bolt caps

#### **Separate Component Parts:**

- ☐ 3067 316 Elongated Bowl with Slow Close Seat
- **4035 216** Unlined Tank



- ☐ 3067 316 Elongated Bowl
- **4035 516** Lined Tank


Nominal Dimensions: 794 x 432 x 765mm (31-1/4" x 17" x 30-1/8")


#### **Compliance Certifications -**Meets or Exceeds the Following Specifications:

- ASME A112.19.2M (and 19.6M)
- · CAN/CSA B45 series

#### To Be Specified

- Colour: 020 White
- Supply with stop:





NOTES:
THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12")
FROM FINISHED WALL TO C/L OF OUTLET.
SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.
\* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.
FOR ADDITIONAL INFORMATION REFER TO INSTALLATION INSTRUCTIONS SUPPLIED.
IMPORTANT. Dimensions of fixture are peripaid and may use within the prepare of the present

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2

established by Ankist damagna (112.19.2). These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

#### UPGRADED VALUE ADDED FEATURES AT NO EXTRA CHARGE

TOI-284

© 2008 American Standard

Model: 20-1456 B The Hampton

## 30 of 46

## **MOEN**<sup>®</sup>

#### DESCRIPTION

- Metal construction with various finishes identified by suffix
- 16" long 3/8" tubing connections Includes metal or 50/50 pop-up type waste assembly where noted **OPERATION**
- Pivot action lever style handle Temperature controlled through 180° degree arc of handle travel **FLOW**
- Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi

#### CARTRIDGE

- 1225 cartridge design
- Nonmetallic/nonferrous and stainless steel material
- Can accommodate reversed piping and back to back installations

- Third party certified to WaterSense®, CSA B-125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Complies with California Proposition 65 and with the Federal Safe
- Drinking Water Act

  ADA for lever handle

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

### Specifications



**CHATEAU® Single-Handle Lavatory Faucet** 

#### with Metal Waste Assembly Model: L4625 series L4631BC


**Bulk Packed (12 per carton):** L64624 series

#### with 50/50 Waste Assembly **Bulk Packed (12 per carton):** L64625 series

#### Less Waste **Bulk Packed (12 per carton):** L64600 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 3-1" DIA. HOLES, 2" ON CENTER





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev 8/15

Model: 20-1456 B The Hampton

## 31 of 46



Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

- Metal construction with various finishes identified by suffix
- Includes non-metalic showerhead, arm, flange and non-metalic diverter tub spout

#### **OPERATION**

- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to  $\pm\,3^\circ$

- Showerhead is limited to 2.5 gpm (9.5 L/min) at 80 psi EP suffix models are limited to 1.75 gpm (6.6 L/min) at 80 psi
- NH suffix models contain no showerhead

#### **CARTRIDGE**

- 1222 cartridge design Accommodates back to back installations
- Nonmetallic/nonferrous and stainless steel material

#### **STANDARDS**

- Third party certified to meet ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- EP suffix models are third party certified to WaterSense®
- ADA ( for lever handle

6.5" (165mm) ESC. DIAM.

#### **WARRANTY**

Lifetime limited warranty against leaks, drips and finish defects

2"CC (51mm) 1 7/8" IPS (48mm) MAX WALL

FINISHED WALL LINE

4-1/2" (114mm)

WALL OPENING

7-1/2" (190mm)

to the original consumer purchaser 5 year warranty if used in commercial installations

### **Specifications**






#### CHATEAU° POSI-TEMP° Single-Handle Tub/Shower Trim Kit

Models: TL181 series - valve trim only (Bulk Packed 12 per carton) TL182 series - shower trim only (Bulk Packed 12 per carton)

TL183 series - tub/shower trim (Bulk Packed 12 per carton)

Valves: 62300 series 2500 series



**THICK WALL APPLICATION CRITICAL DIMENSIONS** 

— 1/2" MIN. CC (13mm) 5/8" MIN. IPS (16mm)

2 1/2" MAX. (63mm)

SHOWER

48" (1219mm) 32" (813mm) AND TUB ONLY

(DO NOT SCALE)

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

TL183sp: Rev. 5/13

## **MOEN**<sup>®</sup>

X3
MASTER ENSUITE
MAIN BATHROOM
BASEMENT BATH

### **Specifications**

#### **DESCRIPTION**

- · Various finishes identified by suffix
- Includes handshower, hose and magnetic dock
- Magnetix™ technology features an innovative magnetic docking system
- · 60" hose that extends reach and flexibility
- EP suffix models assembled with two check valves for backflow prevention
- 1/2" IPS connection

#### **OPERATION**

- Six Spray Settings
- · Magnetic dock rotates to adjust angle of handshower

#### **FLOW**

- Designed to deliver 2.5 gpm (9.5 L/min) MAX at 80 psi
- EP suffix models designed to deliver 1.75 gpm (6.6 L/min) MAX at 80 psi (for models manufactured after 3/1/18)
- EP suffix models designed to deliver 2.0 gpm (7.6 L/min) MAX at 80 psi (for models manufactured before 3/1/18)

#### **STANDARDS**

- Designed and manufactured to comply with the applicable requirements of WaterSense®, ASME A112.18.1/CSA B-125.1,ASSE 1014 and all applicable specifications referenced therein
- EP suffix models are third party certified to WaterSense®

#### **WARRANTY**

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations




Engage™ 6-Function Handshower with Magnetix™ Docking and Hose

Models: 26100 series



**EP Suffix Models Only** 



FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

12/20

Model: 20-1456 B The Hampton

## 33 of 46

## **MOEN**<sup>®</sup>

#### **DESCRIPTION**

Metal construction with various finishes identified by suffix

#### **OPERATION**

- Lever style handles with hot and cold color indicator
- Rotate hot side handle counterclockwise to open (clockwise to close) and the cold side handle (clockwise to open) and (counterclockwise to close)


#### **STANDARDS**

- Third party certified to: ASME A112.18.1/CSA B-125.1, and all applicable requirements referenced therein
- ADA 🕒 for lever handles

#### **WARRANTY**

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multi-family installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations


## Specifications




#### **CHATEAU® Two-Handle Garden Tub Trim**

Models: T994 series

**Valves:** 4792, 4793, 4794, 4796, 4797, 4798





#### **CRITICAL DIMENSIONS**

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev. 3/19

Model: 20-1456 B The Hampton

## 34 of 46

### SC(B)519 | ALITO Collection





#### **Wall Mount**

Strong and sturdy with attractive lines and an imposing frame, the SC(B)519 is fitted with a time-delay OFF feature up to nine minutes, a 550 CFM fan, two bright front mounted LED lights and a digital three-speed push button control panel.

#### **Green Features**



3 Speed Push Button Control Panel



Time-Delay OFF Feature



Long-Lasting LED Lights



Grease Cup



Model Colour Ducting Filters Size CF	FM
--------------------------------------	----

SCB51930 Stainless Steel	6"	Baffle	30"	550
--------------------------	----	--------	-----	-----

Model: 20-1456 B The Hampton


## 35 of 46

### SC(B)519 | ALITO Collection



#### **Features**

- · Wall mount range hood
- 6" round duct adapter
- Non-stick aluminum fan blades
- 3 speed push button control
- 2 LED lights (2 x 1.4W, 4000K)
- · Quick release aluminum mesh filters
- · Standard chimney fits up to 9 ft. ceiling
- · Up to 9 minutes time-delay OFF feature
- Plug-in connection



### **Options**

• Filters:

SCB519 - Quick Release Stainless Steel Baffle Filters

Chimney Flues:

A1.CH10 - short (7'-8' ceilings)

A1.CH18 - standard (8'-9' ceilings)

A1.CH30 - extended (9'-11' ceilings)

• Widths: 24",(30")36"

### **Specifications**

Air Flow Volume: 550 CFM

Electrical Connection: 120 V/60 Hz

Power Consumption: 300 Watts

Current: 2.5 Amps

Fan Speed: 1599 RPM

Fan Type: Centrifugal Blower

· Finishes: Stainless Steel

Ducting: 6" Round

Noise Level: Min. 2 Sones

Max. 6 Sones



36 of 46 Model: 20-1456 B The Hampton



## Whirtpool® 21 cu. ft. Top-Freezer Refrigerator WRT541SZD



Fingerprint-Resistant Stainless WRT541SZDZ

#### Also available in:

White	WRT541SZDW
Black	WRT541SZDB
Monochromatic Stainless Steel	WRT541SZDM

Capacity					
Total Capacity	21 cu. ft.				
Refrigerator Capacity	15 cu. ft.				
Freezer Capacity	6 cu. ft.				
General Features & Propert	ies				
EZ Connect Icemaker Kit					
LED Interior Lighting					
ENERGY STAR® Certified					
Electronic Temperature Controls					
Freezer Temperature Controls					
Clear Door Bins					
Adjustable Door Bins					
Quiet Cooling					
Fingerprint Resistant					
Electrical Details					
Amps 6.5					
Volts 115					
Certifications					
ADA Compliant Yes					
ENERGY STAR® Certified Yes					

Technical Details			
Refrigerator Type	Top-Freezer		
Number of Doors	2		
Number of Interior Refrigerator Shelves	3		
Number of Refrigerator Door Bins	1 Fixed, 4 Adjustable		
Number of Interior Freezer Shelves	1		
Number of Freezer Door Bins	2 Fixed		
Lighting Type	LED		
Ice Maker	Optional		
Ice Maker Location	Freezer		
Dispenser Type	N/A		
Dimensions			
Product Dimensions (H x W x D)	66-1/4" x 32-3/4" x 34"		
Depth with Door Open 90°	62-1/4"		
Cutout Dimensions	Allow extra 1/2" on sides and top Allow extra 1" on rear		
Reference Material			

#### Key Features & Benefits

#### Frameless Glass Shelves


Store more items on wall-to-wall shelves for greater storage flexibility.

#### Flexi-Slide™ Bin

Make space for tall items with the bin that quickly and easily moves side to side.

#### **Humidity-Controlled Crispers**

Store fruits and vegetables in their ideal environment.



**Dimension Guide** Use & Care Guide

**Energy Guide** 

NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXC. WRT541SZDSPECSHEETV01.

Model: 20-1456 B The Hampton

## 37 of 46



#### **Top Mount Refrigerator**

#### **PRODUCT MODEL NUMBERS**

WRT311FZD WRT511SZD WRT541SZD

**Electrical:** A 115-volt, 60-Hz, AC-only, 15-or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.


NOTE: Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting. See "Using the Controls."

**Water:** A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

**IMPORTANT:** The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 30 and 120 psi (207 and 827 kPa).


**Reverse Osmosis Water Supply:** If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

#### **PRODUCT DIMENSIONS**



Model Number	Model Size	Reversible Door	Height - Overall "A"	Height - Top of Cabinet "B"	Depth - Door Open 90° "C"	Depth - With Handles "D"	Depth - Without Handles "E"	Depth - Cabinet Only "F"	Width - Cabinet "G"
WRT311FZD	20.5 cu. ft.	Yes	661/4" (168.3 cm)	65½" (166.4 cm)	621/4" (158.1 cm)	32 <sup>7</sup> / <sub>8</sub> " (83.5 cm)	30 <sup>5</sup> / <sub>8</sub> " (77.8 cm)	28½" (72.4 cm)	32¾" (83.2 cm)
WRT511SZD WRT541SZD	21.3 cu. ft.	Yes	66½" (168.3 cm)	65½" (166.4 cm)	62½" (158.1 cm)	34" (86.4 cm)	32½" (82.3 cm)	28½" (72.4 cm)	32¾" (83.2 cm)

#### LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a  $\frac{1}{2}$ " (1.25 cm) space on each and between overhead cabinets and refrigerator top. Allow at least 1" (2.5 cm) between back of cabinet and the wall. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave 2" (5 cm) minimum on the hinge side (depending on your model) to allow for the door to swing open.

**NOTE:** This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.

Model: 20-1456 B The Hampton





#### Available Finishes/Colours

YWFE515S0JB Black



YWFF515S0JS Stainless Steel



YWFE515S0JW White

#### Manuals & Literature:





Use and Care

<u> Warranty</u>

### 5.3 cu. ft. Whirlpool® electric range with Frozen Bake™ technology

#### YWFE515S0JS

This Whirlpool® electric range with a dual element stove top helps you get dinner to the table. Skip preheating for favorites like pizza with Frozen Bake™ technology. This self cleaning oven also prevents cooked food from getting cold with the Keep Warm setting. Closed door broiling helps keep the kitchen comfortable.

#### **Top Features**

#### FlexHeat™ Dual Radiant Element

Get two elements in one with a 6" inner ring that's great for smaller pots and pans and a 9" expandable outer ring that makes room for larger cookware.

Frozen Bake™ technology
Skip preheating and cook frozen favorites like pizza in fewer steps with preprogrammed settings that automatically adjust cooking times for you.

#### Keep Warm setting

Keep dishes from getting cold with this setting that delivers low heat to the oven.

Closed Door Broiling
Maintain the optimal cooking temperature for food while still keeping the kitchen comfortable and cool using this broiling temperature management system that helps prevent overheating.

Dimensions	
Depth	27 3/4
Height	36
Width	29 7/8

Configuration and Overview	
Freestanding	
Electric	
30	

Exterior	
Door Removable	Yes
Drawer Type	Storage Drawer
Oven Door	Glass Window
Oven Window Size	Extra Large
Handle Color	Stainless Steel
Handle Material	Metal

Exterior	
Handle Type	Reach-Through Handle
Features	
Hot Surface Indicator Light	Yes
Haatin v Flamant On	V


Features	
Hot Surface Indicator Light	Yes
Heating Element On Indicator Light	Yes
Power On Indicator Light	No
Griddle	NA
Automatic Convection Conversion Temperature Adjust	No
Power Outage Compatible	No

Model: 20-1456 B The Hampton

## 39 of 46

## WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

#### **Product Dimensions**



- A. 273/4" (70.5 cm) max. depth with handle
- B. 46<sup>7</sup>/<sub>8</sub>" (119.1 cm) overall height (max.) with leveling legs screwed all the way in\*
- C. 36" (91.4 cm) cooktop height (max.) with leveling legs screwed all the way in\*
- D. 29<sup>7</sup>/<sub>8</sub>" (75.9 cm) width
- E. 255/16" (64.3 cm) depth back of range to front of cooktop\*\*
- F. Model/serial/rating plate (located on the frame behind a top corner of the door or either side of the drawer)

**IMPORTANT:** Range must be level after installation. Follow the instructions in the "Level Range" section. Using the cooktop as a reference for leveling the range is not recommended.


- \*Range can be raised approximately 1" (2.5 cm) by adjusting the leveling legs.
- \*\*Front of door and drawer may extend further forward depending on styling.

#### **Cabinet Dimensions**

Cabinet opening dimensions shown are for 25" (64.0 cm) countertop depth, 24" (61.0 cm) base cabinet depth and 36" (91.4 cm) countertop height.

**IMPORTANT:** If installing a range hood or microwave hood combination above the cooking surface, follow the range hood or microwave hood combination installation instructions for dimensional clearances above the cooktop surface.

A freestanding range may be installed next to combustible walls with zero clearance.



- A. 13" (33.0 cm) max. upper cabinet depth
- B. 30" (76.2 cm) min. opening width
- C. For minimum clearance to top of cooktop, see NOTE\*
- D. 30" (76.2 cm) min. opening width
- E. Outlet 8" (20.3 cm) to 22" (55.9 cm) from either cabinet, 7" (17.8 cm) max. from floor.
- F. Cabinet door or hinges should not extend into the cutout.

\*NOTE: 24" (61.0 cm) minimum when bottom of wood or metal cabinet is covered by not less than 1/4" (6.4 mm) flame retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" (0.4 mm) stainless steel, 0.024" (0.6 mm) aluminum or 0.020" (0.5 mm) copper.

30" (76.2 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet.

Model: 20-1456 B The Hampton

## 40 of 46

## WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

**Electrical Requirements - Canada Only** 

#### AWARNING



**Electrical Shock Hazard** 

Electrically ground range.

Failure to do so can result in death, fire, or electrical shock.

If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path is adequate and wire gauge are in accordance with local codes.

Be sure that the electrical connection and wire size are adequate and in conformance with CSA Standard C22.1, Canadian Electrical Code, Part 1 - latest edition, and all local codes and ordinances.

A copy of the above code standards can be obtained from:

Canadian Standards Association 178 Rexdale Blvd. Toronto, ON M9W 1R3 CANADA

 Check with a qualified electrical installer if you are not sure the range is properly grounded.

Range Rating*		Specified Rating of Power Supply Cord Kit and Circuit Protection
120/240 V	120/208 V	Amps
8.8 - 16.5 KW 16.6 - 22.5 KW	7.8 - 12.5 KW 12.6 - 18.5 KW	40 or 50** 50

<sup>\*</sup>The NEC calculated load is less than the total connected load listed on the model/serial/rating plate.

- A time-delay fuse or circuit breaker is recommended.
- This range is equipped with a CSA International Certified Power Cord intended to be plugged into a standard 14-50R wall receptacle. Be sure the wall receptacle is within reach of range's final location.



Do not use an extension cord.

### **INSTALLATION INSTRUCTIONS**


**Unpack Range** 

#### AWARNING

**Excessive Weight Hazard** 

Use two or more people to move and install range. Failure to do so can result in back or other injury.


- **1.** Remove shipping materials, tape and film from range.
- 2. Remove oven racks and parts package from inside oven.
- 3. Do not remove the shipping base at this time.



A. Shipping base

#### 4. On Ranges Equipped with a Storage Drawer:


Remove the storage drawer. See the "Storage Drawer" section. Use a 1/4" (6.4 mm) drive ratchet to lower the rear leveling legs one-half turn. Use a wrench or pliers to lower front leveling legs one-half turn.



- A. 1/4" (6.4 mm) drive ratchet
- B. Rear leveling leg
- C. Wrench or pliers
- D. Front leveling leg

### On Ranges Equipped with a Warming Drawer or Premium Storage Drawer:

On ranges equipped with a warming drawer or premium storage drawer, the rear legs cannot be accessed by removing the warming drawer or premium storage drawer. It will be necessary to adjust the rear legs from outside the range. Use wrench or pliers to lower the front and rear leveling legs one half turn.



- A. Rear leveling leg
- B. Wrench or pliers
- C. Front leveling leg

<sup>\*\*</sup>If connecting to a 50 A circuit, use a 50 A rated cord with kit. For 50 A rated cord kits, use kits that specify use with a nominal 13/8" (3.5 cm) diameter connection opening.

Model: 20-1456 B The Hampton

## 41 of 46

## WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

#### **Install Anti-Tip Bracket**

## AWARNING



**Tip Over Hazard** 

A child or adult can tip the range and be killed.

Install anti-tip bracket to floor or wall per installation instructions.


Slide range back so rear range foot is engaged in the slot of the anti-tip bracket.

Re-engage anti-tip bracket if range is moved.

Do not operate range without anti-tip bracket installed and engaged.

Failure to follow these instructions can result in death or serious burns to children and adults.


- Remove the anti-tip bracket from where it is taped inside the storage drawer or warming drawer.
- 2. Determine which mounting method to use: floor or wall. If you have a stone or masonry floor, you can use the wall mounting method. If you are installing the range in a mobile home, you must secure the range to the floor.
- 3. Determine and mark centerline of the cutout space. The mounting can be installed on either the left-side or right-side of the cutout. Position mounting bracket against the wall in the cutout so that the V-notch of the bracket is 12<sup>9</sup>/<sub>16</sub>" (31.9 cm) from centerline as shown.



A. 129/16" (31.9 cm) B. Bracket V-notch

 Drill two 1/8" (3 mm) holes that correspond to the bracket holes of the determined mounting method. See the following illustrations.

#### Floor Mounting



Wall Mounting



- 5. Using the Phillips screwdriver, mount anti-tip bracket to the wall or floor with the two  $\#12 \times 1^5/8$ " (4.1 cm) screws provided.
- **6.** Move range close enough to opening to allow for final electrical connections. Remove shipping base, cardboard or hardboard from under range.
- 7. Move range into its final location, making sure rear leveling leg slides into anti-tip bracket.



**8.** Move range forward onto shipping base, cardboard or hardboard to continue installing the range using the following installation instructions.

42 of 46 Model: 20-1456 B The Hampton





Monochromatic Stainless Steel WDF540PADM

#### Also available in:

White	WDF540PADW
Black	WDF540PADB

Capacity		
Total Place Settings	15	
General Features & Properti	es	
Soil Sensor		
In-Door Silverware Basket		
Sani Rinse Option		
Normal Cycle		
Heavy Cycle		
High Temperature Wash Option		
Heated Dry Option		
ENERGY STAR® Certified		
Industry's Best Selling Dishwasher Brand <sup>†</sup>		
Electrical Details		
Amps	15	
Volts	120	
Hz	60	
Certifications		
ENERGY STAR® Certified	Yes	

Technical Details	
Dishwasher Type	Built-in
Control Location	Front
Control Type	Electronic
Number of Wash Cycles	5
Number of Options	5
dBA <sup>*</sup>	53
Number of Racks	2
Tub Material	Plastic
Wash System	Filter
Wash System Type	Removable Filter
Number of Wash Arms	3
Dimensions	
Product Dimensions (H x W x D)	34-1/2" x 23-7/8" x 24-1/2"
Depth with Door Open 90°	49-1/2"
Reference Material	

#### **Dimension Guide**

Install Guide

Use & Care Guide

**Energy Guide** 

Warranty

Key Features & Benefits

#### **Sensor Cycle**


Automatically get the right wash and dry settings for each load with two sensors that measure temperature, soil level and load size during prewash and the wash cycle.

#### 1-Hour Wash Cycle

Clean the dishes you need fast with a cycle that thoroughly takes care of plates, pans and glasses in just an hour."

#### **Cycle Memory**

Quickly start your dishwasher with one button. It automatically remembers the last cycle you picked so it's stored and ready to go.



<sup>\*</sup>Per IEC standards. \*\*Compared to Normal cycle with lightly soiled loads. †Based on 12-month average of unit sales. TraQline 2018. NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice. 

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXA. WDF540PADSPECSHEETV01.

Model: 20-1456 B The Hampton

## 43 of 46



#### PRODUCT MODEL NUMBERS

WDF110PAB	WDF310PLA	WDF530PSY
WDF111PAB	WDF320PAD	WDF540PAD
WDF120PAF	WDF510PAY	WDF730PAY
WDF121PAF	WDF520PAD	WDT710PAY
WDF310PAA	WDF530PAY	WDT720PAD
WDF310PCA	WDF530PLY	WDT770PAY

Electrical Requirements: 120-volt, 60-Hz, AC only, 15- or 20-amp. fused electrical supply. Copper wire only. A time delay fuse or circuit breaker and separate circuit is recommended.

If direct wiring dishwasher: Use flexible, armored,


or nonmetallic, sheathed copper wire with grounding wire that meets the wiring requirements for

your home and local codes and ordinances.

Use a UL listed or CSA approved conduit connector.

#### If connecting dishwasher with a power supply cord:

Use Power Supply Cord Kit (Part No. 4317824) marked for use with dishwashers. Follow the kit



instructions for installing the power supply cord. Power supply cord must plug into a grounded 3 prong, outlet, located in the cabinet next to the dishwasher opening. Outlet must meet all local codes and ordinances.



Water Supply Requirements: A hot water line with 20 to 120 psi (138 to 862 kPa) water pressure. Water temperature must be 120°F (49°C) water at dishwasher. Use 3/8" O.D. copper tubing with compression fitting or flexible braided water supply line (1/2" minimum plastic tubing is not recommended). Use a 90°elbow with ¾"N.P.T. external pipe threads on one end. Do not solderwithin 6" (15.2 cm) from water inlet valve.

Drain Requirements: A new drain hose is supplied with your dishwasher. If this is not long enough, use a new drain hose with a maximum length of 12' (3.7 m) (Part No. 3385556) that meets all current AHAM/IAPMO test standards, is resistant to heat and detergent, and fits the 1" (2.5 cm) drain connector of the dishwasher.

Make sure to connect the drain hose to waste tee or disposer inlet above drain trap in house plumbing and (50.8 cm) minimum above the floor. It is recommended




that the drain hose either be looped up and securely fastened to the underside of the counter or be connected to an air gap.

Make sure to use an air gap if the drain hose is connected to house plumbing lower than 20" (50.8 cm) above subfloor or floor.

Use ½" (1.3 cm) minimum I.D. drain line fittings. If required, the air gap should be installed in accordance with the air gap installation instructions. When connecting the air gap, a rubber hose (not provided) will be needed to connect to the waste tee or disposer inlet.

#### PRODUCT DIMENSIONS




44 of 46

#### **CABINET CUTOUT DIMENSIONS**

**NOTE**: Shaded areas of cabinet walls show where utility connections may be installed.

- \*Measure from the lowest point on the underside of the countertop. May be reduced to 33½" (85.1 cm) by removing the rear leveling legs from dishwasher.
- \*\*Minimum, measured from narrowest point of opening.



Model: 20-1456 B The Hampton

## 45 of 46

#### WHIRLPOOL WASHER Model #: WFW5620HW

Whirlpool Brand Canada English | Washer and Dryers | Washers | Front Load Washers | WFW5620HW



5.2 cu. ft. I.E.C. Closet-Depth Front Load Washer with Load & Go™ Dispenser



5.2 cu. ft. I.E.C. Closet-Depth Front Load Washer with Load & Go™ Dispenser

Model #: WFW5620HW

#### Dimensions

Depth	80.17 cm, 31-9/16 in
Depth With Door Open 90 Degree	143.51 cm, 56-1/2 in
Minimum Height	98.11 cm, 38-5/8 in
Width	68.58 cm, 27.0 in
Appearance	
Appearance  LCD Touch Screen	No
	No Yes

#### Details

Drum Material	Stainless Steel

#### Cycles and Options

Number of Wash Cycles	37	

#### Electrical

Hz	60
Power Cord Included	Yes

46 of 46

#### WHIRLPOOL DRYER Model #: YWED5620HW



7.4 cu. ft. Front Load Electric **Dryer with Intuitive Touch** Controls



7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls

Model #: YWED5620HW

#### Dimensions

Fuel Type	Electric	
Configuration and Overview		
Width	68.58 cm, 27.0 in	
Height	98.42 cm, 38-3/4 in	
Depth With Door Open 90 Degree	138.43 cm, 54-1/2 in	
Depth	78.74 cm, 31.0 in	

#### **Cycles and Options**

Cycle Time Remaining	Yes
Lint Filter Indicator	No
Number of Dryer Cycles	36
Number of Dryness Levels	3

#### Ventilation System

Long Vent	No
Maximum Vent Length	64
Venting Direction	Left, Right, Bottom, Rear

#### Electrical

Hz	60

Power Cord Included Yes