Sales Selection Sheet Checklist

LOT 3191D-23 Model: 20-1790 A The Dunmore PURCHASERS: HILDA, STANNY D?CUNHA/ VENDOR: Heathwood Homes (Huron) Limited **DECK LOT** FINISHED BASEMENT COLD CELLAR **UPGRADED / MODIFIED ELEVATION CORNER UPGRADE** REAR UPGRADE **CEILING UPGRADE - SMOOTH** MAIN FLOOR SECOND FLOOR **BASEMENT** ADDITIONAL ROUGH-INS 200 AMP SERVICE (UPG FOR TOWNS) WET BAR ROUGH-IN **HUMIDIFIER** AIR CONDITIONING (SITE STD) GAS ROUGH-IN STOVE DRYER BBQ ADDITIONAL FIREPLACE KITCHEN: HOODFAN VENTING SIZE **6 IN ROUND DUCT** 7 IN ROUND DUCT **FULL BASEMENT STAIRS:** N/A UPPER BASEMENT STAIRS: All Oak Carpet Grade LOWER BASEMENT STAIRS: All Oak MAIN STAIRS: MEDIA STAIRS (if applicable): N/A LOFT STAIRS (if applicable): N/A MARCH 21/23 BRENDA LUKER **Decor Consultant:** STITUTE OF Purchaser: Date Heathwood Homes (Huron) Limited Date Approved-Locked Date:

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore

Foyer

Page ୀ ରୀ ଭ



n	NATURE OF THE PARTY OF THE PART	3 390
Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
Countertop	9069	MSI Quartz GROUP 1 ICED WHITE ***STD***
Countertop Edge	4010	SINGLE POLISHED STRAIGHT EDGE 3/4 INCH ***STD***
Cabinet Hardware	2086	9677-HARDWARE ***STD***
sland Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
sland Countertop	9069	MSI Quartz GROUP 1 ICED WHITE ***STD***
3acksplash	5721	QT.CD.ARW.0306.BR-Colour and Dimension Bright-Arctic White-3 x 6 ***1***
Backsplash Grout	2226	Grout-(00) White ***STD***
Backsplash Tile Pattern	3060	HORIZONTAL BRICK ***UPG***
loodFan	9904	YWMH31017HZ-Whirlpool Over-The-Range Microwave Hood Combination-SS-30 inch
Comment		
en/Breakfast		-
Flooring	9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***
loor Tile Grout	2225	Grout-(27) Silver ***STD***
loor Tile Pattern	3000	STANDARD SQUARE ***STD***
comment		

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore 3 of 619 15

Flooring	9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
4		
Comment		
Laundry Room		
LAUTHIY KOOTT		*
Flooring	9071	GE.BY.AZR.1313 New Byzantine Azzuro 13x13 ***STD***
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Comment		
Laundry Room Opt.		
Cabinet - Uppers	1111	N/A *****
Cabinet Hardware	1111	N/A *****
Comment		
Mud Room		
Flooring	9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
	* *	

HILDA, STANNY D?CUNHA/

Project: Wallaceton Jnit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore		Locked: Closed:
	Section 1997	
Comment		
Powder Room		
Flooring	9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Plumbing Fixture (Colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment		
Hall		
Flooring	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
Comment		
Dining Room		
Flooring	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
Comment		
Great Room		
Flooring	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
Comment		
Upper Hall		

Flooring

7498

Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch ***3***

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore 619 Sed: 3,122023 08:54 11

Locked:

				Closed.
0.5. 05.23		All satisfactors and the same production of the same state of the	and all the late of the late o	100 100 Transport and a contract of the second of the first city of the second of the
Fini	shed Raseme	ent (Rec) Room/Hall		*
texalia	Sileu Daseille	ent (Rec) Room/Hall	MARK AND	
	Flooring		9507	DY 89418-MINOTAUR-BLACK ICE-40 oz Poly ***STD***

	Comment			
Mas	ter Bedroom		The second second	
	Clearing		9507	DY 89418-MINOTAUR-BLACK ICE-40 oz Poly ***STD***
	Flooring		9307	BY 654 10-WINO PAON BEACK TOLE 40 62 F 5.19
	Comment			
	j			2
				-92
Bed	room 2	CANTINGO SELECTAR SALVEN SON SON SON SELECTION S		
DOM:				*
9,83	Flooring		9507	DY 89418-MINOTAUR-BLACK ICE-40 oz Poly ***STD***
	Comment			
Bed	lroom 3		5	9
EC-1927	CONTRACTOR OF THE SECOND		e e e e e e e e e e e e e e e e e e e	8
	Flooring		9507	DY 89418-MINOTAUR-BLACK ICE-40 oz Poly ***STD***
	Comment			
	Comment			
	3	200 - 1900 - 100 - 1900 D. T.	3,2584	
Mas	ster Ensuite		28	
hanne	Ster Linsuite		- Carrie	
	Cabinet Cold	our/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
		•		
	Countertop		8796	6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD***
				FINISH-FOITING STD
	Countertop E	Edge	1111	N/A *****
	Countertop E	-uge	1111	,
	Cohin-til-	duoro	7672	135-HARDWARE ***STD***
	Cabinet Hard	uware	7672	199-HAKDWAKE SID
	Floor Tile		9071	GE.BY.AZR.1313 New Byzantine Azzuro 13x13 ***STD***
	1 1001 1116		0011	

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore

Page 5 of 9



	Floor Tile Grout	2225	Grout-(27) Silver ***STD***
	Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
	Shower Floor Tile	8661	OD.ON.SWT.0202.MT.N-Ontario Series Mosaic-Snow White Matte-2 x 2 ***STD***
	Shower Floor Tile Grout	2226	Grout-(00) White ***STD***
	Shower Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
	Shower Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***
	Shower Wall Tile Grout	2226	Grout-(00) White ***STD***
	Shower Wall Tile Pattern Shower Jamb(s) and Sill(s)	3070 8923	HORIZONTAL STACKED ***STD*** Shower Jamb / Sill-Thassos White ***STD***
	10.07 No.08 10.07 No. 10 10 10 10		
	Plumbing Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***
	Comment	-01570	
Maii	n Bathroom		
	Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
	Countertop	8796	6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD***
	Countertop Edge	1111	N/A *****
	Cabinet Hardware	7672	135-HARDWARE ***STD***
	Flooring	9071	GE.BY.AZR.1313 New Byzantine Azzuro 13x13 ***STD***
	Floor Tile Grout	2225	Grout-(27) Silver ***STD***

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore

			THE RESIDENCE OF THE PROPERTY
	Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
	Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***
	Wall Tile Grout	2226	Grout-(00) White ***STD***
	Main Bathroom Tile Pattern	3070	HORIZONTAL STACKED ***STD***
	Plumbing Fixture (Colour)	1737	Plumbing Fixtures-WHITE ***STD***
	Comment		
	1000		
in	ished Basement Bathroom		
	Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
	Countertop	8796	6698-46-Countertop-PALOMA POLAR ETCHINGS
			FINISH-Formica ***STD***
	Countertop Edge	1111	N/A *****
	Cabinet Hardware	7672	135-HARDWARE ***STD***
	Flooring	9071	GE.BY.AZR.1313 New Byzantine Azzuro 13x13 ***STD***
	Floor Tile Grout	2225	Grout-(27) Silver ***STD***
			STANDARD SQUARE ***STD***
	Floor Tile Pattern	3000	STANDARD SQUARE STD
		144	
	Shower Floor Tile	8661	OD.ON.SWT.0202.MT.N-Ontario Series Mosaic-Snow
S#55			White Matte-2 x 2 ***STD***
	Shower Floor Tile Grout	2226	Grout-(00) White ***STD***
	Shower Floor Tile Pattern	3000	STANDARD SQUARE ***STD***

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore

Pege 7 ରୀଥ

8 of 619 4 5

Shower Wall Tile	9020	QT.WV.WHT.0810-Weave-White-8 x 10 ***STD***
Shower Wall Tile Grout	2226	Grout-(00) White ***STD***
Shower Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***
Shower Jamb(s)	8923	Shower Jamb / Sill-Thassos White ***STD***
Plumbing Fixture (Colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment	24	7
eat Room Fireplace		
Туре	8865	Dimplex-Electric Fireplace-PF3033HL ***STD***
Mantle	1439	NF 17-Paint Grade Mantle Cผลกรา WHITE ***STD***
Surround Opt.	1111	N/A *****
Comment		
sement Stairs		4
Туре	1711	Carpet Grade Stairs ***OPT. FINISHED BASEMENT***
Colour	7912	Irongate (Gryphon) STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING
Carpet Runner	1111	N/A *****
Handrail/Pickets/Post Type	9119	Handrail only on closed walls (one or two sides per building code) ***STD***
Handrail/Pickets/Post Colours	1729	Carpet Grade-Stain handrail, pickets, stringers, nosing _pos
Handrail/Pickets/Post Colours Carpet	1729 9507	Carpet Grade-Stain handrail, pickets, stringers, nosing _posing _posin

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore

Locked:

loder: 20-1790 A The Dunmore		Closed:
	1.24 7.048 A. M.	
		_ *
Basement Stairs Landings (Upper a	ind Lo	
Flooring	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch ***3***
Comment		
Commont		24 × 320
Main Stairs		
Туре	1714	Oak Stairs ***STD MAIN STAIRS***
Colour	7912	Irongate (Gryphon) STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING
Carpet Runner	1111	N/A *****
Handrail/Pickets/Posts Type	7651	1 5/16 inch Turned pickets with 3 1/2? Turned Post(s)-ALL OAK***STD***
Handrail/Pickets/Posts Colour	1728	Oak Grade-Stain handrail,oak pickets,stringers,treads,risers
Custom Stain/Paint	1111	N/A *****
Comment		- "
	100000000000000000000000000000000000000	
Main Stairs Landing(s)		
Flooring	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
Comment	4	
Throughout		
Walls - Paint Colour	1717	22-Wall-WARM GREY ***STD***
Underpad	1079	500 Series-Underpad ***STD***
Thresholds	2232	Metal Thresholds ***STD***
Switches and Plug	5796	Decora White Switches and Plugs ***STD***
Trim Size	8705	4 1/4 Baseboard and 2 3/4 Casings ***STD***

1716

Trim-WHITE ***STD***

Trim - Paint Colour

HILDA, STANNY D?CUNHA/ Project: Wallaceton Unit: 3191D-23, Phase: 3 Model: 20-1790 A The Dunmore

Comme	nt			The second secon
urchaser:	HILDA, STANNY D?CUNHA	3/13/23 Date	Decor Consultant	3 13 23 Date
			_	STITUME
ırchaser:			mRosen	-03- 71 2003
	7000 00 700 00 00 00 00 00 00 00 00 00 0	Date	Wallaceton	Date Approved

CONSTRUCTION SUMMARY Of 45



Lot: 3191D-23 Model: 20-1790 A The Dunmore Project/Phase: Wallaceton / 3

	The Purchaser(s) acknowledge that they have NOT been referred by an existing Heathwood Homeowner and therefor are not entitled to a referral fee under Heathwood Homes Referral program. Note:
Offer Worksheet	Five Appliances: SS Fridge, Stove, Dishwasher: White Front Loader Washer/Dryer - Townhomes Note:

DisciplineMS.rpt 13dec21 Page 1 of 4

Printed and Sent: 07-Jun-23

12 of 45 construction summary



Lot: 3191D-23 Model: 20-1790 A The Dunmore Project/Phase: Wallaceton / 3

APPLIANCES

Invoice	Qty.	Description
1335	1	- APPLIANCES - WHIRLPOOL OTR SS - YWMH31017HZ
313,492		
25Apr23		
		CABINETRY-Notify; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct Size change t

CABINETRY

Invoice	Qty.	Description
1335 313,492	1	- APPLIANCES - WHIRLPOOL OTR SS - YWMH31017HZ
25Apr23		CABINETRY-Notify; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct Size change (
1335 351,628	1	KITCHEN - CABINETRY - OPT. DEEP FR & GABLES - VIKING II/III - UPG
25Apr23		SKETCH # 3 DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify
1335 352,784	1	- CABINETRY - OPT. LIGHT VALANCE (INCLUDING LIGHT) - VIKING II/III - UPG
25Apr23		ELECTRICAL-Complete Kitchen valance light including switch (Luminiz LED slimline strip light)

CARPET

011111		
Invoice	Qty.	Description
1335	1	- HARDWOOD - UPPER HALL - VINTAGE 3 1/4 IN - UPG
353,783		
25Apr23		
**		CARPET-delete std carpet; INTERIOR TRIM-supply and install quarter rounds; PAINTING-paint quarter round

CERAMICS

Invoice	Qty.	Description
1335	1	KITCHEN OPTIONAL BACKSPLASH - CERAMICS - KITCHEN OPTIONAL BACKSPLASH - BACKSPLASH - UG 1
348,267		
25Apr23		

DRYWALL

DICI	DATE TITLED						
Invoice	Qty.	scription					
1335	1	KITCHEN - CABINETRY - OPT. DEEP FR & GABLES - VIKING II/III - UPG					
351,628							
25Apr23		SKETCH # 3					
**		DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify					
1335	1	- DRYWALL - SMOOTH CEILING IN MAIN FLOOR - UPG					
352,880							
25Apr23							
1		PAINTING-Notify					
1452	1	- ELECTRICAL - POTLIGHT BUNDLE - 8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2					
314,237	*	SWITCHES (SEE LINE VOLTAGE FOR MAIN FLOOR) NOTE: LOCATION MAY VARY FROM REQUEST DEPENDS ON					
ĺ		JOIST PLACEMENT					
26Apr23		4 X KITCHEN ON SEPARATE SWITCH AND 4 X GREAT ROOM ON SEPARATE SWITCH SKETCH # 2					
~~		DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights					

DisciplineMS.rpt 13dec21 Page 2 of 4

Printed and Sent: 07-Jun-23

13 of 45 construction summary



Lot: 3191D-23 Model: 20-1790 A The Dunmore Project/Phase: Wallaceton / 3

ELECTRICAL

Invoice	Qty.	Description
1335 313,492 25Apr23 **	1	- APPLIANCES - WHIRLPOOL OTR SS - YWMH31017HZ CABINETRY-Notify; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct Size change 1
1335 352,784 25Apr23 **	1	- CABINETRY - OPT. LIGHT VALANCE (INCLUDING LIGHT) - VIKING II/III - UPG ELECTRICAL-Complete Kitchen valance light including switch (Luminiz LED slimline strip light)
1452 314,237 26Apr23	1	- ELECTRICAL - POTLIGHT BUNDLE - 8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2 SWITCHES (SEE LINE VOLTAGE FOR MAIN FLOOR) NOTE: LOCATION MAY VARY FROM REQUEST DEPENDS ON JOIST PLACEMENT 4 X KITCHEN ON SEPARATE SWITCH AND 4 X GREAT ROOM ON SEPARATE SWITCH SKETCH # 2 DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights
1452 314,242 26Apr23	1	KITCHEN - ELECTRICAL - RELOCATION OF SWITCHES/LIGHTS (MUST SPECIFY LOCATION) - NOTE: PLUGS CANNOT BE RELOCATED- MUST PURCHASE ADDITIONAL OUTLET. RELOCATE STANDARD KITCHEN LIGHT TO BE CENTERED +/- ABOVE ISLAND ON EXISTING 3 WAY SWITCH SKETCH # 2
1452 314,232 26Apr23	1	GREAT ROOM - ELECTRICAL - EXTRA WALL INTERIOR OUTLET ON EXISTING CIRCUIT (DOES NOT INCLUDE KITCHEN OUTLETS) CENTERED ABOVE FIREPLACE 70" +/- FROM FLOOR SKETCH # 2

FRAMING

Invoice	Qty.	Description	
1335	1	KITCHEN - CABINETRY - OPT. DEEP FR & GABLES - VIKING II/III - UPG	
351,628			
25Apr23		SKETCH # 3	
**		DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify	
1452	1	- ELECTRICAL - POTLIGHT BUNDLE - 8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2	
314,237		SWITCHES (SEE LINE VOLTAGE FOR MAIN FLOOR) NOTE: LOCATION MAY VARY FROM REQUEST DEPENDS ON	
26Apr23		JOIST PLACEMENT 4 X KITCHEN ON SEPARATE SWITCH AND 4 X GREAT ROOM ON SEPARATE SWITCH SKETCH # 2	
**		DRYWALL-Drywall/Ceiling cutouts for potlights: FRAMING-Frame to accommodate potlights	

HARDWOOD

Invoice	Qty.	Description
1335	1	- HARDWOOD - UPPER HALL - VINTAGE 3 1/4 IN - UPG
353,783		
25Apr23		
		CARPET-delete std carpet: INTERIOR TRIM-supply and install quarter rounds: PAINTING-paint quarter round

HEATING / AIR CONDITIONING				
Invoice	Invoice Qty. Description			
1335 313,492	1	- APPLIANCES - WHIRLPOOL OTR SS - YWMH31017HZ		
25Apr23 **		CABINETRY-Notify; ELECTRICAL-delete std range hood; HEATING/AIR CONDITIONING-Duct Size change to		

INTERIOR TRIM AND DOORS

Įιy.	Description
1	- HARDWOOD - UPPER HALL - VINTAGE 3 1/4 IN - UPG
	CARPET-delete std carpet; INTERIOR TRIM-supply and install quarter rounds; PAINTING-paint quarter round
1	

DisciplineMS.rpt 13dec21 Page 3 of 4

14 of 45



CONSTRUCTION SUMMARY

Lot: 3191D-23 Model: 20-1790 A The Dunmore Project/Phase: Wallaceton / 3

PAINT	PAINTING					
Invoice	Qty.	Description				
1335 351,628	1	KITCHEN - CABINETRY - OPT. DEEP FR & GABLES - VIKING II/III - UPG				
25Apr23		SKETCH # 3				
**		DRYWAL-Notify; FRAMING-Modify Bulkhead; PAINTING-Notify				
1335	1	- DRYWALL - SMOOTH CEILING IN MAIN FLOOR - UPG				
352,880						
25Apr23						
**		PAINTING-Notify				
1335	1	- HARDWOOD - UPPER HALL - VINTAGE 3 1/4 IN - UPG				
353,783						
25Apr23						
**		CARPET-delete std carpet; INTERIOR TRIM-supply and install quarter rounds; PAINTING-paint quarter round				

Printed and Sent: 07-Jun-23

20-1790 ELEV. A

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

15 of 45


THE DUNMORE

ELEVATION A | 2,242 SQ. FT.

Includes 452 sq. ft. of Finished Lower Level

WALLACETON

Sketch # 1



LOWER LEVEL ELEVATION A

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

16 of 45

THE DUNMORE


ELEVATION A | 2,242 SQ. FT.

Sketch # 2


Includes 452 sq. ft. of Finished Lower Level

20-1790 ELEV. A


WALLACETON




The state of the s









MAIN BATH (2ND FLR)



OPT. LAUNDRY UPPERS (2ND FLR)



STD. BASEMENT BATH



Standard Vanity & Laundry Scope:

- Powder by others, pedestal
- All vanities include laminate counter
- MetaBox Drawers- not soft close Std. Blum Hinges- not soft close
- doors at sink) Master Ensuite: Top drawers (Full height
- Mains: Full height doors (top drawers Optional laundry base & wall cabinets added if Masters can't accommodate

KITCHENS LIMITED 1350 Showson Drive, Mississauga, ON LAW TCS V H Z U

MODEL: 20-1790 (2004)

WALLACETON, KITCHENER ON

HEATHWOOD HOMES

STANDARD CONTRACT INCLUDES:

Appliance Openings

- Hood Opening: 30"W Std. hood
- Fridge Opening: 37 3/8 "W X 73 3/8" H
- Stove Opening: 30" Freestanding 30cm deep cabinet over fridge
- Dishwasher Opening: 24"

Standard Kitchens Scope:

- 100cm H wall cabinets
- Std. Blumotion Hinges-soft close
- Std. Metabox Drawers- not soft close
- Min 40cm W drawer
- Base pie cut corner cabinets
- Countertop by others Backing on all cabinets
- dishwashers supply only (appliance Upgrade applied paneled fridge & hardware by others)

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

18 of 45

THE DUNMORE

ELEVATION A | 2,242 SQ. FT.

Includes 452 sq. ft. of Finished Lower Level

WALLACETON

Sketch #4

20-1790 ELEV. A 9' HIGHTRAY CEILING MASTER BEDROOM MASTER ENSUITE AUNDRY OPT. UPPERS MAIN BEDROOM 3

SECOND FLOOR ELEVATION A

^{*} Floor plan may vary due to grading conditions.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

19 of 45





NFAS NF17 Mantel CABINET


Unit: 3191D-23, Phase: 3


Model: 20-1790 A The Dunmore

(Keginox

ND1831UA/9







ND1831UA/9 SPECIFICATION

Model ND1831UA/9 is a double (two equal size) bowl undermount sink manufactured by Franke Kindred Canada Limited from 18 gauge stainless steel. Product has silk finished rims and linear brush finished bowls. Sink is fully undercoated. Basket strainer waste fittings (3 1/2", 89 mm) are included. Sink is backed with a limited lifetime warranty.

- O.D. 17 3/4" x 30 7/8" x 8 1/2" (45 x 78 x 22 cm)
- Recommended for minimum 36" cabinet

Franke Kindred Canada Limited

P.O. Box 190, 1000 Franke Kindred Road, Midland, Ontario, Canada, L4R 4K9 Phone: 866-687-7465 Fax: 800-361-8408

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

21 of 45

MOEN

FAUCET DESCRIPTION

- Reflex™ pulldown system offers smooth operation, easy movement and secure docking
 Power Clean™ spray technology
 Metal construction with various finishes identified by suffix

- Quick connect installation
- Pulldown spray with 68" braided hose Flexible supply lines with 3/8" compression fittings
- High arc spout provides height and reach to fill or clean large pots while pulldown wand provides the maneuverability for cleaning or rinsing 360° rotating spout
- Faucet designed for handle to be mounted on right side only

OPERATION

- Lever style handle
- Temperature controlled by 100° arc of handle travel
- Operates with less than 5 lbs. of force
- Operates in stream or spray mode in the pullout or retracted position **FLOW**

Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi

CARTRIDGE

• 1255™ Duralast™ cartridge

STANDARDS


- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9G & 372
- Meets CalGreen and Georgia SB370 requirements Complies with California Proposition 65 and with the Federal Safe Drinking
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA 🖒 for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the
- 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation

Visit www.moen.com/support for complete details and limitations

Specifications




ALIGN™ **Single Handle High Arc Pulldown Kitchen Faucet**

Models: 7565 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA. (OPTIONAL 3-HOLE ESCUTCHEON 141002 AVAILABLE)





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev. 6/20

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

22 of 45



BARRIER FREE (ABOVE COUNTER OR DROP-IN ONLY)

BOULEVARD® PEDESTAL SINK VITREOUS CHINA

BOULEVARD® PEDESTAL SINK

☐ 0641.800 Faucet holes on 8" (203mm) centers (Illustrated)

STD • 0641.400 Faucet holes on 4" (102mm) centers

☐ 0641.100 Center hole only

- Classic styled rectangular pedestal lavatory
- · Vitreous china
- Rear overflow
- Supplied with mounting kit
- Right Height® for greater comfort during use
- Faucet ledge with large deck area (faucet not included)
- Design coordinates with Boulevard® Toilet
- Basin has flat bottom to also allow use as an **above counter** sink or a **drop-in** sink (with u-shaped cut out)

Nominal Dimensions:

24" x 19" x 35-1/2" (610 x 483 x 902mm)

- ☐ 0641.008 Pedestal top-8" (203mm) centers
- ☐ 0641.004 Pedestal top-4" (102mm) centers
- ☐ 0641.001 Pedestal top-center hole only
- ☐ 0010.000 Pedestal only

Bowl sizes:

17" (432mm) wide, 12-1/2" (318mm) front to back, 5" (127mm) deep

Compliance Certifications -

Meets or Exceeds the Following Specifications:

• ASME A112.19.2 - 2008/CSA B45.1-08

To Be Specified:

- ☐ Color: ☐ White ☐ Linen
- ☐ Faucet Finish:
- Supplies:
- ☐ 1-1/4" Trap:
- □ Nipple:



SEE REVERSE FOR ROUGHING-IN DIMENSIONS


^{*} See faucet section for additional models available

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

4merican tandard

BOULEVARD® PEDESTAL SINK



ABOVE COUNTER AND DROP-IN SINK CONFIGURATIONS MEET THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES.

Top of sink installed at 34" (864mm) height from finished floor. Sink installed 5" (127mm) minimum from front edge of countertop. Provide 27" (686mm) knee clearance area.

NOTES:

* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAPS ARE SUGGESTED.

▼ PEDESTAL ANCHORING SCREWS NOT INCLUDED.

■ SUITABLE FOR REINFORCEMENT ONLY. ACTUAL DIMENSIONS MUST BE TAKEN FROM FIXTURE.

FITTING NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL SUPPORTS. INSTALLATION INSTRUCTIONS SUPPLIED WITH LAVATORY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

© 2018 AS America Inc.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

24 of 45

American Standard



BARRIER FREE

COLONY™ COUNTERTOP SINK

VITREOUS CHINA

COLONY COUNTERTOP SINK

- · Vitreous china
- Self-rimming
- · Front overflow
- · Supplied with template
- Faucet deck (Faucet shown not included)

☐ 0346 803 Y Faucet holes on 203 nm (6"), centres	\sim
O346 403 (Illustrated) Faucet holes on 102mm (4") centres	3
₩ <u>₽</u> 346001	~


Centre hole only


Nominal Dimensions: 521 x 448mm (20-1/2" x 17-5/8")


Bowl sizes:

422mm (16-5/8") wide, 279mm (11") front to back, 143mm (5-5/8") deep









COMPLIANCE CERTIFICATIONS -

Meets or exceeds the following Specifications:

- ASME A112.19.2M for Vitreous China Fixtures.
- · CAN/CSA B45 Series.

To Be Specified

- ☐ Colour: ☐ White ☐ Bone ☐ Silver Gray ☐ Linen
- □ Faucet*:
- □ Faucet Finish: Supplies & Stops:
- ☐ Trap 1-1/4" (32 mm):

NOTES:

* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED. FOR COUNTERTOP CUTOUT AND INSTALLATION INSTRUCTIONS USE TEMPLATE SUPPLIED WITH SINK.

SUPPLIED WITH SINK.

FAUCETS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2.

These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

BAS-198 .

^{*} See faucet section for additional models available

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

25 of 45



DEMI™ **Product Specification Sheet**

Two Piece Freestanding Collection

CF2007 Two Piece Freestanding Soaker


Size: 60" x 32" x 22"

1524 mm x 813 mm x 559 mm




- Vacuum formed acrylic reinforced with fiberglass
- Scratch, stain and fade resistant high gloss finish
- Installation friendly two piece design
- Accepts deck mounted faucet
- Includes integral pop up drain and rectangular overflow
- Includes levelling feet


TWO PIECE ASSEMBLY



END VIEW



TOP VIEW



GENERAL SPECIFICATIONS

Average Weight 90 lb 41 kg Bathing Well at bottom 43"x 20" 1092 x 508 mm 195 litres Capacity Drain to Overflow Water Depth Drain to Overflow 406 mm Drain Opening (dia.) 51 mm Overflow Opening 2 1/4"x 1/2" 57 x 13 mm Drain to Floor Clearance

NOTES: Please confirm measurements on actual product to ensure proper identification. Bathtub to be installed on the floor supported by 5 self levelling feet. Adjust if required to level the bathtub for adequate drainage. Refer to installation instructions for additional information.

IMPORTANT: Dimensions of fixtures are nominal and may vary \pm %" (6 mm). Weight may vary \pm 5 lb (2.3 kg). Drawing is not to scale. These measurements are subject to change at manufacturer's discretion.

Compliance Certifications -

Meets or Exceeds the following Specifications:

CAN/CSA - B45 Series





Fax: 416.231.0929 www.mirolin.com

Customer Service: 416.231.5790 Canada, U.S.A.: 800.**MIROLIN**(647-6546) Fax, Canada: 800.463.2236

R0084162 25 Sep. 2018

© 2018 Mirolin Industries Corp.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

26 of 45

American Standard

Style That Works Better

FloWise™ DUAL FLUSH **ELONGATED TOILET**

VITREOUS CHINA


FloWise™ DUAL FLUSH ELONGATED TOILET

2476 216

- Vitreous china
- · Low-consumption Dual Flush Full flush 6.0 Lpf/1.3 gpf, Partial flush 3.0 Lpf/0.66 gpf.
- · Elongated wash down bowl
- · Internal trapway fully-glazed, 2-1/4" (57mm) ballpass
- · Concealed trapway bowl
- · Chrome-plated top mounted push button actuator
- Easy to clean sanitary dam on bowl
- Includes Elongated Slow Close Seat
- 100% factory flush tested
- · 2 bolt caps

Separate Component Parts:

- ☐ 3067 316 Elongated Bowl with Slow Close Seat
- **4035 216** Unlined Tank



- **☐** 3067 316 Elongated Bowl
- **4035 516** Lined Tank


Nominal Dimensions: 794 x 432 x 765mm (31-1/4" x 17" x 30-1/8")


Compliance Certifications -Meets or Exceeds the Following Specifications:

- ASME A112.19.2M (and 19.6M)
- · CAN/CSA B45 series

To Be Specified

- Colour: 020 White
- Supply with stop:





NOTES:
THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12")
FROM FINISHED WALL TO C/L OF OUTLET.
SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.
* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.
FOR ADDITIONAL INFORMATION REFER TO INSTALLATION INSTRUCTIONS SUPPLIED.
IMPORTANT. Dimensions of fixture are peripaid and may use within the prepare of the present IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2

established by Anki Graindau A 112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

UPGRADED VALUE ADDED FEATURES AT NO EXTRA CHARGE

TOI-284

© 2008 American Standard

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

27 of 45

MOEN[®]

DESCRIPTION

- Metal construction with various finishes identified by suffix
- 16" long 3/8" tubing connections Includes metal or 50/50 pop-up type waste assembly where noted **OPERATION**
- Pivot action lever style handle Temperature controlled through 180° degree arc of handle travel

FLOW

Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi

CARTRIDGE

- 1225 cartridge design
- Nonmetallic/nonferrous and stainless steel material
- Can accommodate reversed piping and back to back installations


- Third party certified to WaterSense®, CSA B-125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act

 ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

Specifications



CHATEAU® Single-Handle Lavatory Faucet

with Metal Waste Assembly


Model: L4625 series L4631BC **Bulk Packed (12 per carton):** L64624 series

with 50/50 Waste Assembly **Bulk Packed (12 per carton):** L64625 series

Less Waste **Bulk Packed (12 per carton):** L64600 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 3-1" DIA. HOLES, 2" ON CENTER





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev 8/15

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

28 of 45



Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

- Metal construction with various finishes identified by suffix
- Includes non-metalic showerhead, arm, flange and non-metalic diverter tub spout

OPERATION

- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to $\pm\,3^\circ$

- Showerhead is limited to 2.5 gpm (9.5 L/min) at 80 psi EP suffix models are limited to 1.75 gpm (6.6 L/min) at 80 psi
- NH suffix models contain no showerhead

CARTRIDGE

- 1222 cartridge design Accommodates back to back installations
- Nonmetallic/nonferrous and stainless steel material

STANDARDS

- Third party certified to meet ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- EP suffix models are third party certified to WaterSense®
- ADA (for lever handle

6.5" (165mm) ESC. DIAM.

WARRANTY

Lifetime limited warranty against leaks, drips and finish defects

2"CC (51mm) 1 7/8" IPS (48mm) MAX WALL

FINISHED WALL LINE

4-1/2" (114mm)

WALL OPENING

7-1/2" (190mm)

to the original consumer purchaser 5 year warranty if used in commercial installations

Specifications






CHATEAU° POSI-TEMP° Single-Handle Tub/Shower Trim Kit

Models: TL181 series - valve trim only (Bulk Packed 12 per carton) TL182 series - shower trim only (Bulk Packed 12 per carton) TL183 series - tub/shower trim


(Bulk Packed 12 per carton)

Valves: 62300 series

2500 series



THIN WALL APPLICATION



— 1/2" MIN. CC (13mm) 5/8" MIN. IPS (16mm)

2 1/2" MAX. (63mm)

SHOWER

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

TL183sp: Rev. 5/13

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

29 of 45

MOEN[®]

DESCRIPTION

 Metal construction with various finishes identified by suffix OPERATION

- · Lever style handles with hot and cold color indicator
- Rotate hot side handle counterclockwise to open (clockwise to close) and the cold side handle (clockwise to open) and (counterclockwise to close)


STANDARDS

- Third party certified to: ASME A112.18.1/CSA B-125.1, and all applicable requirements referenced therein
- ADA 🕒 for lever handles

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multi-family installation
- 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations


Specifications




CHATEAU® Two-Handle Garden Tub Trim

Models: T994 series

Valves: 4792, 4793, 4794, 4796, 4797, 4798





CRITICAL DIMENSIONS (DO NOT SCALE)

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN


www.moen.com

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

30 of 45

WMH31017H OVER-THE-RANGE MICROWAVE



GDISHWASHERSAREHURNIYABUE RUATE



Clean up spills on the turntable by simply putting it in the dishwasher.

2-sipieed kioordeminioticirkollass



Match the right amount of ventilation to the dish being prepared and quickly get rid of cooking odors with two different fan speed settings.

MIGHOWAVE BRIEFIER



Get just the right amount of heat and time, whether you're cooking or defrosting, with specific preset options.

OTHER FEATURES

- Add 30 seconds option
- Electronic touch controls
- Adjustable cooktop lighting

	· · ·			-	
	White (W)	Black (B)	Fingerprint Resistaint Stainless Steel (Z)	Silver (S)	
MODEL	WMH31017HW	WMH31017HB	WMH31017HZ	Mileta das	
Max height (in)	17-1/8"	17-1/8"	17-1/8"	17-1/8"	
Width (in)	29-15/16"	29-15/16"	29-15/16"	29-15/16"	
Depth (in)	15-9/16"	15-9/16"	15-9/16"	15-9/16"	





^{*}Performance varies based on installation.

®/™ ©2018 Whirlpool. All rights reserved. 1/18. WC170107A

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

31 of 45

VENTING DESIGN SPECIFICATIONS

This section is intended for architectural designer and builder/contractor reference only.

NOTES:


- Vent materials needed for installation are not provided with microwave hood combination.
- We do not recommend using a flexible metal vent.
- To avoid possible product damage, be sure to vent air outside, unless using recirculation installation. Do not vent exhaust air into concealed spaces, such as spaces within walls or ceilings, attics, crawl spaces, or garages.

For optimal venting installation, we recommend:

- Using roof or wall caps that have backdraft dampers
- Using a rigid metal vent
- Using the most direct route by minimizing the length of the vent and number of elbows to provide efficient performance
- Using uniformly sized vents
- Using duct tape to seal all joints in the vent system
- Using caulking compound to seal exterior wall or roof opening around cap
- Not installing 2 elbows together for optimal hood performance


If venting through the wall, be sure that there is proper clearance within the wall for the damper to open fully.

If venting through the roof, and rectangular-to-round transition is used, be sure there are at least 3" (7.6 cm) of clearance between the top of the microwave oven and the transition piece. See "Rectangular-to-Round Transition" illustration.



Rectangular-to-Round Transition


NOTE: The minimum 3" (7.6 cm) clearance must exist between the top of the microwave oven and the rectangular to round transition piece so that the damper can open freely and fully.



- A. Roof cap
- B. 6" (15.2 cm) min. diameter round vent
- C. Elbow (for wall venting only)
- D. Wall cap
- E. 31/4" x 10" to 6" (8.3 x 25.4 cm to 15.2 cm) rectangular to round transition piece
- F. Vent extension piece, at least 3" (7.6 cm) high

Recommended Standard Fittings

The following length equivalents are for use when figuring vent length. See the examples in "Recommended Vent Length".



- A. Rectangular-to-round transition piece: $3\frac{1}{4}$ " x 10" to 6" = 5 ft $(8.3 \times 25.4 \text{ cm to } 15.2 \text{ cm} = 1.5 \text{ m})$
- B. Roof cap: 31/4" x 10" = 24 ft (8.3 x 25.4 cm = 7.3 m)
- C. 90° elbow: 3½" x 10" = 25 ft (8.3 x 25.4 cm = 7.6 m)
- D. 90° elbow: 6" = 10 ft (15.2 cm = 3 m)
- E. Wall cap: 31/4" x 10" = 40 ft (8.3 x 25.4 cm = 12.2 m)
- F. 45° elbow: 6" = 5 ft (15.2 cm = 1.5 m)
- G. 90° flat elbow: 31/4" x 10" = 10 ft (8.3 x 25.4 cm = 3 m)

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

32 of 45

Recommended Vent Length


A 31/4" \times 10" (8.3 \times 25.4 cm) rectangular or 6" (15.2 cm) round vent should be used.

The total length of the vent system including straight vent, elbow(s), transitions, and wall or roof caps must not exceed the equivalent of 140 ft (42.7 m) for either type of vent. See the "Recommended Standard Fittings" section for equivalent lengths.

For best performance, use no more than three 90° elbows.


To calculate the length of the system you need, add the equivalent lengths of each vent piece used in the system. See the following examples:

31/4" x 10" (8.3 x 25.4 cm) vent system = 73 ft (22.2 m) total



- A. One 31/4" x 10" (8.3 x 25.4 cm) 90° elbow = 25 ft (7.6 m)
- B. 1 wall cap = 40 ft (12.2 m)
- C. 2 ft (0.6 m) + 6 ft (1.8 m) straight = 8 ft (2.4 m)

6" (15.2 cm) vent system = 73 ft (22.2 m) total



- A. Two 90° elbows = 20 ft (6.1 m)
- B. 1 wall cap = 40 ft (12.2 m)
- C. 1 rectangular-to-round transition piece = 5 ft (1.5 m)
- D. 2 ft (0.6 m) + 6 ft (1.8 m) straight = 8 ft (2.4 m)

If the existing vent is round, a rectangular-to-round transition piece must be used. In addition, a rectangular 3" (7.6 cm) extension vent between the damper assembly and rectangular-to-round transition piece must be installed to keep the damper from sticking.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

33 of 45



Whirlpool 21 cu. ft. Top-Freezer Refrigerator WRT541SZD

Fingerprint-Resistant Stainless WRT541SZDZ

Also available in:

-	_	
		White
1	3	AALIITE

WRT541SZDW



WRT541SZDB



WRT541SZDM

Capacity	
Total Capacity	21 cu. ft.
Refrigerator Capacity	15 cu. ft.
Freezer Capacity	6 cu. ft.

General Features & Properties

EZ Connect Icemaker Kit

LED Interior Lighting

ENERGY STAR® Certified

Electronic Temperature Controls

Freezer Temperature Controls

Clear Door Bins

Adjustable Door Bins

Quiet Cooling

Fingerprint Resistant

ENERGY STAR® Certified

6.5	
115	
Yes	
	115

Technical Details	
Refrigerator Type	Top-Freezer
Number of Doors	2
Number of Interior Refrigerator Shelves	3
Number of Refrigerator Door Bins	1 Fixed, 4 Adjustable
Number of Interior Freezer Shelves	1
Number of Freezer Door Bins	2 Fixed
Lighting Type	LED
Ice Maker	Optional
Ice Maker Location	Freezer
Dispenser Type	N/A
Dimensions	
Product Dimensions (H x W x D)	66-1/4" x 32-3/4" x 34"
Depth with Door Open 90°	62-1/4"
Cutout Dimensions	Allow extra 1/2" on sides and top

Allow extra 1" on rear

Reference Material

Dimension Guide

Use & Care Guide

Energy Guide Warranty

Key Features & Benefits

Frameless Glass Shelves


Store more items on wall-to-wall shelves for greater storage flexibility.

Flexi-Slide™ Bin

Make space for tall items with the bin that quickly and easily moves side to side.

Humidity-Controlled Crispers

Store fruits and vegetables in their ideal environment.



GIARAGE LEFT HINGES ON RIGHT HANDLE ON LEFT

NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.
®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXC. WRT541SZDSPECSHEETV01.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

34 of 45



Top Mount Refrigerator

PRODUCT MODEL NUMBERS

WRT311FZD WRT511SZD WRT541SZD

Electrical: A 115-volt, 60-Hz, AC-only, 15or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.


NOTE: Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting. See "Using the Controls."

Water: A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

IMPORTANT: The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 30 and 120 psi (207 and 827 kPa).


Reverse Osmosis Water Supply: If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

PRODUCT DIMENSIONS



Model Number	Model Size	Reversible Door	Height - Overall "A"	Height - Top of Cabinet "B"	Depth - Door Open 90° "C"	Depth - With Handles "D"	Depth - Without Handles "E"	Depth - Cabinet Only "F"	Width - Cabinet "G"
WRT311FZD	20.5 cu. ft.	Yes	661/4" (168.3 cm)	65½" (166.4 cm)	62¼" (158.1 cm)	32%" (83,5 cm)	30%" (77.8 cm)	28½" (72.4 cm)	32¾" (83.2 cm)
WRT511SZD WRT541SZD	21.3 cu. ft.	Yes	661/4" (168,3 cm)	65½" (166.4 cm)	62¼" (158.1 cm)	34" (86.4 cm)	32½" (82.3 cm)	28½" (72.4 cm)	32¾" (83.2 cm)

LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a $\frac{1}{2}$ " (1.25 cm) space on each and between overhead cabinets and refrigerator top. Allow at least 1" (2.5 cm) between back of cabinet and the wall. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave 2" (5 cm) minimum on the hinge side (depending on your model) to allow for the door to swing open.


NOTE: This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

35 of 45





Available Finishes/Colours



YWFE515S0JB

YWFE515S0JS

YWFE515S0JW White

Manuals & Literature:



Installation Instructions



Warranty

5.3 cu. ft. Whirlpool® electric range with Frozen Bake[™] technology

YWFE515S0JS

This Whirlpool® electric range with a dual element stove top helps you get dinner to the table. Skip preheating for favorites like pizza with Frozen Bake™ technology. This self cleaning oven also prevents cooked food from getting cold with the Keep Warm setting. Closed door broiling helps keep the kitchen comfortable.

Top Features

FlexHeat™ Dual Radiant Element
Get two elements in one with a 6" inner ring that's great for smaller pots and pans and a 9" expandable outer ring that makes room for larger cookware.

Frozen Bake™ technology
Skip preheating and cook frozen favorites like pizza in fewer steps with preprogrammed settings that automatically adjust cooking times for you.

Keep dishes from getting cold with this setting that delivers low heat to the oven.

Closed Door Broiling

Maintain the optimal cooking temperature for food while still keeping the kitchen comfortable and cool using this broiling temperature management system that helps prevent overheating.

Depth	27 3/4	Handle Type	Reach-Through Handle
Height	36		
Width	29 7/8	Features	
Configuration and Ove	rview	Hot Surface Indicator Light	Yes
Range Type	Freestanding	Heating Element On Indicator Light	Yes
Fuel Type	Electric	Power On Indicator Light	No
Size (IN,inches)	30	Griddle	NA NA
Exterior	Transfer of the second	Automatic Convection Conversion Temperature Adjust	No
Door Removable	Yes	Power Outage Compatible	No
Drawer Type	Storage Drawer	, 5	4
Oven Door	Glass Window		
Oven Window Size	Extra Large		
Handle Color	Stainless Steel		
Handle Material	Metal		

CANADIAN APPLIANCE SOURCE LP

Page 2 of 20

CANADIAN APPLIANCE SOURCE LP




Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

36 of 45

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

Product Dimensions



- A. 273/4" (70.5 cm) max. depth with handle
- B. 467/s" (119.1 cm) overall height (max.) with leveling legs screwed all the way in*
- C. 36" (91.4 cm) cooktop height (max.) with leveling legs screwed all the way in*
- D. 297/8" (75.9 cm) width
- E. 255/16" (64.3 cm) depth back of range to front of cooktop**
- Model/serial/rating plate (located on the frame behind a top corner of the door or either side of the drawer)

IMPORTANT: Range must be level after installation. Follow the instructions in the "Level Range" section. Using the cooktop as a reference for leveling the range is not recommended.


- *Range can be raised approximately 1" (2.5 cm) by adjusting the leveling legs.
- **Front of door and drawer may extend further forward depending on styling.

Cabinet Dimensions

Cabinet opening dimensions shown are for 25" (64.0 cm) countertop depth, 24" (61.0 cm) base cabinet depth and 36" (91.4 cm) countertop height.

IMPORTANT: If installing a range hood or microwave hood combination above the cooking surface, follow the range hood or microwave hood combination installation instructions for dimensional clearances above the cooktop surface.

A freestanding range may be installed next to combustible walls with zero clearance.



- A. 13" (33.0 cm) max. upper cabinet depth
- B. 30" (76.2 cm) min. opening width
 C. For minimum clearance to top of cooktop, see NOTE*
- D. 30" (76.2 cm) min. opening width
- Outlet 8" (20.3 cm) to 22" (55.9 cm) from either cabinet, 7" (17.8 cm) max. from floor.
- F. Cabinet door or hinges should not extend into the cutout.

*NOTE: 24" (61.0 cm) minimum when bottom of wood or metal cabinet is covered by not less than 1/4" (6.4 mm) flame retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" (0.4 mm) stainless steel, 0.024" (0.6 mm) aluminum or 0.020" (0.5 mm) copper.

30" (76.2 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

37 of 45

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

Electrical Requirements - Canada Only

AWARNING



Electrical Shock Hazard

Electrically ground range.

Failure to do so can result in death, fire, or electrical shock.

If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path is adequate and wire gauge are in accordance with local codes.

Be sure that the electrical connection and wire size are adequate and in conformance with CSA Standard C22.1, Canadian Electrical Code, Part 1 - latest edition, and all local codes and ordinances.

A copy of the above code standards can be obtained from:

Canadian Standards Association 178 Rexdale Blvd. Toronto, ON M9W 1R3 CANADA

Check with a qualified electrical installer if you are not sure the range is properly grounded.

Range Rating*		Specified Rating of Power Supply Cord Kit and Circuit Protection
120/240 V	120/208 V	Amps
8.8 - 16.5 KW	7.8 - 12.5 KW	40 or 50**
16.6 - 22.5 KW	12.6 - 18.5 KW	50

- *The NEC calculated load is less than the total connected load listed on the model/serial/rating plate.
- **If connecting to a 50 A circuit, use a 50 A rated cord with kit. For 50 A rated cord kits, use kits that specify use with a nominal 13/8" (3.5 cm) diameter connection opening.
- A time-delay fuse or circuit breaker is recommended.
- This range is equipped with a CSA International Certified Power Cord intended to be plugged into a standard 14-50R wall receptacle. Be sure the wall receptacle is within reach of range's final location.



Do not use an extension cord.

INSTALLATION INSTRUCTIONS


Unpack Range

AWARNING

Excessive Weight Hazard

Use two or more people to move and install range. Failure to do so can result in back or other injury.


- 1. Remove shipping materials, tape and film from range.
- 2. Remove oven racks and parts package from inside oven.
- 3. Do not remove the shipping base at this time.



A. Shipping base

4. On Ranges Equipped with a Storage Drawer:


Remove the storage drawer. See the "Storage Drawer" section. Use a 1/4" (6.4 mm) drive ratchet to lower the rear leveling legs one-half turn. Use a wrench or pliers to lower front leveling legs one-half turn.



- A. 1/4" (6.4 mm) drive ratchet
- B. Rear leveling leg
- C. Wrench or pliers
- D. Front leveling leg

On Ranges Equipped with a Warming Drawer or Premium Storage Drawer:

On ranges equipped with a warming drawer or premium storage drawer, the rear legs cannot be accessed by removing the warming drawer or premium storage drawer. It will be necessary to adjust the rear legs from outside the range. Use wrench or pliers to lower the front and rear leveling legs one half turn.



- A. Rear leveling leg
- B. Wrench or pliers
- C. Front leveling leg

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

38 of 45

WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

Install Anti-Tip Bracket



Tip Over Hazard

A child or adult can tip the range and be killed.

Install anti-tip bracket to floor or wall per installation instructions.


Slide range back so rear range foot is engaged in the slot of the anti-tip bracket.

Re-engage anti-tip bracket if range is moved.

Do not operate range without anti-tip bracket installed and engaged.

Failure to follow these instructions can result in death or serious burns to children and adults.

- Remove the anti-tip bracket from where it is taped inside the storage drawer or warming drawer.
- Determine which mounting method to use: floor or wall.
 If you have a stone or masonry floor, you can use the wall mounting method. If you are installing the range in a mobile home, you must secure the range to the floor.
- 3. Determine and mark centerline of the cutout space. The mounting can be installed on either the left-side or right-side of the cutout. Position mounting bracket against the wall in the cutout so that the V-notch of the bracket is 129/16" (31.9 cm) from centerline as shown.




A. 129/16" (31.9 cm) B. Bracket V-notch

4. Drill two 1/8" (3 mm) holes that correspond to the bracket holes of the determined mounting method. See the following illustrations.

Floor Mounting








Rear position

Front position

Diagonal (2 options)

Wall Mounting



- Using the Phillips screwdriver, mount anti-tip bracket to the wall or floor with the two #12 x 1⁵/₈" (4.1 cm) screws provided.
- Move range close enough to opening to allow for final electrical connections. Remove shipping base, cardboard or hardboard from under range.
- 7. Move range into its final location, making sure rear leveling leg slides into anti-tip bracket.




 Move range forward onto shipping base, cardboard or hardboard to continue installing the range using the following installation instructions.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

39 of 45





Stainless Steel WDF330PAHS

Also available in:

) White

WDF330PAHW

Black

WDF330PAHB

1
13
erties
Option
ed ·
Dishwasher Brand [†]
and Assembled in the ride
10
120
60
֡֡֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜֜

Certifications

ENERGY STAR® Certified

	*:
Technical Details	
Dishwasher Type	Built-in
Control Location	Front
Control Type	Push Button
Number of Wash Cycles	3
Number of Options	4
dBA*	55
Number of Racks	2
Tub Material	Plastic
Wash System	Filter
Wash System Type	Removable Filter
Number of Wash Arms	2
Dimensions	
Product Dimensions (H x W x D)	34-1/2" x 23-7/8" x 24-1/2"
Depth with Door Open 90°	49-1/2"

Reference Material

Dimension Guide

Install Guide

Use & Care Guide

Energy Guide

Warranty

Key Features & Benefits

1-Hour Wash Cycle


Clean dishes in half the time so your plates, pans and glasses are thoroughly cleaned up and taken care of in just an hour.

Soil Sensor

Determines how dirty dishes are and adjusts the Normal cycle as needed to make sure dishes come out clean.

Normal Cycle

Use for normal amounts of food soil to clean up leftover messes from your day-to-day meals.



^{*}Per IEC standards. **Compared to Normal cycle with lightly soiled loads. †Based on 12-month average of sales. TraQline 2018. NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXA. WDF330PAHSPECSHEETV01.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

40 of 45




Undercounter Dishwasher

PRODUCT MODEL NUMBERS

WDF110PAB	WDF320PAD	WDT710PAH
WDF111PAB	WDF330PAH	WDT720PAD
WDF120PAF	WDF331PAH	WDT730PAH
WDF121PAF	WDF520PAD	WDT735PAG
WDF130PAH	WDF540PAD	WDT735PAH
WDF131PAH	WDF545PAF	

DRAIN REQUIREMENTS

- A new drain hose is supplied with your dishwasher. If drain hose is not long enough, use a new drain hose with a maximum length of 12 ft (3.7 m) that meets all current AHAM/IAPMO test standards, is resistant to heat and detergent, and fits the 1" (25 mm) drain connector of the dishwasher. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Make sure to connect drain hose to waste tee or disposer inlet above drain trap in house plumbing and 20" (508 mm) minimum above the floor. It is recommended that the drain hose either be looped up and securely fastened to the underside of the counter or be connected to an air gap.
- Make sure to use an air gap if the drain hose is connected to house plumbing lower than 20" (508 mm) above subfloor or floor.



- If required, the air gap should be installed in accordance with the air gap installation instructions. When you are connecting the air gap, a rubber hose (not provided) will be needed to connect to the waste tee or disposer inlet.
- Use 1/2" minimum I.D. drain line fittings.

WATER SUPPLY REQUIREMENTS

- This dishwasher has a water heating feature and also requires a connection to a hot water supply line.
- A hot water line with 20 to 120 psi (138 to 862 kPa) water pressure can be verified by a licensed plumber.
- 120°F (49°C) water at dishwasher
- 3/8" O.D. copper tubing with compression fitting or flexible braided water supply line. See the "Tools and Parts" section at the front of the guide for part details and orders.

NOTE: 1/2" minimum plastic tubing is not recommended.

- A 90° elbow with 3/4" hose connection with rubber washer. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Do not solder within 6" (152 mm) of the water inlet valve.
- If installed in new construction, make sure the house water supply lines have been flushed prior to connecting the dishwasher to remove any debris that may exist in the supply line.

NOTE: If replacing an existing dishwasher, it is recommended to install a new water line (see the "Tools and Parts" section at the front of the guide for part details) and drain hose (supplied) with the new dishwasher.

ELECTRICAL REQUIREMENTS

You Must Have:


- 120-volt, 60 Hz, AC-only, 15- or 20-amp, fused electrical supply
- Copper wire only
- A maximum of 2 field wiring supply conductors (12 AWG largest size) plus 1 grounding conductor are permitted in the terminal box.

We Recommend:

- A time-delay fuse or circuit breaker
- A separate circuit

If Connecting Dishwasher with a Power Cord:

- Use a UL Listed power cord kit marked for use with dishwasher. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Plug into a grounded 3 prong outlet. Outlet must meet all local codes and ordinances.



If Connecting Dishwasher with Direct Wiring:

- Use flexible, armored, or nonmetallic sheathed copper wire with grounding wire that meets the wiring requirements for your home and local codes and ordinances.
- Use a UL Listed/CSA Approved metallic strain relief.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.


Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice. Page 1 of 2 W10806908-D-WH 12/16

Unit: 3191D-23, Phase: 3


Model: 20-1790 A The Dunmore

41 of 45


PRODUCT AND CABINET OPENING DIMENSIONS



For 4" (100 mm) toe kick, height of cabinet opening is 341/2" (863 mm).



- A. Insulation may be compressed (not used on all models).
- B. Door handles may protrude forward of the face of the dishwasher, (varies by model).



Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

42 of 45

35

No

Hot, Cold, Cool, Warm

5.0 cu.ft I.E.C. Closet-Depth Front Load Washer with Intuitive Controls

Model: WFW560CHW



Specifications

LCD Touch Screen

Width: 6858.00, 27.0" Centimeters, Inches


Depth: 8016.88, 31-9/16" Centimeters, Inches


Dimensions		Compatibility
Capacity	4-3/10	Works With
Depth	8016.88 cm, 31-9/16 in	Options
Gross Weight	97068688.00 kg, 214 lbs	2014/2012/2012
Net Weight	92532768.00 kg, 204 lbs	Number Of Washer Options
Width	6858.00 cm, 27.0 in	Features
Appearance	[*	
		Stackable
LCD Touch Screen	No	Water Faucet
Window	Yes	Water Faucet
		Cycles
Details		
	e I i i i i i i i i i i i i i i i i i i	Number Of Wash Cycles
Advanced Vibration Control™	No	Fotosian
Dispense System	Detergent, Fabric Softener & Bleach	Exterior
SOMBLE CARROLS CONTROL (SEC.)	.6222-252.xtrs.03491.1	Lid/Door Lock
Eco Monitor/Efficiency Monitor	No.	Lid/Door Swing
Hoses Included	4ft 4in Drain Hose Included	
Internal Heater	No	Modifiers
Maximum Spin Speed	1160	Delay Start
Out Of Balance Sensing	Yes	Number Of Rinse Options
Water Factor	3-1/5	Number Of Soil Levels
Cycles and Options		Number Of Spin Speeds
		Number Of Wash/Rinse Temperate
Number Of Wash Cycles	35	Pre Soak
Electrical		Temperature Selections
The later discussion and the		
Power Cord Included	Yes	
Controls		2
Automatic Temperature Controls	Yes	
Control Location	Front	
Control Cocation	Front	
	190	

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

43 of 45





0 0 0 39" min. (991 mm)

(686 mm)

(25 mm)

24 in ²


(155 cm²)

3" (76 mm)

Drain System It is the responsibility of the installer to install and secure the drain

m) cable tie.

Floor standpipe drain system




hose in to the provided plumbing/drain in a manner that will avoid the drain hose coming out of o leaking from the plumbing/drain.

Drain system can be installed using a floor drain, wall standpipe, floor standpipe, or laundry tub. Select the method you need.

IMPORTANT: To avoid siphoning, only 4.5" (114 mm) of drain hose should be inside standpipe. Always secure drain hose with

Minimum diameter for a standpipe drain: 2" (51 mm). Minimum carry-away capacity: 17 gallons (64 L) per minute. A 1/4" (6 mm) diameter to 1" (25 mm) diameter Standpipe Adapter Kit is available; refer to the Quick Start Guide for online ordering information. Top of standpipe must be at least 39" (762 mm) high; install no higher than 96" (2.4 m) from bottom of washer. If you have an overhead sewer and need to pump higher than 96" (2.4 m), a sump pump and associated hardware are needed. See "Alternate Parts."



0.25" (5 mm)

(25 mm)


(25 mm) (25 mm)

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore


44 of 45

Wall standpipe drain system




See requirements in "Floor standpipe drain system."


Laundry tub drain system



Minimum capacity: 20 gallons (76 L). Top of laundry tub must be at least 39" (991 mm) from the floor; install no higher than 96" (2.4 m) from bottom of washer.



Floor drain system



Floor drain system requires a Siphon Break Kit, 2 Connector Kits, and an Extension Drain Hose that may be purchased separately; refer to the Quick Start Guide for online ordering information. Minimum siphon break height: 28" (710 mm) from bottom of washer. (Additional hoses may be needed.)

Electrical Requirements

AWARNING



Electrical Shock Hazard

Plug into a grounded 3 prong outlet.

Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire, or electrical shock.

- A 120 V, 60 Hz, AC only, 15 or 20 A, fused electrical supply is required. A time-delay fuse or circuit breaker is recommended. It is recommended that a separate circuit breaker serving only this appliance be provided.
- This washer is equipped with a power supply cord having a 3-prong grounding plug.
- To minimize possible shock hazard, the cord must be plugged into a mating, 3-prong, grounding-type outlet, grounded in accordance with local codes and ordinances. If a mating outlet is not available, it is the personal responsibility and obligation of the customer to have the properly grounded outlet installed by a qualified electrician.
- If codes permit and a separate ground wire is used, it is recommended that a qualified electrician determine that the ground path is adequate.
- Do not ground to a gas pipe.
- Check with a qualified electrician if you are not sure the washer is properly grounded.
- Do not have a fuse in the neutral or ground circuit.

GROUNDING INSTRUCTIONS

For a grounded, cord-connected appliance:

This appliance must be grounded. In the event of a malfunction or breakdown, grounding will reduce the risk of electric shock by providing a path of least resistance for electric current. This appliance is equipped with a cord having an equipment-grounding conductor and a grounding plug. The plug must be plugged into an appropriate outlet that is properly installed and grounded in accordance with all local codes and ordinances.

WARNING: Improper connection of the equipment-grounding conductor can result in a risk of electric shock. Check with a qualified electrician or serviceman if you are in doubt as to whether the appliance is properly grounded. Do not modify the plug provided with the appliance: If it will not fit the outlet, have a proper outlet installed by a qualified electrician.

For a permanently connected appliance:

This appliance must be connected to a grounded metal, permanent wiring system, or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment-grounding terminal or lead on the appliance.

SAVE THESE INSTRUCTIONS

Unit: 3191D-23, Phase: 3

Model: 20-1790 A The Dunmore

45 of 45

WHIRLPOOL DRYER Model #: YWED5620HW

Whirlpool Brand Canada English | Washer and Dryers | Dryers | Electric Dryers | WED5620HW





7.4 cu. ft. Front Load Electric
Dryer with Intuitive Touch
Controls



7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls

Model #: YWED5620HW

Dimensions

Depth		78.74 cm, 31.0 in	
Depth With Door Open 90 D	egree	138.43 cm, 54-1/2 in	
Height		98.42 cm, 38-3/4 in	
Width		68.58 cm, 27.0 in	
Configuration and Overvie	w		
Fuel Type		Electric	
Cycles and Options			
Cycle Time Remaining		Yes	
Lint Filter Indicator		No	
Line i ilici ilicitorior		140	
Number of Dryer Cycles		36	
Number of Dryness Levels		3	
Ventilation System			
Lang Vant		Ne	
Long Vent		No	
Maximum Vent Length		64	
The second secon			
Venting Direction		Left, Right, Bottom, Re	ar
Electrical			
Hz		60	
Power Cord Included		Yes	
Fower Cord included		res	