### Sales Selection Sheet Checklist

Model: 20-1841 A ARLINGTON

LOT 696-3

PURCHASERS: ANKARA	AN KUNARATNAM/
VENDOR: Heathwo	ood Homes (Whitby) Limited
	×
	OOR OFF MASTER BEDROOM
OPTIONAL DOUBLE SINKS	IN MASTER ENSUITE BATHROOM
☐ WOB	
DECK	**
FINISHED BASEMENT	
COLD CELLAR	
UPGRADED / MODIFIED ELEVATION	ON RECOMMENDED AND CONTRACT OF THE PROPERTY OF
CORNER UPGRADE	
REAR UPGRADE	
SIDE UPGRADE	
CEILING UPGRADE - SMOOTH	THE CONTRACT CONTRACT OF STREET AND ASSOCIATION OF STREET CONTRACT
MAIN FLOOR	
SECOND FLOOR  BASEMENT	
BASEMENT LOWER LEVEL	
L LOVVLIN LEVEL	
ADDITIONAL ROUGH-INS	) a
ADDITIONAL ROUGH-INS  200 AMP SERVICE (STD 200	)AMP TOWNS)
WET BAR ROUGH-IN	
HUMIDIFIER	
AIR CONDITIONING (SITE S	STD)
GAS ROUGH-IN	
STOVE	
DRYER	
BBQ	
ADDITIONAL FIREPLACE	
KITCHEN: HOODFAN VENTING SIZ	ZE
6 IN ROUND DUCT	
7 IN ROUND DUCT (STD FO	
FULL BASEMENT STAIRS:	Paint Grade
UPPER BASEMENT STAIRS:	N/A
LOWER LEVEL STAIRS:	All Oak
LOWER BASEMENT STAIRS: MAIN STAIRS:	N/A All Oak
MEDIA STAIRS: MEDIA STAIRS (if applicable):	All Oak N/A
LOFT STAIRS (if applicable):	N/A
Oct 7/22 Signature	e OCT 7/22 IRIT SALEM
Date Purchaser:	Date Decor Consultant:
on tile	B. Charles
0	
Date Purchaser:	-10- 0 7 2022 mposen
uronuser.	Date Heathwood Homes (Whithy) Limited

ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON 50100 Feeted: 8 15 20 2 11. 92 4

Locked:

Closed:

A first the second and statement of the second seco	en e	
Cabinet Colour/Style	9157	Viking III-SIMCOE-MOONLIGHT-3DL ***STD***
Island Cabinet Colour/Style	9157	Viking III-SIMCOE-MOONLIGHT-3DL ***STD***
Cabinet Hardware	2086	9677-HARDWARE ***STD***
Countertop	9069	MSI Quartz GROUP 1 ICED WHITE ***STD***
Island Countertop	9069	MSI Quartz GROUP 1 ICED WHITE ***STD***
Countertop Edge	4010	SINGLE POLISHED STRAIGHT EDGE 3/4 INCH ***STD***
Sink	9488	Plumbing-KINDRED Kitchen Sink Collection - Reginox NS1930 U/9-Single Bowl Undermount Sink (or equivalent)-Stainless Steel
Crumb Vac Color	9483	Vacuum-Crumb Vac (Dust Pan)-Black
HoodFan	34	AV1308 Air King 30 STAINLESS STEEL UNDER CABINET RANGE HOOD **STD**
Opt. Backsplash	5721	QT.CD.ARW.0306.BR-Colour and Dimension Bright-Arctic White-3 x 6 ***1***
Opt. Backsplash Grout	2226	Grout-(00) White ***STD***
Opt. Backsplash Tile Pattern	3060	HORIZONTAL BRICK ***STD***
Flooring	9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***
Floor Tile Grout	2225	Grout-(27) Silver ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***

- Purchasers have been advised: standard fridge opening is a minimum  $37\ 3/8\ x\ 73\ 3/8$  inches. Ice Waterline Rough-In is included.
- Standard stove opening is 30 inches and standard dishwasher opening is 24 inches. Any gas stove will require backsplash or stainless steel backing to avoid fire hazards.
- Purchasers acknowledge: Heathwood Homes and its contractors will not be responsible for any kitchen cabinet changes due to appliances dimension changes after sign-off.

Comment			
1			

14 (4) (4) (5)		
9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***	Y
2225	Grout-(27) Silver ***STD***	
3000	STANDARD SQUARE ***STD***	
	2225	***STD***  2225 Grout-(27) Silver ***STD***

AL

### **Customer Colours** ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON Closed: Comment **Powder Room** TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 Flooring 9255 \*\*STD\*\*\* Grout-(27) Silver \*\*\*STD\*\*\* Floor Tile Grout 2225 STANDARD SQUARE \*\*\*STD\*\*\* Floor Tile Pattern 3000 Plumbing Fixtures-WHITE \*\*\*STD\*\*\* 1737 Plumbing Fixture (Colour) Comment **Dining Room** Red Oak Pearl-Vintage 7498 Flooring Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch Comment New size due to revised colour chart see page 39 **Great Room** 7498 Red Oak Pearl-Vintage Flooring Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch Comment New size due to revised colour chart see page 39 Great Room Fireplace Dimplex-Electric Fireplace-PF3033HL \*\*\*STD\*\*\* Type 8865 NF 15-Paint Grade Mantle- Cabinet (Per Plan)-WHITE Mantle 9114 PG 16 \*\*\*STD\*\*\* N/A \*\*\*\*\* 1111 Opt. Surround - Purchasers have been advised: heat from the FP can damage TV above a FP and items placed on mantle. - Heathwood and its contractors will not be liable for any damage on items placed/@installed above a FP after closing. Comment

Upper Hall

Flooring

7498

Red Oak Pearl-Vintage
Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch

New size due to revised colour chart see page 39

An

ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON 5038 Created: 8452022 11.348

Locked:

Master Bedroom	
Flooring 7498	Red Oak Pearl-Vintage
	Engineered-GRYPHON/IRONGATE-3/4 inch x 3 1/4 inch
	***3***
Comment	New size due to revised colour chart see page 39
	Trew size due to revised selection shart ose page se
20	
Bedroom 2	
Flooring 9252	DY 16787 -Dynasty Tex-MYSTIC BEIGE-40 oz
5.00-5 4.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5 5.000-5	Poly***STD***
Comment	
	**
Bedroom 3	
Flooring 9252	DY 16787 -Dynasty Tex-MYSTIC BEIGE-40 oz
<i>t</i> ()	Poly***STD***
Comment	
Comment	9
	*
Master Ensuite	
Cabinet Colour/Style 9158	Viking III-SIMCOE-NAVY BLUE-3DL ***STD***
Cabinet Hardware 2086	9677-HARDWARE ***STD***
Countertop 8796	6698-46-Countertop-PALOMA POLAR ETCHINGS FINISH-Formica ***STD***
Countertop Edge 1111	N/A *****
Countertop Lage	N/A
Floor Tile	TO COMMITTE 1212 CEMPDE White Matte 12 v 12
Floor Tile 9255	TR.SP.WHITE.1313 SEMPRE White Matte 13 x 13 ***STD***
Floor Tile Grout 2225	Grout-(27) Silver ***STD***
Floor Tile Pattern 3000	STANDARD SQUARE ***STD***
Shower Wall Tile 5420	QT.SP.DGR.0810-Splendour-Dark Grey-8 inch x 10 inch
	***STD***
124	
Shower Wall Tile Grout 2226	Grout-(00) White ***STD***
Shower Wall Tile Pattern 3090	VERTICAL STACKED ***STD***
g .	
2,000,10	OD ON OWT COSC MEN O
Shower Floor Tile 8661	OD.ON.SWT.0202.MT.N-Ontario Series Mosaic-Snow White Matte-2 x 2 ***STD***

ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON 50100 replied: 8,15,2012 11.00.40

Locked:

Closed:

	Shower Floor Tile Grout	2226	Grout-(00) White ***STD***
	Shower Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
			**************************************
	Shower Jamb(s) and Sill(s)	8923	Shower Jamb / Sill-Thassos White ***STD***
	Plumbing Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***
-	Comment		
	to the second se		327 377 300 300 300 300 300 300
aiı	n Bathroom		
	Cabinet Colour/Style	9111	Viking III-SIMCOE ORCHID 3DL ***STD***
	oublinet colouii/ctylo	0.111	Timing in divided externib 652 - 67B
	Cabinet Hardware	2086	9677-HARDWARE ***STD***
	Countertop	8806	4987K-07-Countertop-LECHE VESTA-Wilsonart ***STD***
	Countertop Edge	1111	N/A *****
	Floor Tile	8262	TR.ST.GRY.1313-Serpantine-Grey-13x13 ***STD***
			8
	Floor Tile Grout	7704	Grout-(19) Pearl Gray ***STD***
	Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
	Wall Tile	8258	TR.ST.GRY.0810-Serpantine-Grey-8 x 10 ***STD***
	Wall Tile Grout	7704	Grout-(19) Pearl Gray ***UPG***
	Wall Tile Pattern	3090	VERTICAL STACKED ***STD***
	Out Observe Floor Tile	4444	N/A *****
	Opt. Shower Floor Tile	1111	IN/A
	Opt. Shower Floor Tile Grout	1111	N/A *****
	Opt. Shower Floor Tile Pattern	1111	N/A *****
	Opt. Shower Jamb(s) and Sill(s) Plumbing Fixture (colour)	1111 1737	N/A ***** Plumbing Fixtures-WHITE ***STD***

ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON



Locked:

Closed:

wer Level Family Room		
Flooring	9252	DY 16787 -Dynasty Tex-MYSTIC BEIGE-40 oz Poly***STD***
Comment	-1910	
wer Level Laundry Mud Room		
Flooring	5594	GE.KL.GRY.1313-Kelly-Grey-13 inch X 13 inch ***STD***
Floor Tile Grout	2222	Grout-(105) Driftwood ***STD***
Floor Tile Pattern	3000	STANDARD SQUARE ***STD***
Opt. Cabinet Colour/Style - Uppers	1111	N/A *****
Opt. Cabinet Hardware - Uppers	1111	N/A *****
Opt. Cabinet Colour/Style - Base	1111	N/A *****
Opt. Cabinet Hardware - Base Opt. Countertop	1111 1111	N/A ***** N/A *****
Opt. Countertop	1111	19/74
Opt. Countertop Edge	1111	N/A *****
- Optional Bedroom 4 Layout Laund	ry Rough i	in Relocated to Unfinished Basement (No Opt. Cabinet)
0	- 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1 - 1	-3 14 1
Comment		
	V <sub>2</sub> c	
		The state of the s
Lower Level Bedroom 4	1111	N/A *****
Flooring	1111	N/A
Comment		
	2001	<del></del>
. Lower Level Bedroom 4 Hallway	_	
Flooring	1111	N/A *****
Comment		
. Lower Level Bedroom 4 Mud Roo	m	*
Flooring	1111	N/A *****
Floor Tile Grout	1111	N/A *****

ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON

Lower Level and Main Stairs

Type

1712

Oak Stairs \*\*\*STD\*\*\*

Locked:

			_	•
CI	0	20	Ч	

Floor Tile Pattern 1111 N/A ******  Comment  Opt. Lower Level Bedroom 4 Bathroom  Cabinet Colour/Style 1111 N/A ******  Cabinet Hardware 1111 N/A ******  Countertop 1111 N/A ******	
Comment  Opt. Lower Level Bedroom 4 Bathroom  Cabinet Colour/Style 1111 N/A ******  Cabinet Hardware 1111 N/A ******	
Comment  Opt. Lower Level Bedroom 4 Bathroom Cabinet Colour/Style 1111 N/A ******  Cabinet Hardware 1111 N/A ******	
Comment  Opt. Lower Level Bedroom 4 Bathroom Cabinet Colour/Style 1111 N/A ******  Cabinet Hardware 1111 N/A ******	
Opt. Lower Level Bedroom 4 Bathroom  Cabinet Colour/Style 1111 N/A ******  Cabinet Hardware 1111 N/A ******	
Opt. Lower Level Bedroom 4 Bathroom  Cabinet Colour/Style 1111 N/A ******  Cabinet Hardware 1111 N/A ******	
Cabinet Colour/Style 1111 N/A *****  Cabinet Hardware 1111 N/A ******	
Cabinet Hardware 1111 N/A ******	
Cabinet Colour/Style 1111 N/A *****  Cabinet Hardware 1111 N/A ******	
Cabinet Hardware 1111 N/A ******	
Countertop	
Countertop Edge 1111 N/A ******	
Floor Tile 1111 N/A *****	
Floor Tile Grout 1111 N/A ******	
Floor Tile Pattern 1111 N/A ******	
Wall Tile 1111 N/A ******	
Wall Tile 1111 N/A ******	
NAME THE COLUMN ASSESSMENT OF THE PROPERTY OF	
Wall Tile Grout       1111       N/A ******         Wall Tile Pattern       1111       N/A ******	
yvan nie ratten	
Opt. Shower Floor Tile 1111 N/A ******	
Opt. Shower Floor Tile Grout 1111 N/A ******	
Opt. Shower Floor Tile Pattern 1111 N/A ******	
er.	
Opt. Shower Jamb(s) and Sill(s) 1111 N/A ******	
Opt. Shower Jamb(s) and Sill(s)  Plumbing Fixture (colour)  1111  N/A ******  N/A ******	
Comment	

ANKARAN KUNARATNAM/ Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON



Locked:

Closed:

Colour	7912	Irongate (Grypnon) STAIN TO COMPLIMIENT HARDWOOD AND WILL VARY FROM FLOORING
Handrail/Pickets/Posts Type	8148	Single Collar Alt. Plain w/ Shoes with 3 1/2" Square/Cap Post(s)-BLACK ***2***
Handrail/Pickets/Posts Colour	7912	Irongate (Gryphon) STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING
Custom Stain/Paint	1111	N/A *****
Landing(s)	7498	Red Oak Pearl-Vintage Engineered-GRYPHON/IRONGATE-3/4 inch x <del>3 1/4 inch</del>
Opt. Carpet Runner	1111	N/A ****** New size due to revised colour chart see page 39
Comment	51+10	
Basement Stairs		
Туре	1713	Paint Grade Stairs ***STD BASEMENT STAIR ***
Comment		
Throughout	5700	D
Switches and Plug	5796	Decora White Switches and Plugs ***STD***  Metal Thresholds ***STD***
Thresholds	2232 1079	
Underpad Trim Size	8705	500 Series-Underpad ***STD***  4 1/4 Baseboard and 2 3/4 Casings ***STD***
Trim - Paint Colour	1716	Trim-WHITE ***STD*** ✓
Walls - Paint Colour	1717	22-Wall-WARM GREY ***STD***
Comment	=	
Purchaser: ANKARAN KUNARATNA	AM So	Date Decor Consultant Date 13.22
(*) (*)		· Freeze
Purchaser:		mosen -10- 0 7 2022
-		Date Country Lane Date Approved



CONSTRUCTION SUMMA

Lot: 696-3 **Model: 20-1841 A ARLINGTON Project/Phase: Country Lane / 6** 

Offer	Five Appliances: SS Fridge, Stove, Dishwasher: White Front Loader Washer/Dryer? Townhomes
Worksheet	Note:
Offer	Five Thousand Dollars (\$5,000) at D?cor. (No Cash Value) - Townhomes
Worksheet	Note:
Offer	Two Men and a Truck Credit of One Thousand Dollars (\$1000.00) for moving services only, Into your Heathwood Home (No
	Cash Value) The
	Credit is Non-Transferable and cannot be combined with any other offer.
	- Townhomes
Worksheet	Note:
Offer	The Purchaser(s) are a 2 <sup>nd</sup> Time Heathwood buyer, whom lived or have lived at LOT 2131 and are entitled to \$1000 to spend at
	The Décor Store (No Cash Value).
Worksheet	

Page 3 of 3 Printed and Sent: 27-May-23

# 10 of 38 construction summary



Lot: 696-3

**Model: 20-1841 A ARLINGTON Project/Phase: Country Lane / 6** 

### **ADMIN FEE**

Invoice Qty. Description

### **CABINETRY**

Invoice	Qty.	Description
1141 335,871	-	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING
07Oct22 **		SKETCH # 4 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light

### **CERAMICS**

Invoice	Qty.	Description
1141 339,035 07Oct22	1	Kitchen Optional Backsplash - Ceramics - Upgrade 1 Tile - Kitchen Optional Backsplash - UPG
1141 339,139 07Oct22	1	Kitchen Optional Backsplash - Ceramics - Install in Specified Pattern - Kitchen Optional Backsplash - UPG
1141 339,134 07Oct22	1	Main Bath Wall - Ceramics - Upgrade Grout - Main Bath Wall - UPG

### **DRYWALL**

Invoice	e Qty. Description								
1141	1	- Drywall - Smooth Ceilings - Main Floor - UPG							
337,747									
07Oct22									
		PAINTING-Notify							

### **ELECTRICAL**

Invoice	Otro	Description
Invoice	Qty.	Description
1141 335,570	2	THROUGHOUT - ELECTRICAL - CEILING ROUGH-IN (CAPPED)
07Oct22		1X TO BE INSTALLED IN THE CENTRE OF GREAT ROOM - USE STD. SWITCH PLUG 1X TO BE INSTALLED ABOVE THE BREAKFAST BAR- USE KITCHEN TOGETHER WITH SWITCH SEE SKETCH # 3
1141 335,578 07Oct22	1	GREAT ROOM - ELECTRICAL - EXTRA WALL INTERIOR OUTLET ON EXISTING CIRCUIT (DOES NOT INCLUDE KITCHEN OUTLETS)  TO BE INSTALLED ABOVE THE CENTRE OF THE FIRE PLACE 70" +/- FROM FLOOR SEE SKETCH # 3
1141 335,871 07Oct22 **	1	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING SKETCH # 4 CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light

### **PAINTING**

Invoice	Qty.	Description
1141	1	- Drywall - Smooth Ceilings - Main Floor - UPG
337,747		
07Oct22		
**		PAINTING-Notify

DisciplineMS.rpt 13dec21 Printed and Sent: 27-May-23

Page 1 of 3

# 11 of 38



CONSTRUCTION SUMMARY

Lot: 696-3

Model: 20-1841 A ARLINGTON

**Project/Phase: Country Lane / 6** 

### **PLUMBING**

Invoice	Qıy.	Description
1141 335,871	1 1	MASTER ENSUITE - PLUMBING - OPTION FROM ONE SINK TO DOUBLE SINKS INCLUDING ONE ADDITIONAL STD CHATEAU FAUCET OVERMOUNT COLONY SINK ONE EXTRA VANITY LIGHT AND CABINET CONVERSION 2D VIKING
07Oct22		SKETCH# 4
		CABINETRY-2D Convert Cabinetry Viking; ELECTRICAL-Additional Vanity Light

DisciplineMS.rpt 13dec21

Page 2 of 3 Printed and Sent: 27-May-23

Model: 20-1841 A ARLINGTON

12 of 38

SKETCH #1

20-1841 ELEV. A

For BLK 696-2 & 696-3


## The Arlington

ELEVATION A & B: 1,841 SQ. FT.

THE TRAILS OF

COUNTRY LANE

Sunken 4R condition for: BLK 696-2, 696-3, 697-2, 697-3



BASEMENT ELEVATION A & B

Model: 20-1841 A ARLINGTON

13 of 38

SKETCH #2 20-1841 ELEV. A

ELEVATION A & B: 1,841 SQ. FT.


THE TRAILS OF

COUNTRY LANE

The Arlington

For BLK 696-2 & 696-3

Sunken 4R condition for: BLK 696-2, 696-3, 697-2, 697-3



LOWER LEVEL ELEVATION A & B

Model: 20-1841 A ARLINGTON

14 of 38

SKETCH #3

20-1841 ELEV. A


For BLK 696-2 & 696-3

## The Arlington

ELEVATION A & B: 1,841 SQ. FT.

THE TRAILS OF

COUNTRY LANE



WALL INTERIOR OUTLET ABOVE THE CENTRE OF THE FIRE PLACE 70" +/- FROM FLOOR

MAIN LEVEL ELEVATION A

Model: 20-1841 A ARLINGTON

15 of 38


SKETCH #4 20-1841 ELEV. A

The Arlington

ELEVATION A & B: 1,841 SQ. FT.

THE TRAILS OF COUNTRY LANE

For BLK 696-2 & 696-3



UPPER LEVEL ELEVATION A

Project: Country Lane Unit: 696-3, Phase: 6 Model: 20-1841 A ARLINGTON

16 of 38





NFAS NF15 Mantel


Model: 20-1841 A ARLINGTON

## 17 of 38



### NS1930U/9





### **NS1930U/9 SPECIFICATION**

Model NS1930U/9 is a single bowl, undermount sink manufactured for Franke Kindred Canada Limited from 18 gauge, 18-10 stainless steel. Product has mirror finished rim and brush finished bowl. Sink is fully undercoated. Basket strainer waste fitting (3 1/2", 89 mm) are included. Sink is backed with a limited buyer lifetime warranty.

- O.D. 18 3/4" x 29 3/4" x 8 1/2" (48 x 76 x 22 cm)
- Recommended for minimum 36" cabinet

Franke Kindred Canada Limited

P.O. Box 190, 1000 Franke Kindred Road, Midland, Ontario, Canada, L4R 4K9 Phone: 866-687-7465 Fax: 800-361-8408

Model: 20-1841 A ARLINGTON

## 18 of 38

## MOEN

#### **FAUCET DESCRIPTION**

Reflex™ pulldown system offers smooth operation, easy movement and secure docking Power Clean™ spray technology Metal construction with various finishes identified by suffix

Quick connect installation

Pulldown spray with 68" braided hose Flexible supply lines with 3/8" compression fittings

High arc spout provides height and reach to fill or clean large pots while pulldown wand provides the maneuverability for cleaning or rinsing 360° rotating spout

Faucet designed for handle to be mounted on right side only

#### **OPERATION**

Lever style handle

Temperature controlled by 100° arc of handle travel

Operates with less than 5 lbs. of force

• Operates in stream or spray mode in the pullout or retracted position **FLOW** 

Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi

CARTRIDGE

• 1255™ Duralast™ cartridge

### **STANDARDS**

Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements therein including NSF 61/9G & 372


- Meets CalGreen and Georgia SB370 requirements Complies with California Proposition 65 and with the Federal Safe Drinking
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA 🖒 for lever handle

### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the
- 10 year limited warranty when used in a multifamily installation

5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations

## Specifications




ALIGN™ **Single Handle High Arc Pulldown Kitchen Faucet** 

Models: 7565 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA. (OPTIONAL 3-HOLE ESCUTCHEON 141002 AVAILABLE)





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Rev. 6/20



### **BARRIER FREE (ABOVE COUNTER OR DROP-IN ONLY)**

### BOULEVARD® PEDESTAL SINK VITREOUS CHINA

### **BOULEVARD® PEDESTAL SINK**

☐ 0641.800 Faucet holes on 8" (203mm) centers (Illustrated)

STD • 0641.400 Faucet holes on 4" (102mm) centers

### ☐ 0641.100 Center hole only

- Classic styled rectangular pedestal lavatory
- · Vitreous china
- Rear overflow
- Supplied with mounting kit
- Right Height® for greater comfort during use
- Faucet ledge with large deck area (faucet not included)
- Design coordinates with Boulevard® Toilet
- Basin has flat bottom to also allow use as an **above counter** sink or a **drop-in** sink (with u-shaped cut out)

### **Nominal Dimensions:**

24" x 19" x 35-1/2" (610 x 483 x 902mm)

- ☐ 0641.008 Pedestal top-8" (203mm) centers
- ☐ 0641.004 Pedestal top-4" (102mm) centers
- ☐ 0641.001 Pedestal top-center hole only
- ☐ 0010.000 Pedestal only

### Bowl sizes:

17" (432mm) wide, 12-1/2" (318mm) front to back, 5" (127mm) deep

### **Compliance Certifications -**

### Meets or Exceeds the Following Specifications:

• ASME A112.19.2 - 2008/CSA B45.1-08

### To Be Specified:

- ☐ Color: ☐ White ☐ Linen
- ☐ Faucet Finish:
- Supplies:
- ☐ 1-1/4" Trap:
- □ Nipple:




SEE REVERSE FOR ROUGHING-IN DIMENSIONS

<sup>\*</sup> See faucet section for additional models available

Model: 20-1841 A ARLINGTON



### **BOULEVARD®** PEDESTAL SINK



ABOVE COUNTER AND DROP-IN SINK CONFIGURATIONS MEET THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES.

Top of sink installed at 34" (864mm) height from finished floor. Sink installed 5" (127mm) minimum from front edge of countertop. Provide 27" (686mm) knee clearance area.

NOTES:

\* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAPS ARE SUGGESTED.

▼ PEDESTAL ANCHORING SCREWS NOT INCLUDED.

■ SUITABLE FOR REINFORCEMENT ONLY. ACTUAL DIMENSIONS MUST BE TAKEN FROM FIXTURE.

FITTING NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL SUPPORTS. INSTALLATION INSTRUCTIONS SUPPLIED WITH LAVATORY.

**IMPORTANT:** Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

© 2018 AS America Inc.

Model: 20-1841 A ARLINGTON

## American Standard



### **BARRIER FREE**

### **COLONY™ COUNTERTOP SINK**

VITREOUS CHINA

### **COLONY COUNTERTOP SINK**

- · Vitreous china
- Self-rimming
- · Front overflow
- · Supplied with template
- Faucet deck (Faucet shown not included)

☐ 0346 803 → Faucet hotes on 203 mm (6"), centres	$\mathcal{L}$
O346 403 (Illustrated) Faucet holes on 102mm (4") centres	3
₩ <u>₽</u> 6346 661	ر ک
Contro holo only	


Centre hole only

Nominal Dimensions: 521 x 448mm (20-1/2" x 17-5/8")

Bowl sizes:

422mm (16-5/8") wide, 279mm (11") front to back, 143mm (5-5/8") deep





### COMPLIANCE CERTIFICATIONS -

Meets or exceeds the following Specifications:

- ASME A112.19.2M for Vitreous China Fixtures.
- · CAN/CSA B45 Series.

### To Be Specified ☐ Colour: ☐ White ☐ Bone ☐ Silver Gray ☐ Linen □ Faucet\*: □ Faucet Finish: Supplies & Stops: ☐ Trap 1-1/4" (32 mm):

NOTES:

\* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAP ARE SUGGESTED. FOR COUNTERTOP CUTOUT AND INSTALLATION INSTRUCTIONS USE TEMPLATE SUPPLIED WITH SINK.

SUPPLIED WITH SINK.

FAUCETS NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2.

These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

BAS-198 .

<sup>\*</sup> See faucet section for additional models available

Model: 20-1841 A ARLINGTON

## 22 of 38

## American Standard

Style That Works Better

### FloWise™ DUAL FLUSH **ELONGATED TOILET**

VITREOUS CHINA


### FloWise™ DUAL FLUSH ELONGATED TOILET

### **2476 216**

- Vitreous china
- · Low-consumption Dual Flush Full flush 6.0 Lpf/1.3 gpf, Partial flush 3.0 Lpf/0.66 gpf.
- · Elongated wash down bowl
- · Internal trapway fully-glazed, 2-1/4" (57mm) ballpass
- · Concealed trapway bowl
- · Chrome-plated top mounted push button actuator
- Easy to clean sanitary dam on bowl
- Includes Elongated Slow Close Seat
- 100% factory flush tested
- · 2 bolt caps

### **Separate Component Parts:**

- ☐ 3067 316 Elongated Bowl with Slow Close Seat
- **4035 216** Unlined Tank



- ☐ 3067 316 Elongated Bowl
- **4035 516** Lined Tank

Nominal Dimensions: 794 x 432 x 765mm (31-1/4" x 17" x 30-1/8")


### **Compliance Certifications -**Meets or Exceeds the Following Specifications:


- ASME A112.19.2M (and 19.6M)
- · CAN/CSA B45 series

### To Be Specified

- Colour: 020 White
- Supply with stop:







NOTES:
THIS TOILET IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12")
FROM FINISHED WALL TO C/L OF OUTLET.
SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.
\* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.
FOR ADDITIONAL INFORMATION REFER TO INSTALLATION INSTRUCTIONS SUPPLIED.
IMPORTANT. Dimensions of fixture are peripaid and may use within the prepare of the present

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2

established by Ankist damagna (112.19.2). These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

### UPGRADED VALUE ADDED FEATURES AT NO EXTRA CHARGE

TOI-284 © 2008 American Standard 08/08

Model: 20-1841 A ARLINGTON

## 23 of 38

## **MOEN**<sup>®</sup>

#### DESCRIPTION

- Metal construction with various finishes identified by suffix
- 16" long 3/8" tubing connections Includes metal or 50/50 pop-up type waste assembly where noted **OPERATION**
- Pivot action lever style handle Temperature controlled through 180° degree arc of handle travel **FLOW**

### Flow is limited to 1.5 gpm max (5.7L/min) at 60 psi

- CARTRIDGE
- 1225 cartridge design Nonmetallic/nonferrous and stainless steel material
- Can accommodate reversed piping and back to back installations


- Third party certified to WaterSense®, CSA B-125.1, ASME A112.18.1 and all applicable requirements referenced therein including NSF61/9
- Complies with California Proposition 65 and with the Federal Safe
- Drinking Water Act

  ADA for lever handle

#### WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original consumer purchaser
- 5 year warranty if used in commercial installations

## Specifications



**CHATEAU® Single-Handle Lavatory Faucet** 

### with Metal Waste Assembly Model: L4625 series L4631BC


**Bulk Packed (12 per carton):** L64624 series

with 50/50 Waste Assembly **Bulk Packed (12 per carton):** L64625 series

Less Waste **Bulk Packed (12 per carton):** L64600 series

**NOTE:** THIS FAUCET IS DESIGNED TO BE INSTALLED THRU 3-1" DIA. HOLES, 2" ON CENTER





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

Model: 20-1841 A ARLINGTON

# 24 of 38



Buy it for looks. Buy it for life.®

There is more than 1 version of this model. Page down to identify the version you have.

- Metal construction with various finishes identified by suffix
- Includes non-metalic showerhead, arm, flange and non-metalic diverter tub spout

### **OPERATION**

- Handle operates counterclockwise through a 270° arc with off at 6 o'clock and maximum hot at the 9 o'clock position. Shut off in clockwise direction
- Adjustable temperature limit stop to control maximum hot water temperature
- Pressure balancing mechanism maintains selected discharge temperature to  $\pm\,3^\circ$

- Showerhead is limited to 2.5 gpm (9.5 L/min) at 80 psi EP suffix models are limited to 1.75 gpm (6.6 L/min) at 80 psi
- NH suffix models contain no showerhead

### **CARTRIDGE**

- 1222 cartridge design Accommodates back to back installations
- Nonmetallic/nonferrous and stainless steel material

### **STANDARDS**

- Third party certified to meet ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein
- EP suffix models are third party certified to WaterSense®

### ADA ( for lever handle

### **WARRANTY**

- Lifetime limited warranty against leaks, drips and finish defects
- to the original consumer purchaser 5 year warranty if used in commercial installations

### **Specifications**







### CHATEAU° POSI-TEMP° Single-Handle Tub/Shower Trim Kit

Models: TL181 series - valve trim only (Bulk Packed 12 per carton) TL182 series - shower trim only

(Bulk Packed 12 per carton) TL183 series - tub/shower trim (Bulk Packed 12 per carton)

Valves: 62300 series 2500 series





2"CC (51mm) 1 7/8" IPS (48mm) MAX WALL

FINISHED WALL LINE

7-1/2" (190mm)

**CRITICAL DIMENSIONS** 

— 1/2" MIN. CC (13mm) 5/8" MIN. IPS (16mm)

(DO NOT SCALE)

FOR MORE INFORMATION CALL: 1-800-BUY-MOEN

www.moen.com

TL183sp: Rev. 5/13

Model: 20-1841 A ARLINGTON

## 25 of 38







180 CFM/7.0 Sones @ 0.10" SP. Horizontal 180 CFM/7.5 Sones @ 0.10" SP. Vertical

### • **Dimensions**

Overall bottom projection - 18<sup>3</sup>/8"
Overall top projection -12"
Height - 6"

Available widths: 21", 24", 30", 36" & 42"

### Hood Body

Stainless Steel: 24 gauge, grade 430 stainless steel.

Painted: 23 gauge cold rolled commercial grade (CRCQ) steel, auto welded, coated with a baked enamel finish.

#### Motor

2 speed, single coil, thermally protected, permanently lubricated. Rated 120 volts, 60 hz. Complete with 200°C lead wires.

### Lighting

Single 60 watt cook light capacity (bulb not included).

### • **Ducting Options**


Horizontal ducting: 31/4"x10" (duct adapter and damper included). Vertical ducting: 31/4"x10" (duct adapter and damper included). Vertical ducting: 7" round (duct adapter and damper not included). Ductless: removable front vent (charcoal filter not included).

### Fan Blade


One piece polymeric, electronically balanced blade.  $6^{5/8}^{\shortparallel}$  diameter with 5 paddles.

### • Electrical connection

Hood top - 7/8" knockout hole for use with 1/2" cable clamp Hood back - 7/8" knockout hole for use with 1/2" cable clamp



### **AV SERIES**



### • Filters

UL rated, class 2 filter. Grease Filter: RF35 - 87/8"x103/8" (included). Charcoal Filter: RF34 (not included). Combo Grease/Charcoal: RF55 (not included).

### Available Finishes

White, Biscuit, Almond, Black & Stainless Steel.

EXPANDED PERFORMANCE											
		Stati	c Pressure	e (inches d	of w.g.)		Sones	Fan Speed	Power		
Air Flow - CFM	0	0.05	0.1	0.15	0.2	0.25	@ .1 SP	RPM	Watts	Apms	
Vertical Ducting High	246	232	218	203	181	147	7.5	2973	87.0	2.1	
Horizontal Ducting High	225	210	180	175	155	120	7.0	3024	87.0	2.1	

PROJECT							ARCHITEC	T		
LOCATION						ENGINEER				
CONTRACT	ΓOR						SUBMITT	ED BY		DATE
FAN Number i	MODEL Number	CFM	IN W.C.	RPM	WATTS	AMPS	SONES	QTY		EQUIPMENT Marks





**Air King:** 820 Lincoln Avenue West Chester, Pennsylvania 19380-4466 Tel: (610) 692-7400 • 877-304-3785 Fax: (610) 696-8048 Canada: Brampton, Ontario Tel: 905-456-2033 Fax: (905) 456-1015

Model: 20-1841 A ARLINGTON

## 26 of 38



# Whirtpool® 21 cu. ft. Top-Freezer Refrigerator WRT541SZD



Fingerprint-Resistant Stainless WRT541SZDZ

### Also available in:

White	WRT541SZDW
Black	WRT541SZDB
Monochromatic Stainless Steel	WRT541SZDM

Capacity						
Total Capacity	21 cu. ft.					
Refrigerator Capacity	15 cu. ft.					
Freezer Capacity	6 cu. ft.					
General Features & Properti	es					
EZ Connect Icemaker Kit						
LED Interior Lighting						
ENERGY STAR® Certified						
Electronic Temperature Co	ntrols					
Freezer Temperature Contr	ols					
Clear Door Bins						
Adjustable Door Bins						
Quiet Cooling						
Fingerprint Resistant						
Electrical Details						
Amps	6.5					
Volts 115						
Certifications						
ADA Compliant	Yes					
ENERGY STAR® Certified	Yes					

Technical Details	
Refrigerator Type	Top-Freezer
Number of Doors	2
Number of Interior Refrigerator Shelves	3
Number of Refrigerator Door Bins	1 Fixed, 4 Adjustable
Number of Interior Freezer Shelves	1
Number of Freezer Door Bins	2 Fixed
Lighting Type	LED
Ice Maker	Optional
Ice Maker Location	Freezer
Dispenser Type	N/A
Dimensions	
Product Dimensions (H x W x D)	66-1/4" x 32-3/4" x 34"
Depth with Door Open 90°	62-1/4"
Cutout Dimensions	Allow extra 1/2" on sides and top Allow extra 1" on rear
Reference Material	

### Key Features & Benefits

### Frameless Glass Shelves


Store more items on wall-to-wall shelves for greater storage flexibility.

### Flexi-Slide™ Bin

Make space for tall items with the bin that quickly and easily moves side to side.

### **Humidity-Controlled Crispers**

Store fruits and vegetables in their ideal environment.



**Dimension Guide** Use & Care Guide

**Energy Guide** 

NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXC. WRT541SZDSPECSHEETV01.

Model: 20-1841 A ARLINGTON

## 27 of 38



### **Top Mount Refrigerator**

#### **PRODUCT MODEL NUMBERS**

WRT311FZD WRT511SZD WRT541SZD

**Electrical:** A 115-volt, 60-Hz, AC-only, 15-or 20-amp fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.


NOTE: Before performing any type of installation, cleaning, or removing a light bulb, turn the control (Thermostat, Refrigerator or Freezer Control depending on the model) to OFF and then disconnect the refrigerator from the electrical source. When you are finished, reconnect the refrigerator to the electrical source and reset the control (Thermostat, Refrigerator or Freezer Control depending on the model) to the desired setting. See "Using the Controls."

**Water:** A cold water supply with water pressure between 30 and 120 psi (207 and 827 kPa) is required to operate ice maker and water dispenser. If you have questions about your water pressure, call a licensed, qualified plumber.

**IMPORTANT:** The pressure of the water coming out of a reverse osmosis system going to the water inlet valve of the refrigerator needs to be between 30 and 120 psi (207 and 827 kPa).


**Reverse Osmosis Water Supply:** If a reverse osmosis water filtration system is connected to your cold water supply, the water pressure to the reverse osmosis system needs to be a minimum of 40 to 60 psi (276 to 414 kPa).

#### PRODUCT DIMENSIONS



Model Number	Model Size	Reversible Door	Height - Overall "A"	Height - Top of Cabinet "B"	Depth - Door Open 90° "C"	Depth - With Handles "D"	Depth - Without Handles "E"	Depth - Cabinet Only "F"	Width - Cabinet "G"
WRT311FZD	20.5 cu. ft.	Yes	661/4" (168.3 cm)	65½" (166.4 cm)	62½" (158.1 cm)	32 <sup>7</sup> / <sub>8</sub> " (83.5 cm)	30 <sup>5</sup> / <sub>8</sub> " (77.8 cm)	28½" (72.4 cm)	32¾" (83.2 cm)
WRT511SZD WRT541SZD	21.3 cu. ft.	Yes	661/4" (168.3 cm)	65½" (166.4 cm)	62¼" (158.1 cm)	34" (86.4 cm)	32½" (82.3 cm)	28½" (72.4 cm)	32¾" (83.2 cm)

### LOCATION REQUIREMENTS



To ensure proper ventilation for your refrigerator, allow for a  $\frac{1}{2}$ " (1.25 cm) space on each and between overhead cabinets and refrigerator top. Allow at least 1" (2.5 cm) between back of cabinet and the wall. If your refrigerator has an ice maker, make sure you leave some extra space at the back for the water line connections.

If you are installing your refrigerator next to a fixed wall, leave  $2^{\prime\prime}$  (5 cm) minimum on the hinge side (depending on your model) to allow for the door to swing open.

**NOTE:** This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.

Model: 20-1841 A ARLINGTON

## 28 of 38





#### Available Finishes/Colours



YWFE515S0JB Black



YWFF515S0JS Stainless Steel



YWFE515S0JW White

#### Manuals & Literature:





Use and Care

### <u> Warranty</u>

### 5.3 cu. ft. Whirlpool® electric range with Frozen Bake™ technology

### YWFE515S0JS

This Whirlpool® electric range with a dual element stove top helps you get dinner to the table. Skip preheating for favorites like pizza with Frozen Bake™ technology. This self cleaning oven also prevents cooked food from getting cold with the Keep Warm setting. Closed door broiling helps keep the kitchen comfortable.

#### **Top Features**

### FlexHeat™ Dual Radiant Element

Get two elements in one with a 6" inner ring that's great for smaller pots and pans and a 9" expandable outer ring that makes room for larger cookware.

Frozen Bake™ technology
Skip preheating and cook frozen favorites like pizza in fewer steps with preprogrammed settings that automatically adjust cooking times for you.

#### Keep Warm setting

Keep dishes from getting cold with this setting that delivers low heat to the oven.

Closed Door Broiling
Maintain the optimal cooking temperature for food while still keeping the kitchen comfortable and cool using this broiling temperature management system that helps prevent overheating.

**Exterior** 

Dimensions	
Depth	27 3/4
Height	36
Width	29 7/8

Configuration and Overview		
Range Type	Freestanding	
Fuel Type	Electric	
Size (IN,inches)	30	

Exterior	
Door Removable	Yes
Drawer Type	Storage Drawer
Oven Door	Glass Window
Oven Window Size	Extra Large
Handle Color	Stainless Steel
Handle Material	Metal

Handle Type	Reach-Through Handle
Features	
Hot Surface Indicator Light	Yes
Heating Element On Indicator Light	Yes
Power On Indicator Light	No
Griddle	NA
Automatic Convection Conversion Temperature Adjust	No
Power Outage Compatible	No


### CANADIAN APPLIANCE SOURCE LP

Model: 20-1841 A ARLINGTON

# 29 of 38

## WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

### **Product Dimensions**



- A. 273/4" (70.5 cm) max. depth with handle
- B. 46<sup>7</sup>/<sub>8</sub>" (119.1 cm) overall height (max.) with leveling legs screwed all the way in\*
- C. 36" (91.4 cm) cooktop height (max.) with leveling legs screwed all the way in\*
- D. 29<sup>7</sup>/<sub>8</sub>" (75.9 cm) width
- E. 255/16" (64.3 cm) depth back of range to front of cooktop\*\*
- F. Model/serial/rating plate (located on the frame behind a top corner of the door or either side of the drawer)

**IMPORTANT:** Range must be level after installation. Follow the instructions in the "Level Range" section. Using the cooktop as a reference for leveling the range is not recommended.


- \*Range can be raised approximately 1" (2.5 cm) by adjusting the leveling legs.
- \*\*Front of door and drawer may extend further forward depending on styling.

### **Cabinet Dimensions**

Cabinet opening dimensions shown are for 25" (64.0 cm) countertop depth, 24" (61.0 cm) base cabinet depth and 36" (91.4 cm) countertop height.

**IMPORTANT:** If installing a range hood or microwave hood combination above the cooking surface, follow the range hood or microwave hood combination installation instructions for dimensional clearances above the cooktop surface.

A freestanding range may be installed next to combustible walls with zero clearance.



- A. 13" (33.0 cm) max. upper cabinet depth
- B. 30" (76.2 cm) min. opening width
- C. For minimum clearance to top of cooktop, see NOTE\*
- D. 30" (76.2 cm) min. opening width
- E. Outlet 8" (20.3 cm) to 22" (55.9 cm) from either cabinet, 7" (17.8 cm) max. from floor.
- F. Cabinet door or hinges should not extend into the cutout.

\*NOTE: 24" (61.0 cm) minimum when bottom of wood or metal cabinet is covered by not less than 1/4" (6.4 mm) flame retardant millboard covered with not less than No. 28 MSG sheet steel, 0.015" (0.4 mm) stainless steel, 0.024" (0.6 mm) aluminum or 0.020" (0.5 mm) copper.

30" (76.2 cm) minimum clearance between the top of the cooking platform and the bottom of an uncovered wood or metal cabinet.

Model: 20-1841 A ARLINGTON

# 30 of 38

## WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

**Electrical Requirements - Canada Only** 

### AWARNING



**Electrical Shock Hazard** 

Electrically ground range.

Failure to do so can result in death, fire, or electrical shock.

If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path is adequate and wire gauge are in accordance with local codes.

Be sure that the electrical connection and wire size are adequate and in conformance with CSA Standard C22.1, Canadian Electrical Code, Part 1 - latest edition, and all local codes and ordinances.

A copy of the above code standards can be obtained from:

Canadian Standards Association 178 Rexdale Blvd. Toronto, ON M9W 1R3 CANADA

 Check with a qualified electrical installer if you are not sure the range is properly grounded.

Range Rating*		Specified Rating of Power Supply Cord Kit and Circuit Protection
120/240 V	120/208 V	Amps
8.8 - 16.5 KW 16.6 - 22.5 KW	7.8 - 12.5 KW 12.6 - 18.5 KW	40 or 50** 50

<sup>\*</sup>The NEC calculated load is less than the total connected load listed on the model/serial/rating plate.

- A time-delay fuse or circuit breaker is recommended.
- This range is equipped with a CSA International Certified Power Cord intended to be plugged into a standard 14-50R wall receptacle. Be sure the wall receptacle is within reach of range's final location.



Do not use an extension cord.

### **INSTALLATION INSTRUCTIONS**


**Unpack Range** 

### AWARNING

**Excessive Weight Hazard** 

Use two or more people to move and install range. Failure to do so can result in back or other injury.


- 1. Remove shipping materials, tape and film from range.
- 2. Remove oven racks and parts package from inside oven.
- 3. Do not remove the shipping base at this time.



A. Shipping base

### 4. On Ranges Equipped with a Storage Drawer:


Remove the storage drawer. See the "Storage Drawer" section. Use a 1/4" (6.4 mm) drive ratchet to lower the rear leveling legs one-half turn. Use a wrench or pliers to lower front leveling legs one-half turn.



- A. 1/4" (6.4 mm) drive ratchet
- B. Rear leveling leg
- C. Wrench or pliers
- D. Front leveling leg

### On Ranges Equipped with a Warming Drawer or Premium Storage Drawer:

On ranges equipped with a warming drawer or premium storage drawer, the rear legs cannot be accessed by removing the warming drawer or premium storage drawer. It will be necessary to adjust the rear legs from outside the range. Use wrench or pliers to lower the front and rear leveling legs one half turn.



- A. Rear leveling leg
- B. Wrench or pliers
- C. Front leveling leg

<sup>\*\*</sup>If connecting to a 50 A circuit, use a 50 A rated cord with kit. For 50 A rated cord kits, use kits that specify use with a nominal 13/8" (3.5 cm) diameter connection opening.

Model: 20-1841 A ARLINGTON

## 31 of 38

## WHIRLPOOL 30" (76.0 CM) FREESTANDING ELECTRIC RANGES Model YWFE515S0JS

### **Install Anti-Tip Bracket**

## AWARNING



**Tip Over Hazard** 

A child or adult can tip the range and be killed.

Install anti-tip bracket to floor or wall per installation instructions.

Slide range back so rear range foot is engaged in the slot of the anti-tip bracket.


Re-engage anti-tip bracket if range is moved.

Do not operate range without anti-tip bracket installed and engaged.

Failure to follow these instructions can result in death or serious burns to children and adults.

- Remove the anti-tip bracket from where it is taped inside the storage drawer or warming drawer.
- 2. Determine which mounting method to use: floor or wall.


  If you have a stone or masonry floor, you can use the wall mounting method. If you are installing the range in a mobile home, you must secure the range to the floor.
- 3. Determine and mark centerline of the cutout space. The mounting can be installed on either the left-side or right-side of the cutout. Position mounting bracket against the wall in the cutout so that the V-notch of the bracket is 129/16" (31.9 cm) from centerline as shown.



A. 129/16" (31.9 cm) B. Bracket V-notch

 Drill two 1/8" (3 mm) holes that correspond to the bracket holes of the determined mounting method. See the following illustrations.

### Floor Mounting



#### **Wall Mounting**



- 5. Using the Phillips screwdriver, mount anti-tip bracket to the wall or floor with the two  $\#12 \times 1^5/8$ " (4.1 cm) screws provided.
- **6.** Move range close enough to opening to allow for final electrical connections. Remove shipping base, cardboard or hardboard from under range.
- 7. Move range into its final location, making sure rear leveling leg slides into anti-tip bracket.



**8.** Move range forward onto shipping base, cardboard or hardboard to continue installing the range using the following installation instructions.

Model: 20-1841 A ARLINGTON

## 32 of 38



# Whirlpool® 55 dBA\* Front Control Dishwasher WDF330PAH



Stainless Steel

### Also available in:

White	WDF330PAHW
Black	WDF330PAHB

Capacity		
Total Place Settings	13	
General Features & Properties		
Heavy Cycle		
High Temperature Wash Option		
Heated Dry Option		
ENERGY STAR® Certified		
Industry's Best Selling Dishwasher Brand <sup>†</sup>		
Designed, Engineered and Assembled in the U.S.A. with American Pride		
Electrical Details		
Amps	10	
Volts	120	
Hz	60	
Certifications		
ENERGY STAR® Certified	Yes	

Technical Details	
Dishwasher Type	Built-in
Control Location	Front
Control Type	Push Button
Number of Wash Cycles	3
Number of Options	4
dBA <sup>*</sup>	55
Number of Racks	2
Tub Material	Plastic
Wash System	Filter
Wash System Type	Removable Filter
Number of Wash Arms	2
Dimensions	
Product Dimensions (H x W x D)	34-1/2" x 23-7/8" x 24-1/2"
Depth with Door Open 90°	49-1/2"
Poforonco Matorial	

### Reference Material

**Dimension Guide** 

Install Guide

Use & Care Guide

**Energy Guide** 

Warranty

### Key Features & Benefits

### 1-Hour Wash Cycle


Clean dishes in half the time so your plates, pans and glasses are thoroughly cleaned up and taken care of in just an hour.\*

### Soil Sensor

Determines how dirty dishes are and adjusts the Normal cycle as needed to make sure dishes come out clean.

### **Normal Cycle**

Use for normal amounts of food soil to clean up leftover messes from your day-to-day meals.



<sup>\*</sup>Per IEC standards. \*\*Compared to Normal cycle with lightly soiled loads. †Based on 12-month average of sales. TraQline 2018. NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice. 

®/™ © 2020. All rights reserved. Printed in the U.S.A. D200052XXA. WDF330PAHSPECSHEETV01.

Model: 20-1841 A ARLINGTON

# 33 of 38




### **Undercounter Dishwasher**

### PRODUCT MODEL NUMBERS

WDF110PAB	WDF320PAD	WDT710PAH
WDF111PAB	WDF330PAH	WDT720PAD
WDF120PAF	WDF331PAH	WDT730PAH
WDF121PAF	WDF520PAD	WDT735PAG
WDF130PAH	WDF540PAD	WDT735PAH
WDE121DAL	WDESAEDAE	

#### DRAIN REQUIREMENTS

- A new drain hose is supplied with your dishwasher. If drain hose is not long enough, use a new drain hose with a maximum length of 12 ft (3.7 m) that meets all current AHAM/IAPMO test standards, is resistant to heat and detergent, and fits the 1" (25 mm) drain connector of the dishwasher. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Make sure to connect drain hose to waste tee or disposer inlet above drain trap in house plumbing and 20" (508 mm) minimum above the floor. It is recommended that the drain hose either be looped up and securely fastened to the underside of the counter or be connected to an air gap.
- Make sure to use an air gap if the drain hose is connected to house plumbing lower than 20" (508 mm) above subfloor or floor.



- If required, the air gap should be installed in accordance with the air gap installation instructions. When you are connecting the air gap, a rubber hose (not provided) will be needed to connect to the waste tee or disposer inlet.
- Use 1/2" minimum I.D. drain line fittings.

### WATER SUPPLY REQUIREMENTS

- This dishwasher has a water heating feature and also requires a connection to a hot water supply line.
- A hot water line with 20 to 120 psi (138 to 862 kPa) water pressure can be verified by a licensed plumber.
- 120°F (49°C) water at dishwasher
- ³/8" O.D. copper tubing with compression fitting or flexible braided water supply line. See the "Tools and Parts" section at the front of the guide for part details and orders.

NOTE: 1/2" minimum plastic tubing is not recommended.

- A 90° elbow with ³/₄" hose connection with rubber washer. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Do not solder within 6" (152 mm) of the water inlet valve.
- If installed in new construction, make sure the house water supply lines have been flushed prior to connecting the dishwasher to remove any debris that may exist in the supply line.

**NOTE:** If replacing an existing dishwasher, it is recommended to install a new water line (see the "Tools and Parts" section at the front of the guide for part details) and drain hose (supplied) with the new dishwasher.

### **ELECTRICAL REQUIREMENTS**

### You Must Have:


- 120-volt, 60 Hz, AC-only, 15- or 20-amp, fused electrical supply
- Copper wire only
- A maximum of 2 field wiring supply conductors (12 AWG largest size) plus 1 grounding conductor are permitted in the terminal box.

We Recommend:

- A time-delay fuse or circuit breaker
- A separate circuit

### If Connecting Dishwasher with a Power Cord:

- Use a UL Listed power cord kit marked for use with dishwasher. See the "Tools and Parts" section at the front of the guide for part details and orders.
- Plug into a grounded 3 prong outlet. Outlet must meet all local codes and ordinances.



### If Connecting Dishwasher with Direct Wiring:

- Use flexible, armored, or nonmetallic sheathed copper wire with grounding wire that meets the wiring requirements for your home and local codes and ordinances.
- Use a UL Listed/CSA Approved metallic strain relief.

Model: 20-1841 A ARLINGTON


### PRODUCT AND CABINET OPENING DIMENSIONS — 23<sup>7</sup>/8" -(606 mm) — 25¹/₄" -(641 mm) — ³/₄" (19 mm) 30" (762 mm) 331/2" 301 (851 mm) min. with (762 mm) leveling legs removed **4**−3³/₄" (94 mm) 31/2" - 41/2" (88 mm - 106 mm) (533 mm) For 4" (100 mm) toe kick, height of cabinet opening is 341/2" (863 mm). A. Insulation may be compressed (not used on all models). B. Door handles may protrude forward of the face of the dishwasher, (varies by model). Check that all surfaces have no protrusions that would prohibit dishwasher installation. 101/2" NOTE: Shaded areas (864 mm) of cabinet walls show where utility -6<sup>3</sup>/<sub>4</sub>" (102 mm) (172 mm) connections may be installed. (76 mm (159 mm) 2<sup>1</sup>/<sub>4</sub>" (64 mm) 24" / (620 mm) (44 mm) 2" (51 mm) 24' (620 mm) D C. Measured from the lowest point on the underside of the countertop. May be reduced to 33<sup>1</sup>/<sub>2</sub>" (851 mm) by removing the wheels and perforated area of insulation (blanket) on dishwasher. D. Minimum, measured from narrowest point of opening.

Model: 20-1841 A ARLINGTON

# 35 of 38

### 5.0 cu.ft I.E.C. Closet-Depth Front Load Washer with Intuitive Controls

Model: WFW560CHW



### **Specifications**

### Width: 6858.00, 27.0" Centimeters, Inches

### Depth: 8016.88, 31-9/16" Centimeters, Inches


Dimensions	
Capacity	4-3/10
Depth	8016.88 cm, 31-9/16 in
Gross Weight	97068688.00 kg, 214 lbs
Net Weight	92532768.00 kg, 204 lbs
width Appearance	6858.00 cm, 27.0 in
LCD Touch Screen	No
Window	Yes
Details	
Advanced Vibration Control™	No
Dispense System	Detergent, Fabric Softener & Bleach
Eco Monitor/Efficiency Monitor	No
Hoses Included	4ft 4in Drain Hose Included
Internal Heater	No
Maximum Spin Speed	1160
Out Of Balance Sensing	Yes
Water Factor	3-1/5
Cycles and Options	
Number Of Wash Cycles	35
Electrical	
Power Cord Included	Yes
Controls	
Automatic Temperature Controls	Yes
Control Location	Front
LCD Touch Screen	No

### Compatibility Works With No **Options** Number Of Washer Options **Features** Stackable Yes Water Faucet No Cycles Number Of Wash Cycles 35 Exterior Lid/Door Lock Yes Lid/Door Swing Left Modifiers Delay Start No Number Of Rinse Options Number Of Soil Levels 3 Number Of Spin Speeds Number Of Wash/Rinse Temperatures 4 Pre Soak Yes Temperature Selections Hot, Cold, Cool, Warm


Model: 20-1841 A ARLINGTON

# 36 of 38


## Recessed area or closet installation (stacked washer and dryer)




### **Custom under counter installation**



### Recessed area or closet installation (washer only)



### **Custom cabinet installation**




### **Drain System**

It is the responsibility of the installer to install and secure the drain hose in to the provided plumbing/drain in a manner that will avoid the drain hose coming out of o leaking from the plumbing/drain.

Drain system can be installed using a floor drain, wall standpipe, floor standpipe, or laundry tub. Select the method you need.

**IMPORTANT:** To avoid siphoning, only 4.5" (114 mm) of drain hose should be inside standpipe. Always secure drain hose with cable tie.

### Floor standpipe drain system




Minimum diameter for a standpipe drain: 2" (51 mm). Minimum carry-away capacity: 17 gallons (64 L) per minute. A 1/4" (6 mm) diameter to 1" (25 mm) diameter Standpipe Adapter Kit is available; refer to the Quick Start Guide for online ordering information. Top of standpipe must be at least 39" (762 mm) high; install no higher than 96" (2.4 m) from bottom of washer. If you have an overhead sewer and need to pump higher than 96" (2.4 m), a sump pump and associated hardware are needed. See "Alternate Parts"

Model: 20-1841 A ARLINGTON


# 37 of 38

### Wall standpipe drain system




See requirements in "Floor standpipe drain system."


### Laundry tub drain system



Minimum capacity: 20 gallons (76 L). Top of laundry tub must be at least 39" (991 mm) from the floor; install no higher than 96" (2.4 m) from bottom of washer.



### Floor drain system



Floor drain system requires a Siphon Break Kit, 2 Connector Kits, and an Extension Drain Hose that may be purchased separately; refer to the Quick Start Guide for online ordering information. Minimum siphon break height: 28" (710 mm) from bottom of washer. (Additional hoses may be needed.)

### **Electrical Requirements**

### AWARNING



#### **Electrical Shock Hazard**

Plug into a grounded 3 prong outlet.

Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire, or electrical shock.

- A 120 V, 60 Hz, AC only, 15 or 20 A, fused electrical supply is required. A time-delay fuse or circuit breaker is recommended. It is recommended that a separate circuit breaker serving only this appliance be provided.
- This washer is equipped with a power supply cord having a 3-prong grounding plug.
- To minimize possible shock hazard, the cord must be plugged into a mating, 3-prong, grounding-type outlet, grounded in accordance with local codes and ordinances. If a mating outlet is not available, it is the personal responsibility and obligation of the customer to have the properly grounded outlet installed by a qualified electrician.
- If codes permit and a separate ground wire is used, it is recommended that a qualified electrician determine that the ground path is adequate.
- Do not ground to a gas pipe.
- Check with a qualified electrician if you are not sure the washer is properly grounded.
- Do not have a fuse in the neutral or ground circuit.

### **GROUNDING INSTRUCTIONS**

### For a grounded, cord-connected appliance:

This appliance must be grounded. In the event of a malfunction or breakdown, grounding will reduce the risk of electric shock by providing a path of least resistance for electric current. This appliance is equipped with a cord having an equipment-grounding conductor and a grounding plug. The plug must be plugged into an appropriate outlet that is properly installed and grounded in accordance with all local codes and ordinances.

**WARNING:** Improper connection of the equipment-grounding conductor can result in a risk of electric shock. Check with a qualified electrician or serviceman if you are in doubt as to whether the appliance is properly grounded. Do not modify the plug provided with the appliance: If it will not fit the outlet, have a proper outlet installed by a qualified electrician.

### For a permanently connected appliance:

This appliance must be connected to a grounded metal, permanent wiring system, or an equipment-grounding conductor must be run with the circuit conductors and connected to the equipment-grounding terminal or lead on the appliance.

### **SAVE THESE INSTRUCTIONS**

Model: 20-1841 A ARLINGTON

38 of 38

### WHIRLPOOL DRYER Model #: YWED5620HW



7.4 cu. ft. Front Load Electric **Dryer with Intuitive Touch** Controls



Power Cord Included

7.4 cu. ft. Front Load Electric Dryer with Intuitive Touch Controls

Model #: YWED5620HW

Dimensions	
Depth	78.74 cm, 31.0 in
Depth With Door Open 90 Degree	138.43 cm, 54-1/2 in
Height	98.42 cm, 38-3/4 in
Width	68.58 cm, 27.0 in
Configuration and Overview	
Fuel Type	Electric
Cycles and Options	
Cycle Time Remaining	Yes
Lint Filter Indicator	No
Number of Dryer Cycles	36
Number of Dryness Levels	3
Ventilation System	
Long Vent	No
Maximum Vent Length	64
Venting Direction	Left, Right, Bottom, Rear
Electrical	
Hz	60

Yes