Sales Selection Sheet Checklist

Model: 39-3573 A The Cedarvale

LOT 733

1 of 87

PURCHASERS: SENTA, KRISTINA PELTEKOFFI Heathwood Homes (Whitby) Limited VENDOR: V-1 FINISHED BASEMENT WAFFLE CEILING IN GREAT ROOM STACKED UPPERS IN KITCHEN AND SERVERY WOB DECK UPGRADED / MODIFIED ELEVATION **CORNER UPGRADE** 1 REAR UPGRADE **CEILING UPGRADE - SMOOTH** MAIN FLOOR (STD) 1 SECOND FLOOR WITH RESILIENCE CHANEL 1 LOWER LEVEL ADDITIONAL ROUGH-INS 200 AMP SERVICE (STD) WET BAR ROUGH-IN **HUMIDIFIER (STD)** AIR CONDITIONING (STD) GAS ROUGH-IN STOVE DRYER **BBQ** ADDITIONAL GAS FIREPLACE KITCHEN HOODFAN VENTING SIZE 6 IN ROUND DUCT (STD WITH APPLIANCE PACKAGE) 7 IN ROUND DUCT **FULL LOWER LEVEL STAIRS** N/A UPPER LOWER LEVEL STAIRS All Oak LOWER LOWER LEVEL STAIRS All Oak MAIN STAIRS All Oak **Decor Consultant:** A PACE 13 2024 Date Purchaser: Heathwood Homes (Whitby) Limited Date Approved Locked Date:

SENTA, KRISTINA PELTEKOFF/

Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale

2 from 710 8 7

Locked: Closed:

chen/Breakfast		*	
Cabinet Colour/Style	6469	Classic II-MANCHESTER-WINTER WHITE-PAINT MDF ***UPG***	
Island Cabinet Colour/Style	6467	Classic II-MANCHESTER-MACADAMIA-PAINT MDF ***UPG***	
Cabinet Hardware	7676	12843-HARDWARE ***STD***	ĺ
Countertop	8897	Group 4-Quartz-Caesarstone-ORGANIC WHITE # 4600-3/4 inch with built-up edge ***4***	
Island Countertop	8897	Group 4-Quartz-Caesarstone-ORGANIC WHITE # 4600-3/4 inch with built-up edge ***4***	
Countertop Edge	4005	DOUBLE MITRE 1 1/2 INCH ***UPG***	ĺ
Sink	9493	BLANCO QUATRUS U 1 SUPER SINGLE 401248 (min cabinet 36 in)	PG
Crumb Vac Color	9482	Vacuum-Crumb Vac (Dust Pan)-White	
HoodFan	8910	KVWB606DSS-KITCHEN AID 36 inch STAINLESS CHIMNEY HOOD-STAINLESS STEEL-36 inch ***Upg***	PG
Backsplash	9469	KD.OC.PRL.2,5 X 10-Oceani Series-Pearl Glossy-2,5 x 10 UPG 3 ***UPG***	
Backsplash Grout	9837	Grout-Warm Grey #5093 ***STD***]
Backsplash Tile Pattern	3060	HORIZONTAL BRICK ***STD***	ĺ
Flooring	8497	Red Oak UVF-Vintage Red Oak Solid Sculpted Character UVF-HILLSIDE-3/4 inch X 5 inch ***(STD***	
Floor Tile Grout	1111	N/A *****	1
Floor Tile Pattern	1111	N/A *****	

- Purchasers have been advised: standard fridge opening is a minimum $37\ 3/8\ x\ 73\ 3/8$ inches. Ice Waterline Rough-In is included.
- Standard stove opening is 30 inches and standard dishwasher opening is 24 inches. Any gas stove will require backsplash or stainless steel backing to avoid fire hazards.
- Purchasers acknowledge: Heathwood Homes and its contractors will not be responsible for any kitchen cabinet changes due to appliances dimension changes after sign-off.

Comment	

ervery		
Cabinet Colour/Style (including upper	s 63467	Classic II-MANCHESTER-MACADAMIA-PAINT MDF ***UPG***
Cabinet Hardware (including uppers)	7676	12843-HARDWARE ***STD***
Countertop	8897	Group 4-Quartz-Caesarstone-ORGANIC WHITE # 4600-3/4 inch with built-up edge ***4***
ige 1 of 9	100F	DOUBLE MITDE 4.4/2 INCH ***I IDC***



SENTA, KRISTINA PELTEKOFF/ Project: Country Lane Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

Locked:

C	OS	ed
	00	Cu

Countertop ⊏age	4000	DOUBLE WITTRE I 1/2 INCH UPG
Opt. Backsplash	9469	KD.OC.PRL.2,5 X 10-Oceani Series-Pearl Glossy-2,5 x 10
ора Васкоріазії	0403	UPG 3 ***UPG***
Opt. Backsplash Grout	9837	Grout-Warm Grey #5093 ***STD***
Opt. Backsplash Tile Pattern	3060	HORIZONTAL BRICK ***STD***
	5000	
Flooring	8497	Red Oak UVF-Vintage Red Oak Solid Sculpted Character UVF-HILLSIDE-3/4 inch X 5 inch ***STD***
Floor Tile Grout	1111	N/A *****
Floor Tile Pattern	1111	N/A *****
yer		
Flooring	8252	NY.RG.CCB.1224.MT-Regal-Matte Charcoal Black-12 x 24 See Tile Direction on Sketch Page ***4***
Floor Tile Grout	9845	Grout-Charcoal #5047 ***UPG***
Floor Tile Pattern	3050	SIDE TO SIDE ***STD***
Comment		
wder Room		
Flooring	8862	MC.MR.IVO.10HEX-Merino-Ivory-10 inch HEX ***7***
Floor Tile Grout	9838	Grout-Bone #5015 ***STD***
Floor Tile Pattern	3120	VERTICAL HEX ***STD***
Plumbing Fixture (Colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment		



Customer Colours SENTA, KRISTINA PELTEKOFF/ Country Lane 733, Phase: 7 Locked: Model: 39-3573 A The Cedarvale Closed: **Dining Room** Red Oak UVF-Vintage Red Oak Solid Sculpted Character Flooring 8497 UVF-HILLSIDE-3/4 inch X 5 inch *** STD*** Comment **Great Room** 8497 Red Oak UVF-Vintage Red Oak Solid Sculpted Character Flooring UVF-HILLSIDE-3/4 inch X 5 inch *** STD** Comment **Great Room Fireplace** Type 8869 Majestic MERC32 ***STD*** NF 17-Paint Grade Mantle-Flat Wall-WHITE ***STD*** Mantle 1439 PG 42 Surround (STD) 8875 3 pc- 4 inch Marble Surround-Bianca Carrara ***STD*** - Purchasers have been advised: heat from the FP can damage TV above a FP and items placed on mantle. - Heathwood and its contractors will not be liable for any damage on items placed/@installed above a FP after closing. BUILT UP WALL ABOVE FIRE PLACE Comment **Living Room** Red Oak UVF-Vintage Red Oak Solid Sculpted Character Flooring 8497 UVF-HILLSIDE-3/4 inch X 5 inch ***STD** Comment **Mud Room** NY.RG.CCB.1224.MT-Regal-Matte Charcoal Black-12 x 24 See Tile Direction on Sketch Page ***4*** Flooring 8252 Floor Tile Grout 9845 Grout-Charcoal #5047 ***UPG*** Floor Tile Pattern 3050 SIDE TO SIDE ***STD*** Comment Main Hall Red Oak UVF-Vintage Red Oak Solid Sculpted Character UVF-HILLSIDE-3/4 inch X 5 inch ***1STD*** Flooring 8497 Comment Page 3 of 9



Customer Colours SENTA, KRISTINA PELTEKOFF/ Country Lane Locked: 733, Phase: 7 Model: 39-3573 A The Cedarvale Closed: Upper Hall Flooring 8497 Red Oak UVF-Vintage Red Oak Solid Sculpted Character UVF-HILLSIDE-3/4 inch X 5 inch *** STD** Comment **Master Bedroom** Red Oak UVF-Vintage Red Oak Solid Sculpted Character 8497 Flooring UVF-HILLSIDE-3/4 inch X 5 inch ***STD** Comment Bedroom 2 87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Flooring 9504 Comment Bedroom 3 Flooring 9504 87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Comment Bedroom 4 87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Flooring 9504 Comment **Master Ensuite** Cabinet Colour/Style 9205 Classic II-MANCHESTER-MOONLIGHT-PAINT MDF ***UPG*** Cabinet Hardware 7676 12843-HARDWARE ***STD*** Group 1-Quartz-Caesarstone-WHITE SAND # 7041- 3/4 inch B/U MITERED EDGE ***UPG*** Countertop 9810 GROUP 1 - DOUBLE MITRE 1 1/2 INCH ***2*** Countertop Edge 4006 Floor Tile 9056 OV.ET.IGY.2424.PL-Eterna-Imperial Grey Polished-24 x 24 Floor Tile Grout 9837 Grout-Warm Grey #5093 ***STD***

Floor Tile Pattern

Page 4 of 9

3000

STANDARD SQUARE ***STD***



SENTA, KRISTINA PELTEKOFF/

Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale

Page 5 of 9

Locked: Closed:

OV.ET.IGY.1224.PL-Eterna-Imperial Grey Polished-12 x 24 Shower Wall Tile 9057 See Tile Direction on Sketch Page ***5** Shower Wall Tile Grout 9837 Grout-Warm Grey #5093 ***UPG*** Shower Wall Tile Pattern HORIZONTAL STACKED ***STD*** 3070 Shower Floor Tile 9087 OV.ET.IGY.02.HEX.PL Eterna Series Imperial Grey 2 HEX Polished ***7*** Shower Floor Tile Grout 9837 Grout-Warm Grey #5093 ***STD*** Shower Floor Tile Pattern 3120 VERTICAL HEX ***STD*** Shower Jamb(s) and Sill(s) 8925 Shower Jamb / Sill-Sky Grey (Light Grey) ***STD*** Plumbing Fixture (colour) Plumbing Fixtures-WHITE ***STD*** 1737 2X SHOWER NICHE ETERNA SERIES IMPERIAL GREY 2 HEX POLISHED TO BE ON THE

BACK WALL 6" FROM CENTRE (12" APART)

red Ensuite		CI a
Cabinet Colour/Style	9827	Viking IV-WESTPORT-WINTER WHITE ***UPG***
Cabinet Hardware	7676	12843-HARDWARE ***STD***
Countertop	9815	Group 2-Quartz-Caesarstone-GOLDEN SKY # 7524-3/4 inch B/U MITERED EDGE ***2***
Countertop Edge	4007	GROUP 2 TO 7 - DOUBLE MITRE 1 1/2 INCH ***3***
Floor Tile	8862	MC.MR.IVO.10HEX-Merino-Ivory-10 inch HEX ***7***
Floor Tile Grout	9838	Grout-Bone #5015 ***STD***
Floor Tile Pattern	3120	VERTICAL HEX ***STD***
Shower Wall Tile	9459	SO.SB.LHT.0312.GL-Shadebrick-Light (Off White) Glossy-3 x 12 UPG 3 ***UPG***
Shower Wall Tile Grout	9836	Grout-Eggshell #5220 ***STD***
Shower Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***
Shower Floor Tile	8103	OD.ON.SWT.02.HEX.MT-ONTARIO HEXAGON



SENTA, KRISTINA PELTEKOFF/

Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale

70f-1087

Locked: Closed:

		PARTITE ONO PARTITE OF O Z
Shower Floor Tile Grout	9836	Grout-Eggshell #5220 ***STD***
Shower Floor Tile Pattern	3120	VERTICAL HEX ***STD***
		and the land that the land the

Shower Jamb(s) and Sill(s)

Plumbing Fixture (colour)

Comment

8923

Shower Jamb / Sill-Thassos White ***STD***

Plumbing Fixtures-WHITE ***STD***

Ensuite 2 Cabinet Colour/Style 6319 Viking III-MANCHESTER-CAVIAR CL-MAPLE ***STD*** Cabinet Hardware 7676 12843-HARDWARE ***STD*** Group 1-Quartz-Caesarstone-WHITE SAND # 7041- 3/4 Countertop 9810 inch B/U MITERED EDGE ***UPG*** Countertop Edge 4006 GROUP 1 - DOUBLE MITRE 1 1/2 INCH ***2*** Floor Tile HV.RS.LGR.1224.MT-Royal Stone Matte-Light Grey-12 x 9770 24 floor tile directions SEE SKETCH ***5** Floor Tile Grout 9837 Grout-Warm Grey #5093 ***STD*** FRONT TO BACK ***STD*** Floor Tile Pattern 3040 Wall Tile KD.OC.PRL.2,5 X 10-Oceani Series-Pearl Glossy-2,5 x 10 9469 UPG 3 ***UPG*** Wall Tile Grout 9837 Grout-Warm Grey #5093 ***UPG*** Wall Tile Pattern 3060 HORIZONTAL BRICK ***UPG*** N/A ***** Opt. Shower Floor Tile 1111 N/A ***** Opt. Shower Floor Tile Grout 1111 N/A ***** Opt. Shower Floor Tile Pattern 1111

Opt. Showe	Opt. Shower Jamb(s) and Sill(s)		N/A *****
Plumbing F	Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***
Comment	SHOWER NICHE :946	9: KD, OC	PRL. 2.5X10 OCEIANI SERRIES PEARL GLOSSy



SENTA, KRISTINA PELTEKOFF/

Project: Country Lane Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

Page 7 of 9

Locked:

Closed:

ndry Room		
Flooring	8861	MC.MR.SIL.10HEX-Merino-Silver-10 inch HEX ***7***
Floor Tile Grout	9837	Grout-Warm Grey #5093 ***STD***
Floor Tile Pattern	3120	VERTICAL HEX ***STD***
	0.20	
Opt. Cabinet Colour/Style - Upp	ers 6467	Classic II-MANCHESTER-MACADAMIA-PAINT MDF ***UPG***
Opt. Cabinet Hardware - Uppers	s 7676	12843-HARDWARE ***STD***
Opt. Cabinet Colour/Style - Base	e 6467	Classic II-MANCHESTER-MACADAMIA-PAINT MDF ***UPG***
Opt. Cabinet Hardware - Base	7676	12843-HARDWARE ***STD***
COMMENT COUNTER TOP: U ACROSS WASHER		UARTZ GROUP 3 RAVEN #4120 WITH BUILT UP EDGE
er Level Recreation Room	9504	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD***
Flooring	L FIRE PLACE	NF 17 MANTLE NO SURROUND
Flooring Comment STD. ELECTRICAL	L FIRE PLACE	NF 17 MANTLE NO SURROUND
Flooring	L FIRE PLACE	NF 17 MANTLE NO SURROUND 87354-MINOTAUR-OVERCAST-40 oz Poly ***STD***
Comment STD. ELECTRICAL er Level Bedroom Flooring		
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment		
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment er Level Bathroom		
Comment STD. ELECTRICAL er Level Bedroom Flooring	9504	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG***
Comment STD. ELECTRICAL Er Level Bedroom Flooring Comment Er Level Bathroom Cabinet Colour/Style Cabinet Hardware	9504 9827 7676	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG*** 12843-HARDWARE ***STD***
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment er Level Bathroom Cabinet Colour/Style Cabinet Hardware Countertop	9504 9827 7676 9814	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG*** 12843-HARDWARE ***STD*** Group 2-Quartz-Caesarstone-ASHEN MARBLE # 7512-3/4 inch B/U MITERED EDGE ***2***
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment er Level Bathroom Cabinet Colour/Style Cabinet Hardware	9504 9827 7676	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG*** 12843-HARDWARE ***STD*** Group 2-Quartz-Caesarstone-ASHEN MARBLE #
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment er Level Bathroom Cabinet Colour/Style Cabinet Hardware Countertop Countertop Edge	9504 9827 7676 9814 4007	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG*** 12843-HARDWARE ***STD*** Group 2-Quartz-Caesarstone-ASHEN MARBLE # 7512-3/4 inch B/U MITERED EDGE ***2*** GROUP 2 TO 7 - DOUBLE MITRE 1 1/2 INCH ***3***
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment er Level Bathroom Cabinet Colour/Style Cabinet Hardware Countertop	9504 9827 7676 9814	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG*** 12843-HARDWARE ***STD*** Group 2-Quartz-Caesarstone-ASHEN MARBLE # 7512-3/4 inch B/U MITERED EDGE ***2***
Comment STD. ELECTRICAL er Level Bedroom Flooring Comment er Level Bathroom Cabinet Colour/Style Cabinet Hardware Countertop Countertop Edge	9504 9827 7676 9814 4007	87354-MINOTAUR-OVERCAST-40 oz Poly ***STD*** Viking IV-WESTPORT-WINTER WHITE ***UPG*** 12843-HARDWARE ***STD*** Group 2-Quartz-Caesarstone-ASHEN MARBLE # 7512-3/4 inch B/U MITERED EDGE ***2*** GROUP 2 TO 7 - DOUBLE MITRE 1 1/2 INCH ***3*** NY.RG.GRY.1224.PL.N-Regal Polished-Grey-12 x 24 See

0022

OT LIM MHT 0810 Lipinal Mbito 8 v 10 *** CTD***



SENTA, KRISTINA PELTEKOFF/

Project: Country Lane Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

Locked:

Closed:

vvali Tile	0000	Q1.0vv.vv111.0010-0111waii-vv111te-0 x 10 310		
Wall Tile Grout	9836	Grout-Eggshell #5220 ***STD***		
Wall Tile Pattern	3070	HORIZONTAL STACKED ***STD***		

Opt. Shower Floor Tile	9077	OV.ET.IGY.1X3.PL.HER Eterna Series Imperial Grey 1 x 3 Polished ***7***
Opt. Shower Floor Tile Grout	9837	Grout-Warm Grey #5093 ***STD***
Opt. Shower Floor Tile Pattern	3100	VERTICAL HERRINGBONE ***STD ON MESH***



Opt. Shower Jamb(s) and Sill(s)	8923	Shower Jamb / Sill-Thassos White ***STD***
Plumbing Fixture (colour)	1737	Plumbing Fixtures-WHITE ***STD***

Comment SHOWE NICHE TO BE: OV.ET.IGY.1X3 PL.HER. ETERNA SERIES OMPEIAL GREY

Main Stairs		
Туре	1712	(
Colour	9796	H
		1

4740	0-1-04: ********
1712	Oak Stairs ***STD***
9796	Hillside STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING ***99***-STD
0440	Oin als Oallan Alt Disi. (Ot 19 0.4/0.0 10

Handrail/Pickets/Posts Type	8148	Single Collar Alt. Plain w/ Shoes with 3 1/2 Square/Cap
		Post(s)-BLACK ***STD***

Handrail/Pickets/Posts Colour	9796	Hillside STAIN TO COMPLIMENT HARDWOOD AND WILL
		VARY FROM FLOORING ***99***-STD

Custom Stain/Paint	1111	N/A *****
Landing(s)	8497	Red Oak UVF-Vintage Red Oak Solid Sculpted Character

Comment	

N/A *****

1111

Lower	Level	Stairs			
-------	-------	--------	--	--	--

Opt. Carpet Runner

1712	Oak Stairs ***STD***
9796	Hillside STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING ***99***-STD
8148	Single Collar Alt. Plain w/ Shoes with 3 1/2 Square/Cap Post(s)-BLACK ***STD***
9796	Hillside STAIN TO COMPLIMENT HARDWOOD AND WILL VARY FROM FLOORING ***99***-STD
1111	N/A *****
8497	Red Oak UVF-Vintage Red Oak Solid Sculpted Character UVF-HILLSIDE-3/4 inch X 5 inch ***STD***
1111	N/A *****
	9796 8148 9796 1111 8497



Customer Colours SENTA, KRISTINA PELTEKOFF/ Project: Country Lane Unit: 733, Phase: 7 Locked: Model: 39-3573 A The Cedarvale Closed: Comment Throughout Switches and Plug Decora White Switches and Plugs ***STD*** 5796 Thresholds 2232 Metal Thresholds ***STD*** Underpad 1079 500 Series-Underpad ***STD*** Trim Size 5 1/4 inch Baseboard and 3 inch Integrated Backbend Casings ***UPG*** / ***STD in Singles*** 8704 Trim - Paint Colour 1716 Trim-WHITE ***STD*** Walls - Paint Colour 1717 22-Wall-WARM GREY ***STD***

Purchaser:			
)=	Date	Country Lane	Date Approved

Comment

Purchaser:

SENTA, KRISTINA PELTEKOF



Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

0.00	
Offer	Supply and Install Central Air Conditioning
Worksheet	Note:
Offer	Two Men and a Truck Credit of One Thousand Dollars (\$1000.00) for moving services only, Into your Heathwood Home (No
Offici	Cash Value) The Credit is Non-Transferable and cannot be combined with any other offer Singles
Worksheet	Note:
Offer	Classic Collection: Five Appliances: SS Fridge, Stove, Dishwasher: White Front Loader Washer/Dryer (Singles)
Worksheet	Note:
Offer	The Purchaser(s) acknowledge that they have NOT been referred by an existing Heathwood Homeowner and therefor are not entitled to a referral fee under Heathwood Homes Referral program.
Worksheet	
Offer	This is a Walk Out Grading Condition which includes a Balcony off the main floor and a finished Lower Level with full
	bathroom.(version 1)
Worksheet	Note:
Offer	This House requires a Rear Elevation Upgrade Due to Architect Control.
Worksheet	
Worksheet	

12 of 87



Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

Lot: 733

ADMIN FEE

Invoice Qty. Description

Qty. Description

APPLIA	INCES
---------------	-------

Invoice

1746

714,390

10Jan25

		CABINETRY-delete stove uppers; ELECTRICAL-Notify; HEATING/AIR CONDITIONING-Duct Size remains 6 i
CABIN		
Invoice	Qty.	Description
1746 714,515	1.0	KITCHEN - CABINETRY - 15B-45CM WIDE PULL-OUT DOOR BASE CABINET WASTE/RECYCLE CENTRE WITH SOFT-CLOSE ([2] 35L BINS) (AVAILABLE ONLY WITH 45CM WIDE CABINET) -CLASSIC
10Jan25		INCL. TOP DRAWER. TO BE INSTALLED IN THE ISLAND BESIDE THE SINK NOTE: MOVE SINK AND DISHWASHER DOWN TO ACCOMODATE SEE SKETCH # 4
1746 700,219	1.0	SHARED BATHROOM - CABINETRY - MAIN/SHRD-VIKING IV-UPG
10Jan25		WESTPORT CABINET DISCONTINUED- UPGRADED TO CLASSIC II MANCHESTER PAINT GRADE WINTER WHITE AT NO ADDITIONAL COST TO PURCHASER AS PER FRENDEL KITCHENS
1746 700,223	1.0	FINISHED BASEMENT BATHROOM - CABINETRY - BASEMENT-VIKING IV-UPG
10Jan25		WESTPORT CABINET DISCONTINUED- UPGRADED TO CLASSIC II MANCHESTER PAINT GRADE WINTER WHITE AT NO ADDITIONAL COST TO PURCHASER AS PER FRENDEL KITCHENS
1746 713,975	1.0	- HARDWOOD - KITCHEN/BRK - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG
10Jan25 **		CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics
1746 713,976	1.0	- HARDWOOD - SERVERY - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG
10Jan25 **		CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics
1746 700,902	1.0	KITCHEN/SERVERY/BREAKFAST - Cabinetry - Opt. Light Valance Trim and Luminiz LED Slimline Strip Light (including std Servery)- UPG
10Jan25		ELECTRICAL-Complete Kitchen valaance light including switch (Luminiz LED slimline strip light)
1746 714,570 10Jan25	1.0	KITCHEN - CABINETRY - 34H-BASE CABINET FOR BUILT-IN MICROWAVE/SMALL APPLIANCE WITH TRIM KIT WITH DRAWER BELOW (NOT AVAILABLE FOR PANASONIC TRIM KIT NN-TK714SS) (SUPPLY SPECS) (NOT AVAILABLE IN SOME LAMINATES)-CLASSIC SEE SKETCH # 4 AND APPLIANCE SPECS
1746	1.0	MASTER ENSUITE - CABINETRY - 15D-VANITY BANK OF DRAWERS (MAX. WIDTH 55CM)-CLASSIC
714,541 10Jan25		(ADD SOFT CLOSED) TO BE INSTALLED IN THE CENTRE SEE SKETCH # 6
1746 714,512	3.0	KITCHEN - CABINETRY - 10B+8B-POTS AND PANS (3) DRAWERS SOFT-CLOSE TANDEMBOX (WIDTH MIN. 60CM/MAX. 90CM) (SIZE SUBJECT TO FLOOR PLAN)-CLASSIC
10Jan25		SEE SKETCH # 4
1746 714,447	4.0	THROUGHOUT - CABINETRY - 13D-VANITY TOP DRAWER/LOWER DRAWER (PER DRAWER) (METABOX STANDARD LEVELS 1-7, SOFT-CLOSE TANDEMBOX STANDARD LEVELS 8-13)-VIKING
10Jan25		2X FINISHED BASEMENT BATHROOM 2X ENS 2 BATHROOM SEE SKETCH# 6

1.0 KITCHEN - APPLIANCES - KITCHENAID 36 INCH CHIMNEY HOOD SS - KVWB606DSS

SEE SPECS ALSO FOR UPGRADED KITCHEN AND LAUNDRY SPECS

DisciplineMS.rpt 13dec21 Page 2 of 20

13 of 87



CONSTRUCTION SUMMARY

Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

CABINETRY

CABIN	CABINETRY			
Invoice	Qty.	Description		
1746 714,562 10Jan25	1.0	KITCHEN - CABINETRY - 6H-ACCOMMODATE FOR BUILT-IN REFRIGERATOR WITH OVERLAY/PROUD INSTALLATION (TYPICALLY THE DOOR OF THIS UNIT WILL PROTRUDE BEYOND THE CABINETS AND HAVE A VISIBLE VENT OR GRILL) (DECORATIVE PANELS NOT INCLUDED) (PROVIDE SPECS)-CLASSIC FOR 48" FRIDGE SKETCH # 4 SEE FRIDGE SPECS		
1746 389,866 10Jan25 **	1.0	KITCHEN - PLUMBING - KITCHEN SINK UPGRADE - BLANCO QUATRUS U 1 SUPER SINGLE 401248 (MIN CABINET 36 IN) SEE SPEC CABINETRY-upgraded kitchen sink; GRANITE-upgraded kitchen sink		
1746 10Jan25	1.0	KITCHEN - KITCHEN/SERVERY - CABINETRY-3A-Stacked upper for 30cm standard depth (includes stack moulding between cabinets)-Built in Plan (66cm at deep fridge uppers and built in) CLASSIC - UPG SKETCH # 4		
NoCat		DRYWAL-Notify; FRAMING-Modify Bulkhead; GRANITE-delete partial countertop due to Built-in; PAINTING-		
1746 389,832 10Jan25 **	1.0	SERVERY ONLY - PLUMBING - BAR SINK - COMPLETE BAR SINK FOR SERVERY INCLUDES PLUMBING ROUGH-IN AND MOEN ALIGN BAR PREP FAUCET (MODEL: 5965) AND BOSCO UNDERMOUNT SINK (MODEL 207029) (INCLUDING GRANITE SINK CUTOUT/POLISH) - SEE SPECS CABINETRY-Accommodate Servery Sink; CONCRETE AND DRAIN-Additional Stack; GRANITE-Additional Cu		
1746 714,517 10Jan25	2.0	KITCHEN - CABINETRY - 17B-PULL-OUT SPICE RACK CABINET (FULL-HEIGHT CABINET RECEIVES [3] TRAYS, TOP DRAWER CABINET RECEIVES [2] TRAYS) (AVAILABLE ONLY IN 20CM, 25CM, AND 30 CM WIDE CABINETS) -CLASSIC 20 CM. WIDE TO BE INSTALLED ON EACH SIDE OF THE STOVE		
		SEE SKETCH # 4		
1746 714,583 10Jan25	2.0	KITCHEN - CABINETRY - 5K-DECORATIVE POST FOR DEEP ISLAND OR PENINSULA EACH (PLEASE SPECIFY WINDSOR, YORK STYLE) (AVAILABLE IN OAK, MAPLE, AND PAINT) (LAMINATES AVAILABLE ONLY IN YORK STYLE) (66CM - 120CM DEEP)-CLASSIC WINDSOR STYLE POSTS SKETCH # 4 AND 8		
1746 714,544 10Jan25	5.0	MASTER ENSUITE - CABINETRY - 18D-UPGRADE LEVELS 1-4, 5-7 DRAWERS FROM METABOX TO SOFT-CLOSE TANDEMBOX DRAWERS PER DRAWER (BD X 4, BPP X 3, BT/VT X 1, VBD X 3, VPP X 2) (PULL-OUTS MUST ALSO BE COUNTED AND UPGRADED) (SINGLE DRAWER UPGRADES ARE NOT PERMITTED, ALL DRAWERS IN THE ROOM MUST BE UPGRADED - ROOMS CANNOT HAVE BOTH SOFT-CLOSE TANDEMBOX AND METABOX) -CLASSIC ALL DRAWERS		
1746 700,631 10Jan25	1.0	MASTER ENSUITE - CABINETRY - PRINCIPAL ENSUITE-CLASSIC II-UPG		
1746 700,626 10Jan25	1.0	- CABINETRY - KIT/SERVERY -CLASSIC II-UPG		
1746 714,585 10Jan25	1.0	KITCHEN/SERVERY - CABINETRY - 2L-TWO-TONE COLOUR/STYLE SELECTION FOR BASE CABINETS (TALL AND WALL CABINETS MUST BE SAME COLOUR) (MUST BE OF EQUAL OR LOWER LEVEL TO MAIN SELECTION) -CLASSIC KITCHEN PERIMETER TO BE CLASSIC II MANCHESTER WINTER WHITE AND ISLAND AND SERVERY COLOUR TO BE MACADAMIA SKETCH # 4		
1746 714,449 10Jan25	1.0	MAIN BATHROOM - CABINETRY - 15D-VANITY BANK OF DRAWERS (MAX. WIDTH 55CM)-VIKING SHARED BATHEROOM SEE SKETCH # 6		

DisciplineMS.rpt 13dec21

Page 3 of 20



Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

CABINETRY

CABIN		
Invoice	Qty.	Description
1746	1.0	SERVERY ONLY - SERVERY - OPENING FOR A BEVERAGE FRIDGE
10Jan25 NoCat		SEE SKETCH # 4 AND BEV. FRIDGE SPEC
1746 714,535 10Jan25	4.0	SERVERY ONLY - CABINETRY - 10C-INTERIOR PULL-OUT DRAWER FOR DOUBLE-DOOR PANTRY (EACH) (66CM DEEP, MAX. [4] PER PANTRY)-CLASSIC
10Jan23		TO BE INSTALLED IN SERVERY PANTRY SPACE BETWEEN THE DRAWERS FIRST ONE AT THE BOTTOM THE APPROX 15" APART SEE SKETCH# 4
1746 700,632 10Jan25	1.0	LAUNDRY ROOM - CABINETRY - LAUNDRY BASE-CLASSIC II-UPG
1746 700,634 10Jan25	1.0	LAUNDRY ROOM - CABINETRY - OPT LAUNDRY UPPER-CLASSIC II-UPG
1746 714,508	5.0	KITCHEN - CABINETRY - 4B-DUMMY DOOR FOR BASE FINISHED ENDS AND BACK PANELS (EACH)-CLASSIC
10Jan25		DUMMY DOORS FOR ISLAND (UNDER BREAKFAST BAR)
1746 714,508	4.0	KITCHEN - CABINETRY - 4B-DUMMY DOOR FOR BASE FINISHED ENDS AND BACK PANELS (EACH)-CLASSIC
10Jan25		DUMMY DOORS FOR ISLAND END SEE SKETCH # 4 AND 8
1746 714,573	2.0	KITCHEN - CABINETRY - 1J-DUMMY DOOR FOR WALL FINISHED ENDS (EACH)-CLASSIC
10Jan25		UPPER END CABINET SKETCH # 4
1746 714,574	1.0	KITCHEN/BREAKFAST - CABINETRY - 2J-DUMMY DOOR FOR BASE FINISHED ENDS (EACH) -CLASSIC
10Jan25		1X TO BE AT THE END OF BASE CABINET SKETCH # 4
1746 714,578	1.0	KITCHEN - CABINETRY - 7J-DUMMY DOOR FOR COUNTER DEPTH TALL (66CM DEEP GABLE) FINISHED ENDS (6 DOORS)-CLASSIC
10Jan25		TO BE USED AT FRIDGE END SKETCH # 4
1746	3.0	KITCHEN - KITCHEN - 3 X 8' length(18J) Colonial style toe-kick flushin front of island under dummy doors and wrap around base of posts and along sides of island
10Jan25 NoCat		TO BE INSTALLED AROUND THE POST LIKE IN THE MODLE HOME + THE POST SKETCH # 4 AND 8
1746 714,579	1.0	LAUNDRY ROOM - CABINETRY - 8J-CROWN MOULDING (8 FT LENGTH PER PC) (FOR CLARIFICATION OF STYLES, SEE MOULDING MATRIX)-CLASSIC
10Jan25		SKETCH# 6
1746 714,580 10Jan25	1.0	LAUNDRY ROOM - CABINETRY - 11J-LIGHT VALANCE TRIM ONLY (8 FT LENGTH PER PC) (FOR CLARIFICATION OF STYLES SEE MOULDING MATRIX) (LIGHT VALANCE IS APPROX. 5CM [2 IN] HIGH) (PLEASE ENSURE LIGHT FIXTURES USED WILL BE CONCEALED BY THE VALANCE) -CLASSIC TO BE INSTALLED IN TH LAUNDRY ROOM SKETCH # 6

DisciplineMS.rpt 13dec21 Page 4 of 20



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

CABINETRY

Invoice	Qty.	Description
1746 714,390 10Jan25 **	1.0	KITCHEN - APPLIANCES - KITCHENAID 36 INCH CHIMNEY HOOD SS - KVWB606DSS SEE SPECS ALSO FOR UPGRADED KITCHEN AND LAUNDRY SPECS CABINETRY-delete stove uppers; ELECTRICAL-Notify; HEATING/AIR CONDITIONING-Duct Size remains 6 i
1746 700,627 10Jan25	1.0	SERVERY ONLY - CABINETRY - SERVERY UPPER-CLASSIC II-UPG SKETCH # 4
1746 714,499 10Jan25	3.0	KITCHEN - CABINETRY - 15A-GLASS DOOR (EACH) (SPECIFY CLEAR, FROSTED, OR SMOKED GLASS) (UNFINISHED CABINET INTERIOR) (NOT AVAILABLE IN SOME LAMINATES)-CLASSIC TO BE INSTALLED IN THE 3 UPPER CABINETS BESIDE THE FRIDGE (NOT THE STACKED UPPERS) SEE SKETCH # 4 CLEAR GLASS
1746 714,546 10Jan25	1.0	LAUNDRY ROOM - CABINETRY - 7E-TALL GABLE AT LAUNDRY SINK TO SUPPORT COUNTERTOP OVER WASHER/DRYER, SINK REMAINS STANDARD HEIGHT (LAMINATE COUNTERTOP OR STRAPPING FOR GRANITE COUNTERTOP INCLUDED) (MAX. LENGTH 8ft [244CM])-CLASSIC
1746 395,462 10Jan25 **	1.0	LAUNDRY ROOM - PLUMBING-BOSCO LAUNDRY TUB MODEL T207004 18 IN X 16 IN X 10 IN DEEP SEE SPEC GRANITE-see specs
1746 712,256 10Jan25 **	1.0	- GRANITE - ENSUITE BED 2 - GROUP 1 WITH 1 1/2 IN MITER EDGE - UPG CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
1746 712,265 10Jan25 **	1.0	- GRANITE - LOWER BATH - GROUP 2 WITH 1 1/2 IN MITER EDGE - UPG CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
1746 389,724 10Jan25 **	21.3	LAUNDRY ROOM - GRANITE - ADDITIONAL COUNTERTOP PER SQ.FT UPGRADE 3 CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
1746 712,241 10Jan25 **	1.0	- GRANITE - MAIN BATH - GROUP 2 WITH 1 1/2 IN MITER EDGE - UPG CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink

CARP	CARPET			
Invoice	Qty.	Description		
1746 713,971	1.0	- HARDWOOD - M/B - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG		
10Jan25 **		CARPET-delete std carnet: INTERIOR TRIM-supply and install quarter rounds: PAINTING-paint quarter rounds		

DisciplineMS.rpt 13dec21 Page 5 of 20



Lot: 733 Model: 39-3573 A The Cedarvale

Project/Phase: Country Lane / 7

CED	A -	N / T]	
CER	А	VI	

CERAMICS			
Invoice	Qty.	Description	
1746 705,404 10Jan25	1.0	Kitchen - CERAMIC - KITCHEN - BACKSPLASH SINGLES - UG 3 - UPG	
1746 705,405 10Jan25	1.0	Servery - CERAMIC - SERVERY - BACKSPLASH SINGLES - UG 3 - UPG	
1746 710,384 10Jan25	1.0	Foyer - CERAMIC - FOYER - FLOOR - GROUT - UPG	
1746 705,414 10Jan25	1.0	Foyer - CERAMIC - FOYER - FLOOR - UG 4 - UPG	
1746 705,466 10Jan25	1.0	Powder - CERAMIC - POWDER - FLOOR - UG 7 - UPG	
1746 705,454 10Jan25	1.0	Master Bath - CERAMIC - MASTER BATH - FLOOR - UG 6 - UPG	
1746 710,497 10Jan25	1.0	Master Shower - CERAMIC - MASTER SHOWER - FLOOR ON WALL - GROUT - UPG	
1746 705,528 10Jan25	1.0	Master Shower - CERAMIC - MASTER SHOWER - FLOOR ON WALL - UG 5 - UPG	
1746 705,462 10Jan25	1.0	Master Shower - CERAMIC - MASTER SHOWER - MOSAIC - UG 7 - UPG	
1746 713,975 10Jan25 **	1.0	- HARDWOOD - KITCHEN/BRK - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics	
1746 713,976 10Jan25 **	1.0	- HARDWOOD - SERVERY - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics	
1746 390,162 10Jan25	4.0	THROUGHOUT - CERAMICS - SHOWER NICHE 12 in X 24 in X 4 in ON INTERIOR SHOWER WALL WITH MATCHING JAMBS (CHOICE OF SHOWER WALL OR FLOOR TILE AS BACKING; NO SHELVE) 2X MASTER SHOWER, 1X ENSUITE 2, 1X BASEMENT SKETCH # 1, 5 AND 7 FRAMING-accommodate shower niches	
1746 705,416 10Jan25	1.0	Mud Room - CERAMIC - MUD ROOM - FLOOR - UG 4 - UPG	

DisciplineMS.rpt 13dec21

Page 6 of 20



Lot: 733 Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

CERAMICS				
Invoice	Qty.	Description		
1746 710,435 10Jan25	1.0	Mud Room - CERAMIC - MUD ROOM - FLOOR - GROUT - UPG		
1746 705,469 10Jan25	1.0	Main/Shrd Bath - CERAMIC - MAIN/SHRD BATH - FLOOR - UG 7 - UPG		
1746 705,425 10Jan25	1.0	Main/Shrd Bath - CERAMIC - MAIN/SHRD BATH - WALL - UG 5 - UPG		
1746 705,378 10Jan25	1.0	Main/Shrd Bath - CERAMIC - MAIN/SHRD BATH - MOSAIC - UG 2 - UPG		
1746 705,436 10Jan25	1.0	Main Bath 2 - CERAMIC - MAIN BATH 2 - FLOOR - UG 5 - UPG ENS 2		
1746 705,474 10Jan25	1.0	Laundry - CERAMIC - LAUNDRY - FLOOR - UG 7 - UPG		
1746 705,426 10Jan25	1.0	Main Bath 2 - CERAMIC - MAIN BATH 2 - WALL - UG 5 - UPG		
1746 710,447 10Jan25	1.0	Basement Bath - CERAMIC - BASEMENT BATH - FLOOR - GROUT - UPG		
1746 705,413 10Jan25	1.0	Basement Bath - CERAMIC - BASEMENT BATH - FLOOR - UG 4 - UPG		
1746 10Jan25 NoCat		FINISHED BASEMENT BATHROOM - FINISHED BASEMENT BATHROOM - SHOWER FLOOR UPG. 7		
1746 710,379 10Jan25		Main Bath 2 - CERAMIC - MAIN BATH 2 - WALL - GROUT - UPG		
1746 705,477 10Jan25	1.0	Main Bath 2 - CERAMIC - MAIN BATH 2 - WALL - DIAG OR CHECKER - UPG		

DisciplineMS.rpt 13dec21 Page 7 of 20 Printed and Sent: 10-Jan-25



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

CONCRETE AND DRAIN

Invoice	Qty.	Description
1746	1.0	SERVERY ONLY - PLUMBING - BAR SINK - COMPLETE BAR SINK FOR SERVERY INCLUDES PLUMBING ROUGH-IN
389,832		AND MOEN ALIGN BAR PREP FAUCET (MODEL: 5965) AND BOSCO UNDERMOUNT SINK (MODEL 207029)
10Jan25		(INCLUDING GRANITE SINK CUTOUT/POLISH) - SEE SPECS
**		CABINETRY-Accommodate Servery Sink; CONCRETE AND DRAIN-Additional Stack; GRANITE-Additional Cu

DisciplineMS.rpt 13dec21 Page 8 of 20

19 of 87



Lot: 733 Model: 39-3573 A The Cedarvale

Project/Phase: Country Lane / 7

CORNICE MOULDING

Invoice		MOULDING Description
1746	1.0	FOYER - FOYER COFFERED - 7" HERITAGE # 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 3
1746	1.0	LIVING ROOM - LIVING ROOM AND HALLWAY - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 3
1746	1.0	DINING ROOM - DINING ROOM COFFERED - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 3
1746	1.0	POWDER ROOM - POWDER ROOM - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 3
1746	1.0	KITCHEN/SERVERY/BREAKFAST - KITCHEN / BREAKFAST ROOM / SERVERY - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SKETCH # 3
1746	1.0	MUD ROOM - MUD ROOM - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 3
1746	1.0	UPPER HALL - UPPER HALL - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 5
1746	1.0	MASTER BEDROOM - MASTER BEDROOM RAISED CEILING (COFFERED) - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 5
1746	1.0	LAUNDRY ROOM - LAUNDRY ROOM - 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 5
1746	1.0	UPPER HALL - UPPER HALL - ABOVE STAIRS 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SEE SKETCH # 5
1746	1.0	MASTER BEDROOM - MASTER BEDROOM HALLWAY COFFERED CEILING 7" HERITAGE 701 CORNICE MOULDING
10Jan25 NoCat		SKETCH# 5
1746	1.0	MASTER ENSUITE - PRINCIPAL ENSUITE - 7" HERITAGE 701 CORNICE MOLDING
10Jan25 NoCat		SEE SKETCH # 5
1746	1.0	GREAT ROOM - GREAT ROOM - STD. 7" CORNICE MOULDING IN THE WAFFLE CEILING
10Jan25 NoCat		SEE SKETCH #3

DisciplineMS.rpt 13dec21

Page 9 of 20



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

DRYWALL

DKYW		
Invoice	Qty.	Description
1746 711,325 10Jan25	1.0	- DRYWALL - SMOOTH CEILINGS-BASEMENT-UPG
10Jan25		PAINTING-Paint smooth ceiling
1746 711,352	1.0	- DRYWALL - SMOOTH CEILINGS-SECOND FLOOR WITH RESILIENT CHANNEL-UPG
10Jan25		ELECTRICAL-Drop electrical boxes; PAINTING-Paint smooth ceiling
1746 714,376	1.0	GREAT ROOM - WAFFLE CEILING - INSTALL WAFFLE CEILING. COFFERED CEILING IS STANDARD - GREAT ROOM - UPG
10Jan25 **		SKETCH # 2 AND 3 DRYWALL-Standard Smooth Ceiling inside waffles; FRAMING-Strap Ceiling for Potlights; PAINTING-Paint moul (6)
1746	1.0	MUD ROOM - DELETE INTERIOR DOOR
10Jan25 ** NoCat		DELETE DOOR BETWEEN STAIRS LANDING AND MUD ROOM, SEE SKETCH # 2 MODIFICATION
1746 395,461 10Jan25 **	1.0	THROUGHOUT - CLASSIC COLLECTION SCHEDULE A - Choice of 20 LED (3000K) pot lights in finished areas (Second Floor Potlight(s) Require Smooth Ceiling) SEE MORE DETAILS UNDER ELECTRICAL ON MORE POTLIGHTS DRYWALL-Drywall Ceiling cutouts for potlights FRAMING-Frame to accommodate potlights 10X RECREATION ROOM - RELOCATET STD. LIGHT, USE STD. SWITCH, 2X BASEMENT USE STD. 3 WAY SWITCH RELOCATE STD. LIGHT NEAR THE STAIRS 2X BASEMENT HALL -RELOCATE STD. LIGHT, USE SEPARATE SWITCH 2X BASAMENT BATHROOM - RELOCATE STD. CEILING LIGHT, USE STD. CEILINNG SWITCH 4X DINING ROOM - USE SEPARATE SWITCH KEEP STD. LIGHT SEE SKETCH # 1 AND 2
1746	1.0	KITCHEN - KITCHEN/SERVERY - CABINETRY-3A-Stacked upper for 30cm standard depth (includes stack moulding between cabinets)-Built in Plan (66cm at deep fridge uppers and built in) CLASSIC - UPG
10Jan25 ** NoCat		SKETCH# 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; GRANITE-delete partial countertop due to Built-in; PAINTING-
1746 390,206	1.0	GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE
10Jan25 **		SEE SKETCH # 2 AND 9 DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify
1746	1.0	FINISHED BASEMENT BEDROOM - MODIFICATION - DELETE WALL AND DOOR BETWEEN HALLWAY AND BEDROOM KEEP 15" + - (NIB WALL DUE TO HEATING VENT)
10Jan25 ** NoCat		SEE SKETCH # 1 MODIFICATION

Page 10 of 20 DisciplineMS.rpt 13dec21



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

ELECTRICAL

ELEC I		Description
	Γ	,
1746 711,352	1.0	- DRYWALL - SMOOTH CEILINGS-SECOND FLOOR WITH RESILIENT CHANNEL-UPG
10Jan25 **		ELECTRICAL-Drop electrical boxes; PAINTING-Paint smooth ceiling
1746	1.0	KITCHEN/SERVERY/BREAKFAST - Cabinetry - Opt. Light Valance Trim and Luminiz LED Slimline Strip Light (including std
700,902	1.0	Servery)- UPG
10Jan25		
**		ELECTRICAL-Complete Kitchen valaance light including switch (Luminiz LED slimline strip light)
1746 389,800 10Jan25	1.0	- HEATING/AIR - ROUGH-IN GAS LINE FOR GAS STOVE AT MAIN FLOOR (SEE SPECS) (HOOK-UP NOT INCLUDED) LEAVE STANDARD 120 VOLT ELECTRICAL OUTLET ON A SEPARATE CIRCUIT. * SPECIFY IF STANDARD 220V WILL STAY OR BE RELOCATED STD.ELECTRICAL 220V STAY.
**		ELECTRICAL-Notify
1746	1.0	MUD ROOM - DELETE INTERIOR DOOR
10Jan25 ** NoCat		DELETE DOOR BETWEEN STAIRS LANDING AND MUD ROOM, SEE SKETCH # 2 MODIFICATION
1746 395,461 10Jan25	1.0	THROUGHOUT - CLASSIC COLLECTION SCHEDULE A - Choice of 20 LED (3000K) pot lights in finished areas (Second Floor Potlight(s) Require Smooth Ceiling) DRYWALL-Drywall Ceiling cutouts for potlights FRAMING-Frame to accommodate potlights 10X RECREATION ROOM - RELOCATET STD. LIGHT, USE STD. SWITCH, 2X BASEMENT USE STD. 3 WAY SWITCH RELOCATE STD. LIGHT NEAR THE STAIRS
		2X BASEMENT HALL -RELOCATE STD. LIGHT , USE SEPARATE SWITCH 2X BASAMENT BATHROOM - RELOCATE STD. CEILING LIGHT , USE STD. CEILINNG SWITCH 4X DINING ROOM - USE SEPARATE SWITCH KEEP STD. LIGHT SEE SKETCH # 1 AND 2
1746 390,489	1.0	MUD ROOM - ELECTRICAL-AUTOMATIC CLOSET LIGHT (INCLUDING DOOR CONTACTS) DOUBLE DOOR EACH
10Jan25		SKETCH# 2
1746 390,523 10Jan25	2.0	THROUGHOUT - ELECTRICAL-POTLIGHT 3000K (LOWER LEVEL) BUNDLE-8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2 SWITCHES NOTE: LOCATION MAY VARY DEPENDS ON JOIST PLACEMENT DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights 4X LIVING ROOM - USE SEPARATE SWITCH
10341123		2X LIVING ROOM /VHALL USE STD. HALL 3 WAY SWITCH 2X COFFERD HALLWAY CEILING, RELOCATE STD. LIGHT USE STD. 3 WAY SWITCH
		1X UPPER HALLWAY -USE STD. 3 WAY SWITCH 1XUPPER BASEMENT STAIRS (MUDROOM LANDING) -DELET STD. LIGHT , USE SEPARATE SWITCH
		1X POWDER ROOM -USE SEPARATE SWITCH 1X SERVERY , RELOCATE STD. LIGHT , USE EXISITNG SWITCH
		4X BREAKFAST ROOM- RELOCATE STD. LIGHT -USE EXISTING SWITCH SEE SKETCH #'S 2 AND 5
1746 390,523	2.0	THROUGHOUT - ELECTRICAL-POTLIGHT 3000K (LOWER LEVEL) BUNDLE-8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2 SWITCHES NOTE: LOCATION MAY VARY DEPENDS ON JOIST PLACEMENT
10Jan25		DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights 4X MASTER BEDROOM - KEEP STD. LIGHT, USE SEPARATE SWITCH 4X PRINCIPAL ENSUITE -DELETE STD. LIGHT, USE STD. LIGHT SWITCH
		2X PRINCIPAL ENSUITE -DELETE STD. LIGHT, USE STD. LIGHT SWITCH 2X PRINCIPAL SUITE COFFERD CEILING -RELOCATE STD. LIGHT, USE STD. LIGHT SWITCH 3X LAUNDRY ROOM - DELETE STD. LIGHT, USE STD. SWITCH 2X ENSUITE 2 DELETE STD. CEILING LIGHT, USE STD. SWITCH 1X PRINCIPAL WATER CLOSET - DELETE STD. LIGHT, USE STD. SWITCH SKETCH # 5
1746 390,523 10Jan25	1.0	THROUGHOUT - ELECTRICAL-POTLIGHT 3000K (LOWER LEVEL) BUNDLE-8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2 SWITCHES NOTE: LOCATION MAY VARY DEPENDS ON JOIST PLACEMENT DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights 2X UPPER FLOOR HALLWAY - DELETE STD. LIGHT USE STD. 3 WAY SWITCH 6X KITCHEN RELOCATE STD. LIGHT - USE SEPARATE SWITCH
		SKETCH # 2 AND 5

DisciplineMS.rpt 13dec21 Page 11 of 20



Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

ELECTRICAL

ELECT Invoice		CAL Description
1746 390,528	3.0	THROUGHOUT - ELECTRICAL-RELOCATION OF SWITCHES/LIGHTS (MUST SPECIFY LOCATION)-NOTE: PLUGS CANNOT BE RELOCATED- MUST PURCHASE ADDITIONAL OUTLET.
10Jan25		RELOCATE 1X KITCHEN AND 1X BREAKFAST ROOM LIGHT TO BE ABOVE ISLAND- USE KITCHEN LIGHT SEPARATE SWITCH RELOCATE STD. UPPER HALLWAY TO BE IN CETRE OF STAIRS OPENING- USE STD. UPPER HALL 3 WAY SWITCH SEE SKETCH # 2 AND 5
1746 390,206	1.0	GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE
10Jan25 **		SEE SKETCH # 2 AND 9 DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify
1746 390,505	1.0	BEDROOM 3 - ELECTRICAL-LIGHT FIXTURE-ADDITIONAL ROUGH-IN AND COMPLETION INCLUDING LIGHT FIXTURE PER ROOM/HALL
10Jan25		1X TO BE INSTALLED IN THE CLOSET SKETCH # 5
1746 390,523 10Jan25	1.0	THROUGHOUT - ELECTRICAL-POTLIGHT 3000K (LOWER LEVEL) BUNDLE-8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2 SWITCHES NOTE: LOCATION MAY VARY DEPENDS ON JOIST PLACEMENT DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights 2 X MAIN HALL (CLOSE TO STAIRES) USE STD. 3 WAY SWITCH, DELETE STD. CEILING LIGHT 2 X SHARED BATHROOM USE SEPARATE SWITCH DELETE STD CEILING LIGHT 4 X BASEMENT BEDROOM- USE STD. SWITCH -DELETE STD. CEILING LIGHT SEE SKETCH # 'S 1, 2 AND 5
1746 714,586	1.0	KITCHEN - ELECTRICAL-SUPPLY AND INSTALL RECESSED PLUG 120V 15AMP DIRECT LINE (ARC FAULT)
10Jan25		TO BE USED FOR THE MICROWAVE DRAWER SEE SKETCH # 4 SEE SPECS
1746 390,516	1.0	SERVERY ONLY - ELECTRICAL-OUTLET-EXTRA WALL INTERIOR OUTLET (120V/15A) ON A SEPARATE CIRCUIT (ON ARCFAULT)
10Jan25		TO BE USED FOR THE WINE FRIDGE IN THE SERVERY SEE SKETCH # 4 SEE SPECS
1746 390,520	1.0	SERVERY ONLY - ELECTRICAL-OUTLET-INTERIOR DUPLEX OUTLET WITH G.F.I. ON AN EXISTING CIRCUIT
10Jan25		UPG G.F.I SEE SKETCH # 2
1746 390,519	3.0	THROUGHOUT - ELECTRICAL-OUTLET-EXTRA WALL INTERIOR OUTLET ON EXISTING CIRCUIT (DOES NOT INCLUDE KITCHEN OUTLETS)
10Jan25		1X RECREATIN ROOM TO BE INSTALLED 70"+- FROM FLOOR ABOVE THE FIRE PLACE 1X GREAT ROOM TO BE INSTALLED 70"+- FROM FLOOR ABOVE THE FIRE PLACE 1X MASTER BEDROOM TO BE INSTALLED 70"+- FROM FLOOR SEE SKETCH #'S 1,2 AND 5
1746 390,520	1.0	SERVERY ONLY - ELECTRICAL-OUTLET-INTERIOR DUPLEX OUTLET WITH G.F.I. ON AN EXISTING CIRCUIT
10Jan25		SEE SKETCH # 2
1746	1.0	FINISHED BASEMENT BEDROOM - MODIFICATION - DELETE WALL AND DOOR BETWEEN HALLWAY AND BEDROOM KEEP 15" + - (NIB WALL DUE TO HEATING VENT)
10Jan25 ** NoCat		SEE SKETCH # 1 MODIFICATION
1746 714,613 10Jan25	0.6	THROUGHOUT - ELECTRICAL-POTLIGHT (3000K) BUNDLE-8 X 4 INCH SLIM RECESSED LED DOWNLIGHT WHITE TRIM INCLUDES 2 SWITCHES NOTE: LOCATION MAY VARY DEPENDS ON JOIST PLACEMENT DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights 6X GREAT ROOM - USE SEPARATE SWITCH DRYWALL-Drywall/Ceiling cutouts for potlights; FRAMING-Frame to accommodate potlights SEE SKETCH # 2

DisciplineMS.rpt 13dec21 Page 12 of 20



Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

ELECTRICAL

Invoice	Qty.	Description
1746 390,494 10Jan25	1.0	- ELECTRICAL-CAR CHARGER-2 INCH CONDUIT WITH 8X8 BOX FOR FUTURE CAR CHARGER
1746 390,535 10Jan25	2.0	THROUGHOUT - ELECTRICAL-SWITCH-ADDITIONAL SWITCH TO BE USE FOR THE R/I CAP LIGHT 1X BREAKFAST ROOM 1X MAIN HALLWAY (COFFERED CEILING) SKETCH # 2
1746 714,390 10Jan25 **	1.0	KITCHEN - APPLIANCES - KITCHENAID 36 INCH CHIMNEY HOOD SS - KVWB606DSS SEE SPECS ALSO FOR UPGRADED KITCHEN AND LAUNDRY SPECS CABINETRY-delete stove uppers; ELECTRICAL-Notify; HEATING/AIR CONDITIONING-Duct Size remains 6 i
1746 390,528 10Jan25	4.0	- ELECTRICAL-RELOCATION OF SWITCHES/LIGHTS (MUST SPECIFY LOCATION)-NOTE: PLUGS CANNOT BE RELOCATED- MUST PURCHASE ADDITIONAL OUTLET. RELOCATE STD. LIGHT FROM BASEMENT REC ROOM, BASEMENT HALL AY, BASEMENT BATHROOM CEILING AND BASEMENT BEDROOM TO BE INSTALLED: 2X MAIN HALL WAY (COFFERED CEILING WALL) 2X BREAKFAST ROOM TO BE INSTALL AS A R/I CAP LIGHT FOR FUTURE SCONE TO BE 72" -+FROM FLOOR SEE SEPARATE CHARGE FOR A SWITCH SEE SKETCH # 2
1746 10Jan25 NoCat		THROUGHOUT - DIMMER SWITCH GREAT ROOM KITCHEN- POT LIGHT BREAKFAST ROOM - POT LIGHT LIVING ROOM DINING ROOM -POT LIGHT MAIN HALLWAY RECROOM- POT LIGHT KITCHEN (FOR THE R/ICAP LIGHT ABOVE THE ISLAND) SEE SKETCH # 1 AND 2 (MARKED WITH D)

FIREPLACE AND MANTLE			
Invoice	Qty.	Description	
1746 390,206	1.0	GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE	
10Jan25		SEE SKETCH # 2 AND 9	
		DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify	
1746	1.0	FINISHED BASEMENT FAMILY (REC) ROOM - FINISHED REC ROOM - FIREPLACE TO BE IN THE CENTER OF THE WALL +/- SKETCH # 1	
10Jan25 NoCat		MODIFICATION	

DisciplineMS.rpt 13dec21

Page 13 of 20



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

FRAMING

Invoice	Qty.	Description
1746 714,376 10Jan25 **	1.0	GREAT ROOM - WAFFLE CEILING - INSTALL WAFFLE CEILING. COFFERED CEILING IS STANDARD - GREAT ROOM - UPG SKETCH # 2 AND 3 DRYWALL-Standard Smooth Ceiling inside waffles; FRAMING-Strap Ceiling for Potlights; PAINTING-Paint moul (6)
1746	1.0	MUD ROOM - DELETE INTERIOR DOOR
10Jan25 ** NoCat		DELETE DOOR BETWEEN STAIRS LANDING AND MUD ROOM, SEE SKETCH # 2 MODIFICATION
1746 395,461 10Jan25 **	1.0	THROUGHOUT - CLASSIC COLLECTION SCHEDULE A - Choice of 20 LED (3000K) pot lights in finished areas (Second Floor Potlight(s) Require Smooth Ceiling) SEE MORE DETAILS UNDER ELECTRICAL ON MORE POTLIGHTS DRYWALL-Drywall Ceiling cutouts for potlights FRAMING-Frame to accommodate potlights 10X RECREATION ROOM - RELOCATET STD. LIGHT, USE STD. SWITCH, 2X BASEMENT USE STD. 3 WAY SWITCH RELOCATE STD. LIGHT NEAR THE STAIRS 2X BASEMENT HALL -RELOCATE STD. LIGHT, USE SEPARATE SWITCH 2X BASAMENT BATHROOM - RELOCATE STD. CEILING LIGHT, USE STD. CEILINNG SWITCH 4X DINING ROOM - USE SEPARATE SWITCH KEEP STD. LIGHT SEE SKETCH # 1 AND 2
1746 10Jan25 ** NoCat		KITCHEN - KITCHEN/SERVERY - CABINETRY-3A-Stacked upper for 30cm standard depth (includes stack moulding between cabinets)-Built in Plan (66cm at deep fridge uppers and built in) CLASSIC - UPG SKETCH # 4
1746 390,206 10Jan25 **	1.0	DRYWAL-Notify; FRAMING-Modify Bulkhead; GRANITE-delete partial countertop due to Built-in; PAINTING-GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE SEE SKETCH # 2 AND 9 DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify
1746	1.0	FINISHED BASEMENT BEDROOM - MODIFICATION - DELETE WALL AND DOOR BETWEEN HALLWAY AND BEDROOM KEEP 15" + - (NIB WALL DUE TO HEATING VENT)
10Jan25 ** NoCat		SEE SKETCH # 1 MODIFICATION

		ODUCTS / MIRRORS Description
1746	1.0	SHARED BATHROOM - SHARED BATHROOM FRAMELESS CHROME SHOWER
10Jan25 NoCat		
1746	1.0	FINISHED BASEMENT BATHROOM - FINISHED BASEMENT BATHROOM - FRAMELESS SHOWER
10Jan25 NoCat		
1746	1.0	ENSUITE 2 - MATT BLACK TRIMMED PANEL FOR TUB APPROX WIDTH 32" FIXED TO THE WALL WITH U CHANNLE ON THE SIDE AND BOTTOM
10Jan25 NoCat		SEE SKETCH

DisciplineMS.rpt 13dec21 Page 14 of 20



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

GRANITE

Invoice		Description
1746	1.0	- GRANITE - KITCHEN - GROUP 4 WITH 1 1/2 IN MITER EDGE - UPG
712,235 10Jan25		
10Jan23		
1746	1.0	KITCHEN - PLUMBING - KITCHEN SINK UPGRADE - BLANCO QUATRUS U 1 SUPER SINGLE 401248 (MIN CABINET 36
389,866	1.0	IN)
10Jan25		SEE SPEC
**		CABINETRY-upgraded kitchen sink; GRANITE-upgraded kitchen sink
1746	1.0	KITCHEN - KITCHEN/SERVERY - CABINETRY-3A-Stacked upper for 30cm standard depth (includes stack moulding between cabinets)-Built in Plan (66cm at deep fridge uppers and built in) CLASSIC - UPG
10Jan25 ** NoCat		SKETCH# 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; GRANITE-delete partial countertop due to Built-in; PAINTING-
1746	1.0	SERVERY ONLY - PLUMBING - BAR SINK - COMPLETE BAR SINK FOR SERVERY INCLUDES PLUMBING ROUGH-IN
389,832		AND MOEN ALIGN BAR PREP FAUCET (MODEL: 5965) AND BOSCO UNDERMOUNT SINK (MODEL 207029) (INCLUDING GRANITE SINK CUTOUT/POLISH) -
10Jan25		SEE SPECS
**		CABINETRY-Accommodate Servery Sink; CONCRETE AND DRAIN-Additional Stack; GRANITE-Additional Cu
1746	6.0	THROUGHOUT - GRANITE - GRANITE CUTOUT WITH STRAIGHT EDGE POLISH TO ACCOMMODATE UNDER MOUNT VANITY SINK
389,738 10Jan25		SEE SPEC FOR STUDIO SINK
10341123		SEE SPEC FOR STUDIO SINK
1746	1.0	- GRANITE - PRINCIPAL ENSUITE - GROUP 1 WITH 1 1/2 IN MITER EDGE - UPG
712,248		
10Jan25		
1746 389,827	6.0	THROUGHOUT - PLUMBING - AMERICAN STANDARD - SINK OPTIONS - UNDERMOUNT SINK - STUDIO - WHITE - MODEL 0614 000 020 (21 " INCH X 15 " INCH) -
10Jan25		SEE SPEC
**		GRANITE-see specs
1746	6.0	THROUGHOUT - DOUX SINGLE HANDLE LAV FAUCET WITH LIFT ROD DRAIN #S6910 CHROME
10Jan25		
** NoCat		GRANITE-see specs
		2 X PRINCIPAL BATHROOM / 2 X SHARED ENSUITE 1 X ENSUITE 2 AND 1 X LOWER LEVEL BATHROOM
		SEE SPEC
1746 395,462	1.0	LAUNDRY ROOM - PLUMBING-BOSCO LAUNDRY TUB MODEL T207004 18 IN X 16 IN X 10 IN DEEP
10Jan25		SEE SPEC
**		GRANITE-see specs
1746	1.0	- GRANITE - ENSUITE BED 2 - GROUP 1 WITH 1 1/2 IN MITER EDGE - UPG
712,256		
10Jan25		
		CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
1746	1.0	- GRANITE - LOWER BATH - GROUP 2 WITH 1 1/2 IN MITER EDGE - UPG
712,265		
10Jan25		CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
4-1-		
1746 389,724	21.3	LAUNDRY ROOM - GRANITE - ADDITIONAL COUNTERTOP PER SQ.FT UPGRADE 3
389,724 10Jan25		
10341123		CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
	-	

Page 15 of 20 DisciplineMS.rpt 13dec21



Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

GRANITE

Invoice	Qty.	Description
1746	1.0	- GRANITE - MAIN BATH - GROUP 2 WITH 1 1/2 IN MITER EDGE - UPG
712,241		
10Jan25		
		CABINETRY-delete std countertop; GRANITE-see upgraded single hole faucet and undermount sink
1746 389,737 10Jan25		LAUNDRY ROOM - GRANITE - GRANITE CUTOUT WITH STRAIGHT EDGE POLISH TO ACCOMMODATE UNDER MOUNT KITCHEN/LAUNDRY SINK FOR LAUNDRY SINK SEE SPECS

HARDWOOD

Invoice	Qty.	Description
1746 713,975 10Jan25	1.0	- HARDWOOD - KITCHEN/BRK - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG CABINETRY-Raise Cabinet; CERAMICS-Delete Std Ceramics
1746 713,971 10Jan25	1.0	- HARDWOOD - M/B - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG CARPET-delete std carpet; INTERIOR TRIM-supply and install quarter rounds; PAINTING-paint quarter rounds
1746 713,976 10Jan25	1.0	- HARDWOOD - SERVERY - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG CABINETRY-Raise Cabinet: CERAMICS-Delete Std Ceramics

HEATING / AIR CONDITIONING

Invoice		Description Description
1746 389,800 10Jan25	1.0	- HEATING/AIR - ROUGH-IN GAS LINE FOR GAS STOVE AT MAIN FLOOR (SEE SPECS) (HOOK-UP NOT INCLUDED) LEAVE STANDARD 120 VOLT ELECTRICAL OUTLET ON A SEPARATE CIRCUIT. * SPECIFY IF STANDARD 220V WILL STAY OR BE RELOCATED STD.ELECTRICAL 220V STAY. ELECTRICAL-Notify
1746	1.0	MUD ROOM - DELETE INTERIOR DOOR
10Jan25 ** NoCat		DELETE DOOR BETWEEN STAIRS LANDING AND MUD ROOM, SEE SKETCH # 2 MODIFICATION
1746 390,206 10Jan25 **	1.0	GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE SEE SKETCH # 2 AND 9 DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify
1746 389,796 10Jan25	1.0	- HEATING/AIR - ROUGH-IN GAS LINE FOR BBQ AT MAIN FLOOR UP TO 40 FT (QUICK CONNECT NOT INCLUDED); ELECTR ICAL OUTLET PRICED SEPARATELY IF REQUIRED TO BE INSTALLED ON THE BALCONY OFF THE KITCHEN SEE SKETCH # 2
1746 10Jan25 ** NoCat	1.0	FINISHED BASEMENT BEDROOM - MODIFICATION - DELETE WALL AND DOOR BETWEEN HALLWAY AND BEDROOM KEEP 15" + - (NIB WALL DUE TO HEATING VENT) SEE SKETCH # 1 MODIFICATION
1746 714,390 10Jan25 **	1.0	KITCHEN - APPLIANCES - KITCHENAID 36 INCH CHIMNEY HOOD SS - KVWB606DSS SEE SPECS ALSO FOR UPGRADED KITCHEN AND LAUNDRY SPECS CABINETRY-delete stove uppers; ELECTRICAL-Notify; HEATING/AIR CONDITIONING-Duct Size remains 6 i

DisciplineMS.rpt 13dec21 Page 16 of 20



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

INTERIOR TRIM AND DOORS

Invoice	Qty.	Description
1746 713,971	1.0	- HARDWOOD - M/B - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG
10Jan25 **		CARPET-delete std carpet; INTERIOR TRIM-supply and install quarter rounds; PAINTING-paint quarter rounds
1746	1.0	MUD ROOM - DELETE INTERIOR DOOR
10Jan25 NoCat		DELETE DOOR BETWEEN STAIRS LANDING AND MUD ROOM, SEE SKETCH # 2 MODIFICATION
1746	1.0	GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE
390,206 10Jan25 **		SEE SKETCH # 2 AND 9 DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify
1746	1.0	FINISHED BASEMENT BEDROOM - MODIFICATION - DELETE WALL AND DOOR BETWEEN HALLWAY AND BEDROOM KEEP 15" + - (NIB WALL DUE TO HEATING VENT)
10Jan25 NoCat		SEE SKETCH # 1 MODIFICATION
1746	1.0	THROUGHOUT - DO NOT INSTALL ANY PLANK AND POLE IN ALL WALK-IN CLOSETS, BEDROOM 3 CLOSET AND MUDROOM CLOSET
10Jan25 NoCat		SEE SKETCH #'S 1 AND 5

DisciplineMS.rpt 13dec21 Page 17 of 20 Printed and Sent: 10-Jan-25

28 of 87



Lot: 733

Model: 39-3573 A The Cedarvale Project/Phase: Country Lane / 7

PAINTING

Invoice		Description			
1746 713,971	1.0	- HARDWOOD - M/B - 5 IN VINTAGE SCULPTED NSS RED OAK (CHARACTER GRADE) UVF OIL OR PEARL NONE STD AREA - UPG			
10Jan25 **		CARPET-delete std carpet; INTERIOR TRIM-supply and install quarter rounds; PAINTING-paint quarter rounds			
1746 711,325 10Jan25	1.0	- DRYWALL - SMOOTH CEILINGS-BASEMENT-UPG			
**		PAINTING-Paint smooth ceiling			
1746 711,352	1.0	- DRYWALL - SMOOTH CEILINGS-SECOND FLOOR WITH RESILIENT CHANNEL-UPG			
10Jan25 **		ELECTRICAL-Drop electrical boxes; PAINTING-Paint smooth ceiling			
1746 714,376	1.0	GREAT ROOM - WAFFLE CEILING - INSTALL WAFFLE CEILING. COFFERED CEILING IS STANDARD - GREAT ROOM - UPG			
10Jan25 **		SKETCH # 2 AND 3 DRYWALL-Standard Smooth Ceiling inside waffles;FRAMING-Strap Ceiling for Potlights;PAINTING-Paint moul (6)			
1746	1.0	MUD ROOM - DELETE INTERIOR DOOR			
10Jan25 ** NoCat		DELETE DOOR BETWEEN STAIRS LANDING AND MUD ROOM, SEE SKETCH # 2 MODIFICATION			
1746	1.0	KITCHEN - KITCHEN/SERVERY - CABINETRY-3A-Stacked upper for 30cm standard depth (includes stack moulding between cabinets)-Built in Plan (66cm at deep fridge uppers and built in) CLASSIC - UPG			
10Jan25 ** NoCat		SKETCH# 4 DRYWAL-Notify; FRAMING-Modify Bulkhead; GRANITE-delete partial countertop due to Built-in; PAINTING-			
1746 390,206	1.0	GREAT ROOM - FIREPLACE AND MANTLE - BUILT OUT WALL ABOVE FIREPLACE			
10Jan25 **		SEE SKETCH # 2 AND 9 DRYWALL-notify; ELECTRICAL-notify; FRAMING-notify; HEATING/AIR CONDITIONING-notify; INTERIO TRIM-notify; PAINTING-notify			
1746	1.0	FINISHED BASEMENT BEDROOM - MODIFICATION - DELETE WALL AND DOOR BETWEEN HALLWAY AND BEDROOM KEEP 15" + - (NIB WALL DUE TO HEATING VENT)			
10Jan25 ** NoCat		SEE SKETCH # 1 MODIFICATION			

DisciplineMS.rpt 13dec21

Page 18 of 20



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

TOT	TTE	-		
1)1	UN	7	, , ,	 '

Invoice	Qty.	Description	
1746 389,866	1.0	KITCHEN - PLUMBING - KITCHEN SINK UPGRADE - BLANCO QUATRUS U 1 SUPER SINGLE 401248 (MIN CABINET 36 IN)	
10Jan25		SEE SPEC CABINETRY-upgraded kitchen sink; GRANITE-upgraded kitchen sink	
1746 389,832	1.0	SERVERY ONLY - PLUMBING - BAR SINK - COMPLETE BAR SINK FOR SERVERY INCLUDES PLUMBING ROUGH-IN AND MOEN ALIGN BAR PREP FAUCET (MODEL: 5965) AND BOSCO UNDERMOUNT SINK (MODEL 207029)	
389,832 10Jan25		(INCLUDING GRANITE SINK CUTOUT/POLISH) - SEE SPECS	
		CABINETRY-Accommodate Servery Sink; CONCRETE AND DRAIN-Additional Stack; GRANITE-Additional Cu	
1746 390,178	1.0	ENSUITE 2 - PLUMBING - MOEN -CHATEAU - POSI-TEMP TUB/SHOWER WITH 3 FUNCTION DIVERTER VALVE, SLIDE BAR WITH HANDH ELD AND SHOWERHEAD CHROME (MODEL: 62320/U361CI/UT2721/TL183EP/3669EP/A725)	
10Jan25		SEE SPEC	
1746 389,456	2.0	THROUGHOUT - PLUMBING - MOEN -CHATEAU - POSI-TEMP SHOWER WITH 3 FUNCTION DIVERTER VALVE, SLIDE BAR WITH HANDHELD (MODEL: 62320/U361CI/UT2721/TL182EP/3669EP/A725)	
10Jan25		1X SHARED BATHROOM / 1X BASEMENT SEE SPEC	
1746 389,814	1.0	POWDER ROOM - PLUMBING - AMERICAN STANDARD - PEDESTAL SINK - OPT POWDER ROOM BOULEVARD-WHITE MODEL 0641-800 020 8 INCH CENTRES -	
10Jan25		SEE SPEC SEE 8" WIDE SPREAD FAUCET SPECS	
1746	1.0	MASTER ENSUITE - MASTER BATHROOM SHOWER DOUX POSI TEMP SHOWER FAUCET WITH 3 FUNNCTION TRANSFER VALVE TEMP TRIM AND SLIDE BAR WITH HAND HELD SHOWER - CHROME	
10Jan25 NoCat		TS2202EP/U361C1/UTS9204/62320/3887EP/A726 SEE SPECS	
1746 389,827	6.0	THROUGHOUT - PLUMBING - AMERICAN STANDARD - SINK OPTIONS - UNDERMOUNT SINK - STUDIO - WHITE - MODEL 0614 000 020 (21 " INCH X 15 " INCH) -	
10Jan25		SEE SPEC GRANITE-see specs	
1746	6.0	THROUGHOUT - DOUX SINGLE HANDLE LAV FAUCET WITH LIFT ROD DRAIN #S6910 CHROME	
10Jan25 NoCat		GRANITE-see specs 2 X PRINCIPAL BATHROOM / 2 X SHARED ENSUITE 1 X ENSUITE 2 AND 1 X LOWER LEVEL BATHROOM SEE SPEC	
1746	1.0	MASTER ENSUITE - MASTER BATHROOM - DOUX 3 PC TUB FAUCET TRIM ONLY TS983 CHROME	
10Jan25 NoCat		SEE SPEC	
1746	1.0	POWDER ROOM - DOUX TWO HANDLE ADJUSTBLE WIDESPREAD 8" LAV FAUCET WITH LIFT ROD DRAIN #TS6925 / 69000 CHROME	
10Jan25 NoCat		SEE SPEC	
1746 395,462	1.0	LAUNDRY ROOM - PLUMBING-BOSCO LAUNDRY TUB MODEL T207004 18 IN X 16 IN X 10 IN DEEP	
10Jan25		SEE SPEC GRANITE-see specs	
1746 389,904	1.0	LAUNDRY ROOM - PLUMBING - MOEN -ALIGN - KITCHEN - SINGLE HANDLE BAR/PREP FAUCET CHROME (MODEL: 5965) -	
10Jan25		SEE SPEC	

Page 19 of 20 DisciplineMS.rpt 13dec21



Lot: 733

Model: 39-3573 A The Cedarvale **Project/Phase: Country Lane / 7**

WAFFLE CEILING

WHITEE CEIEING		
Invoice	Qty.	Description
1746 714,376	1.0	GREAT ROOM - WAFFLE CEILING - INSTALL WAFFLE CEILING. COFFERED CEILING IS STANDARD - GREAT ROOM - UPG
10Jan25	l	SKETCH # 2 AND 3 DRYWALL-Standard Smooth Ceiling inside waffles; FRAMING-Strap Ceiling for Potlights; PAINTING-Paint moul (6)

Page 20 of 20 DisciplineMS.rpt 13dec21

Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale


31 of 87

39-3573 ELEV. A

TRADITIONS

WOB V1

The Cedarvale




"WALK OUT" VERSION 1 ELEV. A & B

Legal Plan Aug. 2024

^{*} Floor plan may vary due to grading conditions.

Project: Country Lane Lot 733nit97357,3PhleseA7WOB TheoGetdan value The Cedarvale

32 of 87



Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale


33 of 87

39-3573 ELEV. A

WOB



Sketch #3 The Cedarvale





^{*} Floor plan may vary due to grading conditions.

Ţij

Z D E

Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale


35 of 87

Sketch #5


39-3573 ELEV. A




The Cedarvale





^{*} Floor plan may vary due to grading conditions.



BASEMENT BATH









HEATHWOOD HOMES

KITCHENS LIMITED 1350 Shawson Drive, Mississauga, ON LAW ICS ENDEL

T

MODEL: 39-3573 (4504) THE CLASSIC SERIES

COUNTRY LANE, WHITBY

TRADITIONS

Standard Features:

Blum Clip On Hinges Blum Metabox Drawers

Top Drawer in Master

Ensuite

Revision: Date: April 8, 2024 Scale: Not To Scale Drawn By: Sepideh B

Approved By Builder

2 X TOP DRAWERS

Date:

Model: 39-3573 A The Cedarvale


37 of 87

Sketch #7

2 × MASTER BOTH

1 × ENS 21 BATH

1 × BASEMENTBATH







Model: 39-3573 A The Cedarvale

38 of 87

Sketch # 8

2 x During Doors






COLONIAL KICK

SP

Project: Country Lane Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

7

39 of 87





Model: 39-3573 A The Cedarvale

40 of 87

NOTE: **TOP DRAWER** (AND OR SOFT CLOSE OF THE DRAWER) IS **EXTRA CHARGE** AND CAN ONLY BE ADDED IF THE ENTIRE KITCHEN HAS TOP DRAWER THROUGHOUT

18" Wide cabinet : 15B - 45cm wide pull-out door base cabinet waste/recycle centre with soft-close ([2] 35L bins per unit) (available only with 45cm wide cabinet)




24" wide cabinet :16B -60cm wide pull-out door base cabinet waste/recycle centre with soft-close ([4] bins total, including [2] 35L) (available only with 60cm or 24" wide cabinet)





Project: Country Lane Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

41 of 87



GREAT ROOM
BUILD OUT WALL



Project: Country Lane-Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

42 of 87





NFAS NF17 Mantel

FLAT WALL GREAT ROSM & (BUILT OUT WALL) * CABINET IN RECROSM



Model: 39-3573 A The Cedarvale

43 of 87

KITCHEN SINK

BLANCO

Sink Specifications

Colour

SKU

brushed finish

401248

Design and planning tips

Min cabinet size: 36 in (915 mm)

Bowl Depth: 9 in (230.0 mm)

Specifications:

Installation clips, Sink template, Installation instructions, 3 ½" (90 mm) stainless steel strainer


Depending on cabinet construction, a different cabinet size may be required. Consult the cabinet manufacturer.

Codes/Standards: ASME A112.19.3-2017/ CSA

B45.4-17

Optional Accessories

Elevated Grid 406346
Workstation 406344
CapFlow Strainer Cover Ash Cutting Board 406345
Sink Grid 406345



30"

QUATRUS U 1 SUPER SINGLE

Stainless steel brushed finish

Warranty

Limited lifetime warranty on all sinks and faucets. One-year warranty on all accessories and soap dispensers.

Code/Standards Compliance

BLANCO sinks and faucets are third-party tested and certified to CSA, cUPC, ANSI/ASME, IAPMO and NSF standards and listed by applicable certification bodies. For more information on individual product listings, contact our office or listing organization.



Need support? Learn more by watching our sink & faucet How-to videos: https://www.blanco.com/ca-en/support/how-to-videos/how-to-videos-for-sinks/



BLANCO Canada Inc 100 Corporation Drive Brampton ON L6S 6B5 Tel & Fax

Tel: 905-494-2400 Toll free: 1-877-425-2626 Fax: 905-494-2425 Toll free: 1-877-825-2626

While BLANCO strives to provide accurate information, all images and dimensions in this document are intended for reference only and are subject to change at any time without notice. This document is not intended for use as an installation guide. For technical installation details, refer to installation instructions provided with the product. BLANCO assumes no responsibility for the use of superseded or voided specifications.



Model: 39-3573 A The Cedarvale

44 of 87

KITCHEN FAUCET

MOEN[®]

FAUCET DESCRIPTION

Reflex™ pulldown system offers smooth operation, easy movement neties pullidown system offers smooth operation, easy mo and secure docking Power Clean™ spray technology Metal construction with various finishes identified by suffix

Quick connect installation
Pulldown spray with 68" braided hose
Flexible supply lines with 3/8" compression fittings
High arc spout provides height and reach to fill or clean large
pots while pulldown wand provides the maneuverability for cleaning or rinsing 360° rotating spout

Faucet designed for handle to be mounted on right side only

OPERATION

Lever style handle

Temperature controlled by 100° arc of handle travel Operates with less than 5 lbs. of force

Operates in stream or spray mode in the pullout or retracted position FLOW

Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi

CARTRIDGE

Duralast™ cartridge 1255™ Dur.
 STANDARDS


Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all

- applicable requirements therein including NSF 61/9G & 372
 Meets CalGreen and Georgia SB370 requirements
 Complies with California Proposition 65 and with the Federal Safe Drinking
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA for lever handle

WARRANTY

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner
- 10 year limited warranty when used in a multifamily installation 5 year limited warranty when used in a commercial installation Visit www.moen.com/support for complete details and limitations

Specifications




ALIGN™ Single Handle High Arc **Pulldown Kitchen Faucet**

Models: 7565 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA. (OPTIONAL 3-HOLE ESCUTCHEON 141002 AVAILABLE)





FOR MORE INFORMATION CALL: 1-800-BUY-MOEN www.moen.com

Rev. 6/20



Model: 39-3573 A The Cedarvale

45 of 87




SERVERY SINK


Phone: 416-742-1888 | Fax: 416-742-6888 www.boscocanada.com | info@boscocanada.com 5171 Steeles Avenue West | Toronto, Ontario M9L 1R5

Builder Series - Model:207029

Undermount

Rear positioned drain holes to maximize usable bowl and cabinet storage space below





Bosco Canada Inc. is known around the world for producing high quality kitchen sinks that incorporate modern design and functional superiority in every piece they manufacture.

Specifications:

- 304 Stainless Steel
- 18 Gauge
- Strainer
- Undermount Clips
- 7" Deep

Outside: 12 5/8" x 18" x 7"

Inside:

10 5/8" x 16" x 7"

Minimum cabinet size 15"

Certification/Warranty

- ASME A 112.19.3
- CSA B45.4
- · Limited Lifetime Warranty

Optional Accessories



Model: G207029

Unit: 733, Phase: 7
Model: 39-3573 A The Cedarvale info@boscocanada.com

46 of 87




Enter Model# Search

Select Page



Laundry Sinks



T207004

Drop In or undermount

Rear positioned drain holes to maximize usable bowl and cabinet storage space below

Specifications

- · 304 stainless steel 18 gauge
- 18/10 chrome nickel content
- Brushed finish
- Template
- Clips
- Strainer
- 10" Deep

Dimensions

- Outside: 20" x 18" x 10"
- Inside: 18" x 16" x 10"
- Minimum cabinet size 23"

Also available in 8" deep.

SKU: T207004 Categories: Laundry Sinks, Standard Series Tags: 207004, Drop-in sinks, Laundry, Stainless Steel Sinks

Model: 39-3573 A The Cedarvale

47 of 87

SERVERY AND LAMBRY FAUCETS

MOEN

There is more than 1 version of this model. Page down to identify the version you have.

FAUCET DESCRIPTION

- Reflex™ pulldown system offers smooth operation, easy movement Power Clean™ spray technology
 Metal construction with various finishes identified by suffix
 Duralock™ quick connect

- Pulldown spray with 68" braided hose
 Flexible supply lines with 3/8" compression fittings
 High arc spout provides the perfect height and reach for prep sinks while the pulldown feature provides maneuverability for food preparation tasks
- 360° rotating spout provides ability to install handle on either side
 Faucet designed for handle to be mounted on right side
 OPERATION

- Lever style handle
 Temperature controlled by 100° arc of handle travel
 Operates with less than 5 lbs. of force
 Operates in stream or spray mode in the pullout or retracted position
 FLOW

Flow is limited to 1.5 gpm (5.7 L/min) max at 60 psi CARTRIDGE


1255™ Duralast™ cartridge for Single-Handle Faucets

STANDARDS

- Third party certified to IAPMO Green, ASME A112.18.1/CSA B125.1 and all applicable requirements referenced therein including NSF 61/9G & 372
- Meets CalGreen and Georgia SB370 requirements
- Complies with California Proposition 65 and with the Federal Safe Drinking Water Act
- The backflow protection system in the device consists of two independently operating check valves, a primary and a secondary which prevent backflow
- ADA (for lever handle

- Lifetime limited warranty against leaks, drips and finish defects to the original homeowner

 10 year limited warranty when used in a multifamily installation
- 5 year limited warranty when used in a commercial installation
 Visit www.moen.com/support for complete details and limitations



Specifications



ALIGN™ Single Handle High Arc **Pulldown Prep/Bar Faucet**

Models: 5965 series

NOTE: THIS FAUCET IS DESIGNED TO BE INSTALLED THROUGH 1 HOLE, 1-1/2" (38mm) MIN. DIA. (OPTIONAL 3-HOLE ESCUTCHEON 141002 AVAILABLE)



TO ORDER PARTS CALL: 1-800-BUY-MOEN

www.moen.com



BOULEVARD® PEDESTAL SINK VITREOUS CHINA

BARRIER FREE (ABOVE COUNTER OR DROP-IN ONLY)

BOULEVARD® PEDESTAL SINK

0641.800 Faucet holes on 8" (203mm) centers (Illustrated)
STD 0641.400 Faucet holes on 4" (102mm) centers

☐ 0641.100 Center hole only

- · Classic styled rectangular pedestal lavatory
- · Vitreous china
- Rear overflow
- · Supplied with mounting kit
- Right Height® for greater comfort during use
- Faucet ledge with large deck area (faucet not included)
- Design coordinates with Boulevard® Toilet
- Basin has flat bottom to also allow use as an above counter sink or a drop-in sink (with u-shaped cut out)

Nominal Dimensions:

24" x 19" x 35-1/2" (610 x 483 x 902mm)

- ☐ 0641.008 Pedestal top-8" (203mm) centers
- ☐ 0641.004 Pedestal top-4" (102mm) centers
- ☐ 0641.001 Pedestal top-center hole only
- □ 0010.000 Pedestal only

Bowl sizes:

17" (432mm) wide, 12-1/2" (318mm) front to back, 5" (127mm) deep

Compliance Certifications -

Meets or Exceeds the Following Specifications:

• ASME A112.19.2 - 2008/CSA B45.1-08

SEE REVERSE FOR ROUGHING-IN DIMENSIONS

8" Holes

To Be Specified:

- ☐ Color: ☐ White ☐ Linen
- ☐ Faucet Finish:
- ☐ Supplies:
- ☐ 1-1/4" Trap:
- □ Nipple:


^{*} See faucet section for additional models available

Model: 39-3573 A The Cedarvale

49 of 87



BOULEVARD® PEDESTAL SINK VITREOUS CHINA





ABOVE COUNTER AND DROP-IN SINK CONFIGURATIONS MEET THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES. Top of sink installed at 34" (864mm) height from finished floor. Sink installed 5" (127mm) minimum from front edge of countertop. Provide 27" (686mm) knee clearance area.

NOTES:

* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIES AND "P" TRAPS ARE SUGGESTED.

* PEDESTAL ANCHORING SCREWS NOT INCLUDED.

SUITABLE FOR REINFORCEMENT ONLY. ACTUAL DIMENSIONS MUST BE TAKEN FROM FIXTURE.

FITTING NOT INCLUDED AND MUST BE ORDERED SEPARATELY.

PROVIDE SUITABLE REINFORCEMENT FOR ALL WALL SUPPORTS.

INSTALLATION INSTRUCTIONS SUPPLIED WITH LAVATORY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

© 2018 AS America Inc.

spec_0641_BoulevardPedSink Rev 2/18



Model: 39-3573 A The Cedarvale

50 of 87

ALL BATHROOMS SINKS

American Standard

Style That Works Better

& BARRIER FREE

STUDIO™ UNDERCOUNTER SINK VITREOUS CHINA

STUDIO™ UNDERCOUNTER SINK

- Rectangular undercounter mount sink
- · Made from vitreous china
- · Front overflow
- Supplied with mounting kit (047194-0070A) and template
- ☐ 0614.000 Unglazed Rim 540 x 387mm (21-1/4" x 15-1/4")
- ☐ 0614.300 Glazed underside

Bowl size:

464mm (18-1/4") wide 308mm (12-1/8") front to back 171mm (6-3/4") deep

- 0618.000 Unglazed Rim 600 x 422mm (23-5/8" x 16-5/8")
- ☐ 0618.300 Glazed underside

Bowl size:

537mm (21-1/8") wide 356mm (14") front to back 152mm (6") deep

Compliance Certifications -Meets or Exceeds the Following Specifications:


- ASME A112.19.2M for Vitreous China Fixtures
- CAN/CSA B45 series

To Be Specified: □ Color: □ White □ Bone ☐ Linen ☐ Black □ Faucet*: ☐ Faucet Finish: ☐ Supplies: ☐ 1-1/4" Trap:

MEETS THE AMERICANS WITH DISABILITIES ACT GUIDELINES AND ANSI A117.1 ACCESSIBLE AND USABLE BUILDINGS AND FACILITIES - CHECK LOCAL CODES.

Countertop 864mm (34") from finished floor. Lavatory installed 102mm (4") from front edge of countertop.
Countertop thickness to be 25mm (1") maximum.





NOTES:
WE RECOMMEND USING BASIN AS A TEMPLATE TO DETERMINE PROPER CONTOUR. CUT COUNTERTOP 38MM (1-1/2") INSIDE BASIN CONTOUR.
* DIMENSIONS SHOWN FOR LOCATION OF SUPPLIED AND "P" TRAP ARE SUGGESTED.

W UNDERCOUNTER MOUNTING KIT SUPPLIED WITH SINK,
FITTINGS NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.
SEALING COMPOUND SUPPLIED BY OTHERS.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ANSI Standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.

J48

See faucet section for additional models available

Model: 39-3573 A The Cedarvale

51 of 87



$DEMI^{\mathtt{M}}$ Product Specification Sheet

Two Piece Freestanding Collection

CF2007

Two Piece Freestanding Soaker

Size:


60" x 32" x 22"

1524 mm x 813 mm x 559 mm




- Vacuum formed acrylic reinforced with fiberglass
- Scratch, stain and fade resistant high gloss finish
- Installation friendly two piece design
- Accepts deck mounted faucet
- Includes integral pop up drain and rectangular overflow
- Includes levelling feet


TWO PIECE ASSEMBLY



TOP VIEW



END VIEW



GENERAL SPECIFICATIONS

Average Weight 90 lb Bathing Well at bottom

41 kg

Capacity Drain to Overflow

43"x 20" 1092 x 508 mm 195 litres

Water Depth Drain to Overflow Drain Opening (dia.)

16"

406 mm

Overflow Opening Drain to Floor Clearance 21/4"x 1/2" 3 1/4"

57 x 13 mm 83 mm

NOTES: Please confirm measurements on actual product to ensure proper identification. Bathtub to be installed on the floor supported by 5 self levelling feet. Adjust if required to level the bathtub for adequate drainage. Refer to installation instructions for additional information.

IMPORTANT: Dimensions of fixtures are nominal and may vary \pm ½" (6 mm). Weight may vary \pm 5 lb (2.3 kg). Drawing is not to scale. These measurements are subject to change at manufacturer's discretion.

Compliance Certifications -

Meets or Exceeds the following Specifications:

CAN/CSA - B45 Series






60 Shorncliffe Rd., Toronto, Ontario M8Z 5K1 Telephone: 416.231,9030 Fax: 416.231.0929 www.mirolin.com

Canada, U.S.A.: 800.MIROLIN(647-6546) Fax, Canada: 800.463.2236

R0084162 25 Sep. 2018





Model: 39-3573 A The Cedarvale

52 of 87



H2OPTION® SIPHONIC DUAL FLUSH ELONGATED TOILET

VITREOUS CHINA

H2OPTION® SIPHONIC DUAL FLUSH **ELONGATED TOILET**

2887.218

- · Vitreous china
- Ultra high efficiency
 - Full Flush (4.8 Lpf/1.28 gpf)
- Partial Flush (3.4 Lpf/0.92 gpf)
- · Elongated siphon action bowl with direct-fed jet
- Meets EPA WaterSense® criteria
- MaP PREMIUM listed
- Includes EverClean® antimicrobial surface
- PowerWash® rim scrubs bowl with each flush
- 305mm (12") rough-in
- Fully glazed 2" Trapway
- Generous 9" x 8" water surface area
- Chrome plated top mounted push button actuator
- Sanitary bar on bowl
- 2 color matched bolt caps
- Limited lifetime warranty on chinaware and limited five year warranty on all mechanical parts
- ☐ 2887.518 Same as above, except with Tank with AquaGuard Liner

Separate Component Parts:

- ☐ **3706.216** Bowl
- ☐ 4133A.218 Tank
- ☐ 4133A.518 Tank with AguaGuard Liner

Nominal Dimensions:

756 x 380 x 762mm (29-3/4" x 15" x 30")

Fixture only, seat and supply by others


Compliance Certifications -Meets or Exceeds the Following Specifications:

- ASME A112.19.2-2008/CSA B45.1-08 for Vitreous China Fixtures
- CALGreen and Califonia Energy Commission (CEC) Compliant
- US EPA WaterSense® criteria for UHETs

To Be Specified:

- □ Color: □ White □ Bone □ Linen
- ☐ Seat: American Standard #5257A.65C Easy Lift and Clean Elongated Seat with Cover and Slow Close hinges
- ☐ Alternate Seat:
- Supply with stop:





NOTES:
THIS COMBINATION IS DESIGNED TO ROUGH-IN AT A MINIMUM DIMENSION OF 305MM (12") FROM FINISHED WALL TO C/L OF OUTLET.
* DIMENSION SHOWN FOR LOCATION OF SUPPLY IS SUGGESTED.
SUPPLY NOT INCLUDED WITH FIXTURE AND MUST BE ORDERED SEPARATELY.

IMPORTANT: Dimensions of fixtures are nominal and may vary within the range of tolerance established by ANSI Standard A112.19.2 These measurements are subject to change or cancellation. No responsibility is assumed for use of superseded or voided pages.






Model: 39-3573 A The Cedarvale

53 of 87

Doux™





TOUCHLESS LAVATORY FAUCET



Touchless One-Handle MotionSense Wave Lav Faucet S6910EW

Deckplate included

LAVATORY FAUCETS



Single Handle Lav Faucet with Lift Rod Drain

S6910

Deckplate included

ALL BATHROOMS





POWIDER ROOM ONLY

CHROME



To order, combine the model number with one of these finish letter(s): LifeShine® Brushed Nickel (BN), Matte Black (BL) To order Chrome (C) model, use model number only.

MOEN ORDERING GUIDE

DOUX | 95




Model: 39-3573 A The Cedarvale

54 of 87



POSI-TEMP®



Posi-Temp® Tub/Shower Faucet with 3 Function Transfer Valve/Trim and Slide Bar with Hand Shower*

3887EP / U361CI / UTS9204 / TS2203EP / 62320 / A725



MASTER BATHROOM



Eco-Performance Posi-Temp® Tub/Shower Faucet*

TS2203EP / 62320



Eco-Performance Posi-Temp® Shower Only*

TS2202EP / 62320




To order, combine the model number with one of these finish letter[s]: LifeShine® Brushed Nickel [BN], Matte Black [BL] To order Chrome [C] model, use model number only.

Project: Country Lane Unit: 733, Phase: 7 Model: 39-3573 A The Cedarvale

55 of 87

MIASTER BATHROOM





ROMAN TUB FAUCETS



Two Handle Roman Tub Faucet TS983 / 4796



Two Handle Roman Tub Faucet with Hand Shower TS984/9796








Model: 39-3573 A The Cedarvale

56 of 87

ENSUITE 2 TUB


Chateau[®]



Posi-Temp® Tub/Shower Faucet with 3 Function Transfer Valve/Trim and Slide Bar with Hand Shower*


TL183EP / U361CI / UT2721 / 3669EP / A725 / 62320

HARED ANDWEASEMENT SHOWERS



Posi-Temp® Shower Only with 3 Function Transfer Valve/Trim and Slide Bar with Hand Shower*

TL182EP / U361CI / UT2721 / 3669EP / A725 / 62320



Posi-Temp® Tub/Shower Faucet with 4 Function Hand Shower* TL2359EP / 62320

Eco-Performance Posi-Temp® Tub/Shower Faucet*

TL183EP / 62320



Eco-Performance Posi-Temp® Shower Only*

TL182EP / 62320

CHATEAU FINISH OPTION




To order Chrome (C) modeL use



Model: 39-3573 A The Cedarvale

57 of 87

ENSUITE 2 TUB



1

MATTE BLACK



Model: 39-3573 A The Cedarvale

58 of 87

KitchenAid®

36" Wall-Mount Canopy Hood



Stainless Steel KVWB606DSS

General Features & Properties		
LED Task Lights	3	
Halogen Night I	Lights	
Easy In-line Cor	nversion	
Whisper Quiet® at Low Speed	System @ 49 dBA (1.5 Sones)	
Dishwasher Saf Filters	e Commercial-Style Baffle	
3-Speed Electro with Boost Fund	onic Glass Touch Control etion (10 Min.)	

Electrical Details	
Amps	15
Volts	120

Technical Details	
Blower Power	Centrifugal
Hood Type	Wall Mount
CFMs	600
Lighting Type	LED
Number of Speeds	3
Venting Type	Exterior or Recirculating
Dimensions	
Product Dimensions (H x W x D)	24-5/8" x 36" x 19-11/16"

Reference Material

Dimension Guide

Install Guide

Use & Care Guide

Warranty

Key Features & Benefits

600 CFM/65K BTU Threshold


Allows installation over any KitchenAid® regular 36- or 30-inch range or cooktop, and some commercial-style cooking surfaces with outputs up to 65K BTU.

Perimeter Ventilation

Increases ventilation system efficiency by pulling air from the edges of the hood and speeding up the movement of air at the center, allowing it to efficiently handle up to a 65K BTU total output.

Auto Speed Setting

Takes the guesswork out of protecting cabinets from steam, grease, and moisture by automatically adjusting fan speed to ventilation needs depending on the heat being produced.



NOTE: Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to @/TM © 2020. All rights reserved. Printed in the U.S.A. D200104XXE. KVWB606DSpecSheetV01.



Model: 39-3573 A The Cedarvale

59 of 87



RISE™ 48" BUILT-IN SIDE-BY-SIDE REFRIGERATOR WITH EXTERNAL ICE AND WATER DISPENSER

Signature Features

DARING OBSIDIAN INTERIOR

Inspired by volcanic glass, this industry-exclusive dark finish draws attention with high-contrast style. Fine foods and fresh produce emerge like vibrant art, with LED lighting showcasing your ingredients against the alluring interior.

PRECISION TEMPERATURE MANAGEMENT™ SYSTEM

Electronically controlled sensors monitor the environment, automatically adjusting temperatures to maintain the ideal level for optimal food preservation.

SMOOTH CLOSE CRISPER DRAWERS

Each crisper drawer within the refrigerator smoothly opens and closes quietly, even while fully loaded with produce and fresh ingredients.

MULTI-POINT CINEMATIC LIGHTING

Illuminate food items against the Daring Obsidian Interior.
Breathtaking Multi-Point
Cinematic Lighting ramps up in intensity as you open the door to increase visibility and highlight your ingredients.

QUIETEST LUXURY BUILT-IN SIDE-BY-SIDE REFRIGERATOR

Running at 39 dBA, this refrigerator line-up has the quietest luxury built-in side-by-side refrigerators. With no abrupt start or stop cycles, this refrigerator fades into the background and becomes an unobtrusive piece of your kitchen.

$\begin{array}{l} \textbf{RISE}^{\text{TM}} \textbf{ CUSTOM-KNURLED} \\ \textbf{HANDLE} \end{array}$

Forged for an era of striking proportions, robust lines draw the eye and an asymmetrical, diamond-knurled texture wraps around a strong, postured handle.

EXTERNAL ICE AND WATER DISPENSER

Fill your glass with fresh ice and water from a dispenser conveniently located in the door.

SOLID GLASS AND METAL

Each crisper drawer, shelf and door bin in the refrigerator is made up of solid glass and metal, reflecting and diffusing light against the Obsidian interior to enhance the visibility of your items. Each carefully chosen material is naturally durable and odor resistant.

GLASS SHELVING

Showcase your ingredients with full-width glass and metal shelves. The clear glass allows light to filter through the substantial shelves, enhancing the visibility of everything inside the refrigerator.

JBSS48E22L



Dimensions

Depth Closed Excluding Handles: 63.50 cm

Depth Closed Including Handles: 70.33 cm

Depth With Door Open 90 Degree: 128.75 cm

Depth Excluding Doors: 56.83 cm

Gross Weight: 305.27 kg

Freezer Capacity Volume: 291.49 l

Height: 211.77 cm

Height To Top Of Cabinet: 189.23 cm

Net Weight: 280.77 kg

Total Refrigerator Capacity Volume: 832.021

Refrigerator Capacity Volume: 19-1/10

Width Doors Open 90 Degrees: 128.75 cm

Width: 122.87 cm

Depth: 70.48 cm

Controls

Automatic Defrost: Yes

Control Location: Exterior

Control Type: Electronic

Technical Specifications

Exterior Details

Cabinet Color: Grey

Cabinet Finish: Smooth

Door Color: Stainless Steel

Door Finish: Smooth

Door Style: Flat

Handle Color: Stainless Steel

Handle Material: Metal

Handle Type: Reach-Through Handle

Hidden Hinge: Yes

Base Grille Color: Black

Details

Design Expression: RISETM

Filter Details

Fresh Flow Air Filter Included: No

Water Filter Indicator/Reset: Yes

rioduce rieserver. Ye

Water Filter Location: Exterior

Icemaker Details

Icemaker: Factory Installed

Icemaker Location: Freezer

Refrigerator Details

Non Climate Control Drawers: 2 Full-Width

Number of Doors: 2

Number of Interior Shelves: 4

Refrigerator Door Bins:

https://www.jennair.ca/en_ca/printpage.JBSS48E22L.html

R

1/2

Model: 39-3573 A The Cedarvale

Refrigerator Type: Side-by-Side

Installation Option: Built-In

Freezer Details

Freezer Door Bins: 3 Adjustable Full-Width

Freezer Drawer/Basket: 2 Full Width Lower

Freezer Lighting: LED

Freezer Number of Shelves: 6

Freezer Shelves:

- 2 Adjustable Full-Width Wire
 4 Adjustable Full-Width Wire

Certifications

CEE Tier Rating: Tier I

ENERGY STAR Qualified: ENERGY STAR® Qualified

Star K Certified: Yes

Prop 65: Standard

Filter Details

Air Filter Indicator/Reset: No

1 Full-Width Gallon3 Adjustable Full-Width

Refrigerator Lighting: LED

Spill-Proof Glass Shelves: 4 Adjustable Full-Width

Temperature-Controlled Drawers: 1 Full-Width

Smart Compatibility

Connectivity: No

Works With: No

Dispenser Details

Dispenser Options:

Filtered Water

Ice Ice Dispenser Lock

Measured Fill

Dispenser Type: Exterior Ice and Water

LCD Touch Screen: No


Door Ajar/Open Alarm: Yes

Max Cool/Fast Cool: Yes

Sabbath Mode: Yes

®/™ © 2024 JennAir. All rights reserved. Specifications subject to change without notice.





Description		Inches (cm)
Α	Total height	833/8" (211.8)
В	Height to top of doors	741/2" (189.2)
С	Height of Cabinet	71" (180.4)
D	Height to top of machine compartment cover	833/16" (211.3)
E	Depth to machine compartment cover	1915/16" (50.6)
F	Depth with doors	25" (63.5)
G	Depth with handles	2711/16" (70.4)

Interior dimensions	Width Inches (cm)	Height Inches (cm)
Refrigerator Compartment 42" 48"	20 ¹² / ₁₅ " (52.9) - 24 ⁵ / ₁₅ " (61.8)	67 ⁻ / ₁₆ " (170.4)
Freezer Compartment 42" 48"	14 ⁹ / ₁₆ " (36.4) 16 ¹³ / ₁₆ " (42.7)	663/4" (169.6)

Location Requirements


AWARNING



Explosion Hazard

Keep flammable materials and vapors, such as gasoline, away from refrigerator.

Failure to do so can result in death, explosion, or fire.





To ensure proper ventilation for your refrigerator, allow for 1/2" (1.27 cm) of space on each side and at the top. Allow for 1" (2.54 cm) of space behind the refrigerator. If your refrigerator has an ice maker, allow extra space at the back for the water line connections. When installing your refrigerator next to a fixed wall, leave a 2" (5.08 cm) minimum space on each side (depending on your model) to allow the doors to swing open.

NOTES:

- This refrigerator is intended for use in a location where the temperature ranges from a minimum of 55°F (13°C) to a maximum of 110°F (43°C). The preferred room temperature range for optimum performance, which reduces electricity usage and provides superior cooling, is between 60°F (15°C) and 90°F (32°C). It is recommended that you do not install the refrigerator near a heat source, such as an oven or radiator.
- Normal minimum cabinet cut-out width required for product installation is 36" (91.44 cm). However, if the product is placed against an extended wall and the ability to remove the crisper pans is desired, an additional 18" (45.72 cm) of cabinet width is required, so a total cabinet opening width of 54" (137.16 cm) is recommended.

P






\	Description	Inches (cm)
Α	Width from FC side of refrigerator to handle - door fully open 130°	
	48"	11 ⁵ / ₈ " (29.5) 13 ¹ / ₄ " (33.6)
В	Width from FC side of refrigerator to handle - door fully open 110° 42° 48°	7 ⁵ / ₈ " (19.3) 8 ⁷ / ₁₆ " (21.5)
С	Width from FC side of refrigerator to handle - door open 90°	211/16" (6.8)
D	Width from RC side of refrigerator to handle - door fully open 110"	
	42" (48")	9 ⁵ / ₈ " (24.5) 10 ⁷ / ₆ " (27.6)
E	Width from RC side of refrigerator to handle - door fully open 130° 42" 48"	15 ¹ / ₂ " (39.3) 17 ³ / ₄ " (45.1)
F	Depth to machine compartment cover	1915/16" (50.6)
G	Depth without doors	223/8" (56.8)
Н	Depth with doors	25 (63.5)
1	Depth with top grill	2513/18" (65.5)
J	Depth with handles	2711/16" (70.4)
K	Depth with RC door open 90°	47³/₁₅" (119₋9) 50¹¹/₁₅" (128.8)
L	Space required for water lines and power chord	1" (2.54)
М	Space required for side cabinet for the door fully open	6" (15.24)



Unit: 733, Phase: 7
Mode N39-A473 Product Dimeration Guide for in

63 of 87 moders JBS 332 22130/48E22L00

Power chord location



Electrical Requirements

AWARNING



Electrical Shock Hazard

Plug into a grounded 3 prong outlet.


Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire, or electrical shock.

Electrical: A 115V, 60 Hz, AC only, 15A or 20A fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your refrigerator be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.




Water: A cold water supply with water pressure of between 30 and 120 psi (270 kPa and 827 kPa) is required to operate the water dispenser and ice maker. If you have questions about your water pressure, call a licensed, qualified plumber.


Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice. Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

A

Project: Country Lane Unit: 733, Phase: 7 APTIME LANGE Guide for Product Pigners on Guide for Pigners o



	Description	Inches (cm)
A	Width of FC door 48"	17½" (44.4) 20" (50.8)
В	Width of RC door 42 48"	23½" (59.7) 27" (68.6)
С	Space between doors	1/4" (0.65)
D	Overall width with band 48*	42°/:8" (107.2) 48³/:6" (122.4)
E	Height of door handles	45" (114.3)
F	Height to top of door handles	633/8" (161.0)
G	Height of doors	7015/16" (180.2)
Н	Height of grille	39/16* (9.0)
I	Height to bottom of the Dispenser	385/16" (97.3)
J	Width of Dispenser	93/16" (23.3)
K	Height of Dispenser	711/18" (19.5)
L	Water line location distance from side	173/4" (45.0)
M	Water line location distance from front	31/4" (8.2)
N	Height of grille (top)	87/8" (22.6)
0	To bottom of solid soffit (minimum/maximum)	83½" (212.1) 84 ⁵ / ₈ " (215)
P	Overall width with side trims 42" 48"	42 ³ / ₈ " (107.6) 48 ³ / ₈ " (122.8)



Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice. Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice. W11593506A

Model: 39-3573 A The Cedarvale



RISETM 24" BUILT-IN UNDERCOUNTER BEVERAGE CENTER, LEFT SWING

Right

Signature Features

DARING OBSIDIAN INTERIOR

Inspired by volcanic glass, this dark finish erupts with reflective, high-contrast style. Let the object of your desire emerge like vibrant art, begging to be consumed.

UV-RESISTANT THERMAL GLASS

Sustain what satiates. Doublepaned glass filters out ultraviolet light and rejects temperature swings to reserve the finest tastes for your discerning palate.

SMOOTH CLOSE DOOR

Quiet, soft, secure. An articulating hinge discreetly ushers the door open and gently pulls it closed.

Technical Specifications

EMOTIVE CONTROLS

Hold sway over every zone. Let your light-guided touch coax out the flavors of beverages, spirits and beyond.

LED LIGHTING

LED lights instinctively come alive, chasing away shadows to reveal vivid details.

INDEPENDENT TEMPERATURE ZONES

Compose ideal climates for choice beverages and tempting bites. Two temperature zones and six curated presets await your command

GLASS SHELVES

Gaze through platforms of glass wrapped in unyielding shelf frames.

SMOOTH CLOSE RACKS

Smooth moves. Each beechwood rack opens and closes fluidly and quietly, even when fully loaded.

13 BOTTLE CAPACITY

Take your fill. Relish the spinetingling flavors of imbibements at your leisure.





Dimensions

Gross Weight: 59.87 kg

Height: 86.68 cm

Net Weight: 54.88 kg

Width: 60.64 cm

Depth: 60.17 cm

Controls

Automatic Defrost: Yes


Control Lockout: No

Cooling On/Off: Yes

Door Ajar/Open Alarm: Yes

Max Cool/Fast Cool: Yes

Sabbath Mode: Yes





Signature Females

RIGHT SWING DOOR JUBILLAZALL

DARING OBSIDIAN INTERIOR

Inspired by volcanic glass, this dark finish erupts with reflective, high-contrast style Let the object of your desire emerge like vibrant art, begging to be consumed.

UV-RESISTANT LOW-E THERMAL GLASS

Sustain what satistes. Doublepaned glass helps filter out ultraviolet light and helps reject temperature swings to reserve the finest tastes for your discerning palate.

SMOOTH CLOSE DOOR

Quiet, soft, secure. An articulating hinge discreetly ushers the door open and gently pulls it closed.

Team cal Specifications

EMOTIVE CONTROLS

Hold sway over every zone. Let your light-guided touch coax out the flavors of beverages, spirits and beyond.

LED LIGHTING

LED lights instinctively come alive, chasing away shadows to reveal vivid details.

INDEPENDENT TEMPERATURE ZONES

Compose ideal climates for choice beverages and tempting bites. Two temperature zones and six curated presets await your command.

GLASS SHELVES

Gaze through platforms of glass wrapped in unyielding shelf frames

SMOOTH CLOSE RACKS

Smooth moves Each; beechwood rack opens and closes fluidly and quietly, even when fully loaded.

13 BOTTLE CAPACITY

Take your fill. Relish the spinetingling flavors of imbihements at your leisure.



for an one

Depth Closed Excluding Handles: 23-7'8 in

Height. 34-1-2 in

Sec. 1

Ice Maker On/Off. Yes

Control Lockout: No

Cooling On/Off: Yes

Number of Temperature Controlled Zones. 2

Door Ajar/Open Alarm. Yes

Sabbath Mode: Yes

Decision I pre

Design Expression- RISETM

Sugaran Raman

Installation Option: Undercounter

Prop 65: Standard

41-1

Handle Material: Metal

Handle Type. Reach-Through Handle

Handle Location Horizontal

Door Style: Flat

Reversible Door: No

Cabinet Finish: Textured

Window: Yes

PE 19

Intenor Light: LED

1 - 1, . .

Number of Racks: 2

Number of Shelves 2

Rack Front Material. Wood

ADA Compliant: No

Energy Star® Qualified: No

Learning to

Type of Refrigerator: Beverage Center

.

Installation Configuration: Undercounter

7/20/24, 11:57 AM

Project: Country Lane Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale

67 of 87

Exterior Details

Cabinet Color: Black Cabinet Finish: Textured

Door Color: Stainless Steel

Door Style: Flat

Handle Location: Horizontal

Handle Material: Metal

Handle Type: Reach-Through Handle

Reversible Door: No

Cabinet Material: Black Painted Steel

Certifications

ADA Compliant: No

ENERGY STAR Qualified: ENERGY STAR® Qualified

Star K Certified: Yes Prop 65: Standard

Icemaker Details

Ice Maker On/Off: Yes

Details

Ice Maker On/Off: Yes

Number of Racks: 2

Number of Shelves: 2

Rack Front Material: Wood

Refrigerator Type: Beverage Center

Zone 1 Capacity: 24 Bottles

Zone 1 Temperature Range: 33F to 40F

Zone 2 Capacity: 13 Bottles

Zone 2 Temperature Range: 42F to 64F Installation Option: Undercounter

Refrigerator Details

Liner Finish: Plastic

Number of Temperature Controlled Zones: 2

Interior Details

Interior Light: LED

®/™ © 2024 JennAir. All rights reserved. Specifications subject to change without notice.




D IMMdEI:N953503 N The Cedarvale

68 of 87

JENNAIR® DUAL-FUEL RANGES

PRODUCT

	30" DUAL-FUEL RANGE JDRP430H	36" DUAL-FUEL RANGE JDRP436H
Overall Width (A)	29-7/8" (75.9 cm)	35-7/8" (91.1 cm)
Euli nose Height (B)	2-1/8" (5.4 cm)	2-1/8" (5.4 cm)
Control Panel Height (G)	7-1/2" (19.1 c/~)	7-1/2" (19.1 cm)
Door Height (D)	20-11/16° (52.6 cm)	20-11/16" (52.6 cm)
Poor Be Nom (e Handle Top: RISE" (E)	20" (50.8 cm)	20" (50.8 cm)
Door Bottom to Handle Top: NOIR" (E)	20/5/8 · (52.4 cm)	20-5/8" (52.4 cm)
Toe-Krak Keight (F)	6-11/16' (17 cm)	6-11/16" (17 cm)





IMPORTANT: Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All JennAir appliances are appropriately UL, CUL or CSA approved.

W11358022A

DP

Unit: 733, Phase: 7


D MMdE: N953522 N The Cedarvale

JENNAIR® DUAL-FUEL RANGES

PRODUCT

69 of 87

	/		
	30" DUAL-FUEL RANGE JDRP430H	36" DUAL-FUEL RANGE JDRP436H	
Depth with Cantrol Panel Evenhand (6)	27-11/16" (79.3 cm)	27-11/16" (70.3 cm)	
Depth with Handle: RISET(H)	29-13/16/ (75.7 cm)	29-13/16" (75.7 cm)	
Repth with Hamdle, NOIR (H)	29-5/16 (74.5 cm)	29-5/16 (74.5 cm)	
Benth with Book Fully Specially	45-1/2" (118.1 cm)	46-1/2" (118.1 cm)	



TOP VIEW



Unit: 733, Phase: 7


D MdE: N953522 N The Cedarvale

JENNAIR® DUAL-FUEL RANGES

PRODUCT

70 of 87

*	30" DUAL-FUEL RANGE JDRP430H	36" DUAL-FUEL RANGE JDRP436H	48" DUAL-FUEL RANGE
Grakes Top (faight (A))	37-5/16" (94.8 cm)	37-5/16" (94.8 cm)	37-5/16" (94.8/cm)
Gooking Surface Top Haight (B)	36" (91.4 gm)	36' (91.4 cm)	36" (91.4 cm)
Data Top Height (3)	27-13/16" (70.6 cm)	27-13/16" (70.6 cm)	27-13/16" (70.6 cm)
Handle Top Height- RISE - (0)	27" (68.6 cm)	27" (68.6 cm)	27" (68.6 cm)
Handle Top Height: NOIR ~ (D)	27-5/8" (70.2 cm)	27-5/8" (70.2 cm)	27-5/8" (70.2 cm)
Toe-Kick Height (E)	6-11/16" (17 cm)	6-11/16" (17 cm)	6-11/16" (17 cm)
		OPTIONAL ACCESSORIES	
Fright to Topic 2" Stainless Size Backsplash (F)	45" (114.3) min.	45" (114.3) min.	45" (114.3) min.





IMPORTANT: Minimum height dimensions are at the lowest point of the height adjustment range. When the leveling legs are fully extended, all heights have 1-3/4" (4.4 cm) of added height



Unit: 733, Phase: 7

D MdE: N953522 N The Cedarvale


JENNAIR® DUAL-FUEL RANGES

PRODUCT

4

71 of 87

/			
	30" DUAL-FUEL PANGE JDRP430H	36" DUAL-FUEL RANGE JDRP436H	48" DUAL-FUEL RANGE 3DRPS48H
Depth with Book Fully Open (5)	46-1/2" (118.1 cm)	46-1/2" (118.1 cm)	46-1/2" (118.1 cm)
Copts with DISE? Handle (N)	29-13/16 ⁻ (75.7 cm)	29-13/16" (75.7 cm)	29-13/16" (75.7 cm)
Depth with NOIR THantle (H)	29-5/16 (74.5 cm)	29-5/16" (74.5 cm)	29-5/16" (7+.5 cm)
Depth with Control Panel Gwerhang (i)	27-11/16" (70.3 cm)	27-11/16" (70.3 cm)	27-11/16" (70.3 cm)
Depth to Toe-Kick with Door (1)	29-3/8" (67 cm)	26-3/8" (67 cm)	26-3/8" (67 cm)
Depth with RISE - Dear (K)	27-1/4" (69.2 cm)	27-1/4" (69.2 cm)	27- / 4" (69.2 cm)
કોલુન્ટ્રેન પ્રવૃત્તિ NOIX ^ન ઉલ્લય (K)	27-1/4" (69.2 cm)	27-1/4" (69.2 cm)	27-1/4" (69.2 cm)





Unit: 733, Phase: 7

D IMMdEI: \$953563 A The Cedarvale


JENNAIR® DUAL-FUEL RANGES

OPENING AND CLEARANCE

72 of 87

	30" DUAL-FU/:L RANGE	36" DUAL-FUEL RANGE	48" DUAL-FUEL RANGE JDRP548H
Combustible Area Above Gooking Surface Width (A)	30" (76/2 cm) min.	36" (91.4 cm) min.	48" (121.9 cm) n in.
Echlom of Cabinet Height Above Cooking Sir lare (3)*	42" (06.7 cm) min.	58" (147.3 cm) min.	58" (147.3 gm) min.
Eaction of Galainet Height Above Countertop (O)	18" (38.1 cm) min.	18" (45.7 cm) min.	18" (46.7 cm) min.
Distance to Fixed Wall or Compustible Matterial (9)	12" (30.5 cm) min	12" (30.5 cm) min.	12" (30.5 cm) min.
Spening Width (E)	30" (762 cm) min.	36" (91.4 cm) min.	48 ' (121.9 cm) min.

^{*}If installing a hood or hood liner above the range, follow the hood or hood liner instructions for dimensional clearances above the cooking surface





Project: Country Lane

Unit: 733, Phase: 7

D IMMdEI: No. 3523 N The Cedarvale


JENNAIR® DUAL-FUEL RANGES

OPENING AND CLEARANCE

73 of 87

	30" DUAL-FUEL RANGE JDRP47.0H	36" DUAL-FUEL RANGE JDRP436H	48" DUAL-FUEL PANCE JDRP548H	
Spra Germaleanth (F)	13 (33 cm) max.	13" (33 cm) max.	13" (33 cm) max.	
Depth to Wall (6)°	6" (15.2 cm) min.	6" (15.2 cm) min.	6 (15.2 cm) min.	

If the back wall is constructed of a combustible material and a backsplash is not initialled, a 5" (15.2 cm) minimum clearance is required





D MMLE: N9S8572 NTSe Cedarvale

74 of 87

JENNAIR® DUAL-FUEL RANGES


ELECTRICAL REQUIREMENTS

	/			
	30" DUAL-FUEL RANGE JDRP430H	36" DUAL-FUEL RANGE JDRP436H	48" DUAL-FUEL RANGE JDRP548H	
Electrical Zone Width (A)	22" (55.9 cm)	28' (71.1 cm)	40° (101.6 cm)	
Électrical Zone Height (B)	15" (38/1 cm)	15" (38.1 cm)	(38.1 cm)	
Bigavical Zone Depath (6)	5" (12.7 cm)	5' (12.7 cm)	5' (12.7 cm)	


ELECTRIC REQUIREMENTS CHECKLIST

- ☐ A 240 volt, 60 Hz, fused, grounded circuit is required.
- ☐ For 30" and 36" ranges, use a 40-amp circuit.
- ☐ For 48" ranges, use a 50-amp circuit.
- ☐ A dedicated circuit is recommended.

RECOMMENDED ELECTRICAL ZONE



WIDTH TO ELECTRICAL CONDUIT



IF YOU HAVE QUESTIONS ABOUT YOUR ELECTRICAL SUPPLY, CALL A LICENSED, QUALIFIED ELECTRICIAN.

K

Project: Country Lane

Unit: 733, Phase: 7

D MM 5: N9\$8572 NT\$ e Cedarvale


JENNAIR® DUAL-FUEL RANGES

GAS REQUIREMENTS


75 of 87

	30" CONNECTED DUAL-FUEL RANGE JDRP430H	36" CONNECTED DUAL-FUEL RANGE JDRP436H	48" DUAL-FUEL RANGE JDRPS48H
Ges Spaning Width (A)	6" (15/2.cm)	14" (35.6 cm)	24" (61 cm)
Gas Opening Height (B)	3" (7.6 cm)	3" (7.6 cm)	3" (7.6 cm)
ess Geaning Dapth (&	f" (12.7 cm)	5" (12.7 cm)	(12.7 cm)
Distance from Side Cabinet to Gas Opening (D)	6" (15.2 cm)	6" (15.2 cm)	6' (15.2 cm)
Wildlife to Gas Inlat (E)	12-3/4" (32.4 cm)	12-3/4" (32.4 cm)	12-3/4" (32.4 cm)

RECOMMENDED GAS ZONE



WIDTH TO GAS INLET



IF YOU HAVE QUESTIONS ABOUT YOUR GAS SUPPLY, CALL A LICENSED, QUALIFIED SERVICE TECHNICIAN.





36" RISE™ DUAL-FUEL PROFESSIONAL-STYLE RANGE

Signature Features

REMOTE ACCESS

Preheat. Check cooking status. Personalize settings. Connect to WiFi for real-time notifications and control your appliance from anywhere. Tap and swipe on both iOS and Android devices.*

JENNAIR® CULINARY

With step-by-step support, savor the full culinary experience backed by customized algorithms, featuring full-color food photography, doneness levels, pan types and menuspecific tips.

SMOOTH CLOSE DOOR

Quiet, soft, secure. Your oven gently pulls the door closed.

Technical Specifications

HALO-EFFECT KNOBS

A halo of luminary LEDs glows softly when the burner is lit or the oven is on.

DUAL-FAN TRUE CONVECTION

Steady heat, circulated by whirling metal blades, weaves around every flat tine. Beyond baking, wield your cooking prowess with the help of the culinary center through the app, from marbled meats to succulent

SMOOTH CLOSE DOOR

Quiet, soft, secure. Your oven gently pulls the door closed.

CAST IRON GRATES

Robust geometric grates form one graceful surface, crafted to withstand heavy woks and

CONNECTED TEMPERATURE PROBE

Know when dinner is done without ever opening the door. Precision readings of food's internal temperature are sent directly to the app.

20,000 BTU DUAL-STACKED POWERBURNER

This 20,000 BTU dual-stacked PowerBurner can handle highpowered cooking while still being gentle enough for delicate simmering with turndown of 1,650 BTU.

JDRP436HL



Dimensions

Depth: 75.72 cm

Depth Closed Excluding Handles: 70.33 cm

Depth Closed Including Handles: 75.73 cm

Depth With Door Open 90 Degree: 118.11 cm

Gross Weight: 201.39 kg

Height: 91.44 cm

Net Weight: 176.45 kg

Oven Interior Depth: 41.40 cm

Oven Interior Height: 36.32 cm

Oven Interior Width: 75.95 cm

Width: 91.12 cm

Common Size: 36

Electrical

Power Cord Included: Yes

Cooktop Details

Auto Re-ignition:

- YesYes
- Cooktop Control Knob Type:
 - Metal
 - Metal

Cooktop Control Knob Color:

- Stainless Steel
- Stainless Steel

Cooktop Control Type:

- Knobs Knobs
- Cooktop Control Location:
 - Front
 - Front

Cooktop Surface Color:

- Black
- Black

Cooktop Surface Material:

- Porcelain Coated Steel
- Porcelain Coated Steel

Griddle Included:

Oven Cavity Details

Convection Functions:

- Bake
- Roast
- Bake
- Broil Roast

Door Removable:

- YesYes

Hidden Bake Element:

- YesYes

Interior Color:

- BlackBlack

Number of Oven Lights:

- 3

Number of Oven Racks:

- Number of Rack Guides:

• 5

Unit: 733, Phase: 7

Model: 39-3573 A The Cedarvale

Print Page 77 of 87

N/AN/A

Heating Element On Indicator Light:

NoNo

Hot Surface Indicator Light:

NoNo

Ignition Type: Flame-Sensing™ Re-ignition

Cooktop Configuration: All Burners

Exterior Details

Door Type:

Metal & Glass

Metal & Glass

Handle Color:

Stainless SteelStainless Steel

Handle Type:

Towel BarTowel Bar

Handle Material:

MetalMetal

Oven Control Knob Color:

Stainless SteelStainless Steel

Oven Control Knob Type:

MetalMetal

Oven Control Location:

FrontFront

Oven Control Type:

KnobsKnobs

Oven Window Size:

LargeLarge

Details

Cooktop Configuration:

All BurnersAll Burners

Design Expression:

• RISETM • RISETM

Fuel Type:

Dual FuelDual Fuel

Natural Gas Convertible:

LP Convertible:

Yes - Kit Included
Yes - Kit Included

• 5

Oven Cleaning Type:

Self-CleaningSelf-Cleaning

Oven Cooking System:

True Convection
 True Convection

Oven Light Type: Halogen

Oven Rack Type:

Gliding Roll-OutGliding Roll-Out

Automatic Convection Conversion Temperature

Oven Light Switch Location: Oven Control

Element/Burner Details

Center Front Element-Burner Power:

20,000 BTU20,000 BTU

Center Front Element-Burner Type:

Dual-Stacked Burner
 Dual-Stacked Burner

Center Rear Element-Burner Power:

9000BTU9000BTU

Center Rear Element-Burner Type:

Dual-Stacked Burner
 Dual-Stacked Burner

Cooktop Element Style:

Sealed Burner
Sealed Burner

Left Front Element-Burner Power:

20,000 BTU20,000 BTU

Left Front Element-Burner Type:

Dual-Stacked Burner
 Dual-Stacked Burner

Left Rear Element-Burner Power:

18,000 BTU18,000 BTU

Left Rear Element-Burner Type:

DualDual

Number of Cooking Element-Burners:

Right Front Element-Burner Power:

20,000 BTU20,000 BTU

Right Front Element-Burner Type:

Dual-Stacked Burner
 Dual-Stacked Burner

Right Rear Element-Burner Power:

• 18,000 BTU

Project: Country Lane Unit: 733 Phase: 7 UNDER COUNTER MICROWAVE VEW THE THE COUNTER MICROWAVE VEW THE THE COUNTER MICROWAVE VEW THE THE THE COUNTER MICROWAVE VEW THE MICROWAVE VEW THE COUNTER MICROWAVE VEW THE MICROWAVE V

Significant Features

1.2 CUBIC FOOT CAPACITY

Explore your options. There's room for whatever you're craving.

MULTI-STAGE PROGRAMMING

Control at will. Combine up to four power levels and keep your meal warm until you're ready to

950-WATT MICROWAVE

This luxury under counter microwave offers 950 watts of power, along with exceptional cooking and heat performance.

STEALTH FLUSH INSTALL

Flush-to-cabinet design creates a subtly striking, unbroken line across the kitchen. The microwave drawer merges discreetly into undercounter cabinetry-a bold move for open kitchen designs, islands and creative explorations.

SENSOR REHEAT

Detecting humidity released by food, an intuitive sensor programs the appropriate remaining reheat time.

EMOTIVE CONTROLS

Striking, intuitive and easy to clean. Inviting controls wait expectantly for the lightest touch to unleash performance.

ONE TOUCH ACCESS

With zero handles, a flat-front design provides limitless integration and opens at your

DIVERGENT DRAWER DESIGN

Surrender to open and creative configurations with discrect integration that fits anywhere you can dream up.

ADD MINUTE

Microwave Selections:

· Add A Minute

Auto Cook

Beverage Control Lock Cook Cook Power

Defrost
Dinner Plate
End of Cycle Signal
Fresh Vegetable
Frozen Entree
Keep Warm
Off/Cancel

Defrost

Pause

This one-touch selection automatically adds a minute to the cooking time at 100% power INTOFS24IL



Capacity, 1-1:5

Depth. 26-3:16 in

Height: 15.0 in

Width 24.0 in

Number of Keypads: 28

Number of Quick Touch/One-Touch Selections:

Location of Controls: Right

Watts: 1670

Technical Sheet Technis

Size. 24 in

Microwave Type Drawer

Interior Depth 16-9/16

Interior Height: 7-1/8

Interior Width 17-15-16

Sensor Cooking: Yes

Cooking Power: 950 w

Cavity Finish: Powder Coat

Convection: No

Grill: No

Interior Light: Incandescent

Turntable: NA

Scrolling Electronic Display Yes

Number of Power Levels: 11

Clock: Yes

One Touch Cooking: Yes

Night Light: No

harma.

Number of Sensor Control Keypads: 3


Popcom Potato Reheat Soften/Melt Sound On'Off Timer

Model: 39-3573 A The Cedarvale 24" (61.0 CM) AND 30


79 of 87

R. 15³/16" (395.3 mm)

Cabinet Dimensions




Model: 39-3573 A The Cedarvale




Dimension A:
24" (61.0 cm) Product - 23"/s" (60.6 cm)
30" (76.2 cm) Product - 29"/s" (76.0 cm);
Dimension B:
JMDFS24GS Model - 15/s" (4.1 cm)
GMDFS30HL Model - 1" (4.2 cm)
JMDFS24HM Model - 13/s" (4.4 cm)
JMDFS30HM Model - 11/s" (4.4 cm)

В

Optional 27" (08.6 cm) Trim Kir.



The drawer opens 151/4" (38.7 cm).



80 of 87

AWARNING



Electrical Shock Hazard

Plug into a grounded 3 prong outlet.

Do not remove ground prong.

Do not use an adapter.

Do not use an extension cord.

Failure to follow these instructions can result in death, fire, or electrical shock.

IMPORTANT: Observe all governing codes and ordinances. **Required:**

 A 120 V, 60 Hz, AC-only, 15 or 20 A electrical supply with a fuse or circuit breaker.

Recommended

- A time-delay fuse or time-delay circuit breaker
- A separate circuit serving only this Microwave Drawer

GROUNDING INSTRUCTIONS

For all cord connected appliances:

The microwave oven must be grounded. In the event of an electrical short circuit, grounding reduces the risk of electric shock by providing an escape wire for the electric current. The microwave oven is equipped with a cord having a grounding wire with a grounding plug. The plug must be plugged into an outlet that is properly installed and grounded.

WARNING: Improper use of the grounding plug can result in a risk of electric shock. Consult a qualified electrician or serviceman if the grounding instructions are not completely understood, or if doubt exists as to whether the microwave oven is properly grounded.

Do not use an extension cord. If the power supply cord is too short, have a qualified electrician or serviceman install an outlet near the microwave oven. A short power supply cord is provided to reduce the risks resulting from becoming entangled in or tripping over a longer cord.

SAVE THESE INSTRUCTIONS



Model: 39-3573 A The Cedarvale

INSTALLATION REQUIREMENTS

These installation instructions cover different models. The appearance of your particular model may differ slightly from the illustrations in these Installation Instructions.

Gather the required tools and parts before starting installation. Read and follow the instructions provided with any tools listed here.

Tools needed

- Tape measure
- 1/8" (3.17 mm) drill bit
- #2 Phillips screwdriver
- Marker or pencil
- Drill

Parts supplied

The Microwave Drawer is preassembled.

- 1" (2.5 cm) mounting screws (4)
- 1" (2.5 cm) deflector screws (2)
- Flush mount deflector (1)

Optional Parts

- 27" (68.6 cm) Trim Kit (W11170223) for JMDFS24GS
- 27" (68.6 cm) Trim Kit (W11264778) for JMDFS24HM

Verification needed

- Installer must confirm presence of anti tip block. Refer to the anti-tip block section in the manual.
- Check local codes. Check existing electrical supply. See "Electrical Requirements".
- It is required that all electrical connections be made by a licensed, qualified electrical installer.

This product is suitable for use below electric or gas built-in ovens. This product is not suitable for use below cooktops.

The Microwave Drawer may be located in a cabinet or below the counter, and/or below a built-in oven. Check the opening where the Microwave Drawer will be installed. The location must provide:

IMPORTANT: Observe all governing codes and ordinances.

- Wood cabinetry.
- Cutout opening that is plumb and square. See "Minimum Cutout Dimensions" in the "Minimum Dimensions" section.
- Cutout floor that is solid, level, and flush with bottom of cabinet cutout.
- Support for weight of at least 100 lbs (45.4 kg), which includes Microwave Drawer and items placed inside.
- Grounded electrical outlet. See the "Electrical Requirements" section.
- Minimum installation clearances for installation location. See the "Minimum Dimensions" section.
- Complete enclosure around the recessed portion of the Microwave Drawer.


Minimum Wall Oven Combination Installation Clearances

For proper installation, the following minimum clearances must exist above and below the cutout opening.

1 of 87

NOTE: Upper oven must have heat deflector kit installed to direct exhaust away from microwave console (Refer to Wall Oven Manual for Deflector Kit Installation)

A



A. Upper oven cutout

B. Microwave drawer cutout





RISE™ 24" BUILT-IN DISHWASHER, 38 DBA

Signature Features

QUIETEST LUXURY DISHWASHER BRAND

Based on normal cycle

ENHANCED CINEMATIC

Shine a spotlight on clean. Packed with 18 LED lights that ramp up to full intensity, JennAir brand's best lighting coverage chases away shadows to illuminate daring Obsidian racks.

38 DBA TRANQUILITY SYSTEM

JENNAIR dishwashers run quietly without sacrificing performance

HIGH-CAPACITY 3RD RACK WITH WASH

The largest 3rd Level Rack in the luxury industry glides with quiet and ease, even when fully loaded with tapas bowls, large rocks glasses and cocktail shakers.

SUPERIORGLIDE UPPER

Strong and stable. The upper rack glides smoothly and quietly, even when fully loaded. Each rail features 52 ball bearings for quiet operation.

RAPID WASH CYCLE

This wash cycle cleans dishes in about an hour and is ideal for any get-together, diversion or intimate night in.

11% MORE LOADING HEIGHT

WATERLOCK LEAK DETECTION SYSTEM

Measures and monitors the flow of water throughout the cycle through three levels of protection against potential sources of leaks. If there is a problem, the dishwasher will drain the tub and

15 PLACE SETTING CAPACITY

Intimate affairs. Lavish afterparties. Enough capacity for a service of 15 means there's always room for one more.

JDPSS246LL



Depth: 62.23 cm

Depth Closed Excluding Handles: 62.23 cm

Depth With Door Open 90 Degree: 129.54 cm

Gross Weight: 45.36 kg

Height: 85.09 cm

Net Weight: 40.37 kg

Width: 60.64 cm

Controls

Automatic Temperature Controls:

Control Type:

Tap Touch with Display

Tap Touch with Display

Control Location:

• Hidden

Top Hidden

Top

End of Cycle Signal:

Yes

Technical Specifications

Details

Built-In Water Softener:

- · No

Design Expression:

- RISETM

Dishwasher Cycle Selection:

- 1-Hour Wash
- Cookware Crystal
- Normal
- Refresh
- Sensor 1-Hour Wash
- Cookware
- Crystal Normal
- Refresh
- Sensor

Dishwasher Type:

- · Built-In

Dishwasher Option Selections:

- · 1-24 Hour Delay
- Bottom Rack Wash Hi Temp Wash
- Sani Rinse®

Exterior Details

Handle Material:

- MetalMetal

Handle Type:

- Towel BarTowel Bar

Magnetic Door:

- NoNo

Control Panel Color: Black

Certifications

ADA Compliant:

- No
 No

CEE Tier Rating:

- Tier I
- Tier I

CUL:

Energy Star Qualified:

· ENERGY STAR® Qualified

https://www.jennair.ca/en_ca/printpage.JDPSS246LL.html



Status Light:

Electrical

Multi-ColorMulti-Color

Power Cord Included:

- Top Rack Wash 1-24 Hour Delay Bottom Rack Wash
- Hi Temp Wash
 Sani Rinse®
- Top Rack Wash

Dispensers:

- Detergent and Rinse AidDetergent and Rinse Aid

Drying System Type:

- Fan Dry with Heating ElementFan Dry with Heating Element

Number of Racks:

Number of Place Settings:

Rack Material:

- NylonNylon

Rinse Aid Dispenser Level Indicator:

Sensor:

Sound Package:

True Hold Door:

- YesYes

Tub Material:

- Stainless SteelStainless Steel
- Wash System:

 - FilterFilter

Water Filtration:

- YesYes

Handle Material: Metal

Decibel Level: 38

Handle Type: Towel Bar

Tub Style: Built-in Tall Tub 24in.

Exterior Details

Door Style:

Handle Color:

- · Stainless Steel
- Stainless Steel

ENERGY STAR® Qualified

NSF Certified:

Prop 65:

- StandardStandard

Star K Certified:

- Yes Yes

Interior Details

- Interior Light:

Installation Considerations

Hoses Included:

- Both Fill Hose and DrainBoth Fill Hose and Drain

Cycles

Number of Wash Cycles:

Rack Details

Lower Rack Extras:

- Stainless Steel Wash ArmStainless Steel Wash Arm

Second Level Rack Adjustable:

- 2 Position2 Position

Second Level Rack Cushion-Tip Tines:

- YesYes

Second Level Rack Extras:

- 6 Stemware Holders
 Stainless Steel Wash Arm
- 6 Stemware Holders Stainless Steel Wash Arm

Second Level Rack Fold-Down Tines:

- 1 Row 6 Position1 Row 6 Position

Third Level Rack Adjustable:

Third Level Rack Removable:

- Yes

Third Level Rack Type:

- Third rack with dual rotating wash tubes
 Third rack with dual rotating wash tubes

Culinary Basket: Yes

Lower Rack Utility Basket: No

84 of 87




24[®] **DISHWASHER**DETAILED PLANNING DIMENSIONS GUIDE

JDPSS246LL, JDPSS246LM, JDPSG244LS, JDPSS244LL, JDPSS244LM, JDPSG244P**, JDPSS244P**
23%" (W) x 33%" (H) x 24½" (Depth without Handle)

JDPSS245LX 23%" (W) x 335%" (H) x 243%" (Depth without Handle)

PRODUCT DIMENSIONS



19114	DESCRIPTION	DIMENSIONS
A	Width of door	23%" (60.6 cm)
B*	Height to top of handle	31% (80.1 cm)
с	Height of adjustable toe kick	3½" (8.8 cm) - minimum 4½" (10.8 cm) - maximum
D	Width of recessed dishwasher	237/s" (60.6 cm)
Et	Depth without door	225/s" (57.5 cm)
	Depth with Towel Bar Handle	27½" (69.2 cm)
F	Depth with Pocket Handle	24½" (62.2 cm)
	Depth with Wood panel	24 ³ / ₄ " (62.9 cm)**
G*	Height to bottom of door (minimum)	35/1s" (8.4 cm)
Н*	Height to top of door (minimum)	337/16" (84.9 cm)
lie.	Height of recessed dishwasher (minimum)	335/a" (85.4 cm)
J†	Depth with door fully open (minimum)	50³/1s" (127.4 cm)
Kt	Depth with toe kick (minimum)	20 ¹³ /16" (52.9 cm)

†Insulation blanket thickness not included, can be crushed up to 1/8 ' (0.3 cm), or removed along the top perforate section for additional clearance.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice

W11453119C



^{*}Dishwasher can be raised 17/16" (3.7 cm) with feet fully extended.

^{**}Considering 3/4" wood panel thickness.






249 **ごISHWASHER** DETAILED PLANNING DIMENSIONS GUIDE

JDPSS246LL, JDPSS246LM, JDPSG244LS, JDPSS244LL, JDPSS244LM, JDPSG244P**, JDPSS244P** 23%" (W) x 33%" (H) x 24½" (Depth without Handle)

JDPSS245LX 23%" (W) x 335%" (H) x 243%" (Depth without Handle)

OPENING/CLEARANCE DIMENSIONS

IMPORTANT: Check that all surfaces have no protrusions that would prohibit dishwasher installation.



- A. Measured from the lowest point on the underside of the countertop. May be reduced to 33%" minimum (85.4 cm) minimum by removing the feet and perforated area of insulation (blanket) on dishwasher.
- B. Minimum, measured from narrowest point of opening

NOTE: Corner locations require a 2" (5.1 cm) minimum clearance between the side of the dishwasher door and the wall or cabinet.

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice

Dimensions are for planning purposes only For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.



LG LAUNGRY

The Cedarvale

6 of 870 LG

WM6500H A

5.6 cu. ft. Mega Capacity Smart Front Load Energy Star Washer with TurboWash® 360° and AI DD® Built-In Intelligence

5.0 cu. ft. Mega Capacity

Digital Dial Control with LCD Display & Touch Button Control Panel

TurboWash® 360° Technology

AI DD®: AI Fabric and Weight Sensors with Smart Pairing

LG ThinQ® Technology with ThinQ Care

Allergiene® Cycle

Cold Wash Technology

NeveRust® Stainless Steel Drum

ENERGY STAR® Certified & ENERGY STAR Most Efficient

Direct Drive Motor 10-Year Limited Warranty









Proactive Smart Alerts to Keep Your Appliances Running Smoothly

- Preventative Alerts help you stay a step ahead of potent al issues to find proactive solutions before problems arise.

 Avoid preventable repairs and service calls with real-t-me diagnostics for a hassle-free experience.

 Integrated within LG's ThinQ app a smart home hub for managing your smart devices and appliances



SUMMARY		WASH DETAILS		MOTOR AND AGITATOR	
Type	Front Load Washer	No. of Wash/Rinse Temps	5	Motor Type	Inverter Direct Drive Motor
Capacity (cu.ft)	S.0 - u. tc	Wash-Rinse Timps	Ex. Hot Hot Warm, Cold, Tap Cold	Axis	H-rzontal
Matching Electric Dryer	DLEX6500B DLEX6500W	No of Spin Speeds	5	MATERIALS AND FINISHES	
Matching Gas Dryer	DLGX65018 / DLGX6501W	Spin Speeds	Ex. High, High, Medium, Low, No opin	NevePust® Stainless Steel Drum	"es
Color	Black Stee (8), White (W)	Max RPM	1300	Cabinet	223
APPEARANCE		Water Levels	Load Senting	Control Panel	Pented Steel
LCD Display	Yes	No. of Soil Levels	s	Top Plate	Painted Steel
Touch Buttons	Yes	FABRIC CARE FEATURES		Door / Rim	Glass / Shiny Rose Go d
Oial-A-Cycle®	Yes	AI DD*	Yes	Door Cover	te-pered Glass Door
ENERGY		TurboWash* 360 Technology	Yes	All Available Colors	Back Steel (B), White; W.)
ENERGY STAR® Most Efficient	Yes	Steam Technology	Yes	CERTIFICATION	
ENERGY STAR* Certified	Yes	Allergiene* Lytle	Yes	AAFA	Yes
CEE Tier	Tier2	Sanitary Cycle	Yes	POWER SOURCE	
IMEF	2 92	Cold Wash Option	Yes	Ratings	UC Listed
tWF	3.0	CONVENIENCE FEATURES		Electrical Requirements	120V, 10 Amps
WASH PROGRAMS		Vibration Sensing : Cabinet	Yes	Туре	Stectric
No. of Prop. 2ms	25	Vibration (ensor)		OPTIONS/ACCESSORIES	
	Norma Al Wash Bedding, Dehcates, Towels, Quick Wash, Heavy Duty, Allergiene®, Perm Press, Tub Clean, Bright Whites™ Sanitary,	rueBalance* Ant -Vibratier System 4 Tray Dispenser	Yes Prewash, Main Wash (with riguid detergent cup), Bleach, Fabric Softener	Pedestal (WxH+D)	WDP68, WDP6W 27" x 13 5/8" x 25 3/8" (43 7/8" D with door apen)
Wakir Programs	Rinse-Spin Spin Only, Hand/Wool,	End of Cycle Signal	Yes	LG Sidekick Pedestal Washer	WD300CB, WD300CW
	Active Wear, Swimwear Kids Wear Jeans, Dresses, Color Care, Sweat	LoadSense	Yes	LG Sidekick** Pedestal Washer (Wallad)	27" x 14 1/9" x 30 3/4" (50 1/2 with drawer open:
	Stains, Small Load, Large Load, X	Control Lock	Yes	Stacking Kit	KSTK4
	Large Load	Auto Suds Removal	Yes	DIMENSIONS	13714
WASH OPTIONS		Leveling Legs	4 Adjustable Legs	Product (WxHxD)	47° x 39° x 33 1/8°
No of Opinion	15	Drum L ght	Yes	Depth with Door Open	17 3/4"
	TurboWash®, Steam, Fresh Care,	ThinQ+ TECHNOLOGY		Carton (WxHxD)	29 1/2" x 42 1/8" x 34 1/4"
Uptions	Pre-wash, Remote Start, Delay V/Josh Wi-Fi, Add Item, Extra Rinse, Control Lock, Drum Light, ColdWash, Signal, Cycle List Edit, Cycle Optimization	Smart Diagnosis	Yes	Weight (Product/Carton)	202.6 / 216.5 lbs
		WFr	Yes	LIMITED WARRANTY	1.207 2.33 10
		ThinQ Care	Yes	Parts and Labor	1 Year
		Energy Manitor ng	Yes		16 Years
		Tub Clean Coach	Yes	Drum	3 Years
				UPC CODES	
				WM6S00HBA (Black) WM6S00HWA (White)	195174052921 195174048689
AND THE PERSON NAMED IN COLUMN TWO IS NOT THE OWNER.			The second secon	AND PROPERTY OF THE PROPERTY O	The second secon

🕾 EVEST G. Electronics USA, Inc. All rights reserved "LG Life's Good" is a registered trademark of LG Corp. All other product and brand mames are trademarks or registered trademarks of their respective own; is Design, features and specification; are subject to



7.4 cu. ft. Capacity Energy Star Smart Front Load Dryer with Al Sensor Dry & TurboSteam®

7.4 cu. ft. Ultra Large Capacity Digital Dial Control with LCD Display & Touch Button Control Panel Al Sensor Dry with Smart Pairing TurboSteam®, SteamFresh®, and SteamSanitary® Technology Wrinkle Care Option LG ThinQ® Technology with ThinQ Care

FlowSense® Duct Clogging Indicator Tempered Glass Door (Reversible) NeveRust® Stainless Steel Drum ENERGY STAR® Certified

AVAILABLE COLORS





Proactive Smart Alerts to Keep Your Appliances Running Smoothly

- Preventative Alerts help you stay a step ahead of potential issues to find proactive solutions before problems arise.

 Avoid preventable repairs and service calls with real-time diagnostics for a hassle-free experience


 Integrated within LG's ThinQ app—a smart home hub for managing your smart devices and appliances.

FABRIC CARE FEATURES

MATERIALS AND FINISHES NeveRust® Stain ess Steel Drum

Donr A. Available Colors

Al Sentor Dry



POWER SOURCE

Fatings

87 of 870 LG

SUMMARI	
Туре	Front Load Dryer
Vent Type	Vented
Oryer Type	Elec: DLEX6500B / DLEX6500W Gan DLGX6501B/ DLGX6501W
Capacity	7.4 cu, ft.
Matching Washer	WM6S00HBA / WM6S00HWA
Sensor Dry	Yes
Steam	Yes .
Color	Black Steel (B), White (W)
APPEARANCE	
LCD Display	Yes
Touch Buttons	Yes
Dial-A-Cycle®	Yes
DRYER PROGRAMS	
No. of Programs	23
Programs (Sensor Dry)	Delicates, Towe 1, Quick Dry, Timed Dry, Power Dry Perm, Press, SteamFresh ¹⁴ , Heavy Outy, Air Dry, Steam San tary ¹⁴ , Supe- Dry Active Wear, Denim > Jeans, Blanket Refresh, Low Temp Dry, Overnight Dry, Easy Ironing, Small- oad, Large Load Dry, Xillarge Load Dry
No of Cations	- 11
Ортонь	Cycle Optimization, Damp Dry Signa., Wrinkle Care, Coutro 1 ock Wi-Fi. Energy Saver, TurboSteam ^a Reduce Static, Remote Start Drum Light, Signal
Temperature Settings	High, Med, High, Medium Low, Ultra Low
Drying Levels	Very Dry, More Dry, Normal Dry, Less Dry, Damp Ory
Manual Dry "imes	10 min 100 min (10 min incremer tal)

	163
Sensor Dry	Yes
Precise Temperature Control with Variable Heater	Yes
Steam	TurboSte=m6
CONVENIENCE FEATURES	
> Minute Installation Check	Ye
End of Cycle Signal	Ye
Frum Light (Door Open)	Yes
Reversible Door	Yes
Flav/Sense* Duct Clagging Indicator	Yet
Wrinkle Care Option	Ye:
Control Lock	Ye,
Venting Option	Electric: 4 Way Venting / Gas 3 Way Venting
4 Adjustable Legs	Yex
Remaining Time Display : Status Indicator(s)	Yes
ThinQ® TECHNOLOGY	公司从京都公司,以
Smart Diagnosis	Yes
Wi-Fi	Ye;
ThinQ Care	Ye;
Remote Start and Cycle Monitor	Yes
Energy Monitoring	Ye:
ENERGY	
ENERGY STAR Certified	Ye:
1222	

	Slectrical Requirements	Elec: 120/240V, 60Hz, 26A : Gas: 120V 60Hz 11 SA
	Туре	Electric, Gas
	2TU Rating	Gas. 20,000
	OPTIONS	
	LP Conversion Kit	383EEL3002D
	Side Vent ng Krt	3911EZ9131X
	Drying Rack	3750EL1001A
	Pedestal	WDP6B, WDP6W
	Pedestal (WxHxD)	27" x 13 5/6" x 28" (43 7/8" D with door open)
	DIMENSIONS	
	Product (WxHxD)	27" × 39" × 29 3/4"
	Depth with Door Open	S1 3/8"
	Carton (WxHxD)	28 31 '32' x 46 29/64" x 31 27/64"
	Product Weight (Ibs.)	Electric 124,3 lbs./ Gas: 136,0 lbs.
N.Y.	Carton Weight (lbs.)	Electric 136,5 lbs./ Gas: 146,6 lbs.
	LIMITED WARRANTY	
	Parts & Labor	1 Year
	Grom	3 Years
	UPC CODES	
	DLEX6SOOB (Black)	195174052945
	DLGX6S018 (Black)	195174052969
	DLEX6SOOW (Whit-)	195174049075
	DLGX6S01W (White)	195174048535

CSA Listed

10 2023 LG Electronics USA, Inc. A Frights reserved. "LGFF's Good" is a registered trademark of LG Corp. All other product and brand names are trademarks or registered trademarks of their respective owners. Design, features and specifications are subject to read without motive. Non-metric weights and measurement care programmate. Some features may require four transport of some of the product and are subject to change without notice. Non-metric weights and measurement care programmate. Some features may require four features may require to change without notice.

Painted Steel Tempered Glass Door

Black Steel (B), White (W)

