

Teefy Developments Limited / 9130 Bathurst

Lot/Unit: 84 Phase/Building: 1 Model/Floor Plan: Bedford(22-2)

CA	BI	[N]	\mathbb{E}'	R	Y

Inv. 3485	1 - CABINETRY - KITCHEN - UPGRADE - 10 - ROYAL PLUS - SUPPLY AND INSTALL	
Line 45632	Note:	
22Jan16 / 11Feb16		

CABINETRY ACCESSORIES

Inv.3485	3 - CROWN MOULDING - NOT APPLICABLE FOR THERMOVISION - PRICE IS PER 8 FOOT LENGTH	
Line 46085	Note:	
22Jan16 / 11Feb16		
Inv.3485	3 - LIGHT VALANCE - NOT APPLICABLE FOR THERMOVISION - PRICE PER 8 FOOT LENGTH	
Line 46086	Note:	

CABINETRY APPLIANCE - FRIDGE

Inv. 3485	1 - 59 CM FRIDGE CABINET - 1 GABLE & CABINET 59 CM DEEP - DEEP - UPGRADE 2	
Line 46101	Note:	
22Jan16 / 11Feb16		

CABINETRY BASE CABINETS

Inv. 3485	1 - BASE PIE CUT CORNER - UPGRADE 2	
Line 46103	Note:	
22Jan16 / 11Feb16		

CABINETRY HARDWARE

Inv. 3485	1 - KITCHEN - CABINET HARDWARE - UPGRADE 2 - DISPLAY BOARD	
Line 46098	Note:	
22Jan16 / 11Feb16		

CABINETRY HOOD FANS

Inv.3485	1 - ACCOMMODATE FOR MICROWAVE HOOD FAN COMBO - PURCHASER HAS SUPPLIED SPECS - CABINETS MUST BE ACCOMMODATED FOR FREE STANDING GAS RANGE BELOW.	
Line 45643	Note:	
22Jan16 / 11Feb16		

CABINETRY VANITY

Inv.3485	1 - VANITY BANK OF DRAWERS - 55 CM MAXIMUM - STANDARD LINE	
Line 46100	Note:	
22Jan16 / 11Feb16		

CABINETRY WALL AND HUTCH

Inv.3485	2 - KITCHEN UPPER - MATCHING INTERIOR FOR GLASS DOOR CABINETS - PRICE IS PER CABINET - STANDARD LINE	
Line 46083	Note:	
22Jan16 / 11Feb16		



Teefy Developments Limited / 9130 Bathurst

Lot/Unit: 84 Phase/Building: 1 Model/Floor Plan: Bedford(22-2)

Inv.3485	2 - KITCHEN UPPER - GLASS DOOR FROSTED - WHITE CABINET INTERIOR - STANDARD LINE	
Line 46084	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - UPPER ANGLE CORNER - PRICE IS PER UNIT - UPGRADE 2	
Line 46102	Note:	
22Jan16 / 11Feb16		

COUNTER TOP - KITCHEN

Inv.3485	1 - SUPPLY AND INSTALL 3CM STONE COUNTER TOP WITH STANDARD SQUARE EDGE – GROUP 4 IN THE KITCHEN WITH ISLAND AND FLUSH BREAKFAST BAR	
Line 46079	Note:	
22Jan16 / 11Feb16		

COUNTER TOP - VANITY

22Jan16 / 11Feb16		
Line 46093	Note:	
	EDGE – GROUP 3 IN THE POWDER ROOM	
Inv. 3485	1 - SUPPLY AND INSTALL 2CM STONE COUNTER TOP WITH STANDARD SQUARE	
22Jan16 / 11Feb16		
Line 45642	Note:	
Inv.3485	1 - SUPPLY AND INSTALL 2CM STONE COUNTER TOP WITH STANDARD SQUARE EDGE – GROUP 5 IN THE MAIN BATHROOM	
22Jan16 / 11Feb16		
Line 45641	Note:	
HIV.3403	EDGE – GROUP 5 IN THE ENSUITE - BATHROOM	
Inv.3485	1 - SUPPLY AND INSTALL 2CM STONE COUNTER TOP WITH STANDARD SQUARE	
22Jan16 / 11Feb16		
Line 45639	Note:	
	- X1 IN POWDER ROOM	
	- X1 IN MAIN BATH	
	- X2 IN MASTER ENSUITE	
Inv. 3485	4 - SINK CUT OUT - DOES NOT INCLUDE SINK	

ELECTRICAL

Inv. 3485	1 - SUPPLY AND INSTALL ADDITIONAL INTERIOR RECEPTACLE ON SEPARATE	
	CIRCUIT (IE: MICROWAVE, FREEZER)	
	- X1 IN KITCHEN FOR FUTURE MICROWAVE OVER THE RANGE	
Line 45644	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL LIGHT VALANCE ROUGH IN (INCLUDES 1 SWITCH)	
Line 46087	Note: LOCATION AS PER SKETCH ATTACHED.	
22Jan16 / 11Feb16		



Teefy Developments Limited / 9130 Bathurst

Lot/Unit: 84 Phase/Building: 1 Model/Floor Plan: Bedford(22-2)

Inv.3485	14 - ELECTRICAL - MINI LOW VOLTAGE HALOGEN POT LIGHT - 1ST FLOOR -	
	LOCATION SKETCH ATTACHED	
	- X4 IN KITCHEN	
	-STANDARD KITCHEN LIGHTING TO BE RELOCATED	
	- X4 IN BREAKFAST	
	- X6 IN FAMILY ROOM	
Line 46089	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - STANDARD KITCHEN LIGHTING TO BE RELOCATED & CENTERED ABOVE	
	ISLAND AS MUCH AS POSSIBLE	
Line 46091	Note:	
22Jan16 / 11Feb16		
Inv. 3485	3 - SUPPLY AND INSTALL DIMMER SWITCH DECORA (120V - 500W)	
	- X1 IN KITCHEN FOR POTLIGHTS	
	- X1 IN BREAKFAST FOR POTLIGHTS	
	- X1 IN FAMILY ROOM FOR POTLIGHTS	
Line 46097	Note:	
22Jan16 / 11Feb16		

HARDWOOD

Inv. 3485	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP	
	WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- BEDROOM 2	
Line 45610	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP	
	WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- UPPER HALL	
Line 45622	Note:	
22Jan16 / 11Feb16		
Inv. 348 5	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP	
	WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- BREAKFAST	
Line 45624	Note:	
22Jan16 / 11Feb16		
Inv. 348 5	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP	
	WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- GREAT ROOM	
Line 45626	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP	
	WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- MASTER BEDROOM	
Line 45618	Note:	
22Jan16 / 11Feb16		
Inv. 348 5	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP	
	WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- BEDROOM 3	
Line 45611	Note:	
22Jan16 / 11Feb16		



Teefy Developments Limited / 9130 Bathurst

Lot/Unit: 84 Phase/Building: 1 Model/Floor Plan: Bedford(22-2)

Inv. 3485	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- LANDING 1ST TO 2ND	
Line 45623	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- KITCHEN	
Line 45625	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - SUPPLY AND INSTALL HARDWOOD - UPGRADE 4 VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL- DINING ROOM	
Line 45627	Note:	
22Jan16 / 11Feb16		

HEATING AND AIR CONDITIONING

Inv. 3485	1 - GAS LINE - ROUGH-IN ONLY - FIRST CONNECTION- FOR BBQ	
Line 46080	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - GAS LINE - ROUGH-IN ONLY - FOR STOVE TO INCLUDE 110V CODE REQUIREMENT	
Line 46081	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - UPDGRDE GAS LINE FROM 3/4 INCH TO 1 INCH	
Line 46082	Note:	
22Jan16 / 11Feb16		

MISCELLANEOUS

PLUMBING

Inv.3485	4 - SUPPLY AND INSTALL CONTRAC CAMDEN UNDERMOUNT SINK - IN LIEU OF THE STANDARD OVERMOUNT - MODEL 4210CHY - X2 IN MASTER ENSUITE - X1 IN MAIN BATH - X1 IN POWDE ROOM	
Line 45640	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL WATERLINE ROUGH-IN TO THE FRIDGE LOCATION (NO HOOK UP)	
Line 46088	Note: LOCATION AS PER SKETCH ATTACHED.	
22Jan16 / 11Feb16		
Inv.3485	1 - MASTER ENSUITE - SUPPLY AND ENSTALL SQUARE DRAIN IN LIEU OF THE STANDARD ROUND.	
Line 46099	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - SUPPLY AND INSTALL ARBOR SINGLE HANDLE PULL DOWN KITCHEN FAUCET - MODEL 7594SRS - IN SRS FINISH	
Line 46104	Note:	
22Jan16 / 11Feb16		



Teefy Developments Limited / 9130 Bathurst

Lot/Unit: 84 Phase/Building: 1 Model/Floor Plan: Bedford(22-2)

Inv.3485	1 - SUPPLY AND INSTALL TRANSITIONAL STYLE SOAP/LOTION DISPENSER IN KITCHEN - MODEL S3946SRS - IN SRS FINISH	
Line 46105	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - MASTER ENSUITE - SUPPLY AND INSTALL VOSS ROMAN TUB WITH HANDHELD SHOWER - MODEL 9796/T694 - CHROME FINISH	
Line 46106	Note:	
22Jan16 / 11Feb16		

TILE - BACKSPLASH

Inv.3485	1 - BACKSPLASH - HONED MARBLE BACKSPLASH - ABOVE COUNTER & BEHIND STOVE ONLY	
Line 46092	Note:	
22Jan16 / 11Feb16		

TILE - FLOOR

Inv. 348 5	1 - SUPPLY AND INSTALL FLOOR TILE - UPGRADE 4 - VESTIBULE FLOOR	
Line 45633	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - SUPPLY AND INSTALL FLOOR TILE - UPGRADE 4 POWDER ROOM FLOOR	
Line 45634	Note:	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL FLOOR TILE - UPGRADE 3 ENSUITE BATHROOM	
	FLOOR	
Line 45635	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - SUPPLY AND INSTALL FLOOR TILE - UPGRADE 3 MAIN BATHROOM FLOOR	
Line 45636	Note:	
22Jan16 / 11Feb16		
Inv.3485	1 - SUPPLY AND INSTALL FLOOR TILE - UPGRADE 3 - ENSUITE BATH SHOWER	
	FLOOR	
Line 46107	Note:	
22Jan16 / 11Feb16		

TILE - WALL

Inv. 3485	1 - SUPPLY AND INSTALL WALL TILE - UPGRADE 5 - ENSUITE BATH SHOWER ON	
	ONE WALL IN A HORIZONTAL STACKED - 12x24 NIAGARA FALLS ON LONGER	
	WALL - STANDARD TILE TO BE ON SMALLER WALL AND CEILING	
Line 46094	Note: SEE SKETCH ATTACHED	
22Jan16 / 11Feb16		
Inv. 3485	1 - SUPPLY AND INSTALL WALL TILE - UPGRADE 5 - SHOWER ON ONE WALL IN A	
	HORIZONTAL STACKED - 12x24 NIAGARA FALLS ON CENTER WALL - STANDARD	
	TILE TO BE ON SIDE WALLS AND CEILING	
Line 46096	Note: SEE ATTACHED SKETCH	



Teefy Developments Limited / 9130 Bathurst

Lot/Unit: 84 Phase/Building: 1 Model/Floor Plan: Bedford(22-2)

EXTRAS AS PER OFFER

Stainless Steel Fridge, Stove and Dishwasher and front loading washer and dryer in white from Vendors standard samples, no cash value, not transferable. (Supplied only not installed) ** to - arrange delivery call: The Brick commercial sales division at Worksheet Note:	
Rogers Free Services Package includes 6 months of: Highspeed home phone, TV service, and highspeed internet Worksheet Note:	

This Document is Extremely Time Sensitive - Printed $\underline{25 \text{ Feb } 16}$ at $\underline{12:04}$

Page 6 of 6

SENATOR

INTERIOR COLOUR SCHEME

Purchasers: Vajiheh Nourmofidi & Behnam Shayegan Property: 84 of Plan -Telephone Res. / Bus: / Project: Teefy Developments Limited Decor Advisor: Nicole Soares Model and Elevation: Bedford(22-2) Layout Changes: Yes No Sketch Attached: Yes No Exterior Colour Scheme: 1. Cabinetry Style and Colour Counter Top Hardware Kitchen / Breakfast NEW YORK MAPLE: AVOCADO *1141 PURE WHT - SQ EDGE 12895 *1141 PURE WHT - SQ EDGE NEW YORK MAPLE: AVOCADO 12895 Kitchen Island Laundry Room MONTREAL PAINT: WINTER WHITE 9671 Powder Room *4600 ORGANIC WHT - SQ EDG MONTREAL MAPLE: SHALE GREY 9671 Main Bathroom MONTREAL MAPLE: OYSTER *5220 DREAMY MARFIL-SQ EDG 9671 Master Ensuite Bathroom MONTREAL MAPLE: OYSTER *5212 TAJ ROYALE - SQ EDGE 9671 Second Ensuite Bathroom (If Applicable) MONTREAL PAINT: WINTER WHITE GIRONA CAVERN 4897K-52 Lower Level Bath 9671 Appliances Custom Size Fridge Valance Lighting Microwave / Range Hood No O Yes Yes O No Yes \(\) No Cooktop / Rangetop **Built in Wall Oven** Slide-in Range O Yes No O Yes No () Yes No Comment

2. Flooring	Selection
Foyer	*NIAGERA FALLS 12X24: WHITE - TO BE INSTALLED IN A STD STACKED PATTERN
Main Hall	*VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Back Hall	LOWER LEVEL HALL- PAPILIO: 64676 OLIVE CREAM 19513 PAUL FACES (V.) (10
Breakfast	"VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Laundry Room	ALPES 13X13: WHITE
Kitchen	"VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Powder Room	*NIAGERA FALLS 12X24: WHITE - TO BE INSTALLED IN A STD STACKED PATTERN
Main Bathroom	*COPPER 12X24: BEYEZ- TO BE INSTALLED IN A STD STACKED PATTERN
Master Ensuite	*COPPER 12X24: BEYEZ- TO BE INSTALLED IN A STD STACKED PATTERN
Bathroom (If Applicable)	*MASTER ENSUITE SHOWER FLOOR- QUEBEC 2x2 MOSAIC: STERLING GREY FS
Mud Room	
Lower Level Bath	ALPES 13X13: WHITE
Living Room	
Dining Room	*VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Family / Great Room	"VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Den / Library / Study	
Basement Landing (If Appl	ies)
Lower Landing (If Applicab	le)
Upper Landing	"VINTAGE 5" HAND SCRAP WHITE OAK ENG, HARDWOOD: GOTHAM PEARL
Upper Hall	"VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Master Bedroom	*VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD; GOTHAM PEARL
Bedroom #2	"VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Bedroom #3	*VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL
Bedroom #4	
Bedroom #5	
Recreation Room	PAPILIO: 84676 OLIVE CREAM 19513 POLE PAGES (C) (P)

Flooring Continued on Page 2

dar

Page 1 of 3

Printed 2/11/2016 17:05:25

SENATOR

INTERIOR COLOUR SCHEME

Purchasers:	Vajiheh Nourmofidi & Behna	m Shayegan	Property: 84	of Plan -	
Telephone Res. / Bus	s: /		Project: Te	efy Developments Li	mited
Decor Advisor:	Nicole Soares	Model and	l Elevation : Be	dford(22-2)	
2. Flooring - Continu	Jed				
	_		_		
Upgrade Underpad	Type STANDARD		Area LOWER L	.EVEL	
O	Capped		Runner - *		
Carpet on Stairs	Саррец		Kumer -	Opgrade	
Comment					er e termenet e e
3. Plumbing Fixtures	/ Faucets				
Kitchen	UPG Second	d Ensuite	[Powder Room	STD
Master Ensuite	STD & UPG			Other Room	
Main Bathroom	STD Lower I	Level Bath	STD		
Comment					
!					
4. Wall Tile	9				
	Tile Selection		Listello	Insert Insert Select	ion
Main Bathroom Master Ensuite	SEE COMMENT				
Tub Deck	N/A			<u> </u>	
Tub Apron	N/A	<u></u>			
Tub Surround	N/A				
Shower Stall	SEE COMMENT				
Second Ensuite					
Lower Level Bath	ALPES 8x10: WHITE				
Kitchen Backsplash	SEE COMMENT BELOW				
Complete Backsplash	 				
GM.COL.WHT.12II MASTER BATH:BF HORIZONTAL	PLASH: MARBLE HONED - BIA RR.HN) RICK 8X12 GLOSSY: WHITE: S /F.8X10: IVORY ON SIDE WAI	MALL WALL/NIAG	ARA FALLS 12X	(24: GREY: LARGE	WALL
-5. Fireplace					
•	Living Room	Family Room	An Day Dies - Citt	Other Room - Sp	· · · · · · · · · · · · · · · · · · ·
	Purchased As Per Plan N/A	Purchased	As Per Plan N/A	Purchased A	s Per Plan N/A
Fireplace Type		STANDARD BL	F 50		<u> </u>
Mantle Type					
Over Mantle					
Colour / Stain					
Surround		STANDARD			
Hearth					
Comment					

Printed 2/11/2016 17:05:25

Page 2 of 3

CAN

Initial:

INTERIOR COLOUR SCHEME ENAT Vajiheh Nourmofidi & Behnam Shayegan Property: 84 of Plan -Purchasers: Telephone Res. / Bus: Project: Teefy Developments Limited Model and Elevation: Bedford(22-2) Decor Advisor: Nicole Soares 6. Trim Carpentry Interior Doors Door Hardware STANDARD 2 Panel Arch Top Interior Trim STANDARD Comment 2 Panel Square Top ○ 6 Panel Initial for Door Style Y N Val 7. Railings and Pickets STANDARD PACKAGE Railing Package FLAT BLACK METAL Railing Colour STAINED **Picket Colour** STAINED Wood Stairs O No Oak Tread Colour STAIRS TO BE STAINED TO MATCH *VINTAGE 5" HAND SCRAP WHITE OAK ENG. HARDWOOD: GOTHAM PEARL AS MUCH AS POSSIBLE *** PURCHASER IS AWARE THAT STAIN WILL NOT BE A 100% TRUE MATCH AS STAIRS ARE STAINED ON SITE 8. Plaster Mouldings and Medallions Kitchen/Breakfast Fover Main Hall Den/Library Living Room Lower Landing **Dining Room** Family Room Comment **Wall Paint** Smooth Ceilings O First Floor SENATOR WHITE First Floor incl. Second Floor Hall First and Second Floor Throughout Not Applicable Trim Paint STANDARD 10. Additional Comments 11. Disclaimers and Notes 1) Colours of all materials are as close as possible to builder's selection, but not necessarily identical due to variances in manufacturing 2) Any extras listed above are null and void unless accompanied by a separate invoice/amendment. Said invoice must be paid in full. The Purchaser acknowledges that after Interior Colour Selection form is signed and dated, no further changes will be permitted other than re-selection due to unavailability. 4) The Purchaser acknowledges reading and accepting the "Senator Homes Décor Centre Disclaimers" form. This document contains other miscellaneous disclaimers. This Interior Colour Selection is final and approved by: Purchaser: Date: FEB 1 1 2016 Signature:


Date: FEB 1 1 2016

Vendor:

Teefy Developments Limited

BEDFORD 9130 8

2420 SQ.FT. / 2251 SQ.FT. WITH OPTIONAL TANDEM GARAGE




C-CABIQ FTELEPHONE D-DATA.

BEDFORD - TH-22-2

SENATOR HOMES - TEEFY

STD. LAYOUT






M

OPT. LIGHT VALANCE (X3)

OPT. CROWN (X3)



-ENSUITE (UPPER FLOOR) ELEV A -UPG, INT END, SIDE FLEV A


-KITCHEN (MAIN FLOOR) ELEV A -UPG. INT END, SIDE ELEV A

-MAIN BATH (UPPER FLOOR) ELEV A -UPG. INT END, SIDE ELEV A

""NO OPT LAUNDRY UPPERS***
(INC STACKED UNIT)

NO OPT. LOWER LEVEL VANITY*

OPTIONAL CABINETRY (STANDARD ELEVATION)



-OP1. LAUNDRY UPPERS (LOWER LEVEL)
-UPG INT END, SIDE UPG ELEV A
-OP1. LAUNDRY UPPERS (ALT. LOWER LEVEL)
-OP1. ALT. INT END, SIDE ELEVATION

(BASE CABINETRY NOT REFLECTED ON DWG'S)

TOR HOMES OR CENTRE GEEB 11 2016

☑ Electrolux ICON®

French Door Refrige

E23BC78IPS profess







Custom Temp Drawer™

Enjoy the ultimate in versatility with 9 preset selections including White/Sparkling Wine, Fish/Shellfish, Cheese plus three customizable settings that ensure foods stay at the ideal temperature for serving and maintaining freshness.



Custom-Design* Organization System

With our flexible Tri-Level freezer organization system you can keep your freezer well organized. The three Smooth-Gide* baskets with removable dividers and top removable baskets allow you to configure the space to neatly fit large and small items.



Theatre Lighting

Transition LED lighting gradually illuminates the interior with soft but ample light as you open the door.



PureAdvantage* Filtration Systems

Our filtration system keeps clean, filtered air circulated throughout to prevent odor transfer and keeps fresh, clean water and ice at your fingertips.

23 CU.FT. COUNTER-DEPTH

CAPACITIES	
Total Capacity	22.6 Cu. Ft.
Fresh Food Volume	15.7 Cu. Ft.
Freezer Volume	6.9 Cu.Ft.
Total Shelf Area	26.45 Sq. Ft.
Fresh Food Shelf Area	18.72 Sq.Ft.
Freezer Shelf Area	7.7 Sq.Ft.
50 (10 (10 (10 (10 (10 (10 (10 (
EXTERIOR	
Professional Doors and Handle Design	Yes
Wave-Touch* Electronic Controls	Yes
Door Hinge Covers	Yes
lce/Water Dispenser	Yes
Custom-Self Temperature Control System and Display	Yes
Crushed/Cubes/Water	Yes
Air and Water Filter Indicator/Reset	Yes
ice Maker On/Off	Yes
Fast Freeze*	Yes
Lock/Dispenser Light Control	Yes/Yes
FRESH FOOD CONVENIENCES	
PureAdventage* Water & Ice / Air Filtration	Yos
Water Fifer Location	Bottom Left
Temp Alarm System / Door Ajar Alarm / Power Failure Alarm	Yes
Custom-Design" Glass Shelves	THE RESERVE TO THE PERSON NAMED TO THE PERSON
The state of the s	3 Half Width 1 Quarter Width
Smooth-Glide* Humidity-Controlled Left Crisper	Yes
Smooth-Glide® Humidity-Controlled Right Crisper	Yes
Custom Temp Drawer*	Yes
Wine Fack	Yes
Clear Gallon Adjustable Door Bins	1
Clear 1/2-Gallon Adjustable Door Bins	1
Clear 2-Liter/1/2-Gallon Removable Door Bins	2
Locking Clear Utility Bin	Yes
Tit-Out Can Rades	2
Theatre Ramp-Up Multilevel Lighting – LED	Yos
Automatic Ice Maker	Yes
FREEZER CONVENIENCES	
Self-Closing Drawer	Yes
Stiding Full-Width Freezer Baskers	
acting runnialit ricezer baskes	3 Smooth-Gloe* (2 with Dividers)
Plastic Basket Tray	1
Tit-Out Wire Door Racks	1 -
Theatre Ramp-Up Multilevel Lighting - LED	Yes
ADDITIONAL FEATURES	The state of the s
ENERGY STAR*	Yes
Sabbath Mcde (Star-K® Certified)	Yes
ACCESSORIES	
Coller Kit - PN# ECK23CDS*	Optional
Louvered Trim Kt - PN# 241723001*	Optional
Water Fitter Replacement Cartridge - PN# EWF01	Optional
Air Fiter Replacement Cartridge - PN# EAFCBF	Optional
NAMES AND ADDRESS OF THE PARTY	
SPECIFICATIONS	
Overall Exterior Dimensions –	
Height (with Hinges and 3/8" Rollers)	69-1/2"
Cabinet Width/Door Width	35-5/8"/36"
Depth (Including Handle) (with 90° Doors Open)	29-1/2" 42-9/16"
(with Drawer Fully Extended)	44-1/2" Blots Bottom Book
Power Supply Connection Location	Right Bottom Rear
Water Inlet Location	Left Bottom Rear
Voltage Rating	120V/60Hz/15 or 20/
Connected Load (kW Rating) @ 120 Volts ²	1.02
Minimum Circuit Required (Amps)	15

^{*}For distalled Louvered Trim Kit and Collar Kit installation instructions, refer to Product Installation Guides on the web at electroluxicom.com.

electroluxicon.ca




An electrical supply with grounded three-pring receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (MPN 70) and focal codes & archances.

NOTE: Always consult focal and national electric and plumbing codes. Pafer to Product installation Guide for detailed installation instructions on the web at electrolusion.cs.

Specifications subject to change.

French Door Refrigerator



Counter-Depth French Door Refrigerator Specifications

- Product Weight 338 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The power supply circuit must be installed in accordance with current edition of National Electrical Code (NFPA 70) and local codes & ordinances.
- Voltage Fating -120V/60Hz/15 or 20 Amps
- Connected Load (kW Fating) @120 Volts = 1.02kW
- Amps @ 120 Volta = 8.5 Amps
- Always consult local and national electric & plumbing codes.
- · Floor should be level surface of hard material, capable of supporting fully loaded refingerator.
- When installing refrigerator adjacent to wall, cabinet or other appliance that
 extends beyond front edge of unit, 20" minimum clearance recommended to
 allow for optimum 120" to 180" door swing, providing complete drawer/orsper
 access and removal. (Absolute 4-1/2" minimum clearance will CNLY allow for
 90"door swing which will provide drawer/orisper access with restricted removal.)
- . To ensure optimum performance, avoid installing in direct sunlight or close proximity to range, dishwasher or other heat source.
- For proper ventilation, front grille MUST remain unobstructed.
- · Recess electrical outlet when possible.
- Water recess on rear wall recommended to prevent water line damage.
- Water Pressure Cold water line must provide between 30 and 100 pounds per square inch (psi).

- Copper tubing with 1/4" O.D. recommended for water supply line with length equal to distance from rear of unit to household water supply line plus 7 additional feet. Optional Water Supply Installation Kits available.
- · Adjustable front rollers to assist with door alignment.
- If optional Collar Kit (PN# ECK23CDS) is to be used, different cutout cimensions are required. (Refer to Collar Kit ECK23CDS Installation Specifications page on web.)
- If optional Louvered Trim Kit (PN# 241723001) is to be used, different outout dimensions are required. (Pefer to Louvered Trim Kit 241723001 Installation Specifications page on web.)

"Built-In Look" Specifications

- . Minimum opening of 70-1/4" H x 36"W x 25"D required to allow for ease of installation, proper air circulation, and plumbing/electrical connections.
- Remove all wall/floor molding prior to installation.

Note: For planning purposes only. Refer to Product Installation Guide on the web at electroluxicon.ca for detailed instructions.

Optional Accessories

- Collar Kit IPN # ECK23CDS).
- Louvered Trim Kit (PN# 241723001).
- PureAct/antage* Water Filter Replacement Cartridge (PN# EWF01).
- PureAdvantage* Air Filter Replacement Cartridge (PN# EAFCBF).



Electrolux Major Appliances, N.A.

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • electroluxicon.ca E23BC78IPS 01/12 © 2012 Electrolux Major Appliances, NA

> SENATOR HOMES FEB 1 1 2016 TALS:_



GAS FREESTANDING RANGE

Featuring IQ-Touch" Electronic Controls



SIGNATURE FEATURES



FRONT CONTROL DESIGN

Effortlessly upgrade your back-control range to built-in style. This range will easily replace traditional 30" freestanding ranges.



OVAL BURNER + INCLUDED GRIDDLE

Allows you to cook with larger pots and parts or use the complementary griddle to achieve a variety of perfect flavors!



PERFECT TASTE™ CONVECTION

For consistently delicious taste and texture, home chars rely on our convection heat, which circulates air evenly for better baking



PERFECT TASTE™ TEMP PROBE

The Perfect Taste" Temp Probe lets you cook each dish to perfection. It does more than measure temperature — it alerts you when food has reached the desired Temp Probe lets you temperature and automatically adjusts to the Keep Warm setting, so you never overcook your food and deliver perfect results every time.

El30GF45QS

PRODUCT DIMENSIONS

36-1/8" - 36-5/8" 29-7/8" Width Depth (including handle) 28-5/16"

MORE EASY-TO-USE FEATURES

MIN-2-MAX® GAS BURNER

Designed with a dual-flame sealed burner, this cooktop provides exceptional power and precision to unlock new flavors.

A LUXURY-GLIDE® OVEN RACK

With a ball bearing system, the over rack is so smooth if extends effortlessly so you can more easily manage the transfer of all dishes, even heavy ones.

CONTINUOUS GAS GRATES

Designed for cooking multiple dishes at a time, these grates allow easy movement of even the heaviest pots and pans from burner to burner — without lifting. Plus, they create a streamlined look.

DEEP-WELL DESIGN

Keeps spills contained for easy cleanup.

WARMER DRAWER

Maintain the perfect temperature of your food until serving time.

PLATINUM STAR® LIMITED WARRANTY

Our exclusive limited warranty that includes 3-year coverage on parts and one year on labor-

CONVECTION CONVERSION

Automatically adjusts standard baking temperatures to convection temperatures, for perfect, consistent results.

6 COOKING MODES

Bake, Broil, Convection Bake, Convection Roast, Keep Warm and Slow Cock.

KEEP WARM SETTING

Maintain food at the perfect serving temperature with this setting — it's a great feature when you're entertaining.


Available in:



BURNER	BTU
Mir-2-Max* Dual Flame Sealed Burne:	750 - 15,000
Secled Power Burner	14,200
Sepled Precision Burner	9,501
Sasted Precision Rumer	5.00)
Centre Humer	10,018

Signific Count on product regulation with Electricis Math Avenue withortic days of purchase. Functions American participant for a separate part of Education and American participant for a separate participant f

ELECTROLUXAPPLIANCES.CA



GAS FREESTANDING RANGE

El30GF45QS



CONTROL PANEL FEATURES	
Q-Touch TM Electronic Oven Control	Yes
Professional-Grade Burner Controls	161
Glass Front Display	Yes
Electronic Clock & Timer	nes
Temperature Display	'hes
Automatic Oven (Delay, Cook & 06)	'Yes
DOOKTOP FEATURES	
Sealed Power Burner - 18,000 BTU	1
Sealed Power Burner – 14,20C BTU	1
Sealed Precision Eurner - 9,500 ETU	1
Sealed Precision Eurner - 5,000 ETU	1
Centre Oval Burner - 10,000 ETU	1
Continuous Grates with Deep-Well Top	,161
Seamless Cooktop	Yes
Sectric Pillotiess Ignition	Yes
DVEN FEATURES	
Capacity	4.5 Cu. Ft.
Hidden Bake Burner Sake Burner – 18,000 BTU	Yes
Soll Burner - 13.500 BTJ	Yes
Convection Burner - 350 Walls	Yes
Cabalt Blue Interior	Yes
Self-Clean Options with Coor Look	Yes
Perfect Taste "Convection	Vec
Cacking Modes -	100
Bake, Broit, Convection Bake, Convection Roast, Keep Warm, Slew Cook	6
Baking Options — Temperature Probe, Delay Bake, Convection Convert	3
Oven Light	Yes
ocury-Glide® Racks	1
Conventional Racks	1
Convection Reasting Rack	1
ADDITIONAL FEATURES	
Lucury-Hold M Oven Door	
Extra-Large Glass Window	Yes
Name: Drawer	Yes
Adjustable Laveling Loga	Yes
Sabbath Mode (Star-K [®] Certified)	Yes
ACCESSORIES	
Bricdle - PN# 318251608	Included
P Gas Conversion Kit	Included
Meat Probe	Included
Stainless Steel Eackguard – PN # A02535501	Optional
SPECIFICATIONS	
Colour -	
Stainless Steel	S
Sas Inlet/Power Cord Location	Right Bottom Rear
Voltage Fating	120V 60Hz 15A
Connected Load (kW Rating) & 120 Volts-	1.80
Amps © 120 Volts	15
Shipping Weight (Approx.	285 Lbs.
For use on adequately when I 2014, deplicated circuit toping 2-wise service with a a bit property for sale operation. NOTE: Always consult local and national electric and gas codes. Refer in Product bu	



Height (Adjustable)	36-1/8" - 38-5/8"
Width	29-7/8"
Depth (including handle) (with 90° Door Open)	28-5/16* 45
OVEN CAVITY DIMENSIONS	
Height	17-1/2"
Width	24-1/8"
Depth	18-3/4"






Electrolux Major Appliances, N.A.

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • electroluxappliances.ca
EI306F45Q 10/15 © 2015 Electrolux Major Appliances, NA


We reserve the right to change specifications or discontinue models without notice.

Printed in Canada





Built-In Dishwasher





Signature Features



30-Minute Fast Wash Cycle Quick Wash Cycle allows you to

thoroughly wash dishes in half the time.



Largest Usable Capacity

even your dinner party dishware fits.



SatelliteSpray[™] Arm

An innovative rotating wash zone gives you 400% more water coverage, largeting virtually every spot in your dishwasher for a truly protossional level clean.



Perfect Stemware™ Cycle

spotless and clean.

PRODUCT DIMENSIONS

33-3/4" - 35-3/4" 23-3/4" 24-1/4"

MORE EASY-TO-USE FEATURES

IQ-Touch™ Controls

For those who like to have their options always visible on their dishwasher, the IO-Touch" control panel displays all of your options, at all times.

Easy-Lift Adjustable Racks

Versatile racking system easily adjusts to provide the perfect place for all your dishware — no pinching, pulling, or toggling required.

Auto Wash Feature

A Smart Soil Sensor technology that determines how long the wash cycle should run, for a more effective operation.

AquaLux* Wash System
A unique washing system that uses alternating wash
arms, for a quicter and more afficient operation.

Luxury Soft Grip Racks

Luxury Soft Grip Facks hold plastics and dishware in place, and prevent flipping, for a more thorough clean.

Perfect Sternware Grips Six flexible ordes peoply hold sterny

Six flexible grips gently hold stemwa trons for a secure wash, every time. ware and other delicate

Luxury-Glide® Racks

With our Luxury-Glide" technology, upper and lower racks are so smooth they extend effortlessly.

Sure-2-Fit® Racking System

The most versa;ile and acjustable racking system — there's a perfect place for over 130 items, from chopsticks to stockpots to stamware. In its lowest position, you can fit 10" dinner plates in the top rack and 12" dinner plates in the bottom.

More Cycles

With up to ten cycles — including Heavy, Normal, Fast Wash, Auto, Upper Rack Only, Eco Wash, Sternwere, Rinse Only, Delicate, and "My Favourite" — you can choose the perfect wash for any occasion.

"My Favourite" Settings

A programmable setting that lets you customize the wash for your unique deemup heads.

electroluxicon.ca




Built-In Dishwasher

F24ID74QPS professional series



FEATURES	
Stain ess Steel Interior	Yes
Loury-Hold" Door	Yes
Custom-Set* Options	Yes
Theatre UED Lighting	Yes
ritegrated IQ-Touch" Controls	Yes
ED Indicator Lights	Yes
fall-Tub Design	Yes
ProClean* Wash System	Yes
Satel IteSpray "Arm .uxury-Cleen " Technology	Yes
.uxury-Clean* Technology	Yes
.uxury-Quiet" Sound Package / (Approx. dBA)	Yes/43.0
Wash Levels	5
Aqua-Lux* Wash System	Yes
eak-Detection System	Yes
Adjustable Rinse Aid Dispenser with Indicator	Yes
ENERGY STAR®	Yes
CYCLES	
Auto Wash	Yes
Delicate	Yes
Sep Wash	Yes
avourite	Yes
Heavy	Yes
Normal	Yes
Perfect Sterriware*	Yes
30-Min, Fast Wash	Yea
Rinse Only	Yes
Joper Rack	Yes
OPTIONS	
Air Dry	Yes
NSF® Certified Sanitize Option	Yes
Delay Start	30 Min 24 Hrs.
RACK SYSTEM	
Sure-2-Fif® Rack System	Yes
Joper Rack -	2000
Adjustable Height	Yes
Cup Clips	4
Cup Shelf/Sterrware Holder	2/Yes
Fold-Down Tines	4 Rows
Rack Handle	Yes
Verse-Tray**	Yes
Lower Rook	
Fold-Down Tines	6 Rows
Knife Holder	Yes
Utility Tray/Shelf	Yes
Sternware/Champagne Glass Holders	4
Silverware Basket	3-Piece Split
Special Items Cover/Mesh Small Items Bag	Full Set
SPECIFICATIONS	
Power Supoly Connection Location	Right Bottom Fro
	Left Bottom Fron
Water Inlet Location	Yes
Leve Ing Legs	4.0 - 8.0
Leve Ing Legs	15 - 120
Leveling Legs Nater Usage (Gallons) – Normal Cycle	15 - 120 Yes
Leveling Legs Nater Usage (Gallons) – Normal Cycle Nater Pressure (PSI)	
Leveling Legs Nater Usage (Gallons) – Normal Cycle Nater Pressure (PS) Integral Air Gap on Bupply	Yes
Leveling Lags Water Usage (Gallons) – Normal Cycle Water Pressure PS) Integral Ar Gap on Supply Voltage Rating	Yes 120V/60Hz
Leveling Logs Nater Usage (Gallons) – Normal Cycle Nater Pressure PSI rhtgrid Air Gap on Buspily Voltage Rating Connected Load (KW Rating) © 120 Volts ¹	Yes 120V/60Hz 1.44



Height (Adjustable)	33-3/4" 35-3/4"
Wdh	23-3/4"
Depth (Including Door) (with Door 90° Doon)	24-1/4" 50-1/4"

Electrolux Major Appliances, N.A.

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • electroluxicon.ca

E24ID74QPS 03/15

© 2015 Electrolux Major Appliances, N.A.



high standards of quarry at Bectstan home Products, his mean we are combinite violeing to improve our products. We reserve the signific ordinary specializations or decontinue models without notice.

Printed in Canada





Over-the-Range Microwave

EI30BM6CPS





Gives you oven results at microwave speed—perfect for roasting, cooking and beking everything from steaks to cupcakes.



stirring fan and turntable to heat your food evenly every time.



Quartz Grill Element

Provides a true oven bake finish.



Cook display prompts you through Quick Meal options and Dinner Recipes.

30" OVER-THE-RANGE	CONVECTION MICROWAVE
n - r - 1	100.0

Watte	1.8 Cu. Ft.
	1000
Oven Interior	Stainless Steel
Interior Light	Yes
14-1/4" Glass Turntable	Yes
Control Panel Features	
Q-Tauch" Electronic Controls	Yes
Convection	Yes
	Yes
Front Displey with Blue LED	Yes
Electronia Clock & Timer	- Contraction
Humidity Sensor	Yes
Power Leve's	10
Touch Pad Controls	31
Fast Cook Options	Yes
Cock-2-Perfection® Technology	Yes
Auto-Start	Yes
Auto-Defrest Options	6
Auto-Cook Options - Quick Meal (4), Dinner Recipes (5)	9
Auto-Wett/Soften Options – ce Creem (1), Creem Cheese (1), Butter (1), Chocolata (1)	4
Auto-Rehest Options – Breads (2), Plasta (1)	3
Beverage (0.5 – 2.0 Cups)	Yes
Sensor-Cook Options =	1 4 2
Sersior-Cook Options - Cook (S), Reheat (1), Popcorn (I), Baked Potato (1), Frozen Vegetables (1), Fresh Vegetables (1)	10
Multi-Stage Cooking Options	4
Shartcut Options	5
Add 3C Seconds	Yes
CONTRACTOR	5
Custom Help Options	
Panel Lock	Yes
Demo Mode	Yes
Adjustable Sound Level For Timers/Reminders	Yes
More/Less Function	Yes
Glass Window	Yas
Ventilation System	Vac
	Yes Commonthis
Hood Fan	
Exhaust Duct	Convertible:
Exhaust Duct Exhaust Fan (400 CFM)	4-Speed
Exhaust Duct Exhaust Fan (400 CFM) Charcoal Filters (Fecinculated Installation)	4-Speed 1
Exhaust Duct Exhaust Fan (400 CFM)	4-Speed
Exhaust Duct Exhaust Fan (400 CFM) Charcoal Filters (Recirculated Installation) Grease Filters	4-Speed 1
Exhaust Duct Exhaust Fan (400 CFM) Chareca: Filters (Recirculated Installation) Grease Filters Accessories	4-Speed 1 2
Exhaust Duct Exhaust Fan 400 CFM; Charcoal Filters (Recirculated Installation) Grease Filters Accessories Metal Rack	4-Speed 1
Exhaust Duct Exhaust Fan (400 CFM) Chareca: Filters (Recirculated Installation) Grease Filters Accessories	4-Speed 1 2
Exhaust Duct Exhaust Fan (400 CFM) Charcoal Filters (Reproduited Installation) Grease Filters Accessories Metal Rack 36" Filter Kit	4-Speed 1 2 Included
Exhaust Duct Exhaust Fan (400 CFM) Charcoal Filters (Recirculated Installation) Grease Filters Accessaries Metal Rock 36° Filter Kit. Starriess Steel - PN # MWFILKTSS	4-Speed 1 2 Included
Exhaust Duct Exhaust Fan (400 CFM) Charcoal Filters (Reprodukted Installation) Grease Filters Accessories Metal Rack 30° Filter Kit Stantiess Steel - PN # MW/FIDKTSS Specifications	4-Speed 1 2 Included
Exhaust Duct Exhaust Fan (400 CFM) Charcos Filters (Recirculated Installation) Grease Filters Accessories Metal Rack 30° Filter Kt. Stantiess Steel - PN + MW/FIDKTSS Specifications Colour -	4-Speed 1 2 Included Optional
Exhaust Duct Exhaust Fan 400 CFM; Chercoel Filters (Fechroulated Installation) Grease Filters Accessories Metal Rack 30° Filter Kit. Starriess Steel – PRI # MW/FILKTSS Specifications Colour – Stairiess Steel	4-Speed 1 2 Included Optional
Exhaust Duct Exhaust Fan (400 CFM) Charcoal Filters (Recirculated Installation) Grease Filters Accessaries Metal Rack 30° Filter Kit. Stainless Steel – PN # NWFILKTSS Specifications Colour – Stainless Steel Oven Cavity Dimensions –	4-Speed 1 2 Included Optional
Exhaust Duct Exhaust Fan 400 CFM; Charcos Filters (Fechroulaned Installation) Grease Filters Accessories Metal Rack 30° Filter Kt. Szamiess Steel - PN + NW/FILKTSS Specifications Colour - Stainiess Steel Oven Cavity Dimensions - Height Width	4-Speed 1 2 Included Optional 5
Exhaust Duct Exhaust Fan 400 CFM; Charcos Filters (Facinculated Installation) Glasse Filters Accessories Metal Rack 30° Filter Kit Staintess Steel - PN # NW/FILKTSS Specifications Colour - Staintess Steel Oven Cavity Dimensions - Height Width Dopth	4-Speed 1 2 Included Optional 5 P-15/16* 2(-1)44*
Exhaust Duct Exhaust Fan (400 CFM) Charcoel Filters (Fechoulated Installation) Grease Filters Accessories Metal Rack DC Filter (Rt. Stantiess Steel – PRL # MW/FILKTSS Specifications Colour – Stantiess Steel Dren Carkty Dimensions – Height Width Dooth Product Dimensions –	4-Speed 1 2 Included Optional 5 9-15/16* 21-1/4* 14-23/32*
Exhaust Duct Exhaust Fan (400 CFM) Charcosi Fiters (Fediroushed Installation) Grease Fiters Accessories Metal Rack SC Fiter Kt. Samiles Steel - PRI + MW/FILKTSS Specifications Colour - Stamless Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (Including Lower Extrusion)	4-Speed 1 2 Included Optional 5 9-15/16* 21-1/4* 14-23/32* 17-9/16*
Exhaust Duct Exhaust Fan 400 CFM; Charcos Filters (Fechrouland Installation) Grease Filters Accessories Metal Rack 36° Filter Kt. Szarriess Steel - PN # NW/FILKTSS Specifications Colour - Starriess Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (Including Lower Extrusion) Width	4-Speed 1 2 Included Optional 5 9-15/16* 21-1/4* 14-23/32* 17-9/16* 29-7/8*
Exhaust Duct Exhaust Fan (400 CFM) Charcosi Fitters (Fechroulaned Installation) Grease Fitters Accessories Metal Rack 30° Fitter Kit Staminess Steel – PRI # MWFILKTSS Specifications Colour – Staminess Steel Oven Carvity Dimensions – Height Width Dopth Product Dimensions – Height (including Lower Extrusion) Width Depth (its Centre of Arc - Including Rear Extrusion)	4-Speed 1 2 Included Optional 5 9-15/16* 21-1/4* 14-23/32* 17-9/16* 29-7/6* 17-3/8*
Exhaust Duct Exhaust Fan 400 CFM) Charcosi Fiters (Fediroushed Installation) Grease Fiters Accessories Metal Rack SC Fiter Kt Samiess Steel - PN + MWFILKTSS Specifications Colour - Starliess Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Power Supply Connection Location	4-Speed 1 2 Included Optional 5 9-15/16* 21-14* 14-23/32* 17-3/16* 29-7/8* Right Top Rear
Exhaust Duct Exhaust Fan (400 CFM) Charcos Filters (Fechrouland Installation) Grease Filters Accessories Metal Rack 30° Filter Kr. Stanriess Steel - PN + NW/FILKTSS Specifications Colour - Starriess Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (nobuding Lower Extrusion) Width Depth (Including Lower Extrusion)	4-Speed 1 2 Included Optional 5 P-15/16* 21-1/4* 14-23/32* 17-9/6* 29-7/6* 17-3/6* Right Top Reer 12/07/50/Fb/15
Exhaust Duct Exhaust Fan (400 CFM) Charcos Filters (Fechrouland Installation) Grease Filters Accessories Metal Rack 36° Filter (R: Stainless Steel - PT4 * NWFILKTSS Specifications Colour - Stainless Steel Oven Cavity Dimensions - Height Width Depth Product Dimensions - Height (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Voltage Rating Connected Load («W Rating) & 120 Volts*	4-Speed 1 2 Included Optional 5 9-15/16* 21-14* 14-23/32* 17-3/16* 29-7/8* Right Top Rear
Exhaust Duct Exhaust Fan (400 CFM) Charcosi Fiters (Fediroushed Installation) Grease Fiters Accessories Metal Rack 30° Fiter Kt Samiess Steel - PRI * MWFILKTSS Specifications Colour - Starliess Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (notuding Lower Extrusion) Width Depth (to Cavitre of Arc - Including Rear Extrusion) Power Supply Connection Location Voltage Rating Connected Load (kW Rating) 39 120 Vots* Amps @ 120 Vots*	4-Speed 1 2 Included Optional 5 9-15/16* 21-14* 14-23/2* 17-9/16*
Exhaust Duct Exhaust Fan (400 CFM) Charcos Filters (Fechrouland Installation) Grease Filters Accessories Metal Rack 36° Filter (R: Stainless Steel - PT4 * NWFILKTSS Specifications Colour - Stainless Steel Oven Cavity Dimensions - Height Width Depth Product Dimensions - Height (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Voltage Rating Connected Load («W Rating) & 120 Volts*	4-Speed 1 2 Included Optional 5 9-15/16* 21-14* 14-23/32* 17-9/16* 29-7/6* 17-3/6* Right Top Pear 12/04/50/Hz/15
Exhaust Duct Exhaust Fan (400 CFM) Charcosi Fiters (Fediroushed Installation) Grease Fiters Accessories Metal Rack 30° Fiter Kt Samiess Steel - PRI * MWFILKTSS Specifications Colour - Starliess Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (notuding Lower Extrusion) Width Depth (to Cavitre of Arc - Including Rear Extrusion) Power Supply Connection Location Voltage Rating Connected Load (kW Rating) 39 120 Vots* Amps @ 120 Vots*	4-Speed 1 2 Included Optional 5 9-15/16* 21-14* 14-23/2* 17-9/16* 19-78* 17-3/8* 17-3/8* Right Top Reer 12/07/50/Hb/15, 17-1
Exhaust Duct Exhaust Fan (400 CFM) Charcos Filters (Fechouland Installation) Grease Filters Accessories Metal Rack 30° Filter Kit. Samiless Steel - PRI + MW/FILKTSS Sectifications Colour - Stainless Steel Oven Cavity Dimensions - Height Width Depth Product Dimensions - Height (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Depth (Including Lower Extrusion) Width Control of Arc - Including Rear Extrusion) Fower Supply Connection Location Voltage Rating Connected Load (kW Rating) © 120 Volts* Frequency (Whiz)	4-Speed 1 2 Included Optional S 9-15/16* 21-1/4* 14-23/32* 17-3/16* 29-7/6* 17-3/8* 17-3/16* 29-7/6* 17-3/8* 17-3/16* 29-7/6* 17-3/16* 29-7/6* 17-3/16* 17-3
Exhaust Duct Exhaust Fan (400 CFM) Charcos Filters (Fechrouland Installation) Grease Filters Accessories Metal Rack 36° Filter Kt. Saminess Steel - PN + NW/FILKTSS Specifications Colour - Stainless Steel - PN + NW/FILKTSS Specifications Colour - Stainless Steel Oven Cavity Dimensions - Height Width Dopth Product Dimensions - Height (Including Lower Extrusion) Width Dapth (Including Lower Extrusion)	4-Speed 1 2 Included Optional 5 9-15/16* 21-1/4* 14-23/32* 17-3/16* 29-7/8* 17-3/8
Exhaust Duct Exhaust Fan (400 CFM) Charcosi Fiters (Fediroushed Installation) Grease Fiters Accessories Metal Rack 30° Fiter Kit Stantiess Steel – PRI # MWFILKTSS Specifications Colour – Stantiess Steel – PRI # MWFILKTSS Specifications Colour – Stantiess Steel Oven Cartly Dimensions – Height (Mobiling Lower Extrusion) Width Dopth Product Dimensions – Height (Including Lower Extrusion) Width Dapth (to Centre of Arc - Including Rear Extrusion) Power Supply Connection Location Voltage Rating Connected Load (vM Rating) (# 120 Vots* Amps (# 120 Vots* Frequency William Microwave – Watts (# 120 Vot Input Convection – Watts (# 120 Vot Input	4-Speed 1 2 Included Optional 5 9-15/16* 21-1/4* 14-23/32* 17-9/16* 29-7/6* 17-3/8* Right Top Reer 120N/50/Hy/15, 1.71 14.3 2450 1050


NOTE: Always consult rocal and national electric codes. Refer to Product installation Guide for calmad installation nativistions on the web at electrological and actual code.

electroluxappliances.ca



Over-the-Range Microwave





30" Over-the-Range Microwave Specifications

- Product Weight 70 Lbs.
- Voltage Pating 120V/60 Hz/15 Amps
- Connected Load (kW Rating) @ 120 Volts = 1.71 kW (For use on adequately wired 120V, dedicated circuit having 2-wire service with a separate ground wire. Appliance must be grounded
- for safe operation.)

 Amps @ 120 Volts = 14.3 Amps
- Always consult local and national electric codes.
- Grounded cutiet should be located in cabinet above, with hole in base to route power cord. Carefully follow top template instructions for power cord clearance when installing beneath smooth, flat cabinets.
- cord clearance when installing beneath smooth, flat cabinets.

 Microwave's ventilation system is preset to recirculate air inside with no ducting system required. Exhausting air cutside is optional, using either vertical or horizontal ducting system. (Refer to Ducted Option Specifications for outside ventilation.)

 For safe and proper installation, microwave MUST be mounted to BOTH a top cabinet AND a wall, and connected to at least one wall stud. Can NOT be installed in isand or peninsula cabinet arrangements.

 Cabinet bottom MLIST be level to insure proper installation.
- Cabinet bottom MUST be level to insure proper installation.
- Cabinet MUST be capable of supporting a total load of 135 lbs.
- Filler blocks recommended for installation when cabinet front hangs below recessed bottom shelf.
- Minimum distance of 30" required from cocking surface to bottom edge of top cabinet.
- Minimum distance of 66" required from floor to top of microwave.
 Opening between cabinets MUST be 30" wide and free of obstructions. For openings up to 36" wide, order optional 36" Filler Kit to fill in gap between unit and cabinets.
- Allow 26" minimum clearance for 90° door swing.

Ducted Option Specifications

- For outside ventilation.
- Exhaust duct adapter will be needed for outside ventilation, to mate with standard 3-1/4" x 10" rectangular duct. If round duct required, rectangular-to-round transition adapter will be needed with no more than 6" clarmeter.
- For most efficient airflow exhaust, use a straight run or as few elbows as possible with a maximum duct length of 3-1/4* x 10* rectangular or 6* diameter round duct, not to exceed 120 equivalent feet.
- For horizontal installation, be sure to allow enough space between wall studs to accommodate exhaust.
- Refer to installation instructions on web for detailed out preparation and converting exhaust vent blower system for exterior exhaust ventilation.

Note: For planning purposes only. Refer to Product Installation Gui on the web at electroluxappliances.ca for detailed instruction


Optional Accessories

- 36° Filler Kit: S = (PN # MWFILKTSS).

Electrolux Major Appliances, N.A.

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • electroluxappliances.ca © 2015 Electrolux Major Appliances, N.A.

Printed in Canada



5.1 Ou Pt.



Front Load Washers

EWFLS70J SS/IW

Wave-Touch® Electronic Controls Featuring Perfect Steam®







Island White



Largest Capacity Washer!

Wash the most in one load with our 5.1 cu. ft. (I.E.C.) washer.



Fastest Wash Time²

Fifteen minutes to wash.



Specialty Cycles

Clean all your special items including pet beds, stuffed animals, wool and more.



Cleanest Front Load Wash³

Our front load washer offers exclusive technology that gets your clothes the cleanest.



Based on manufacturer's specifications. Volume per LE.C. In: Y Stat. 60456, 4th ea. based on 4.42 cu. ft. D.C.E. measurement. Fastest time based on smallest load/Fast Wash and Fast Dry cycles selected for various load compositions. Based on AHAM washability lest protocol for leading brand front load washers with normal cycle lines less than 50 minutes. 27" ELECTRIC FRONT LOAD WASHERS

Dispatity I.E.U.	O.I CO.FI.
Features	
Wave-Touch® Electronic Controls with LCD Display	Yes
Perfect Steam" Wash System	Yes
Perfect Balance* System	Yes
Luxury-Quiet" Sound System	Yes
Luxury-Design® Lighting	Yes
Touch-2-Open */ (Close) Door	Yes
Luxury-Gilde" Touch-2-Open"/(Close) Dispenser Brawer	Yes
Full Fabric Stain Removal Guide	Yes
ExpertCare* Wash System	Yes
Integral Water Heater	Yes
Stainless Steel Wash Drum	Yes
Automatic Temperature Control	Yes
Automatic Water Level Adjustment	Yes
Auto Prewash Detergent Dispenser (Liquid/Powder)	Yes
Auto Bleach Dispenser (Liquid Only)	Yes
Auto Detergent Dispenser (Liquid/Powder)	Yes
Auto Fabrio Softener Dispenser (Liquid Only)	Yes
Turnble Speed (RPM)	48-52 Variable
Spin Speed (RPM)	1,400
Reversible Door	Yes
ENERGY STAR* Most Efficient*	Yes
NSF* Corlifed	Sanitize/Allergen

Cyeles			- 1111
Fast Wash".	My Favouritos (3	Deep Clean	Sanitize",

Heavy Duty", Whites", Colors", Normal", Active Weer", Casual", Delicates, Hand Wash, Spin Only "Can be used with Add Steam option)	9
Specialty Cycles – Jerrs, Fast Sanitize, Stuffed Animats', Fet Begs', Clean Washer, Steam Prewash', Kids Wear', Fast Steam', Woo ("Can be used with Add Steam option)	
Individual Custom Options (3) – Additional user settings, each with 11 cycles, 9 Specialty and 3 My Favourites (23)	

Total Cycles Available	90
Options	
Wash/Rinse Temperature Combinations	9
Temperature Selections	6
Add Steam	8
Spin Speed Selections	6
Soil Level Selections	6
Delay Start (Hours)	22
Enc-of-Cycle Chime	Adjustab e

Freestanding, Under Counter*, Stacked (Under Dryer),	Yes	_
Pedestal, Hidden (in Closet), Second Floor		

ccessories	
	Optional
Dryar Stacking Kit – PN# STACKIT4X	Optional

DIAIN HOSE EXICISION KIT - PINK 127090000	Optional
Mobile Home Installation Kit − PN# 137067200	Optional
Specifications	
Colour -	
3 Iver Sands	38
Island White	W
Product Dimensions –	
Height (Without 15" Pedestal / With 16" Pedestal)	38*/53*
Width	27*
Depth (to Center of Arc Not Including Hose) (with 90° Door Open)	31-1/2" 50-5/0"
Power Supply/ Water Inlet Location	Top Right Rear / Top Left Rear
Voltage Rating	120V/60Hz/15A
Connected Load (kW Rating) 6 120 Volts [‡]	1.4
Watts @ 120 Volts	1,000
Amps @ 120 Volts	12


247 Lbs. Shipping Weight (Approx.)
Side-by-Side units in under-cour company reagants in unancomme katallation require custom-bulk countering and/or cabinety.

For use on adequately wred 1207, decirated should having 2-wire service with a separate ground wire.

Appliance must be grounded for also because.

Apparation from our generated for agent between MATE. Alterproportion of the MATE and Apparation of the Apparation of the MATE. Alterproportion for the MATE and Apparation of the MATE


electroluxappliances.ca



Front Load Washers

EWFLS70J SS/IW





Front Load Washer Specifications

- Product Weight 237 Lbs.
- An electrical supply with grounded three-prong receptacle is required. The
 power supply circuit must be installed in accordance with current edition
 of National Electrical Code (ANSI/NFPA 70) and local codes & ordinances.
 (Do not use same circuit as dryer.)
- Voltage Rating =120V/50Hz/15 Amps
 Amps @120 Volts = 12 Amps
- Connected Load (kW Rating) @120 Volts = 1.4kW
- Equipped with 120V 3-wire power supply cord, approx. 60* long.
- Always consult local and national electric & plumbing codes. To maximize detergent effectiveness, ambient temperature should never be below 60°F.
- Can be installed alone, with or without optional 15" pedestal drawer, or stacked beneath matching Electrolux Dryer, which requires installation of optional dryer stacking kit. (For installation details, refer to instructions included with optional pedestal or stacking kit or on web.)
- Can be built in with matching Electrolux Dryer in under-counter, recessed or closet installation. Installations requiring countertop and/or cabinetry will require custom building. (Refer to Built-in Installations on this page for cutout dimensions. For additional installation details, refer to Product Installation Guide on web.)
- Closet installation requires vented door with 2 unobstructed louvered openings, minimum 60 sq.in. each, located 3" from too and bottom of door. Full-length120 sq.in. opening also acceptable. Allow 1" clearance between door and fronts of units.

- Do NOT install in area exposed to dripping water or outdoor weather conditions, or where gasoline or other flammables, including automobiles, are kept or stored.
- Floor MUST be solid with 1" maximum slope. To ensure vibration or movement does not occur, reinforcement of floor may be necessary. Do NOT install on carpeted surface.
- Leveling legs supplied to level washer properly and reduce excessive noise and vibration.
- H/C water faucets MUST be installed within 42" of washer's water inlet and MUST be 3/4" garden hose type, to connect to 48-1/2" inlet hoses
 Water pressure MUST be between 30 and 120 psi with NOT more than 10 psi pressure difference between hot and cold.
- Drain required with standpipe diameter of 1-1/4" min. and height of 24" min./96" max. above floor, capable of eliminating 17 gallons per minute. Attached 59" drain hose can reach 79"-high standpipe.

Note: For planning purposes only. Refer to Product Installation Guide on the web at electroluxappliances.ca for detailed instructions.

Optional Accessories

- Pedestal Drawers Silver Sands (PN# EPWD15SS), Island White (PN# EPWD15IW).
 Dryer Stacking Kit (PN# STACKIT4X).
- Drain Hose Extension Kit (PN# 137098000).
- Mobile Home Installation Kit (PN# 137067200).



Electrolux Major Appliances, N.A. CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-265-8352 • electroluxappliances.ca

EWFLS70J 06/13

© 2013 Electrolux Major Appliances, NA

we are constantly working to improve our pro-to change appealing for discount







Electric Front Load Dryers

EWMED7CJ SS/IW

Wave-Touch® Electronic Controls Featuring Perfect Steam®









Largest Capacity Dryer Dry the most in one load with 8.0 cu. ft. capacity



Fastest Dry Time² Fourteen minutes to dry.



Specialty Cycles
A cycle for virtually anything including pet beds, stuffed animals, workout gear and more.



Perfect Steam" Dryer

The latest technology removes wrinkles and freshens clothes. "Add Steam" option can be used with select cycles.



27" ELECTRIC FRONT LOAD DRYERS

Capacity I.E.C.	8.0 Cu.Ft.
Features	
Signature Soft-Arc Door Design	Yes
Wave-Touch® Electronic Controls with LCD Display	Yos
Perfect Steam" Dry System	Yes
Perfect Tumble" Dry System	Yes
Luxury-Quiet* Bound System	Yes
Luxury-Design® Lighting	Yes
Lexury-Dry" System	Yes
Touch-2-Open"/ (Crose) Door	Yes
Exact Dry" Moisture Sensor	Yes
Stainless Steel Dryer Drum	Yes
umble Speed (RPM)	50
Reversible Door	Yes
Adjustable Leveling Legs	Yes
NSF* Certified	Sanitize

Fast Dry, My Favourites (3), Heavy Duty*, Bulky/ Bedding*, Mixed Loed*, Towels, Normal*, Active Wear*, Casua*, Delicate*, Perfect Steam**, Timed Dry (*Can be used with Add Steam option)	14	
Specialty Cycles - Jeans, Warm Up, Stuffed Animais*, Per Beds, Fast Steam, Comforter, Kids Wear, Air Clean, Wool ("Can be used with Add Steam option)	9	
Individual Custom Options (3) – Additional user settings, each with 11 cycles, 9 Specialty and 3 My Favourites (23)	66	
Total Cycles Available	92	
Options		
Temperature Selections	7	Ξ
Add Steam	9	
Electronic Auto Dry System	Yes	
Manual Timed Dry Selections	6	Т

Delay Start (Hours) Enc-of-Cycle Chime Eco-Friendly Adjustable Anti-Static Line Dry

Freestanding, Under Counter', Stacked (Above Washer), Peciasta, Hidden (In Closet), Second Floor, 4-Way Dryer Verbing	Yes

Accessories Limay-Glide* Touch-2-Open*/(Close) Pedestal – See Sack for Part Numbers Dryer Stacking Kit – PNA STACK/TAX Mobile Home Installation Kit – PNA 137087200

Dry ng Rack - PN# 137453000	Optional
Specifications	
Colour -	
Silver Sands	SS
Island White	IW
Product Dimensions =	- 1000
Height (Without 15" Pedestali (With 15" Pedestali	38° 53°
Width	27"
Depth (to Center of Arc Including Door and Exhausti (with 90° Door Open)	31-1/2"
Maximum Exhaust Duct Length³ (Ft.)	125
Power Supply Connection Location	Bottom Fight Rear
Voltage Rating	240V/60Hz/30A
Connected Load (kW Fating) @ 240 Volts	6.48
Amps @ 240 Volts	27
Heating Element @ 240 Volts (Watts)	5,400
Shipping Weight (Approx.)	140 Lbs.
	The second secon

Based on manufacturer specifications.

Fisales fane based on immalest load Fisal Wash and Fast Dry cycles selected for various load compoflight metal chart prohibmed, semi-inject cycleshared and allow deductions for efforce and metal. Plefer to installation Caule on web for adordonal information.


electroluxappliances.ca



Electric Front Load Dryers

EWMED7CJ SS/IW





Electric Dryer Specifications

- Product Weight 130 Lbs.
- Voltage Rating 240V/80 Hz/30 Amps
- Single phase 3- or 4-wire cable, 240 Volt, 60 Hertz AC only electrical supply with ground required on separate circuit fused on both sides of line. (Do not use same circuit as washer.)

 - Connected Load (kW Rating) @ 240 Volts = 6.48 kW
- Amps @ 240 Volts = 27 Amps
- Amps @ 240 Volts = 27 Amps
 Dryer MUST employ a 3-conductor NEMA 10-30 type SRDT or 4-conductor NEMA 14-30 type SRDT or ST (as required), rated at 240 volt AC minimum, 30 amp power supply cord marked for use with clothes dryers (not supplied).
 Grounding through neutral link prohibited in specific applications and certain locales, requiring use of 4-wire system. (For detailed electrical requirements, refer to Product Installation Guide on web.)
- Always consult local and national electric & plumbing codes.
- Can be installed alone, with or without optional 15" pedestal drawer, or stacked above matching Electrolux Washer, which requires installation of optional dryer stacking kit. (For installation details, refer to instructions included with optional pedestal or stacking kit or on web.)
- Can be built in with matching Bectrolux Washer in under-counter, recessed or closet installation. Installations requiring countertop and/or cabinetry will require custom building. (Refer to Built-In Installations on this page for cutout dimensions. For additional installation details, refer to Product Installation Guide on web.)
- Closet installation requires vented door with 2 unobstructed louvered openings, minimum 60 sq. in, each, located 3" from top and bottom of door. Full-length 120 sq. in, opening also acceptable. Allow 1" clearance between door and fronts of units.

- Do NOT install in area exposed to dripping water or outdoor weather conditions, or where gasoline or other flammables, including automobiles, are kept or stored.
- Floor MUST be solid with 1" maximum slope. To ensure vibration or movement does not occur, reinforcement of floor may be necessary. Do NOT install on carpeted surface.
- Dryer MUST exhaust to outside of building, NOT into any concealed space.
- Dryer equipped for 4-way venting and approved for up to 125-foot-equivalent of duct length, determined by length of run and number of elbows needed.
- Exhaust installation requires minimum 4"-diameter rigid or semi-rigid metal duct with approved, unobstructed vent hood having swing-out damper(s), if installing rigid metal duct (preferred), do not exceed MAXIMUM venting run ength of 125 ft., allow deductions for elbows and vents. If installing semi-rigid metal duct, do not exceed MAXIMUM venting run length of 8 ft., always allow deductions for elbows and vents (Refer to Product Installation Guide on web for additional information). Do NOT use flexible plastic or metal foil duct and use shortest run prossible. metal foil duct and use shortest run possible.
- Leveling legs supplied to level dryer properly and reduce excessive noise and vibration.
- Water inlet hose for steam setting connects to cold water supply with "Y" connector and requires 3/4" clearance between back of unit and wall.

Note: For planning purposes only. Refer to Product Installation Guide on the web at electroluxappliances.ca for detailed instructions.

Optional Accessories

- Pedestal Drawers Silver Sands (PN# EPWD15SS), Island White (PN# EPWD15IW).
- Dryer Stacking Kit (FN# STACKIT4X).
- Mobile Home Installation Kit (PN# 137067200).
- Drying Rack (PN# 137453000).

Printed in Canada

Electrolux Major Appliances, N.A.

CANADA • 5855 Terry Fox Way • Mississauga, ON L5V 3E4 • 1-800-285-8352 • electroluxappliances.ca

EWMED7CJ 10/13

© 2013 Electrolux Major Appliances, NA



KITCHEN.

Arbor

Transitional





Single Handle Kitchen Faucet with Side Spray*

(Use model number only for Chrome finish)

Not available in BL finish



Single Handle Pullout Kitchen Faucet²



Single Handle Pull-Down Bar/Prep Faucet²

† To order, combine the model number with one of these finish letters:



* Single or Three Hole Installation ± Single Hole Installation Only





9130-BH

Soap or Lotion Dispensers

Traditional | Transitional | Modern



Traditional Styled Soap/Lotion Dispenser±




Modern Styled Soap/Lotion Dispenser±

KITCHEN



Transitional Styled Soap/Lotion Dispenser±





± Single Hote installation Only



CAMDEN 9130- 84 16" SQUARE UNDERMOUNT SINK



Undermount Sink

Product Specs:

- Vitreous china
- · Front overflow hole
- · Template and mounting hardware supplied

Overall Dimensions (W x D x H):

(OD): 406mm(16") x 406mm(16") x 190mm(71/2") (ID): 345mm(13%") x 345mm(13%") x 140mm(51/2")


Compliance Certifications:

Meets or exceeds the following:

- · IAPMO cUPC
- ASME A112.19.2 / CSA B45.1-2008


Shipping:


Cube 1.43 GW 24 lbs



standard A112.19.2. These measurements for use of supersoded or voided pages. surements are subject to change or cancellation. No respon

*Bone and Bisouit available through Direct import (CIF) only.





CONTRAC® 5970 Chedworth Way, Unit A, Mississauga, Ontario Canada L5R 3V5 ◆ 1.888.256.7551 www.contrac.ca

Revised: January 2015


X2 MASTER BATH MAIN BATH (2NO FLE) POWDER ROOM

ATOR HOMES ECOR CENTRE JAN 2 2 2016



Teefy - Lot 84

MAIN BATH SECOND FLOOR ONLY



12x24 TO BE INSTALLED HORIZONTAL STACKED ON CENTER REAR WALL ONLY


8XID - TO BE INSTALLED HORIZONTAL STACKED ON TUB SIDE WALLS AND ON CEILING.

FLOOR THE DOOR IN A STACKED PATTERN

SENATOR HOMES
DECOR CENTRE
FEB 1 1 2016



MASTER ENSUITE SHOWER ONLY ON SECOND FLOOR.



TO BE INSTALLED HORIZONTA 12x24 - STACKED ON LARGER WALL ONLY

TO BE INSTALLED HOKIZONTAL Bx12 STACKED ON SMALLER WALL AND ON CEILING.

FLOORING TO BEI INSTALLED HORIZONTAL TO THE DOOR

FEB 1 1 2016

Voss

Transitional



Roman Tub





10 Digital™ Roman Tub



IO Digitat™ Roman Tub with Handheld Shower





IO Digital™ Remote Control for Roman Tub

Matching tub drain assembly available. Please see $Bath\ Hardware\ and\ Home\ Care\ Section$. † To order, combine the model number with one of these finish letters





SENATOR HOMES
DECOR CENTRE
FEB 1 1 2016