

CONSTRUCTION SUMMARY

KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)

Lot/Unit: 97 Phase/Building: 5A Model/Floor Plan: Louis (4203) Elev B 4 Bed - 4+1 Bath

CABINETRY

Inv. 5673	1 - To accommodate for a 36" stove opening in lieu of the standard 30" stove opening.	
Line 72622	Note:	
12Jul22 / 12Jul22		

CABINETRY APPLIANCE - FRIDGE

Inv.5673	1 - To supply & install the 66CM DEEP FRIDGE ENCLOSURE - COUNTER DEPTH WITH - 1 WALL - 1 66CM DEEP GABLE AND 1 66CM DEEP CABINET - THIS IS NOT A ZERO CLEARANCE ENCLOSURE. STANDARD HEIGHTS AND WIDTHS WILL BE USED. in the kitchen see sketch # 1	
Line 72624	Note: See fridge spec's attached.	
12Jul22 / 12Jul22		

CABINETRY HOOD FANS

Inv. 5673	1 - To supply & install a 36" standard style stainless steel hood fan in lieu of the standard hood fan.	
Line 72621	Note:	
12Jul22 / 12Jul22		

CABINETRY MICROWAVE OVEN STOVE COOKTOP

Inv. 5673 Line 72623 12Jul22 / 12Jul22	1 - To supply & instal accomodations for the future BUILT-IN TALL APPLIANCE CABINET WITH DRAWER - S BELOW FOR PANEL-MOUNT - PROUD - OR TRIM KIT INSTALLATIONS - TRIM KIT REQUIRED - SUPPLY ALL SPECS AND INSTALLATION GUIDES - COUNTER DEPTH -in the kitchen Note: See sketch # 1	
Inv. 5673	1 - To accomodate for the future COOKTOP CABINET WITH FALSE TOP DRAWER AND POTS AND PANS DRAWERS BELOW - SUPPLY SPECS - in the kitchen see sketch # 1	
Line 72619	Note:	
12Jul22 / 12Jul22		

CABINETRY VANITY

Inv. 5673	1 - To supply & install a VANITY BANK OF DRAWERS - in the master ensuite see sketch # 2	
Line 72625	Note:	
12Jul22 / 12Jul22		

CARPET

Inv. 5673	1 - To supply & install the upgrade ESCAPE TO MAUI carpet throughout the 2nd floor in lieu of the standard carpetsee colour chart for details.	
Line 72630	Note:	
12Jul22 / 12Jul22		

COUNTER TOP

Inv. 5673	1 - To supply & install accommodations to the quartz countertop for the future 36" cook top at stove location in the kitchen see spec's see sketch # 1	
Line 72620	Note:	
12Jul22 / 12Jul22		

This Document is Extremely Time Sensitive - Printed $\underline{13 \text{ Jul } 22}$ at $\underline{21:05}$

Page 1 of 3

ummaryMS.rpt 28Feb20-1 Printed and Sent: 13-Jul-22



CONSTRUCTION SUMMARY

KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)

Lot/Unit: 97 Phase/Building: 5A Model/Floor Plan: Louis (4203) Elev B 4 Bed - 4+1 Bath

Inv. 5673	1 - As per schedule "PE": Vendor to include level 1, 2cm. quartz in all bathrooms, as per plan, in lieu of the inlcuded laminate counter tops. Selections to be made from builders standard	
	samples.	
Line 72569	Note:	
12Jul22 / 12Jul22		

ELECTRICAL

ELECTRIC	CAL	
Inv. 5673	1 - To supply & install the standard T.V. rough in the great room and master bedroom see sketch # 1 & # 2	
Line 72570	Note: Install the standard T.V. at approx. 66" + - up from the floor centered to the F/P in the great room.	
12Jul22 / 12Jul22		
Inv.5673	1 - To supply & install the standard Phone (CAT 5) rough in in the great room, master bedroom & bedroom # 4 see sketch # 1 & # 2	
Line 72571	Note: Install the standard Phone (CAT 5) at approx. 66" + - up from the floor centered to the F/P in the great room.	
12Jul22 / 12Jul22		
Inv. 5673	1 - To SUPPLY AND INSTALL AN ADDITIONAL BASIC RECEPTACLE (NOT	
	DEDICATED) at approx. 66" + - up from the floor centered to the F/P mantle	
Line 72612	Note: in the great room see sketch # 1	
12Jul22 / 12Jul22	This is for a future wall mount T.V.	
	NO CONDUIT PIPE HAS BEEN PURCHASED.	
Inv. 5673	1 - Relocate the standard light from the upper stair landing to the O.T.B. area on the second	
	floor see sketch # 2	
Line 72613	Note: No reinforcing purchased.	
12Jul22 / 12Jul22		
Inv. 5673	1 - To SUPPLY AND INSTALL EXTRA CEILING BOX ROUGH IN CAPPED (DOES NOT	
	INCLUDE SWITCH) over the kitchen island area in the kitchen see sketch # 1	
Line 72614	Note: This cap will be connected to a sep. switch, switch sold sep.	
12Jul22 / 12Jul22		
Inv. 5673	1 - To supply & install AN ADDITIONAL SINGLE POLE SWITCH connected to the	
	upgraded capped elec. over the kitchen island in the kitchen.	
Line 72615	Note:	
12Jul22 / 12Jul22		
Inv. 5673	1 - To SUPPLY AND INSTALL EXTRA 240 STOVE PLUG for the future built in wall	
	oven/microwave combo in the kitchen see spec's see sketch # 1	
Line 72617	Note:	
12Jul22 / 12Jul22		

HEATING AND AIR CONDITIONING

Inv. 5673	1 - As per schedule "PE": Vendor to install capped gas line (rough in only) at rear of home for future BBQ location. Location to be finalized at vendors sole discretion.	
Line 72567	Note:	
12Jul22 / 12Jul22		
Inv. 5673	1 - As per schedule "PE": Vendor tosupply & install air conditioning unit, sized accordingly from vendors standard samples.	
Line 72568	Note:	
Line /2500	Note.	

This Document is Extremely Time Sensitive - Printed $\underline{13\ Jul\ 22}$ at $\underline{21:05}$

Printed and Sent: 13-Jul-22



CONSTRUCTION SUMMARY

KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)

Lot/Unit: 97 Phase/Building: 5A Model/Floor Plan: Louis (4203) Elev B 4 Bed - 4+1 Bath

Inv. 5673	1 - To supply & install a capped gas rough in at stove area in kitchen, to include a 110V elec. outlet code requirement.	
Line 72616	Note:	
12Jul22 / 12Jul22		

MISCELLANEOUS

PLUMBING

Inv. 5673	1 - To supply & install the LAVATORY SINK - CONTRAC CALVIN UNDERMOUNT -	
	MODEL 4220CFY in ensuite # 3's bathroom in lieu of the standard top mount sink see spec's	
Line 72626	Note: Still to install the standard lav facuet.	
12Jul22 / 12Jul22		
Inv. 5673	5 - To supply & install the VANITY SINK - CONTRAC CATENA UNDERMOUNT -	
	MODEL 4210CIY in the powder room, master ensuite, ensuite #2 & ens. # 4 in lieu of the	
	standard top mount vanity sinks see spec's	
Line 72627	Note: Still to install the standard lav facuet.	
12Jul22 / 12Jul22		
Inv. 5673	1 - To supply & install the MIRILOYN " BROOKE" free standing tub in the master ensuite in	
	lieu of the standard free standing tub see spec's	
Line 72628	Note:	
12Jul22 / 12Jul22		
Inv. 5673	1 - To supply & install the KITCHEN SINK - BLANCO QUATRUS U2 DBL	
	UNDERMOUNT MODEL 401247 in the kitchen in lieu of the standard undermont kitchen	
	sink see spec's	
Line 72629	Note: Still to install the standard single hole kitchen faucet, NO PLATE.	
12Jul22 / 12Jul22		
Inv. 5673	1 - To suply & install a WATERLINE ROUGH-IN TO THE FRIDGE LOCATION (NO	
	HOOK UP) in the kitchen.	
Line 72618	Note:	
12Jul22 / 12Jul22		

EXTRAS AS PER OFFER

5 FREE APPLIANCES – STAINLESS STEEL FRONT - FRIDGE; STOVE AND DISHWASHER. WHITE WASHER AND DRYER (SUPPLIED ONLY, NOT INSTALLED, FROM BUILDERS STANDARD LINE). AN APPLIANCES VOUCHER WILL BE GIVEN BY OUR DECOR CONSULTANT AT THE TIME OF BOOKING YOUR COLOUR A Worksheet Note:	
VENDOR TO INSTALL CAPPED GAS LINE (ROUGH-IN ONLY) AT REAR OF HOME FOR FUTURE BBQ LOCATION. LOCATION TO BE FINALIZED AT VENDORS SOLE DISCRETION. Worksheet Note:	
VENDOR TO SUPPLY & INSTALL AIR CONDITIONING UNIT, SIZED ACCORDINGLY, FROM VENDORS STANDARD SAMPLES. Worksheet Note:	
VENDOR TO INCLUDE LEVEL 1, 2CM QUARTZ IN ALL BATHROOMS, AS PER PLAN, IN LIEU OF THE INCLUDED LAMINATE COUNTER TOPS. SELECTIONS TO BE MADE FROM BUILDERS STANDARD SAMPLES. Worksheet Note:	

This Document is Extremely Time Sensitive - Printed $\underline{13 \text{ Jul } 22}$ at $\underline{21:05}$

Page 3 of 3

Printed and Sent: 13-Jul-22

KINGSIIEN

Elegrina

INTERIOR COLOUR SCHEME

5A-10+97

Purchaser: TARANVIR SINGH MINHAS Property: 97 of Plan - Draft Approval SB17-03-08 Telephone Res. / Bus: / Project: KINGSMEN (THAMES) INC. Decor Advisor: Barbara Coccia Model and Elevation: Louis (4203) Elev B 4 Bed - 4+1 Bath Layout Changes: Yes No Sketch Attached: Yes No Exterior Colour Scheme: 1. Cabinetry Style and Colour Hardware Kitchen / Breakfast #3, Simcoe Moonlight #1, C/S # 9141 Ice Snow 3cm. #12881 Handle Kitchen Island #3, Simcoe Moonlight #1, C/S # 9141 Ice Snow 3cm. #12881 Handle Laundry Room Powder Room #3, Simcoe Moonlight #1, C/S # 9141 Ice Snow 2cm. #12881 Handle Main Bathroom Master Ensuite Bathroom #3, Simcoe Rain Cloud #1, C/S # 3040 Cement 2cm. #9671 Handle Second Ensuite #3, Simcoe Rain Cloud #1, C/S # 3040 Cement 2cm. #9671 Handle Bathroom (If Applicable) Ens. #3's Bathroom #3, Simcoe Rain Cloud #1, C/S # 3040 Cement 2cm. #9671 Handle Ens. #4's Bathroom #3, Simcoe Rain Cloud #1, C/S # 3040 Cement 2cm. #9671 Handle Appliances Custom Size Fridge Valance Lighting Microwave / Range Hood Yes \(\) No O Yes No No Yes No Cooktop / Rangetop Built in Wall Oven Slide-in Range Yes O No Yes O No Comment O Yes

2. Flooring	Selection
Foyer	13 x 13" Malena Ice
Main Hall	3 1/2" Elements Oak Strugeon
Back Hall	Ens. #4's Bathroom: 13 x13" Malena Carbon
Breakfast	(Including Pantry) 13 x 13" Malena Ice
Laundry Room	13 x 13" Cinq Grey
Kitchen	13 x 13" Malena Ice
Powder Room	13 x 13" Malena Ice
Main Bathroom	Ens. #2's Bathroom: 13 x 13" Malena Carbon
Master Ensuite	13 x 13" Malena Carbon
Bathroom (If Applicable)	Ens. # 3's Bathroom: 13 x 13" Cinq Black
Mud Room	13 x 13" Malena Ice
Mas. Ens. & Ens. 2's shower	floor: 2x2" Ontario Snow white Matte
Living Room	(Sitting room) 3 1/2" Elements Oak Strugeon
Dining Room	1
Family / Great Room	3 1/2" Elements Oak Strugeon
Den / Library / Study	/
Basement Landing (If Applie	es) —
Lower Landing (If Applicable	e)3 1/2" Elements Oak Strugeon
Upper Landing	(if applicable) 3 1/2" Elements Oak Strugeon
Upper Hall	**Escape to Maui # 89827 Misty Horizon
Master Bedroom	**Escape to Maui # 89827 Misty Horizon
Bedroom #2	**Escape to Maui # 89827 Misty Horizon
Bedroom #3	**Escape to Maui # 89827 Misty Horizon
Bedroom #4	**Escape to Maui # 89827 Misty Horizon
Bedroom #5	I
Mas. Ens. &Ens. #2's	Shower jamb: Anatolia marmiline SNOW

Flooring Continued on Page 2

JUL 1 3 2022



Initial:

KINGSI^IIEN

Printed 7/12/2022 17:30:39

Purchaser:

TARANVIR SINGH MINHAS

INTERIOR COLOUR SCHEME

5A 10t97

Property: 97 of Plan - Draft Approval SB17-03-08


Telephone Res. / Bus	s: /				Proj	ect: KI	NGSM	EN (THAMES) INC.
Decor Advisor:	Barbara	Coccia		Model an					Bed - 4+1 Bath
2. Flooring - Continu	uea -								
Upgrade Underpad		Туре			Α	rea			
		Standard			2	nd, Floo	r		
Carpet on Stairs		Capped			R	unner - *	Upgrade	,	
Comment		1			1				
1									
Plumbing Fixtures	/ Faucets								
Kitchen	Star	ndard	Second Ens	suite	Standard	d	Pow	der Room	Standard
Master Ensuite	Stan	ndard					Othe	r Room	,
Main Bathroom	1		Ens. #3 & #4	s bathroom	Standard	d			
Comment									
	raded the u	nder moun	t sink in the ki	tchen etill to	inetall the	standa	rd cinal	le hele kitche	n faucet,NO PLATE
Purchaser has up	araded to u	nder moun	tsinks in AII	the bathroom	install the	nstall th	ru singi ie stand	dard lav fauce	n raucet, NO PLATE
					o, our to	inotali d	ic stairt	adia lav lauce	
4. Wall Tile									
4. Man The	Tile Selecti	on				Listello	Insert	Insert Select	ion
Main Bathroom	1							moert ocicot	1011
Master Ensuite									
Tub Deck	1								
Tub Apron	1						H		
Tub Surround	/								
Shower Stall	8x 10" Cinq	Black				H			
Second Ensuite	8x 10" Cinq					H	H		
Ens. #3's bathroom	8x10" Maler					H	H		
Ens. #4's bathroom	8x 10" Cinq					H	Ħ		
Kitchen Backsplash	/	Diaux				\vdash	\exists		
Complete Backsplash	,					H	H		
Jonipiete Backsplasti	1					ш			
Comment					FIFE	7 1	7	Д ППП	
Install the standard				cked			111		
horizontally to ALL t	athrooms v	vnere appli	cable.			- -			
						3 P			
					horzonial slack	ed	brick pollem	wertical das	ked diagonal/diamond
5. Fireplace			81						
1	iving Room			Family Room			Otl		ecify Great room
	-	As Per Plan	N/A	Purchased	As Per Plan	N/A		Purchased A	s Per Plan N/A
Eiroplana Turna	0		•	O	O	•			• 0
Fireplace Type								ront Facing	
Mantle Type								1F-08	
Over Mantle							/		
Colour / Stain							V	White	
Surround							1		
Hearth							1		
Comment			REC	EIVED					
I				ACCOUNT OF					
			JUL 1	3 2022					
								6	
								(IM)	
					Init	ial:			Page 2 of 3

KINGSI^IIEN

INTERIOR COLOUR SCHEME

5A-10197

Purchaser: Telephone Res. /	TARANVIR SINGH MINHAS Bus: /		erty: 97 of Plan - Draft Approval SB17-03-08
Decor Advisor:	Barbara Coccia		tion: Louis (4203) Elev B 4 Bed - 4+1 Bath
6. Trim Carpentry			(3.27, 2.27,
	Standard handle Standard		Interior Doors 2 Panel Arch Top 2 Panel Square Top 6 Panel
7. Railings and Pi Railing Package Railing Colour Wood Stairs Comment		Picket Colour Tread Colour	Initial for Door Style
8. Plaster Mouldir Foyer Main Hall Living Room Dining Room Family Room Comment	ngs and Medallions / / / / / / /	Kitchen/Breakfas Den/Library Lower Landing	st / / / / / / / / / / / / / / / / / / /
9. Wall Paint Kingsmen White		Smooth Ceili	ings First Floor First Floor incl. Second Floor Hall First and Second Floor Throughout Not Applicable
10. Additional Con	nments	Trim Pa	int Kingsmen White
Any extras listed a The Purchaser act than re-selection The Purchaser act other miscellaneous	derials are as close as possible to builder's selection above are null and void unless accompanied by a sknowledges that after Interior Colour Selection for due to unavailability. Purchaser's knowledges reading and accepting the "Kingsme bus disclaimers. Selection is final and approved by:	separate invoice/amendmirm is signed and dated, no s Initials in Group Décor Centre Disc	ent. Said invoice must be paid in full. further changes will be permitted other




GROUND FLOOR EL. B

The floor plans and elevations shown are pre-construction plans and may be revised or improved as necessitated by architectural controls and the construction process. The measurements adhere to the rules and regulations of the TARION Warranty Corporation's official method for the calculation of floor area. Materials, specifications and floor plans are subject to change without notice. All house renderings are artist's concept only. Actual usable floor space may vary from the stated floor area. All options shown are upgrades. E. & O. E.

SCHEDULE "B Page 3 of 3

Lot 97 Phase 5A Model: Louis (4203) Elev B 4 Bed - 4+1 Bath Standard




SECOND FLOOR EL. B

The floor plans and elevations shown are pre-construction plans and may be revised or improved as necessitated by architectural controls and the construction process. The measurements adhere to the rules and regulations of the TARION Warranty Corporation's official method for the calculation of floor area. Materials, specifications and floor plans are subject to change without notice. All house renderings are artist's concept only. Actual usable floor space may vary from the stated floor area. All options shown are upgrades. E. & O. E.

SCHEDULE "B-T" Page 2 of 3

SCHEDULE "B-1" Floor Plan

Lot 97 Phase 5A Model: Louis (4203) Elev B 4 Bed - 4+1 Bath Standard



The floor plans and elevations shown are pre-construction plans and may be revised or improved as necessitated by architectural controls and the construction process. The measurements adhere to the rules and regulations of the TARION Warranty Corporation's official method for the calculation of floor area. Materials, specifications and floor plans are subject to change without notice. All house renderings are artist's concept only. Actual usable floor space may vary from the stated floor area. All options shown are upgrades. E. & O. E.

SCHEDULE "B-1" - Page 1 of 3

nitials: TW

LOT: 97 THAMES PH. 5 A RE: UPG.UNDER MOUNT KITCHEN

SINK

BLANCO

Sink Specifications

Colour

SKU

brushed finish

401247

Design and planning tips

Min cabinet size: 36 in (915 mm)


Bowl Depth: 9 in (230.0 mm)

Specifications:

Installation clips, Sink template, Installation instructions, 3 ½" (90 mm) stainless steel strainers

Depending on cabinet construction, a different cabinet size may be required. Consult the cabinet manufacturer.

QUATRUS U 2



O Taramu, or say




LOT: 97 THAMES PH. 5 A

RE: UPG. FREE STANDING TUB

FOR MASTER ENSUITE


Free Standing Tub



Mirolin Brooke CF2002 68x36x23

- Acrylic Bath
- 2PC Construction
- · End Drain Application
- F2 Drain Assembly







LOT: 97 THAMES PH. 5 A RE: UPG. UNDER MOUNT VANITY SINK FOR ENSUITE #3

1 Taramis

CALVIN

1914" OVAL UNDERMOUNT SINK

☐ 4220CFY

Undermount Sink

PRODUCT SPECS:

- Vitreous china
- Front overflow hole
- Template and mounting hardware ASME A112.19.2 / CSA B45.1-2013 supplied

DIMENSIONS:

Outer:

490mm W x 410mm D x 195mm H 19¼" W x 16%" D x 7%" H

430mm W x 350mm D x 145mm H 17" W x 13%" D x 5%" H

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO cUPC

SHIPPING

Cube 1.53


GW 19 lbs






TO BE SPECIFIED Soft White


NOTES: Dimensions of fixtures are nominal and may vary within the range of logisarios established by ASME standard A11219.2. These measurements are subject to thenge or dance lation. No responsibility is assumed for use of supersocial or validad pages.




DETAIL OF MOUNTING CLIP



Note: ▲ Dimensions shown for location of supplies and "P" trap are suggested.





LOT: 97 THAMES PH. 5 A

RE: UPG. UNDER MOUNT VANITY SINKS FOR POWDER ROOM, MASTER ENS., ENS # 2 &

ENS.#4

CATENA

RECTANGULAR UNDERMOUNT SINK

☐ 4210CIV

Undermount Sink

COMPLIANCE CERTIFICATIONS

Meets or exceeds the following.

- OBC Section 3.8 Sarner Free design and CSA BBSI Standard

- IAPMO CUPC

SHIPPING Cube 1.72 GW 27 lbs

PRODUCT SPECS:

Vitreous clana

Front overflow hole.

Template and incurring hardware
 ASME A32.9.2 / CSA 845.1 supplied
 OBC Section 3.8 Samer Free

DIMENSIONS:


Cuter:

Slomm W.s. 390mm D.s. 190mm H.

20" W x 15%" D x 7%" H

458mm W x 340mm D x M0mm H

8" W x B N" D x 5 5" H








NOTES: Determines of tenants are nominal and may cary within the range of Education collections by ASA: itemated ASP NOTES in the examination of the collections are represented by the collections are required by a described to yielded page.

While the examination of the described page of the equation of the collections are collections are collections are collections are collections and the collections are collections are collections.



X Tarsenvis



LOT: 97 THAMES PH. 5 A RE: FRIDGE SPEC'S

LG LFXC22596S



of Terronvir By



LOT: 97 THAMES PH. 5 A RE: FRIDGE SPEC'S


CONT


Terranvix

14 INSTALLATION

Dimensions and Clearances

- Check the dimensions of the appliance and the installation path to ensure there is sufficient room to move the
 refrigerator through doors or narrow openings.
- If an opening is too narrow to fit the refrigerator through, the doors must be removed.
- The installation location chosen for the refrigerator should allow space behind the unit for connections and airflow and space in front to open the doors and drawers.
- Too small of a distance from adjacent items may result in lowered freezing capability and increased electricity consumption charges. Allow at least 24 inches (610 mm) in front of the refrigerator to open the doors, and at least 2 inches (50.8 mm) between the back of the refrigerator and the wall.





-	List	LFXS28596*/ LMXS28596*	LFXS26596*	LFXC22596
A	Depth without handle	33 3/4* (857 mm)	32 3/8* (822 mm)	28 3/4" (728 mm)
В	Width	35 3/4* (908 mm)	35 3/4" (908 mm)	35 3/4" (906 mm)
С	Height to Top of Case	68 3/8* (1737 mm)	68 3/8" (1737 mm)	68 3/8" (1737 mm)
D	Height to Top of Hinge	69 3/4" (1772 mm)	69 3/4" (1772 mm)	69 3/4" (1772 mm)
E	Back Clearance	2" (50 mm)	2" (50 mm)	2" (50 mm)
F	Depth without Door	29 7/8" (759 mm)	28 1/2" (724 mm)	24 3/4" (630 mm)
G	Depth (Total with Door Open 90°)	48 1/2" (1232 mm)	47 1/8" (1197 mm)	43 1/2" (1103 mm)
Н	Front Clearance	24" (610 mm)	24" (610 mm)	24" (610 mm)
1	Depth With handle	36 1/4" (921 mm)	34 7/8" (886 mm)	31 1/4* (792 mm)



LOT: 97 THAMES PH. 5 A RE: 36" GAS COOK TOP SPEC'S




& Torranuir

Built-In Cooktop

FPGC3677RS

36" Gas



Product Dimensions

4-V4"


Available in:

Stainless (S)

Height


BTU 14,000 Right Front Right Reel 760 - 6,000 Left Front 9.500 Left Reor 9.500

Signature Features



PowerPlus* Burner

But your and sauté with power. The PowerPlus' Burner delivers strong performance, every time with 12,200 BTU.




PrecisionPro Controls™

Prepare a range of distins with praction, whether you're simmening, sautéiny searing or boiling.



Durable, Continuous Grates

Cook a variety of dishes at the same time with ease. Our durable, confinious cast i on grates allow you to slide a variety of heavy po's and pans across ourners. Plus, they're dishwasher-safe so you can clean with



Stainless Steel Cooktop

The entire cockton surface is stairless steel to clend with the other appliances in your latchen.



frigidaire.ca

LOT: 97 THAMES PH. 5 A RE: 36" GAS COOK TOP SPEC'S CON'T

& Taranuir Syl

Built-In Cooktop

FPGC3677RS 36" Gas


FRIGIDAIRE

PROFESSIONAL.

Features	
Controls	PrecisionPro**
Surface Type	Stainless Steel Recessed
Sealed Gas Burners	Yes
Crates	Continuous Cust Iron w/Black Matte Finish
Right Front Burner (BTU)	14,000
Right Rear Burner (BTU)	750 to 5,000
Left Front Burner (BTU)	9,500
Left Rear Burner (BTU)	9,500
Centre Burner (BTU)	18.200
Control Location	Centre Front
Knob Colour	Stainless
Клор Туре	Cast Metal
Optional Accessories	
Griddle	Included
Specifications	
Power Supply Connection Location	Right Rear
Gas Supply Connection Location	Right Rear
LP Gas Conversion Kit	included
Voltage Rating	120V/60Hz/15A
Amos @ 120 Velta	1.0
Minimum Circuit Required (Arnos)	15
Approved for Electric Single Wall Oven Combination Installation	Yes
Shipping Weight (Approx.)	60 l.bs.

For use on adequately wined ISOV disdicated circuit having 2-wise ground with a separate ground with Applicated must be grounded for safe operation.

Cooktops are approved for installation areas only of our Electric Single Wall Overs



NOTE: For planning purposes only. Always consult local and netional electric and gas codes. Before to Product Installation Guide for detailed installation instructions on the large at Philabers.



Product Dimensions		Cutout Dimensions	
A-Width	30"	Width (Min.)/(Max.)	55-7/8"/34-1/4"
B-Depth	21-3/4*	Depth (Min.)/(Max.)	19-3/8"/19-3/4"
C-Height	4-1/4"	Height	8"

Granite Countries



Accessories information available on the web at frigidaire as

LOT: 97 THAMES PH. 5 A RE:BUILT IN WALL OVEN/MICRO. SPEC'S " NO FLUSH INSTALLATION"

HOME APPLIANCES

LG COOKING

LWC3063

Combi Wall Oven

1.7 cu.ft. Microwave (Speed Oven) Infrared Heating™

4.7 cu.ft. Oven True Convection Steam Cooking Self+EasyClean SmartThinQ® Technology



CONTROL



Enjoy new ways to control your home with LG smart appliances

- SmartThinQ®

Oven Cooking mode Oven Control Features









Total Oven Capuc ty (cu. ft.)	6.4 (Upper & Lower)
Colors	Stainless Steel / Black Stainless Steel
UPPER OVEN FEATURES	
Eapacity(nicht)	1.7
Interior(Cavity) - Upper MWO / Lower Oven	Stainloss / Enamel Coating
Microwave Power output	950W
Microwave mode power consumption	165DW
Convection Bake mode power consumption	1600W
Broil mode power consumption	1300W
Convection Element (W)	1500W (Sheath heater)
Bool Upper Element (W)	1200W (500W + 700W)
Broil Lower Element (W)	375W
Microwave	Yes
Convection Balle	Yes
Broil	Yes
Speed cook	Wis
- = of Defrost (9 Menu)	Meat / Poultry / Fish / Bread
- + of Sensor cook (9Menu)	Bevarage / Casserole / Chicken / Pasta / Fizza / Plate of food / Rico / Soup / Vegetable
- n of Aum cook (200/onu)	Bacon/reguler stood / Bagels(frozen) / Baked potatoos(7-3to/av) / Browne / Cod fillets(1 b) / Gom cog/frozen) / Fresh wegetable / Frozen thicker wings / Frozen fries / Frozen chicken maggets / Frozen store wegetable / Golf bonad (sleet, frozen) / Hamburgen (1/2" trick) / Lamb chops(1/2" trick) / Hamburgen (1/2" trick) / Lamb chops(1/2" trick) / Bonad / Pork chops(1/2" trick) / Rice / Salmon / Pork chops(1/2" trick, 6-7oz) / Quir os / Riberye steels(1" thick 14-15oz) / Rice / Salmon steels(1" thick) / Seussage / Shon sceals(1" trick, 18-21oz) / Jender oin / Vegetable-canned
- = of Soften (4Menu)	Butter / Cream Cheese/ Frosting / Ice Cream
- = of Melt (SMeriu)	Butter / Caramel / Cheese ! Chocolare / Mershmallow
LOWER OVEN FEATURES	
Capacity(cuft)	4,7
EasyFlean [®]	Yes
Self Clean	Yes (3,4,5 hours)
Verlable destring time	Yes (3,4,5 hours)
Variable broil	Yes (FullCenter / HighMed Low)
Brail element	2,500 watts inner / 1,500 watts outer
Bake element	2,500 wasts
Bake element type	Hidden (A pass)
# of rack position	5
12 hrs. shut-off	Yes
- + of light;	Z (Halogon Lamp)
Convection conversion	Yes
-Convection element	Yes (2,000 watts Sheath heater)
Convection System/Mode/Cooking System	True Convection

Single Speed

ConeBake / ConeRoast / Bake / Brok / Screm Bake / Sceam Russ: / Probe / more mode (Fwolite/V/arm/Procf)

Glass Touch (SmoothTouch™)

Display	White VFD
Language	English / Spanish / French
Smart Function	WI-F / Smart Buzzer
Clock	12 hr or 24 hr (option)
Kitchen Timer	Yes
Timed Cook	Yes
Temperature Unit of Measure	Fahrenheit / Celsius
Cooking Complete Reminder Volume	Beeper (1.Loud, 2. nw, 3.Mute)
Sabbath Mode	Yes
APPEARANCE	
Available Colors	Steinless Steel / Black Steinless Steel
Handle/Knobs	Stainless Steel Finish (Auminum) Bladd Stainless Steel Finish (Aluminum)
Gven Door Feature	Wide/figw ^w Window
Scratch-Resistan:	Yes
PrintProof™ Firesh	Yes (Black Stainless Steel Only)
SmartFhing® SMART FEATURES	
Smart Diagnosis**	Yes
Wi-Fi Connectivity	Yes
Warks with	Google Assistant and Amagon Alexa.
SmortThinQ® with Innit and SideChef	Yes
DIMENSIONS/CLEARANCES/WEIGHT	

Scretch-Resistant	Yes
PrintProof™ Firesh	Yes (Black Stainless Steel Only)
SmartFhing® SMART FEATURES	
SmartDiagnosis**	Yes
Wi-Fi Connectivity	Yes
Warks with	Google Assistant and Amazon Alexa.
SmortThinQ® with Innit and SideChef	Yes
DIMENSIONS/CLEARANCES/WEIGHT	
Shipping Weight (bs)	244 lbs
Product Weight (ISS)	1941bs
Product (W x H = D)	29 3/4" x 43 5/11" x 24 1/2"
Cut-out (WHHXD)	28 1/2" × 43 7/16" × 23 1/2"
Overall Depth (in) - including handle	26 7/8"
Oven Interior Cimersions (Upper) (in) (WxHxD)	20 8/11" x 8 9/25" x 17 5/13"
Oven Interior Dimensions (Lower) (in) (WxHxD)	24 1/2" x 17 5/8" i: 18 7/8"
Carton Dimensions (in) (W x H x D)	33" x 30" x 50"
POWER/RATINGS	
Max. Amp load	40A
Racing	7 BW
Requirements	120 / 240 VAC, 120 / 208 VAC
ACCESSORIES	
Glass Tray(Upper)	Yes
Metal Tray(Upper)	Yes
Rack(Upper)	Yes
Broder pan & Gnd	Yes
Gliding Rack	T.
Heavy Duty Rack	2
Mest probe	Yes
Scouring Pad	Yes
WARRANTY	
Per ts & Lebor	1 Year
UPC CDDES	
LWC3063ST (Stainless Stee')	048231339810
LWC3063BD (Black Steinless Steel)	046231339827

E) 2013-16 Electronics USA, Inc. All rights reserved, "LG Ufe's Good" is a registered trademark of Electronics and brandmarks are trademarks or registered trademarks of their respective owners. Design. Features and specifications are subsect to charge without one ce. Non-metric weights and measurements are approximate features may require internet across. Content and services may very by product and are subject to charge without motion. 2/21/19

LOT: 97 THAMES PH. 5 A RE:BUILT IN WALL OVEN/MICRO. SPEC'S CON'T "NO FLUSH INSTALLATION"



HOME APPLIANCES

LG COOKING

LWC3063_ Combi Wall Oven


QUICK INSTALL & CLEARANCES


For full installation directions/clearances please refer to the corresponding User Manual and Installation Guide.

Control of the Contro	
DIMENSIONS / CLEARANCES / WEIGHT	
I be continued and a second of the particular particular and a second of the second of	
Product Dimensions (in) (W x H x D)	29 3M* x 43 5/11" x 24 1/2"
Cut-out (W+H+D)	28 1/2" x 43 7/16" x 23 1/2
Overall Depth (in) - including handle	26.7/8*
Actual Depth with Door Open (Upper) (in):	37.1"
Actual Depth with Door Open (Lower) (in)	45.7"
Overnintenar Dimensions (Upper) (n) (W v H v D)	20 8/11" x 8 9/25" x 17 5/13"
Diversional Dimensions (Lower) (in) (W x H x D)	24 1/2" x 17 5/8" x 18 7/8"
Carton Cimersions (in) (W.K.F. x.D)	33" × 30" × 50"
POWER RATINGS	
Max. Ampload	4QA
Rating	7.8kW
Requirements	120 / 240 VAC 120 / 208 VAC

INSTALLATION REQUIREMENTS

- The cabinet base platform must be able to support 202 lbs (91.65 kg) for a Microwave Combination Wall Oven, if the cabinet does not have a solid bottom, two braces or runners must be installed level with the bottom of the cutout to support the weight of the oven. Make sure the base is level and the front of the cabinet is square. If the cabinet base is not level, the oven racks will tend to slide out when opening the door.
- If marks, blemishes or the cutout opening are visible above the installed over, it
 may be necessary to add wood shims under the runners and front trim until the
 marks or opening are covered,
- If the cabinet does not have a fruit frame and the sides are less than 3/4" (1.9 cm) thick, shim both sides equally to establish the current width.
- The junction box must be flush with the rear wall of the cabinet as shown below.
- Allow at least a 23" clearance for the door depth when it is open.
- Kitchen cabinets in contact with the oven must be heat resistant up to 194°F (90°C), and fronts of nearby units up to at least 158°F (70°C).






A Terramun Syl



ELECTRICAL CONNECTIONS

- Be sure the wall oven is installed and grounded properly by a qualified installer or service technician.
- This wall oven must be electrically grounded in accordance with local codes or in their absence, with the National Electrical Code ANSI/NFPA No.70- latest edition in United States, or with CSA Standard C22.1-1982 and C22.2 No.01982 (or latest edition), Canadian Electrical Code, Part 1, and all local codes and ordinances.
- This wall oven must be supplied with the proper voltage and frequency, and connected to an individual, properly grounded branch circuit, protected by a circuit breaker or fuse. For the circuit breaker or fuse required by this model, see the rating plate to find the wattage consumption and refer to the table below to get the circuit breaker or fuse amperage.
- A Microwave Combination Wall Oven can consume up to 7,800 W at 240 VAC. A 50 Amp circuit breaker with wire gauge #8 AWS must be used.
- Do Not ground to a gas pipe.
- Do Not have a fuse in the neutral or grounding circuit,
- A U.L-listed conduit connector must be provided at the junction box.
- Prepare the electrical connection as follows:
- Turn off the circuit breaker or remove fuses to the oven branch circuit.
- With the over positioned directly in front of the cabinet opening, connect the flexible conduit to the electrical junction box as shown below. Position the conduit in such a manner that it will be on top of the oven in a natural loop when the oven is installed.



- If local codes permit connection of the frame grounding conductor to the neutral (white) wire, follow the instructions for a 3-wire circuit connection.
- If used in mobile homes or new construction, or a recreational vehicle, or local codes do not permit connection of the frame grounding conductor to the neutral(white) wire, follow the instructions for a 4-wire circuit connection.

INSTALL THE OVEN

- Install the oven into the cabinet as follows:
- Slide the oven into the opening.
 - a. Loop (do not tie) a 36" (91 cm) string around the conduit before the even is slid into place. Lay the string over the top of the even and use it to keep the conduit from falling behind the oven.
 - b. Lift oven into cabinet cutout using the oven opening as a grip. Carefully push against the oven front frame. Do not push against outside edges.
 - While sliding the oven back, pull the string so that the conduit lies on the top of the oven in a natural loop.
 - d. When you are sure the conduit is out of the way, slide the oven 3/4 way back into the opening. Remove the string by pulling on one end of the loop.
- Secure the over.
 - a. Using the mounting holes on the oven side trim as a guide, drill pilot holes for screws provided. (For securing the Combi Oven, use a minimum of 4 screws, one on each side in both the upper and lower ovens.)
- b. Secure the oven to the cabinet with screws provided. If the cabinet is particle board, you must use 3/4" particle board screws. Those may be purchased at any hardware store.
- Sele From Sele For Se
- Install the metal bottom trim.
 - a. Place the metal bottom trim centered over the pre-drilled mounting holes on the lower base.
- b. Using 3 screws provided secure the bottom trim to the bottom edge of the cabinet.
- Reinstall the over door.

