

KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)

Lot/Unit: 40    Phase/Building: 5A    Model/Floor Plan: Edward (3602) Elev C 4 Bed - 2+1 Bath

CABINETRY APPLIANCE - FRIDGE

Inv.5651	1 - Relocate the standard fridge opening in the kitchen... see sketch # 5	
Line 72482	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & insall the 66CM DEEP FRIDGE ENCLOSURE - COUNTER DEPTH WITH - 1 WALL - 1 66CM DEEP GABLE AND 1 66CM DEEP CABINET - THIS IS NOT A ZERO CLEARANCE ENCLOSURE. STANDARD HEIGHTS AND WIDTHS WILL BE USED. - see sketch # 5	
Line 72483	Note: See spec's attached.	
13Jun22 / 25Jul22		

CABINETRY BASE CABINETS

Inv.5651	1 - To supply & instal the BASE PIE CUT CORNER -in the kitchen... see sketch # 5	
Line 72485	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install a different colour kitchen island... see colour chart for details.	
Line 72486	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To accomdate for a future wine fridge in the kitchen...see sketch #5	
Line 72494	Note: See spec's attached.	
13Jun22 / 25Jul22		

CABINETRY HARDWARE

Inv.5651	1 - To supply & install the KITCHEN - CABINET HARDWARE - UPGRADE 1 - DISPLAY BOARD.. see colour chart for details.	
Line 72487	Note:	
13Jun22 / 25Jul22		
Inv.5651	3 - To supply & intall the VANITY - CABINET HARDWARE - UPGRADE 1 - DISPLAY BOARD to the powder room, master ensuite and main bathroom...see colour chart for details.	
Line 72488	Note:	
13Jun22 / 25Jul22		

CABINETRY MICROWAVE OVEN STOVE COOKTOP

Inv.5651	1 - To supply & install accomodations BUILT-IN TALL APPLIANCE CABINET WITH DRAWER - S BELOW FOR PANEL-MOUNT - PROUD - OR TRIM KIT INSTALLATIONS - TRIM KIT REQUIRED in the kitchen...see spec's ... see sketch # 5	
Line 72492	Note:	
13Jun22 / 25Jul22		

CABINETRY VANITY

Inv.5651	1 - To supply & install a VANITY BANK OF DRAWERS - in the master ensuite bathroom.. see sketch # 6	
Line 72464	Note:	
13Jun22 / 25Jul22		

**KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)**

**Lot/Unit: 40    Phase/Building: 5A    Model/Floor Plan: Edward (3602) Elev C 4 Bed - 2+1 Bath**

Inv.5651	1 - To INCREASE VANITY TO KITCHEN HEIGHT 90CM HIGH - MAINTAINS VANITY DEPTH - in the master ensuite bathroom.	
Line 72465	Note:	
13Jun22 / 25Jul22		

**CABINETRY WALL AND HUTCH**

Inv.5651	1 - To supply & install the COMBO - UPPER ANGLE CORNER PER UNIT WITH GLASS DOOR AND FINISHED INTERIOR - CLEAR - GLASS - in the kitchen... see sketch #5	
Line 72484	Note:	
13Jun22 / 25Jul22		

**CARPET**

Inv.5651	1 - To supply & install the upraded ESCAPE TO MAUI carpet to the master bedroom, bedroom # 2, #3 & # 4 in lieu of the standard carpet... see colour chart for details.	
Line 72470	Note:	
13Jun22 / 25Jul22		

**COUNTER TOP**

Inv.5651	1 - To supply & instal the Level # 4 quartz countertop in the kitchen ( incl. the island ) in lieu of the standard quartz.. see colour chart for details.	
Line 72476	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & instal the Level # 2 quartz countertop in the master ensuite in lieu of the standard quartz... see colour chart for details.	
Line 72477	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the QUATRZ shower niche " IMPERIAL BLACK" in the master ensuite shower... see sketch # 5 for installation location.	
Line 72460	Note:	
13Jun22 / 25Jul22		

**ELECTRICAL**

Inv.5651	1 - To supply & install the standard T.V. rough in in the great room and master bedroom.. see sketch # 4 & # 5	
Line 72445	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the standard Phone ( CAT 5 ) rough in in the great room, master bedroom and bedroom # 4.. see sketch # 4 & # 5	
Line 72446	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To SUPPLY AND INSTALL AN ADDITIONAL BASIC RECEPTACLE (NOT DEDICATED) at approx. 66" + - up from the floor centered to the F/P mante in	
Line 72447	Note: the family room... see sketch # 4	
13Jun22 / 25Jul22                      This is for a future wall mount T.V.		

**KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)**

**Lot/Unit: 40    Phase/Building: 5A    Model/Floor Plan: Edward (3602) Elev C 4 Bed - 2+1 Bath**

Inv.5651  Line 72448  13Jun22 / 25Jul22	<b>1</b> - To SUPPLY AND INSTALL CONDUIT FOR TV OVER THE FIREPLACE – TERMINATED IN SAME ROOM at approx. 66" + - up from the floor centered + - to the F/P mantle and terminated next to + - the standard T.V. & Phone (CAT 5) rough in.... see sketch # 4  Note: This is for a future wall mount T.V.	
Inv.5651  Line 72451  13Jun22 / 25Jul22	<b>1</b> - To supply & install FOUR exterior pot lights connected to a sep. switch... see sketch # 6  Note:	
Inv.5651  Line 72452  13Jun22 / 25Jul22	<b>1</b> - To supply & install SIX pot lights in the great room connected to the standard switch..see sketch #4  Note: Do not supply or install the standard ceiling light in the great room.	
Inv.5651  Line 72453  13Jun22 / 25Jul22	<b>1</b> - Relocate the standard kitchen ceiling light over to the kitchen island area... see sketch # 4  Note:	
Inv.5651  Line 72454  13Jun22 / 25Jul22	<b>1</b> - To supply & install FOUR pot lights in the kitchen connected to a sep. switch... see sketch # 4  Note:	
Inv.5651  Line 72455  13Jun22 / 25Jul22	<b>1</b> - Relocate the standard ceiling light from the upper stair landing to the O.T.B. area on the second floor... see sketch # 5  Note:	
Inv.5651  Line 72456  13Jun22 / 25Jul22	<b>1</b> - To SUPPLY AND INSTALL REINFORCING FOR A CEILING light at the O.T.B. area on the second floor... see sketch # 6  Note:	
Inv.5651  Line 72493  13Jun22 / 25Jul22	<b>1</b> - To SUPPLY AND INSTALL EXTRA 240 STOVE PLUG for the future built in wall oven/microwave combo in the kithcen... see spec's... see sketch # 5  Note:	
Inv.5651  Line 72495  13Jun22 / 25Jul22	<b>1</b> - To SUPPLY AND INSTALL AN ADDITIONAL BASIC RECEPTACLE (DEDICATED CIRCUIT AND INCLUDES ARC FAULT BREAKER) for the future wine fridge in the kitchen...  Note: See spec's... see sketch # 5	

**FIREPLACE**

Inv.5651  Line 72480  13Jun22 / 25Jul22	<b>1</b> - To supply & install the FIREPLACE SUROUND - ONE SIDED FIREPLACE - 3 PIECE MARBLE SURROUND to the F/P in the great room...see colour chart for details.  Note:	
Inv.5651  Line 72481  13Jun22 / 25Jul22	<b>1</b> - To supply & install the FIREPLACE HEARTH - ONE SIDED FIREPLACE - MARBLE HEARTH to the F/P in the Great room... see colour chart for details.  Note:	

**KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)**

**Lot/Unit: 40    Phase/Building: 5A    Model/Floor Plan: Edward (3602) Elev C 4 Bed - 2+1 Bath**

**HARDWOOD**

Inv.5651	1 - To supply & install the 3 1/2" Elements stained engineered hardwood to the main floor area include stair landings where applicable in lieu of the standard hardwood... see colour chart for details.	
Line 72466	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the 3 1/2" Elements stained engineered hardwood to the upper hallway area where applicable in lieu of the standard carpet.. see colour chart for details.	
Line 72467	Note:	
13Jun22 / 25Jul22		

**HEATING AND AIR CONDITIONING**

**MISCELLANEOUS**

Inv.5651	1 - To supply & install the OPTIONAL WAFFLE CEILING in the great room.. see sketch # 4	
Line 72457	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To accomodate for a future 48" stove opening in the kitchen in lieu of the standard stove opening ... see spec's	
Line 72489	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install a 3/4" gas rough in to the stove including the 110V electrical code requirement; and to supply & install an 8" vent above the stove area and to accomodate the upgraded 48" hood fan...	
Line 72490	Note: See sketch for approx. measurement for center of stove.	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the 48" CYCLONE PTB 81248 Stainless Steel hood fan in the kitchen in lieu of the standard hood fan... see spec's	
Line 72491	Note:	
13Jun22 / 25Jul22		

**PAINT AND DRYWALL**

Inv.5651	1 - To PAINT EXTRAS - STAIN RAILINGS WITH IRON PICKETS (INCLUDING STAIRS)... see colour chart for details.	
Line 72469	Note:	
13Jun22 / 25Jul22		

**PLUMBING**

Inv.5651	2 - To supply & install Hot water supply to the back of the toilet with shut off valve by the toilet supply for the master and main bathrooms.	
Line 72458	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the WATERLINE ROUGH-IN TO THE FRIDGE LOCATION (NO HOOK UP) in kitchen... see sketch # 4 for new location of the fridge..	
Line 72449	Note:	
13Jun22 / 25Jul22		

KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)

Lot/Unit: 40    Phase/Building: 5A    Model/Floor Plan: Edward (3602) Elev C 4 Bed - 2+1 Bath

Inv.5651	1 - To supply & install a WATERLINE ROUGH-IN TO THE DRYER LOCATION (NO HOOK UP) in the laundry room.	
Line 72450	Note:	
13Jun22 / 25Jul22		
Inv.5651	5 - To supply & install the VANITY SINK - CONTRAC CATENA UNDERMOUNT - MODEL 4210CIY in the powder room, master ensuite and main bathroom in lieu of the standard top mount vanity sinks... see spec's	
Line 72461	Note: Still to install the standard lav. faucets.	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the KITCHEN SINK - BLANCO QUATRUS U2 DBL UNDERMOUNT MODEL 401247 in the kitchen in lieu of the standard top mount kitchen sink... see spec's	
Line 72462	Note: Still to install the standard single hole "NO PLATE" kitchen faucet.	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the KITCHEN SOAP DISH - MOEN CHROME - MODEL 3944 in the kitchen... see spec's See sketch # 5 for installation location.	
Line 72463	Note:	
13Jun22 / 25Jul22		

RAILING

Inv.5651	1 - To supply & install the RAILING - UPGRADE 1 - METAL HANDRAIL 3 INCH OVAL IN OAK - PICKETS STEEL ½ INCH SQUARE, PLAIN, WITH SHOES IN FLAT BLACK - POSTS 3½ INCH SQUARE, WITH CAP OAK IN OAK in lieu of the standard pickets and rails.	
Line 72468	Note:	
13Jun22 / 25Jul22		

TILE

Inv.5651	1 - Do not supply or install any of the towel bars, toilet paper holders or soap dishes in ALL bathrooms.	
Line 72459	Note:	
13Jun22 / 25Jul22		

TILE - FLOOR

Inv.5651	1 - To supply & install the UPGRADE 4 - FLOOR TILE - STACKED - FOYER TILE in lieu of the standard floor tiles.	
Line 72471	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the UPGRADE 4 - FLOOR TILE - STACKED - POWDER ROOM TILE in lieu of the standard floor tiles.	
Line 72472	Note:	
13Jun22 / 25Jul22		
Inv.5651	1 - To supply & install the UPGRADE 4 - FLOOR TILE - STACKED - LAUNDRY ROOM TILE in lieu of the standard floor tiles.	
Line 72473	Note:	
13Jun22 / 25Jul22		

KINGSMEN (THAMES) INC. / Havelock Corners (Kingsmen)

Lot/Unit: 40    Phase/Building: 5A    Model/Floor Plan: Edward (3602) Elev C 4 Bed - 2+1 Bath

Inv.5651	1 - To supply & install the UPGRADE 4 - FLOOR TILE - STACKED - KITCHEN / BREAKFAST TILE in lieu of the standard floor tiles.	
Line 72474	Note:	
13Jun22 / 25Jul22		

TILE - WALL

Inv.5651	1 - To supply & install the standard 8x 10" wall tile on the 10" side in a 70/30 + - off set horizontal brick pattern to the master ensuite shower where applicable	
Line 72475	Note:	
13Jun22 / 25Jul22		

Inv.5651	1 - To supply & install a - BACKSPLASH TILE - 70/30 + - horizontal brick pattern - KITCHEN SPLASH TILE in the kitchen ... see colour chart for details.	
Line 72498	Note:	
13Jun22 / 25Jul22		

TRIM

Inv.5651	1 - To supply & install the INTERIOR DOORS - UPGRADE TO LIVINGSTON HOLLOW CORE throughout where applicable in lieu of the standard interior doors.	
Line 72478	Note:	
13Jun22 / 25Jul22		

Inv.5651	1 - To supply & install the DOOR LEVER - UPGRADE TO HALIFAX SQUARE ROSE PASSAGE LEVERS - MATTE BLACK " TO INCLUDE THE BLACK HINDGES " throughout in lieu of the standard hardware and hindges.	
Line 72479	Note:	
13Jun22 / 25Jul22		

EXTRAS AS PER OFFER

5 FREE APPLIANCES – STAINLESS STEEL FRONT - FRIDGE; STOVE AND DISHWASHER. WHITE WASHER AND DRYER (SUPPLIED ONLY, NOT INSTALLED, FROM BUILDERS STANDARD LINE). AN APPLIANCES VOUCHER WILL BE GIVEN BY OUR DECOR CONSULTANT AT THE TIME OF BOOKING YOUR COLOUR A <i>Worksheet</i> Note:	
VENDOR TO INSTALL CAPPED GAS LINE (ROUGH-IN ONLY) AT REAR OF HOME FOR FUTURE BBQ LOCATION. LOCATION TO BE FINALIZED AT VENDORS SOLE DISCRETION. <i>Worksheet</i> Note:	
VENDOR TO SUPPLY & INSTALL AIR CONDITIONING UNIT, SIZED ACCORDINGLY, FROM VENDORS STANDARD SAMPLES. <i>Worksheet</i> Note:	
VENDOR TO INCLUDE LEVEL 1, 2CM QUARTZ IN ALL BATHROOMS, AS PER PLAN, IN LIEU OF THE INCLUDED LAMINATE COUNTER TOPS. SELECTIONS TO BE MADE FROM BUILDERS STANDARD SAMPLES. <i>Worksheet</i> Note:	

**Purchasers:** CHINMAY SHIRISH KULKARNI & Titksha Bhelke **Property:** 40 of Plan - Draft Approval SB17-03-08  
**Telephone Res. / Bus:** (647) 450-1106 / **Project:** KINGSMEN (THAMES) INC.  
**Decor Advisor:** Barbara Coccia **Model and Elevation:** Edward (3602) Elev C 4 Bed - 2+1 Bath  
**Layout Changes:** ☐ Yes ☒ No **Sketch Attached:** ☒ Yes ☐ No **Exterior Colour Scheme:**

1. Cabinetry	Style and Colour	Counter Top	Hardware
Kitchen / Breakfast	#3, Simcoe Rain Cloud	*#4, C/S #5141 Misty Carrina 3cm	**# 117MB Black
Kitchen Island	**#3, Simcoe Navy Blue	*#4, C/S #5141 Misty Carrina 3cm	**# 117MB Black
Laundry Room	/		
Powder Room	**#3, Simcoe Navy Blue	#1, C/S # 9141 Ice Snow 2cm.	**# 117MB Black
Main Bathroom	#3, Soho LPL Cafe Noir	#1, C/S # 9141 Ice Snow 2cm.	**# 117MB Black
Master Ensuite Bathroom	#3, Simcoe Orchid	*#2, C/S # 3100 Jet Black 2cm.	**# 117MB Black
Second Ensuite Bathroom (If Applicable)	/		
	/		
	/		

Appliances	<b>Custom Size Fridge</b> <input checked="" type="radio"/> Yes <input type="radio"/> No	<b>Valance Lighting</b> <input type="radio"/> Yes <input checked="" type="radio"/> No	<b>Microwave / Range Hood</b> <input type="radio"/> Yes <input checked="" type="radio"/> No
	<b>Cooktop / Rangetop</b> <input type="radio"/> Yes <input checked="" type="radio"/> No	<b>Built in Wall Oven</b> <input type="radio"/> Yes <input checked="" type="radio"/> No	<b>Slide-in Range</b> <input type="radio"/> Yes <input checked="" type="radio"/> No
Comment			

## 2. Flooring

	Selection
Foyer	**upg. 4, 24 x 24" Mayfair Calacatta Oro Polished HD. Polished Porcelain STACKED
Main Hall	* 3 1/2" Elements oak Sturgeon
Back Hall	/
Breakfast	**upg. 4, 24 x 24" Mayfair Calacatta Oro Polished HD. Polished Porcelain STACKED
Laundry Room	**upg. 4, 24 x 24" Mayfair Calacatta Oro Polished HD. Polished Porcelain STACKED
Kitchen	**upg. 4, 24 x 24" Mayfair Calacatta Oro Polished HD. Polished Porcelain STACKED
Powder Room	**upg. 4, 24 x 24" Mayfair Calacatta Oro Polished HD. Polished Porcelain STACKED
Main Bathroom	13 x 13" Cinq Black
Master Ensuite Bathroom (If Applicable)	13 x 13" Cinq Black
Mud Room	/
Master Ens.&Main Bathroom	Shower floor: 2x2" Ontario Snow White MATTE
Living Room	/
Dining Room	* 3 1/2" Elements oak Sturgeon
Family / Great Room	* 3 1/2" Elements oak Sturgeon
Den / Library / Study	/
Basement Landing (If Applies)	
Lower Landing (If Applicable)	* 3 1/2" Elements oak Sturgeon
Upper Landing	* 3 1/2" Elements oak Sturgeon
Upper Hall	* 3 1/2" Elements oak Sturgeon
Master Bedroom	* Escape To Maui # 89827 Misty Horizon
Bedroom #2	* Escape To Maui # 89827 Misty Horizon
Bedroom #3	* Escape To Maui # 89827 Misty Horizon
Bedroom #4	* Escape To Maui # 89827 Misty Horizon
Bedroom #5	/
Master Ens & main bathroom	Shower jamb: Anatolia Marmiline SNOW

RECEIVED

JUL 25 2022

Flooring Continued on Page 2

Initial:

TB CK

Page 1 of 3

**Purchasers:** CHINMAY SHIRISH KULKARNI & Titiksha Bhelk  
**Telephone Res. / Bus:** (647) 450-1106 /  
**Decor Advisor:** Barbara Coccia  
**Property:** 40 of Plan - Draft Approval SB17-03-08  
**Project:** KINGSMEN (THAMES) INC.  
**Model and Elevation:** Edward (3602) Elev C 4 Bed - 2+1 Bath  
**2. Flooring - Continued -**

Upgrade Underpad	Type	Area
	Standard	Master bedroom, bedroom #2, #3 & #4
Carpet on Stairs	Capped	Runner - *Upgrade
Comment	/	/

### 3. Plumbing Fixtures / Faucets

Kitchen	Standard	Second Ensuite	/	Powder Room	Standard
Master Ensuite	Standard			Other Room	/
Main Bathroom	Standard				

#### Comment

Purchaser has upgraded to an under mount kitchen sink, still to install the standard single hole kitchen faucet NO PLATE.  
Purchaser has upgraded to under mount sinks in ALL bathrooms, still to instal the standard lav. faucets.

### 4. Wall Tile

	Tile Selection	Listello	Insert	Insert Selection
Main Bathroom	8x10" Cinq Black	<input type="checkbox"/>	<input type="checkbox"/>	
Master Ensuite				
Tub Deck	13x13" Cinq Black	<input type="checkbox"/>	<input type="checkbox"/>	
Tub Apron	13x13" Cinq Black	<input type="checkbox"/>	<input type="checkbox"/>	
Tub Surround	13x13" Cinq Black	<input type="checkbox"/>	<input type="checkbox"/>	
Shower Stall	8x10" Cinq Black	<input type="checkbox"/>	<input type="checkbox"/>	
Second Ensuite	/	<input type="checkbox"/>	<input type="checkbox"/>	
	/	<input type="checkbox"/>	<input type="checkbox"/>	
	/	<input type="checkbox"/>	<input type="checkbox"/>	
Kitchen Backsplash	*3x6"MalowGlossySmoke 70/30+ - horizontal brickpattern	<input type="checkbox"/>	<input type="checkbox"/>	
Complete Backsplash	/	<input type="checkbox"/>	<input type="checkbox"/>	

#### Comment

To install the standard 8x10" wall tile on the 10" side in a 70/30 + - off set horizontal pattern to the master ensuite shower, where applicable. To install the standard 8x10" wall tile on the 10" side stacked horizontal in the main bathroom shower, where applicable.



horizontal stacked



brick pattern



vertical stacked



diagonal/diamond

### 5. Fireplace

	Living Room			Family Room			Other Room - Specify Great Room		
	Purchased	As Per Plan	N/A	Purchased	As Per Plan	N/A	Purchased	As Per Plan	N/A
Fireplace Type	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>	<input checked="" type="radio"/>	<input type="radio"/>
Mantle Type							Front Facing		
Over Mantle							NF-08		
Colour / Stain							/		
Surround							White		
Hearth							* Nero marquina marble		
Comment							* Nero marquina marble		

RECEIVED

JUL 25 2022

TB

CL

Initial:

Page 2 of 3

**Purchasers:** CHINMAY SHIRISH KULKARNI & Titiksha Bhele  
**Telephone Res. / Bus:** (647) 450-1106 /  
**Decor Advisor:** Barbara Coccia  
**Property:** 40 of Plan - Draft Approval SB17-03-08  
**Project:** KINGSMEN (THAMES) INC.  
**Model and Elevation:** Edward (3602) Elev C 4 Bed - 2+1 Bath

### 6. Trim Carpentry

Door Hardware \*\*Upgrade handle

Interior Trim Standard

Comment

Purchaser has upgraded the interior doors, see upgrades to details.

#### Interior Doors

☐ 2 Panel Arch Top

☐ 2 Panel Square Top

☐ 6 Panel

Initial for Door Style

TB CK

### 7. Railings and Pickets

Railing Package \* Upg. # 1 Metal picket package

Railing Colour Elements Sturgeon

Wood Stairs ☐ No ☒ Oak

Picket Colour BLACK

Tread Colour Elements Sturgeon

Comment

/

### 8. Plaster Mouldings and Medallions

Foyer /

Main Hall /

Living Room /

Dining Room /

Family Room /

Kitchen/Breakfast /

Den/Library /

Lower Landing /

Comment

/

### 9. Wall Paint

Kingsmen White

Smooth Ceilings

☐ First Floor

☐ First Floor incl. Second Floor Hall

☐ First and Second Floor

☒ Throughout

☐ Not Applicable

Trim Paint Kingsmen White

### 10. Additional Comments

/

RECEIVED

JUL 25 2022

### 11. Disclaimers and Notes

- Colours of all materials are as close as possible to builder's selection, but not necessarily identical due to variances in manufacturing.
- Any extras listed above are null and void unless accompanied by a separate invoice/amendment. Said invoice must be paid in full.
- The Purchaser acknowledges that after Interior Colour Selection form is signed and dated, no further changes will be permitted other than re-selection due to unavailability. TB CK Purchaser's Initials
- The Purchaser acknowledges reading and accepting the "Kingsmen Group Décor Centre Disclaimers" form. This document contains other miscellaneous disclaimers.

This Interior Colour Selection is final and approved by:

Purchaser:

Signature: 

Date:

07/07/2022

Signature: 

Date:

07/07/2022

Vendor:

KINGSMEN (THAMES) INC.

**SCHEDULE "B-1"**  
**Floor Plan**




SCHEDULE "B-1" - Page 3 of 3

Initials:

**SCHEDULE "B-1"**  
**Floor Plan**

Lot 40  
Phase 5A  
Model: Edward (3602) Elev C 4 Bed - 2+1 Bath  
Standard

SKETCH #5



**SECOND FLOOR EL. C**

The floor plans and elevations shown are pre-construction plans and may be revised or improved as necessitated by architectural controls and the construction process. The measurements adhere to the rules and regulations of the TARIION Warranty Corporation's official method for the calculation of floor area. Materials, specifications and floor plans are subject to change without notice. All house renderings are artist's concept only. Actual usable floor space may vary from the stated floor area. All options shown are upgrades. E. & O. E.

LOT 40 THAMES PH. 5 A  
RE: UNDER MOUNT KITCHEN SINK AND  
SOAP DISPENSER

# BLANCO

## Sink Specifications

Colour	SKU
brushed finish	401247


## QUATRUS U 2

### Design and planning tips

- Min cabinet size: 36 in ( 915 mm )
- Bowl Depth: 9 in ( 230.0 mm )

Specifications:  
Installation clips, Sink template, Installation instructions, 3  
½" (90 mm) stainless steel strainers

Depending on cabinet construction, a different cabinet  
size may be required. Consult the cabinet manufacturer.



*[Handwritten signature]*  
x *[Handwritten signature]*



Transitional Soap or Lotion  
Dispenser

Model 3944

Chrome



LOT 40 THAMES PH. 5 A  
RE: UNDER MOUNT SINKS FOR ALL  
BATHROOMS

CATENA  
RECTANGULAR UNDERMOUNT SINK

4210CIY Undermount Sink

PRODUCT SPECS:

- Vitreous china
- Front overflow hole
- Template and mounting hardware supplied

DIMENSIONS:

Outer:

510mm W x 390mm D x 190mm H  
20" W x 15 1/2" D x 7 1/2" H

Inner:

458mm W x 340mm D x 140mm H  
18" W x 13 1/2" D x 5 1/2" H



COMPLIANCE CERTIFICATIONS

Meets or exceeds the following:

- IAPMO CUPC
- ASME A112.19.2 / CSA B45.1
- OBC Section 3.8 Barrier Free design and CSA B651 Standard

SHIPPING

Cube 1.72  
GW 27 lbs



TO BE SPECIFIED  
C/C/S  
S/CIT 21" 10

NOTES: Dimensions of fixtures are nominal and may vary within the range of tolerances established by ASME standard A112.19.2. These measurements are subject to change or cancellation. No responsibility is assumed for use of supplemented or revised pages.  
Products are designed to comply with CSA B651 Barrier Free and OBC Section 3.8 requirements. It shall be the responsibility of the installer to comply with the local accessibility codes and standards prior to installing the product.





*[Handwritten signature]*  
*[Handwritten signature]*

RECEIVED  
JUL 25 2022

Lot: 40  
 Thames 5A  
 Re: 48" Hood Fan

## PTB812 | PRO Collection

**Cyclone**<sup>®</sup>  
 Breathe Better



### Undermount

Cyclone is excited to introduce its grandest undermount ever. Perfect for high-heat cooking. The PTB812 has an incredible 3-speed 1200 CFM fan wrapped in an imposing 18" tall wall-mount style stainless steel body. Quickly rid your kitchen of smoke and grease. Comes with durable and dishwasher-friendly baffle filters, 3 bright LED lights and a 8" duct connection for optimal performance and convenient installation, all backed by the best warranty in the business.

### Green Features



3 Speed  
 Push Button  
 Control Panel



Dishwasher Safe  
 Baffle Filters




Time-Delay  
 OFF Feature



Grease Cup



Long-Lasting  
 LED Lights



Grease Tray



Model	Colour	Ducting	Filters	Size	CFM
PTB81236	Stainless Steel	8"	Baffle	36"	1200
PTB81242	Stainless Steel	8"	Baffle	42"	1200
PTB81248	Stainless Steel	8"	Baffle	48"	1200
PTB81236MB	Matte Black	8"	Baffle	36"	1200

*[Handwritten Signature]*  
 \_\_\_\_\_  
*[Handwritten Signature]*  
 \_\_\_\_\_



Lot: 40  
Thames SA  
Re: 48" Hood Fan

## PTB812 | PRO Collection

**Cyclone**<sup>®</sup>  
Breathe Better

### Features

- Undermount range hood
- 8" round duct adapter
- Non-stick aluminum fan blades
- 3 speed push button control
- 3 LED lights (3 x 1.4W, 4000K)
- Dishwasher-safe baffle filters with integrated handles
- 3 minutes time-delay OFF feature
- Plug-in connection



### Options

- Chimney Flues:
  - TBD - short (8' ceilings)
  - TBD - extended (9' ceilings)
- Widths: 36" 42" 48"
- Finishes: Stainless Steel, Matte Black

Note: 42" and 48" in stainless steel only

### Specifications

- |                                      |                                |  |
|--------------------------------------|--------------------------------|--|
| • Air Flow Volume: 1200 CFM          | • Current: 2.5 Amps            | • Finishes: Stainless Steel, Matte Black |
| • Electrical Connection: 120 V/60 Hz | • Fan Speed: 1599 RPM          | • Ducting: 8" Round                      |
| • Power Consumption: 300 Watts       | • Fan Type: Centrifugal Blower | • Noise Level: Min. 2 Sones<br>Max. TBD  |



Toronto • Vancouver • Boston

*[Handwritten Signature]*  
\_\_\_\_\_  
*[Handwritten Signature]*  
\_\_\_\_\_

5/22/22, 1:13 PM


KitchenAid® 48" Smart Commercial-Style Gas Range with Griddle Imperial Black KFGC558JBK | KitchenAid

KitchenAid® 48" Smart Commercial-Style Gas Range with Griddle

MSRP: \$12,196.99

ADD TO CART

☐ COMPARE



KitchenAid® 48" Smart Commercial-Style Gas Range With Griddle

Model: KFGC558JBK

★★★★☆ 3.9 (21) Write a review

Key Features

- Even-Heat™ True Convection
- Chrome-Infused Electric Griddle
- Smart Appliance
- Two 20,000 BTU Ultra Power™ Dual-Flame Burners
- Three-Level Convertible Grates

Color

Imperial Black



*Shrump Kulkarni*  
*Delkphg*


DIMENSIONS

2 of 30

COMMERCIAL-STYLE RANGES  
 PRODUCT DIMENSIONS

MODEL #	48" (121.9 cm) RANGES DUAL-FUEL/GAS KFDC55BJ/KFGC55BJ	
Unit of Measurement	in	cm
Overall Width (A)	47 <sup>7</sup> / <sub>16</sub>	121.6
Bullnose Height (B)	2 <sup>7</sup> / <sub>16</sub>	5.6
Control Panel Height (C)	5 <sup>7</sup> / <sub>16</sub>	13.5
Door Heights (D)	20 <sup>1</sup> / <sub>16</sub>	52.6
Door Bottoms to Handle Tops (E)	20	50.8
Secondary Oven Door Width (F)	17 <sup>7</sup> / <sub>16</sub>	45.1
Main Oven Door Width (G)	29 <sup>7</sup> / <sub>16</sub>	75.2
Toe-Kick Height (H)	5 <sup>7</sup> / <sub>16</sub>	14

[Handwritten signature]  
 [Handwritten signature]



FRONT VIEW

**IMPORTANT:** Dimensional specifications are provided for planning purposes only.  
 Do not make any cutouts based on this information. Refer to the Installation Guide before  
 selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation.  
 All KitchenAid® appliances are appropriately UL, CUL or CSA approved.

**KitchenAid®**

DIMENSIONS


7 of 30

COMMERCIAL-STYLE RANGES

INSTALLATION/CLEARANCE DIMENSIONS

MODEL #	30" (76.2 cm) RANGES DUAL-FUEL/GAS KFDC500J/KFGC500J		36" (91.4 cm) RANGES DUAL-FUEL/GAS KFDC506J/KFGC506J		48" (121.9 cm) RANGES DUAL-FUEL/GAS KFDC556J/KFGC556J	
	in	cm	in	cm	in	cm
Combustible Area above Cooking Surface Width (min.) (A)	30	76.2	36	91.4	48	121.9
Bottom of Cabinet Height above Cooking Surface (min.) (B)*	42	106.7	58	147.3	58	147.3
Bottom of Cabinet Height above Countertop (min.) (C)	18	45.7	18	45.7	18	45.7
Distance to Fixed Wall or Combustible Material (min.) (D)	12	30.5	12	30.5	12	30.5
Opening Width (min.) (E)	30	76.2	36	91.4	48	121.9

\* If installing a hood or hood liner above the range, follow the hood or hood liner instructions for dimensional clearances above the cooking surface.



FRONT VIEW

**IMPORTANT:** Dimensional specifications are provided for planning purposes only. Do not make any cutouts based on this information. Refer to the Installation Guide before selecting cabinetry, verifying electrical/gas connections, making cutouts or beginning installation. All KitchenAid® appliances are appropriately UL, CUL or CSA approved.

**KitchenAid®**

*[Handwritten Signature]*  
*[Handwritten Signature]*

**KitchenAid**

27 cu. ft. French Door Refrigerator  
KRFF507H



Stainless Steel with PrintShield™ Finish  
KRFF507HPS

Also available in:

- ☐ White KRFF507HWH
- ☐ Black KRFF507HBL
- ☐ Black Stainless Steel with PrintShield™ Finish KRFF507HBS

Key Features & Benefits

- ExtendFresh™ Temperature Management System**  
Separately monitors the temperatures in the refrigerator and freezer.
- Pull Out Tray**  
Ideal space to store large platters of appetizers and then access them with ease.
- FreshChill™ Temperature-Controlled Full-Width Pantry**  
A manual temperature setting lets you maintain the freshness of a variety of ingredients.

Capacity

Total Capacity	27 cu. ft.
Refrigerator Capacity	19 cu. ft.
Freezer Capacity	8 cu. ft.

General Features & Properties

- In-Door-Ice® System
- 2-Tier Freezer Drawer with Storage Dividers
- Metallic Accents on Shelf Trim
- SatinGlide® Crispers and Pantry
- Humidity Controlled Crispers
- Measured Water Fill
- Through-the-Door Ice and Water Dispenser
- Slide-Away Split Shelf

Electrical Details

Amps	15
Volts	115

Certifications

ENERGY STAR® Certified	Yes
------------------------	-----

Technical Details


Refrigerator Type	French Door
Number of Doors	3
Number of Interior Refrigerator Shelves	5
Number of Refrigerator Door Bins	3 Adjustable, 2 Fixed
Number of Interior Freezer Shelves	2 Plastic
Number of Freezer Door Bins	1 Pizza Pocket
Lighting Type	LED
Ice Maker	Factory Installed
Ice Maker Location	Refrigerator Door
Dispenser Type	Exterior Ice and Water

Dimensions

Product Dimensions (H x W x D)	69-7/8" x 35-11/16" x 36-5/8"
Depth with Door Open 90°	48"
Cutout Dimensions	Allow extra 1/2" on sides and top. Allow extra 1" on rear.

Reference Material

- [Dimension Guide](#)
- [Use & Care Guide](#)
- [Energy Guide](#)
- [Warranty](#)



NOTE: Dimensions are for planning purposes only. For complete details, see installation instructions packed with product. Specifications subject to change without notice.  
©/™ 2020. All rights reserved. Printed in the U.S.A. D20C052XXC, KRFF507H/SPECSHEETV01.

**LOT 40 THAMES PH. 5 A**  
**RE: BUILT IN WALL OVEN/MICRO. COMBO**  
**NO FLUSH INSTALLATION**

*Chinmoy Kumar*  
*G. K. Singh*

**KitchenAid® 27" (68.6 cm) and 30" (76.2 cm) Electric Built-In Microwave/Oven Combination**

**PRODUCT MODEL NUMBERS**

KEMS309E KOCE500E KOCE507E

**ELECTRICAL CONNECTION**


If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path and the wire gauge are in accordance with local codes. Check with a qualified electrical installer if you are not sure the oven is properly grounded.

This oven must be connected to a grounded metal, permanent wiring system.

Be sure that the electrical connection and wire size are adequate and in conformance with the National Electrical Code, ANSI/NFPA 70-latest edition or CSA Standards C22.1-94, Canadian Electrical Code, Part 1 and C22.2 No. 0-M91-latest edition, and all local codes and ordinances.

To properly install your oven, you must determine the type of electrical connection you will be using and follow the instructions provided for it here.

- Oven must be connected to the proper electrical voltage and frequency as specified on the model/serial/rating plate. See the following illustration.



A. Model/serial/rating plate

- Models rated from 7.3 to 9.6 kW at 240 volts (5.4 to 7.4 kW at 208 volts) require a separate 40-amp circuit. Models rated at 4.8 kW and below at 240 volts (3.6 kW and below at 208 volts) require a separate 30-amp circuit.
- A circuit breaker is recommended.
- Connect directly to the fused disconnect (or circuit breaker box) through flexible, armored or nonmetallic sheathed, copper cable (with grounding wire). See "Make Electrical Connection" section.
- Flexible conduit from the oven should be connected directly to the junction box.
- Do not cut the conduit. The length of conduit provided is for serviceability of the oven.
- A UL listed or CSA approved conduit connector must be provided.
- If the house has aluminum wiring, follow the procedure below:
  1. Connect a section of solid copper wire to the pigtail leads.
  2. Connect the aluminum wiring to the added section of copper wire using special connectors and/or tools designed and UL listed for joining copper to aluminum.


Follow the electrical connector manufacturer's recommended procedure. Aluminum/copper connection must conform with local codes and industry accepted wiring practices.

For power requirements, refer to the following table.


Model	Voltage	Amperage (L1)*	Amperage (L2)*	Rating (W)
KOCE507E/KOCE500E	120/240	32	30	8000
KOCE507E/KOCE500E	120/208	30	28	6600

\*Amperage values noted above are for information purposes only; the units are rated in watts.

**PRODUCT DIMENSIONS**



**Cabinet Dimensions**



\* NOTE: The cabinet height can be between 41" (104.1 cm) and 41 $\frac{1}{2}$ " (105.6 cm) for microwave/oven combination.

LOT 40 THAMES PH. 5 A  
RE: BUILT IN WALL OVEN/MICRO. COMBO  
NO FLUSH INSTALLATION

**INSTALLATION INSTRUCTIONS**  
**~~27"~~ (68.6 CM) AND 30" (76.2 CM) ELECTRIC BUILT-IN**  
**MICROWAVE/OVEN COMBINATION**

**INSTRUCTIONS D'INSTALLATION**  
**ENSEMBLE FOUR À MICRO-ONDES ET FOUR**  
**CONVENTIONNEL ÉLECTRIQUES ET ENCASTRÉS**  
**DE ~~27"~~ (68,6 CM) ET 30" (76,2 CM)**

**Table of Contents/Table des matières**

<b>BUILT-IN MICROWAVE/OVEN COMBINATION SAFETY.....</b>	<b>2</b>	<b>SÉCURITÉ DU FOUR À MICRO-ONDES ET DU FOUR</b>	
<b>INSTALLATION REQUIREMENTS.....</b>	<b>2</b>	<b>CONVENTIONNEL COMBINÉS ET ENCASTRÉS.....</b>	<b>9</b>
Tools and Parts.....	2	<b>EXIGENCES D'INSTALLATION.....</b>	<b>9</b>
Built-In Microwave/Oven Combination.....	2	Outils et pièces.....	9
Location Requirements.....	2	Exigences d'emplacement de l'ensemble four	
Electrical Requirements.....	3	à micro-ondes et four conventionnel encastrés.....	10
<b>INSTALLATION INSTRUCTIONS.....</b>	<b>4</b>	Spécifications électriques.....	11
Prepare Built-In Microwave/Oven Combination.....	4	<b>INSTRUCTIONS D'INSTALLATION.....</b>	<b>12</b>
Remove Oven Door(s).....	4	Préparation de l'ensemble four à micro-ondes et four	
Replace Oven Door(s).....	5	conventionnel encastrés.....	12
Make Electrical Connection.....	6	Dépose de la/des porte(s) du four.....	12
Install Oven.....	7	Réinstallation de la/des porte(s) du four.....	12
Install Warming Drawer Deflector Kit (Only for Ovens		Raccordement électrique.....	13
Installed Above Warming Drawers).....	7	Installation du four.....	14
Complete Installation.....	8	Installation de l'ensemble de déflecteur pour tiroir-réchaud	
		(uniquement pour les fours installés au-dessus d'un tiroir-	
		réchaud).....	15
		Achever l'installation.....	16


**IMPORTANT:**

Save for local electrical inspector's use.

**IMPORTANT :**

À conserver pour consultation par l'inspecteur local des installations électriques.

W10725683B

**LOT 40 THAMES PH. 5 A  
RE: BUILT IN WALL OVEN/MICRO. COMBO  
NO FLUSH INSTALLATION**


*[Handwritten signature: O. J. Fuller]*  
*[Handwritten signature: T. J. Kelly]*

- Electrical supply junction box should be located 3" (7.6 cm) maximum below the support surface when the oven is installed in a wall cabinet. A 1" (2.5 cm) minimum diameter hole should have been drilled in the left rear corner of the support surface to pass the appliance cable through to the junction box.
- Oven support surface must be solid, level and flush with bottom of cabinet cutout. Floor must be able to support a total weight (microwave and built-in oven) of 208 lbs (95 kg) for 27" (68.6 cm) models or 249 lbs (113 kg) for 30" (76.2 cm) models.

**IMPORTANT:** To avoid damage to your cabinets, check with your builder or cabinet supplier to make sure that the materials used will not discolor, delaminate or sustain other damage. This oven has been designed in accordance with the requirements of UL and CSA International and complies with the maximum allowable wood cabinet temperatures of 194°F (90°C).

**Product Dimensions**

**27" and 30" (68.6 cm and 76.2 cm) Ovens**



**27" (68.6 cm) models**


- A. 42 3/8" (108.0 cm) overall height
- B. 25 3/8" (64.6 cm) recessed width
- C. 41" (104.1 cm) recessed height
- D. 23 1/4" (59.1 cm) max. recessed depth
- E. 27" (68.6 cm) overall width
- F. 48" (121.9 cm) flexible conduit length measured from the conduit clamp located at the rear of the oven. Do not remove the conduit clamp.

**30" (76.2 cm) models**

- A. 42 3/8" (108.0 cm) overall height
- B. 28 3/8" (72.2 cm) recessed width
- C. 41" (104.1 cm) recessed height
- D. 23 1/4" (59.1 cm) max. recessed depth
- E. 30" (76.2 cm) overall width
- F. 48" (121.9 cm) flexible conduit length measured from the conduit clamp located at the rear of the oven. Do not remove the conduit clamp.

**Cabinet Dimensions**

**27" and 30" (68.6 cm and 76.2 cm) Ovens**



**27" (68.6 cm) models**

- A. 27" (68.6 cm) min. cabinet width
- B. 1" (2.5 cm) top of cutout to bottom of upper cabinet door
- C. 19 1/4" (48.9 cm) bottom of cutout to floor is recommended. 4"-19 1/2" (10.2-48.9 cm) bottom of cutout to floor is acceptable.
- D. 25 1/2" (64.9 cm) cutout width
- E. 1 1/2" (3.8 cm) min. bottom of cutout to top of cabinet door
- F. 41 3/8" (105 cm)\* recommended cutout height
- G. 24" (60.7 cm) cutout depth

**30" (76.2 cm) models**

- A. 30" (76.2 cm) min. cabinet width
- B. 1" (2.5 cm) top of cutout to bottom of upper cabinet door
- C. 19 1/4" (48.9 cm) bottom of cutout to floor is recommended. 4"-19 1/2" (10.2-48.9 cm) bottom of cutout to floor is acceptable.
- D. 28 1/2" (72.4 cm) cutout width
- E. 1 1/2" (3.8 cm) min. bottom of cutout to top of cabinet door
- F. 41 3/8" (105 cm)\* recommended cutout height
- G. 24" (60.7 cm) cutout depth

**\*NOTE:** The cutout height can be between 41" and 41 1/2" (104.1 cm and 105.6 cm) for microwave/oven combination.

**Electrical Requirements**

If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path and wire gauge are in accordance with local codes.

Check with a qualified electrical installer if you are not sure the oven is properly grounded.

This oven must be connected to a grounded metal, permanent wiring system.

Be sure that the electrical connection and wire size are adequate and in conformance with the National Electrical Code, ANSI/NFPA 70-latest edition or CSA Standards C22.1-94, Canadian Electrical Code, Part 1 and C22.2 No. 0-M91-latest edition, and all local codes and ordinances.

A copy of the above code standards can be obtained from:

National Fire Protection Association  
1 Batterymarch Park  
Quincy, MA 02169-7471

CSA International  
8501 East Pleasant Valley Road  
Cleveland, OH 44131-5575


**LOT 40 THAMES PH. 5 A  
RE: BUILT IN WALL OVEN/MICRO. COMBO  
NO FLUSH INSTALLATION**

*Jimmy Hall*  
*John*

**Electrical Connection**

To properly install your oven, you must determine the type of electrical connection you will be using and follow the instructions provided for it here.

- Oven must be connected to the proper electrical voltage, amperage, and frequency as specified on the model/serial/rating plate. See the following illustration.



A. Model/serial/rating plate

- Models rated from 7.3 to 9.6 kW at 240 volts (5.4 to 7.4 kW at 208 volts) require a separate 40-amp circuit. Models rated at 4.8 kW and below at 240 volts (3.6 kW and below at 208 volts) require a separate 30-amp circuit.
- A circuit breaker is recommended.
- Connect directly to the fused disconnect (or circuit breaker box) through flexible, armored or nonmetallic sheathed, copper cable (with grounding wire). See "Make Electrical Connection" section.

- Flexible conduit from the oven should be connected directly to the junction box.
  - Do not cut the conduit. The length of conduit provided is for serviceability of the oven.
  - A UL listed or CSA approved conduit connector must be provided.
  - If the house has aluminum wiring, follow the procedure below:
    1. Connect a section of solid copper wire to the ends of the flexible conduit leads.
    2. Connect the aluminum wiring to the added section of copper wire using special connectors and/or tools designed and UL listed for joining copper to aluminum.
- Follow the electrical connector manufacturer's recommended procedure. Aluminum/copper connection must conform with local codes and industry accepted practices.

For power requirements, refer to the following table.

Model	Voltage	Amperage (L1)*	Amperage (L2)*	Rating (W)
KOCE507E/ KOCE500E	120/240	32	30	8000
KOCE507E/ KOCE500E	120/208	30	28	6600

\*Amperage values noted above are for information purposes only. The units are rated in watts.

## INSTALLATION INSTRUCTIONS

### Prepare Built-In Microwave/Oven Combination

1. Decide on the final location for the oven. Locate existing wiring to avoid drilling into or severing wiring during installation.

### **WARNING**

#### **Excessive Weight Hazard**

**Use two or more people to move and install oven.**


**Failure to do so can result in back or other injury.**

2. To avoid floor damage, set the oven onto cardboard prior to installation. Do not use handle or any portion of the front frame for lifting.
3. Remember to remove bottom vent from the foam packing on top of oven.
4. Remove the shipping materials and tape from the oven.
5. Remove the hardware package from inside the bag containing literature.
6. Remove and set aside racks and other parts from inside the oven.
7. Move oven and cardboard close to the oven's final location.


### Remove Oven Door(s)

**IMPORTANT:** Use two hands to remove oven door.

1. Prior to removing the oven door, prepare a surface where you will place it. This surface should be flat and covered with a soft blanket, or use the corner posts from your packaging material.
2. Open the oven door.
3. Locate the oven door hinge locks in both corners of the oven door, and then rotate the hinge locks toward the oven door to the unlocked position. If the door hinge lock is not rotated fully (see illustration B), the door will not remove properly.



A. Oven door hinge lock in locked position



B. Oven door hinge lock in unlocked position

*[Signature]*  
*[Signature]*


**KitchenAid**

UNDER COUNTER WINE  
CELLAR

KUWR314KSS, KUWL314KSS, KUWR314KBS,  
KUWL314KBS, KUWR214KSB, KUWL214KSB,  
KUWR214KPA, KUWL214KPA

Detailed Planning Dimensions Guide

Product Dimensions



- \* Add 5/8" (1.6 cm) to the height dimension when leveling legs are fully extended
- \*\* For custom panel models, this will vary
- † Add 1/4" (6.4 mm) to the height dimension for height with hinge covers.

Variant	Depth (no handle)
Panel ready models (with 3/4" panel)	23 13/16" (60.7 cm)
Stainless and black stainless	23 5/8" (60.2 cm)

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.




Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

LOT 40 THAMES PH. 5 A  
RE:WINE FRIDGE SPEC'S

*[Handwritten signature]*  
*[Handwritten signature]*

Dimension	Description	Panel ready models (with 3/4" panel)	Stainless and black stainless models
A	Width of door	23 <sup>3</sup> / <sub>4</sub> " (60.3 cm)	23 <sup>3</sup> / <sub>4</sub> " (60.3 cm)
B	Width of the grille	23 <sup>13</sup> / <sub>16</sub> " (60.5 cm)	23 <sup>13</sup> / <sub>16</sub> " (60.5 cm)
C	Height to top of handle	**	31 <sup>1</sup> / <sub>8</sub> " (78.85 cm)
D	Width from side of wine cellar to handle – door open 90°	**	2 <sup>1</sup> / <sub>3</sub> " (5.95 cm)
E	Depth without door	21 <sup>11</sup> / <sub>16</sub> " (55.1 cm)	21 <sup>11</sup> / <sub>16</sub> " (55.1 cm)
F	Depth with door	23 <sup>13</sup> / <sub>16</sub> " (60.7 cm)	23 <sup>5</sup> / <sub>8</sub> " (60.2 cm)
G	Depth with handle	**	26 <sup>7</sup> / <sub>16</sub> " (67.15 cm)
H	Depth with door open 90°	47 <sup>15</sup> / <sub>16</sub> " (121.8 cm)	47 <sup>15</sup> / <sub>16</sub> " (121.8 cm)

\*\*For custom panel models, this will vary.




Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

*[Signature]*  
*[Signature]*


Opening Dimensions



**NOTE:** Make sure there is 3" (7.6 cm) space between wine cellar and adjacent appliance/wall for door swing.

Electrical Supply Location

- Lighter grey area indicates recommended recessed power outlet (located behind the wine cellar).
- Power cord length is 60" (152.4 cm).
- For flush installation, the power outlet can be installed in adjacent cabinetry with a cutout on the power cord side for routing of the power cord.



Dimensions

A	3" (7.55 cm)	D	12 1/16" (30.64 cm)
B	4 1/2" (11.37 cm)	E	2 13/16" (55.16 cm)
C	9 1/4" (23.47 cm)	F	1 3/4" (4.44 cm)

Because Whirlpool Corporation policy includes a continuous commitment to improve our products, we reserve the right to change materials and specifications without notice.

Dimensions are for planning purposes only. For complete details, see Installation Instructions packed with product. Specifications subject to change without notice.

Electrical Requirements

**⚠ WARNING**



Electrical Shock Hazard

- Plug into a grounded 3 prong outlet.
- Do not remove ground prong.
- Do not use an adapter.
- Do not use an extension cord.
- Failure to follow these instructions can result in death, fire, or electrical shock.

A 115 V, 60 Hz, AC only, 15 A or 20 A fused, grounded electrical supply is required. It is recommended that a separate circuit serving only your wine cellar be provided. Use an outlet that cannot be turned off by a switch. Do not use an extension cord.

Location Requirements

**⚠ WARNING**



Explosion Hazard

- Keep flammable materials and vapors, such as gasoline, away from wine cellar.
- Failure to do so can result in death, explosion, or fire.

For the wine cellar to be flush with the front of the base cabinets, remove any baseboards or moldings from the rear of the opening.

Flooring under product must be at the same level as the room. If the floor of the opening is not level with the kitchen floor, shim the opening to make it level with the kitchen floor.