## Energy Efficiency Design Summary (Part 9 Residential)

This form is used to summarize the energy efficiency design of the project. Information on completing this form is on the reverse

Application No:		For use by Pr	incipal Authority  Model/Certification Number			
A. Project Information						
Arlington 2011 A,B,C				Unit number	Lot/Con ZZ	
Municipality Z	Pestel	<del>eede**</del>	Reg. Plan number / other desci	ription	1112	
201 WA	سمد	EBURC	CET.	471	1412	
B. Compliance Option						
SB-12 Prescriptive [SB-12 - 2.1.1.	Table: 2.1.1.2A Package: A B C D E F G H I J K L M					
☐ SB-12 Performance* [SB-12 - 2.1.2.] * Atta			Attach energy performance calculations using an approved software			
☐ <i>ENERGY STAR</i> ®* [SB-12 - 2.1.3.] * A			* Attach BOP form			
☐ EnerGuide 80*		* House must be evaluated by NRCan advisor and meet a rating of 80				
C. Project Design Conditions		1				
Climatic Zone (SB-1): Heating Equipment Efficiency Space Heating Fuel Source						
© Zone 1 (< 5000 degree days) © ≥ 90% AFUE		E11E	■ Gas	□ Propane	□ Solid Fuel	
□ Zone 2 (≥ 5000 degree days) □ ≥ 78% < 90% AFUE			Oil	□ Electric	□ Earth Energy	
Windows+Skylights+Glass Doors  Gross Wall Area = 174,05 m <sup>2</sup> 0/ Windows+ 9.05 9/			Other Building Conditions  □ ICF Basement □ Walkout Basement □ Log/Post&Beam			
Gross Wall Alea = 174.05 III % Windows+		9.05 %	☐ ICF Above Grade	☐ Slab-on-ground	U	
D. Building Specifications [prov	ride values a	nd ratings of the				
Building Component	RSI/	R values		ponent	Efficiency Ratings	
The state of the s			Windows & Doors <sup>1</sup>			
Ceiling with Attic Space 8.81			Windows/Sliding Glass Doors		1.8	
Ceiling without Attic Space 5.46			Skylights			
Exposed Floor 5.46			Mechanicals		·	
Walls Above Grade 3.87			Space Heating Equip. <sup>2</sup>		92%	
Basement Walls 3.52			HRV Efficiency (%)		60%	
Slab (all >600mm below grade)			DHW Heater (EF)		0.62	
Slab (edge only ≤600mm below grade) 1.76 Slab (all ≤600mm below grade, or heated) 1.76			NOTES  1. Provide U-Value in W/m2.K, or ER rating			
Slab (all ≤600mm below grade, or heated)		Provide AFUE or indicate if condensing type combined system used				
E. Performance Design Verific	cation [cor	nplete applicable	sections if SB-12 Performar	nce, Energy Star or E	nerGuide80 options used]	
SB-12 Performance: The annual energy consumption usin The annual energy consumption of the The software used to simulate the an	nis house a nual ener	as designed is gy use of the	sGj building is:	is	_Gj (1 Gj =1000Mj)	
The building is being designed using	an air leal	rage of	air changes per hou	r @50Pa.		
ENERGY STAR: BOP form attached	. The hous	se will be labe	led on completion by:			
ENERGY STAR and EnerGuide80: Evaluator/Advisor/Rater Name:			Evaluator/Advisor/Rater L	.icence #:		
F. Designers [names of designers wh	o are respon	sible for the build	ling code design and whose	plans accompany the	permit application]	
Architectural Santos Dolormente, BCIN 21715 D			Mechanical		•	
		20, 2012				
orm authorized by OHBA, OBOA, LMCBO. February 6, 2012						