Energy Efficiency Design Summary (Part 9 Residential)

Supplementary Standard SB-12									
This form is to be completed and signed by the person who reviews and takes responsibility for the energy efficiency design of the project. Information on completing this form is contained on the reverse.									
For use by Principal Authority									
Application No. Model/Certification Number:									
A. Project Information Phoenix Homes:			PLATIN		<u> </u>	(03036)			
Building Number, Street Name 303 Wave			CEBURS	CRT	Unit Number		Lot / Con.	23	
Municipality Ottawa Postal Code			Reg. Plan Number / Other Description					tion	
B. Compliance Option									
SB-12 Prescriptive [SB-12 - 2.1.1.]			2.1.1.2A Package: i						
SB-12 Performance* [SB-12 - 2.1.2.]		* Attach er	* Attach energy performance calculations using an approved software						
Energy Star®* [SB-12 - 2.1.3.]		* Attach BOP form. House must be labeled on completion by Energy Star							
EnerGuide 80® *		* House must be evaluated by NRCan advisor and meet a rating of 80							
C. Project Design Conditions									
Climatic Zone (SB-1) Heating Equipment Efficiency Space Heating Fuel Source									
Zone 1 (< 5000 degree days)	≥ 90% AF	UE	Gas Propane Solid Fuel					uel	
Zone 2 (≥ 5000 degree days) [one 2 (≥ 5000 degree days)			Oil Electric Earth Energy					
Windows + Skylights + Glass Doors			Other Building Conditions						
Gross Wall Area = 332.95 m ²	% Windows+	11.62 %	☐ ICF Basement ☐ Walkout Basement ☐ Log / Post and Beam						
Gross Window+ Area = 38.70 m ² CF Above Grade Slab on Grade									
D. Building Specifications									
Building Component	RSI / R values		Building Component			Efficiency Ratings			
Thermal Insulation	0.01		Windows & Doors ¹			10			
Ceiling with Attic Space Ceiling without Attic Space	8.81 5.46		Windows/Sliding Glass Doors Skylights			1.8			
Exposed Floor	5.46		Mechanicals				.,		
Walls Above Grade	3.87		Space Heating Equip.2			92%			
Basement Walls	3.52		HRV Efficiency (%)			60%			
Slab (all >600mm below grade)			DHW Heater (0.62	0.62				
Slab (edge only ≤600mm below grade)	1.76		NOTES 1. Provide U-Value in W/m2.K, or ER rating						
Slab (all ≤600mm below grade, or heated)	e, or 1.76			2. Provide AFUE or indicate if condensing type combined system used					
E. Performance Design Verification [complete applicable sections if SB-12 Performance, Energy Star or EnerGuide80 options used]									
SB-12 Performance: The annual energy consumption using Subsection 2.1.1. SB-12 Package is Gj (1 Gj =1000Mj) The annual energy consumption of this house as designed is Gj The software used to simulate the annual energy use of the building is: The building is being designed using an air leakage of air changes per hour @50Pa.									
Energy Star. BOP form attached. The house will be labeled on completion by:									
Energy Star and EnerGuide80:									
Evaluator / Advisor / Rater Name: Evaluator / Advisor / Rater License #:									
F. Declaration [by the person who reviews and takes responsibility for the energy efficiency design]									
I certify that I have reviewed the design documents submitted with the permit application, that the information contained on this form is consistent with the design documents, and that information used in any annual energy use calculations, if applicable, is a true representation of the design documents.									
Name: Ken Viljoen Viljoen Architec In 300A Wilson Ave OAA License 2393 Tel 416-630-2255	e Si	gnature: -	K.1	leljoën		Date:	APRIL 18-20)12	