

SITE
COPY
City of Ottawa

City of Ottawa
Building Services Branch

AUG 19 2021

Building Code Reviewed

Signature

GLUED AND NAILED

LEVEL AND FLOOR CONTAINER NOTES	
Current Date:	6/13/2019
File Name:	Cheasapeake 4Bed ABEF.mmdl
Level Name:	1st Floor
Building Code - Design Methodology:	NBCC 2010
Floor Container:	FC1
Floor Area Loading is:	40 Live Load & 15 Dead Load
Maximum Allowed Deflection	L/480 Live Load & L/240 Total Load

Products					
PlotID	Length	Product	Plies	Net Qty	
L0 - FJ1 @ 16" O.C.	42-00-00	9 1/2" NI-20	1	6	
L0 - FJ2 @ 16" O.C.	22-00-00	9 1/2" NI-20	1	6	
L0 - FJ3 @ 16" O.C.	19-00-00	9 1/2" NI-20	1	8	
L0 - FJ4 @ 16" O.C.	18-00-00	9 1/2" NI-20	1	1	
L0 - FJ5 @ 16" O.C.	17-00-00	9 1/2" NI-20	1	1	
L0 - FJ6 @ 16" O.C.	16-00-00	9 1/2" NI-20	1	1	
L0 - FJ7 @ 16" O.C.	14-00-00	9 1/2" NI-20	1	28	
L0 - FJ8 @ 16" O.C.	13-00-00	9 1/2" NI-20	1	8	
L0 - FJ9 @ 16" O.C.	10-00-00	9 1/2" NI-20	1	2	
L0 - FJ10 @ 16" O.C.	7-00-00	9 1/2" NI-20	1	2	
L0 - FJ11 @ 16" O.C.	6-00-00	9 1/2" NI-20	1	2	
L0 - FJ12 @ 16" O.C.	5-00-00	9 1/2" NI-20	1	1	
L0 - FJ11	5-00-00	9 1/2" NI-20	1	4	
L0 - FJ11	3-00-00	9 1/2" NI-20	1	1	
L0 - BM1	15-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	2	4	
L0 - BM2	14-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1	1	
L0 - BM3	10-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	2	2	
L0 - BM4	9-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1	1	
L0 - BM5	6-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1	2	
L0 - BM6	6-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	2	2	
L0 - BM7	5-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1	1	
L0 - BM8	5-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	2	4	
L0 - BM9	4-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1	1	
L0 - BM10	2-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1	1	
L0 - Ca1	12-00-00	1 1/8" x 9 1/2" APA Rim Board	1	15	
L0 - Bk1	39-00-00	9 1/2" NI-20	1	1	

Accessories

PlotID	Length	Product	Plies	Net Qty
5/8" Plywood or OSB (19/32" APA Rated Sheathing 40/20 Exposure 1)			1	52

Connector Summary

Qty	Manuf	Product	Skew	Supported Mtl
29	SIMPSON	LT259	-	9 1/2" NI-20
1	SIMPSON	LSSUI25	31° (L)	9 1/2" NI-20
7	SIMPSON	SUL25695	45° (L)	9 1/2" NI-20
1	SIMPSON	SUR1819	-	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E
3	SIMPSON	HUS18110	-	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E
2	SIMPSON	HHUS410	-	2- 1 3/4" x 9 1/2" Nordic Lam 24F-1.9E

THIS DESIGN COMPLIES WITH:

- PART 4 OR 9 OF OBC 2012 Reg. 332/12
- NORDIC LAM CCMC: 13216-R
- NORDIC JOISTS CCMC: 13032-R
- WEST FRASER CCMC: 12904

(REFER TO INDIVIDUAL FLOOR DRAWINGS
FOR SPECIFIC LOADS & SPACING)

FLOOR NOTES:

- FLOOR JOIST SYSTEMS ABOVE
THE GARAGE HAS BEEN
DESIGNED WITHOUT A
DIRECTLY APPLIED CEILING.
USE APPLICABLE BLOCKING OR
STRAPPING WHERE REQUIRED
AS INDICATED ON THE FRAMING
PLAN.
- BLOCKING MATERIAL WILL BE
SUPPLIED AND INDICATED AS
"BLOCKING". NO LONGER ONLY
12' LENGTHS.



GRANDOR LUMBER INC.
ALPA LUMBER GROUP

JOB:

PHOENIX HOMES
CHEASAPEAKE 4 BED
A,B,E,F
1ST FLOOR 1 OF 2

DATE:

6/17/2019

41-06-00

54-01-00

47-03-00

2-04-00

3-02-00

1-04-00

11-07-00

10-04-00

6-02-00

1-11-00

10-00-00

1-06-00



SITE
COPY
City of Ottawa

City of Ottawa
Building Services Branch

AUG 19 2021

Building Code Reviewed

Signature

GLUED AND NAILED

LEVEL AND FLOOR CONTAINER NOTES	
Current Date:	6/13/2019
File Name:	Cheasapeake 4Bed ABEF.mmdl
Level Name:	2nd Floor
Building Code - Design Methodology:	NBCC 2010
Floor Container:	FC2
Floor Area Loading is:	40 Live Load & 15 Dead Load
Maximum Allowed Deflection	L/480 Live Load & L/240 Total Load

Products			
PlotID	Length	Product	Plies Net Qty
L1 - FJ1 @ 16" O.C.	42-00-00	9 1/2" NI-20	1 3
L1 - FJ2 @ 16" O.C.	24-00-00	9 1/2" NI-20	1 1
L1 - FJ3 @ 16" O.C.	22-00-00	9 1/2" NI-20	1 1
L1 - FJ4 @ 16" O.C.	19-00-00	9 1/2" NI-20	1 5
L1 - FJ5 @ 16" O.C.	17-00-00	9 1/2" NI-20	1 4
L1 - FJ6 @ 16" O.C.	16-00-00	9 1/2" NI-20	1 6
L1 - FJ7 @ 16" O.C.	15-00-00	9 1/2" NI-20	1 1
L1 - FJ8 @ 16" O.C.	14-00-00	9 1/2" NI-20	1 19
L1 - FJ9 @ 16" O.C.	13-00-00	9 1/2" NI-20	1 11
L1 - FJ10 @ 16" O.C.	5-00-00	9 1/2" NI-20	1 1
L1 - FJ11 @ 16" O.C.	3-00-00	9 1/2" NI-20	1 1
L1 - FJ12 @ 16" O.C.	22-00-00	9 1/2" NI-40x	1 1
L1 - FJ13 @ 16" O.C.	19-00-00	9 1/2" NI-40x	1 1
L1 - FJ14 @ 16" O.C.	18-00-00	9 1/2" NI-40x	1 1
L1 - BM1	20-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	2 2
L1 - BM2	16-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1 2
L1 - BM3	15-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	2 2
L1 - BM4	14-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1 2
L1 - BM5	13-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1 1
L1 - BM6	9-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1 1
L1 - BM7	7-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1 1
L1 - BM8	4-00-00	1 3/4" x 9 1/2" Nordic Lam 24F-1.9E	1 1
L1 - Ca1	12-00-00	1 1/8" x 9 1/2" APA Rim Board	1 13
L1 - Bk1	26-00-00	9 1/2" NI-20	1 1

Accessories			
PlotID	Length	Product	Plies Net Qty
		5/8" Plywood or OSB (19/32" APA Rated Sheathing 40/20 Exposure 1)	1 40

Connector Summary				
Qty	Manuf	Product	Skew	Supported Mtl
5	SIMPSON	SUL25695	45° (L)	9 1/2" NI-20
3	SIMPSON	LT259	-	9 1/2" NI-20
2	SIMPSON	HUS1810	-	1 3/4" x 9-1/2" NL
2	SIMPSON	SUR1819	-	1 3/4" x 9-1/2" NL

THIS DESIGN COMPLIES WITH:

- PART 4 OR 9 OF OBC 2012 Reg. 332/12
- NORDIC LAM CCMC: 13216-R
- NORDIC JOISTS CCMC: 13032-R
- WEST FRASER CCMC: 12904

(REFER TO INDIVIDUAL FLOOR DRAWINGS
FOR SPECIFIC LOADS & SPACING)

FLOOR NOTES:

- FLOOR JOIST SYSTEMS ABOVE
THE GARAGE HAS BEEN
DESIGNED WITHOUT A
DIRECTLY APPLIED CEILING.
USE APPLICABLE BLOCKING OR
STRAPPING WHERE REQUIRED
AS INDICATED ON THE FRAMING
PLAN.
- BLOCKING MATERIAL WILL BE
SUPPLIED AND INDICATED AS
"BLOCKING". NO LONGER ONLY
12' LENGTHS.



GRANDOR LUMBER INC.
ALPA LUMBER GROUP

JOB:

PHOENIX HOMES
CHEASAPEAKE 4 BED
A,B,E,F
2ND FLOOR 2 OF 2

DATE:

6/17/2019