



TRINSIC®

Single Handle Pull-Down Bar / Prep Faucet

MODEL#: 9959-CZ-DST

- 1 or 3-hole installation
- Delta MagnaTite Docking holds spray wand firmly in place
- Backed by Delta Faucet's Lifetime Limited Warranty

Finish: **Champagne Bronze**




Delta MagnaTite Docking uses a powerful integrated magnet to pull your faucet spray wand precisely into place and hold it there so it stays docked when not in use. Delta faucets with DIAMOND Seal Technology perform like new for life with a patented design which reduces leak points, is less hassle to install and lasts twice as long as the industry standard*. Kitchen faucets with Touch-Clean Spray Holes allow you to easily wipe away calcium and lime build-up with the touch of a finger. You can install with confidence, knowing that Delta faucets are backed by our Lifetime Limited Warranty. *Industry standard is based on ASME A112.18.1 of 500,000 cycles.


- MagnaTite Docking uses a powerful integrated magnet to snap your faucet spray wand precisely into place and hold it there so it stays docked when not in use and doesn't droop over time
- Soft, rubber Touch-Clean spray holes allow you to easily wipe away calcium and lime build-up with the touch of a finger
- DIAMOND Seal Technology is less hassle to install and helps your faucet perform like new for life, reducing leak points and lasting twice as long as the industry standard
- Everything you need is together in one convenient box, including integrated InnoFlex PEX supply lines
- 1 or 3-hole 8" installation
- ADA Compliant
- High-arc pull-down swivels 360degrees
- 54 in. long hose provides outstanding reach

Technology

 MagnaTite® Docking ⓘ

 DIAMOND™ Seal Technology ⓘ

Special Features

 Touch-Clean® ⓘ

 Volume Control ⓘ

 Brilliance® Finish ⓘ

 ADA Compliant ⓘ



 Chat with an Expert

Product Support, Repair Parts & Technical Specifications

- [View Maintenance & Installation Sheet](#)
- [View Technical Specifications](#)
- [View Parts & Accessories Diagram](#)

Installation Information

Number of Handles :	singlehandle
Escutcheon :	Optional Escutcheon Available
Flow Rate :	1,80 gpm @ 60 psi, 6,8 L/min @ 414 kPa
Spout Height :	13"
Spout Length :	6-1/2"
Deck to Outlet :	8-3/8"
Fittings Type :	3/8" compression fittings
Drain Type :	NA
Deck Thickness :	2,5"
Supply Line :	InnoFlex Pex-C Supply Lines
Valve Type :	Euromotion DIAMOND(TM) Valve
Pull-out/Pull-down :	Yes
Tall/High Arc :	Yes

