



APPLIANCE CHECKLIST

It may seem early to be thinking about appliances, but they are an important part of your kitchen design and may require upgrades to your HVAC, plumbing and electrical plans. It’s important that we are provided with your appliance information during the structural and foundation part of the Design Process, so that these upgrades can be included on your invoice, if required.

ITEM	BRAND	MODEL NUMBER
FRIDGE	CAFE	CWE19SP4NW2
DISHWASHER	CAFE	CDT875P4NW2
RANGE	CAFE	CCHS950P4MW2
Type: Gas <input type="checkbox"/> Electric <input checked="" type="checkbox"/> Induction <input checked="" type="checkbox"/> Waterline Required <input type="checkbox"/> Electrical: 15 Amp <input type="checkbox"/> 40 Amp <input checked="" type="checkbox"/> 50 Amp <input type="checkbox"/>		
WALL OVEN	NA	
Type: Gas <input type="checkbox"/> Electric <input type="checkbox"/> Waterline Required <input type="checkbox"/> Electrical: 30 Amp <input type="checkbox"/> 40 Amp <input type="checkbox"/>		
WARMING DRAWER	NA	
Electrical: 15 Amp <input type="checkbox"/> Other: Specify		
COOKTOP	NA	
Type: Gas <input type="checkbox"/> Electric <input type="checkbox"/> Induction <input type="checkbox"/> Electrical: 15 Amp <input type="checkbox"/> 40 Amp <input type="checkbox"/> 50 Amp <input type="checkbox"/>		
BUILT IN MICROWAVE	CAFE	CWL112P4RW5
Electrical: 15 Amp <input type="checkbox"/> 20 Amp <input checked="" type="checkbox"/> 240 Volt <input checked="" type="checkbox"/> 120 Volt <input type="checkbox"/>		
MICROWAVE TRIM KIT	NA	
OTR MICROWAVE	NA	
WASHING MACHINE	LG	WKEX200HBA
DRYER	LG	WKEX200HBA
Type: Gas <input type="checkbox"/> Electric <input type="checkbox"/> Stacked <input checked="" type="checkbox"/>		
OTHER: HOODFAN	CYCLONE	BX21228
OTHER: WINE FRIDGE	CAFE	CCP06BP4PW2
OTHER:		

Hood Fans must be purchased through Phoenix Homes, and will require an upgrade to a make up air system for any hood fans above 300CFM. Standard hood fan vent pipe is 6”.

A make up air system is a required upgraded for all gas stoves/cooktops.

Any changes from the standard kitchen plan and/or standard electrical, plumbing and electrical specifications/plans may be subject to additional fees.

Community: DIAMONDDVIEW (3)
Purchaser Signature:

DocuSigned by:
Rosa Brown
E7F3520E8BB840C...


Lot #: 114
Purchaser Signature:

Café™ Built-In Microwave Drawer Oven

CWL112P4RW5 / CWL112P2RS1 / CWL112P3RD5



ALSO
AVAILABLE IN



CWL112P2RS1
Stainless Steel



CWL112P3RD5
Matte Black

FEATURES & BENEFITS

Sensor Cook & Sensor Reheat - Microwave sensor cooking automatically adjusts the time and power for delicious results with packaged foods, leftovers and more.

Glass Touch Controls - Sleek touch controls make this smart microwave easy to use and clean.

Drawer Door - This easy open microwave extends like a cabinet drawer and sits lower than a typical countertop unit for added convenience and easy access.

Electronic Open - Simply push a button to open the handleless microwave door.

1.2 cu. ft. - This mid-sized microwave has plenty of capacity thanks to the innovative drawer design.

Convenient Controls - Quickly microwave your favorites with ease using intuitive cooking controls.

FEATURES

Control Type	Glass Touch
Electronic Digital Display with Clock	Yes
Style	Built-In
Interior Oven Light	Incandescent
Power Levels	10
Microwave Sensor Cooking Controls	Popcorn Potato Chicken Fish Meat Vegetable - Fresh Vegetable - Frozen Vegetable - Canned
Control Features	Add 30 Sec Mute On/Off Start/Pause Clear/Off Lock controls Power Level Timer Set Clock Express Cook Weight/Time Defrost Cook Time Open Close Melt Soften Beverage Popcorn Sensor Reheat Sensor Cook
Microwave Oven Interior	Coated
Microwave Watts (IEC-705)	1,000W

CAPACITY

Total Capacity (cubic feet)	1.2 cu ft
-----------------------------	-----------

TECHNICAL DETAILS

Electrical Input - 120V Watts	1500
Input Volts/Hertz	120/60

WEIGHTS & DIMENSIONS

Approximate Shipping Weight	80 lb
Cabinet Width	24 in
Cavity (W x H x D)	17-1/4 x 7-1/8 x 17-1/2
Net Weight	69 lb
Overall Depth	23-5/16 in
Overall Height (Rear)	14-19/32 in
Overall Height (Front)	15-15/16 in
Overall Width	23-7/8 in

WARRANTY

Parts warranty	Limited 1-year entire appliance Limited 5-year magnetron tube
Labor warranty	Limited 1-year entire appliance
Warranty notes	See written warranty for full details




Café™ Built-In Microwave
Drawer Oven

CWL112P4RW5 / CWL112P2RS1 / CWL112P3RD5




DIMENSIONS AND INSTALLATION INFORMATION (IN INCHES)


OVERALL DIMENSIONS



STANDARD INSTALLATION



FLUSH INSTALLATION




- [A] Junction box location (May also be located in adjacent cabinet.)
- [B] To reduce the risk of tipping of the drawer, the Anti-Tip block must be properly installed located 14-13/16" above the floor on which the Microwave Drawer will sit. The Anti-Tip block must be provided and pre-installed by the purchaser of the product or builder before install can be done. The Anti-Tip block prevents serious injury that might result from spilled hot liquids.
- [C] Cleats may be visible and should be finished to match cabinetry.
- [D] The face of the shelf must sit 1-7/8" back from the face of the cabinet. See installation instructions for further details including the installation of 24" flush mount deflector vent.

Dimensions in parentheses are in centimeters unless otherwise noted. Actual product dimensions may vary due to manufacturing tolerances.

Café™ Stainless Interior Built-In Dishwasher with Hidden Controls

CDT875P4NW2 / CDT875P3ND1 / CDT875P2NS1



CDT875P4NW2
Matte White with Brushed Bronze handles



ALSO
AVAILABLE IN



CDT875P3ND1
Matte Black with Brushed Stainless handles



CDT875P2NS1
Stainless Steel with Brushed Stainless handles

FEATURES & BENEFITS

Ultra Wash & Dry Plus – Expect precision cleaning and superior dryness on fine china, dinnerware and even dishwasher-safe plastics, with exceptional features like Variable-Pressure Jets and Dual-Convection Ultra Dry

Loading Flexibility – Clean up quickly after hosting any event with a dishwasher that accommodates large items – like charcuterie platters – and dishwasher-safe plastics, like storage containers, conveniently in the lower rack

Status Center – Continue conversations without interruption and easily know when extra dinnerware is available via an LCD screen that displays the dishwasher cycle status

Adjustable Upper Racks – You'll have room for your finest stemware and space for tall bakeware with a rack that can be moved two inches up or down, creating ultimate loading flexibility

WiFi – Always have clean dishes ready for surprise guests with WiFi Connect, which lets you operate your dishwasher from your smartphone. Track and automatically reorder detergent and rinse aid with just the tap of an app

Create a look that matches your personal style – Select any combination of premium finishes and hardware options to create a stunning look customized to any owner's taste

APPEARANCE

Door Style	Long Door with Top Controls
Installation	Side Installation or Top Installation Included; Built-Up Floor Capable; Flush Cabinet Installation
Door Appearance	Full-length flat door

FEATURES

Style	Built-In
Tub and Door Liner	Stainless Steel
Tub Type	Tall Tub
Control Type	Cap Touch Controls; 12 Touchpads
Dishwasher Control Features	Cycle Countdown with LCD Status Center on door; Multi function display; Last Cycle Memory; Audible End-of-Cycle Signal
Wash System	3-Level; 800 Series
Wash System Features	Variable Speed Dual Pumps and Motors; Automatic Temperature Control; Drain Pump; Hard Food Disposer with removable filter; Reversing Quad Blade Lower Wash Arm; Quad Blade Middle Wash Arm; Deep Clean Silverware Jets; Side Jets; 90+ Spray Jet Wash System; Hidden Heater; Automatic HotStart; Bottle Jets (4)
Sensor	Clean Sensor
Wash Arms	3 Wash Levels; Lower- Reversing Quad Blade; Middle - Quad Blade; Bottle Jets; Jets - Variable Pressure; Deep Clean Silverware Jets
Water Filtration System	100% Filtration with Hard Food Disposer and Removable Filter
Dispenser	Rinse Aid with Indicator and Adjustment; Electronic Low Rinse Aid Sensor
Number of Cycles	5
Dishwasher Cycles	Auto; Pots; Normal; China; Express
Number of Options	10
Dishwasher Options	Delay Start 1-12 Hr.; Hi-Temp Wash; Presoak + Sanitize (NSF Certified); Heated Dry Off; Normal Dry; Dual Convection Ultra Dry; Wash Zone Upper Only; Wash Zone Lower Only; Start/Reset; Bottle Wash; Lock Controls
Rack Features	2 Utility Shelves with Stem Safe and Chop-stick slots - Upper Ball-Tipped Tines; Adjustable Upper Rack; 3-Piece Silverware Basket with Cell Covers; Full Extension Slides - Upper
Racking Material	Nylon
Rack Color	Black Pearl
Number of Place Settings	Up to 16
Upper Rack	Premium Height Adjustable; Ball-Tip Tines; 2 Stem Safe Shelves; Chop stick slots; 1/2 fixed tines, 1/2 fold down tines
Lower Rack	Fixed tines with Bottle Jets; 1 Rack handle
Additional Protection	Ball-Tip Tines; 1/2 fixed tines, 1/2 fold down tines
Dishwasher Drying Features	Active Flood Protection
Floor Protection	Dual Convection Ultra Dry; Ultra/Normal/Off; Fan Assist Dry
Leveling System	Leak Pan w/ Sensor; Active Flood Protection
Latch	3 Leveling Legs
Showroom Power Mode	Pull with Handle
WiFi Connect	Yes
Exterior Style	Built-In
Racking System	Traditional
	Full 3rd Rack

ECONOMICAL/QUIET

Quiet Package	39 dBA
Quiet Features	Quiet Water Valve; Sealed Toe Kick; Tub Collar Trim
Motor Type	Variable Speed
Outer Wrap	Full-wrap Blanket; Bitumen
Door Insulation	Insulation; Mastic

WEIGHTS & DIMENSIONS

Cabinet Width	24 in
Approximate Shipping Weight	137 lb
Net Weight	124 lb
Overall Height	34 in
Height w/ Legs Retracted - Minimum Height	33-3/8 in
Height w/Legs Extended - Maximum Height	34-5/8 in
Overall Depth	24 in
Overall Width	23-3/4 in



Café™ Stainless Interior Built-In
Dishwasher with Hidden Controls

CDT875P4NW2 / CDT875P3ND1 / CDT875P2NS1




TECHNICAL DETAILS

Calrod Heater Watts	400/1200
Power Connection	Optional cord kit (GPFCORD - WX09X70910, WX09X70911)
Volts/Hertz/Amps	120 V; 60 Hz; 10.2 A


WARRANTY

Parts warranty	Limited 1-year entire appliance
Labor warranty	Limited 1-year entire appliance
Warranty notes	See written warranty for full details


DIMENSIONS




INSTALLATION DIMENSIONS




ADDITIONAL ACCESSORIES




Brushed Bronze
CXADTH1PMBZ
(Standard on Matte White)



Brushed Stainless
CXADTH1PMSS
(Standard on Matte Black and Stainless steel)



Brushed Black
CXADTH1PMBT



Brushed Copper
CXADTH1PMCU

Café™ Energy Star® 18.6 Cu. Ft. Counter-Depth French-Door Refrigerator

CWE19SP4NW2 / CWE19SP3ND1 / CWE19SP2NS1



CWE19SP3ND1
Matte Black with
Brushed Stainless handles



ALSO
AVAILABLE IN



CWE19SP2NS1
Stainless Steel
with Brushed
Stainless handles



CWE19SP3ND1
Matte Black with
Brushed Stainless handles

APPEARANCE

Counter-depth design	Yes
Exterior design	Contoured doors
Handle design	Café™
Hidden door hinges	Yes

FEATURES

Configuration	French door
WiFi connect	ConnectPlus
Temperature management features	Turbo cool setting; Multiflow air system with electronic sensors
Defrost type	Frost Guard
Control type	Upfront electronic temperature controls; Digital temperature display
Dispenser	Internal water
Icemaker	Factory-installed
Water filtration	GE water filtration 6 month; XWF; water filter indicator light
Filter location	Upper right corner
Door alarm	Yes
Fresh food cabinet drawers	Multi-level drawers; 2 humidity controlled drawers; 1 full-width, adjustable temperature drawer
Fresh food cabinet shelves	5 total; glass; 4 split adjustable; 1 Quick Space shelf
Fresh food door bins	8 Clear Look; 6 adjustable with gallon storage; 2 fixed
Fresh food features	Interior lighting - dual level LED
Freezer storage baskets	2 total; 1 full-width, full-extension plastic
Freezer cabinet drawer features	Freezer drawer
Freezer features	Interior lighting - LED; ice bucket
Exterior style	Counter-depth
Leveling system	2 point front adjustable
Performance features	Easily removable door gaskets

CAPACITY

Total capacity (cubic feet)	18.6 cu. ft.
Fresh food capacity	13.57 cu. ft.
Freezer capacity	5.01 cu. ft.

WEIGHTS & DIMENSIONS

Overall depth	31 in
Overall height	69-7/8 in.
Overall width	32-3/4 in.
Case depth without door	24-1/8 in.
Depth with door open 90°	42-in.
Depth without handle	29-in.
Height to top of case	68-5/8 in.
Height to top of hinge	69-3/4 in.
Width w/door open 90° incl. handle	40-1/2 in.
Approximate shipping weight	252 lb.
Net weight	232 lb.

FEATURES & BENEFITS

Enjoy the aesthetic and amenities of a French-door refrigerator that fits in a **33-inch opening**

Create a built-in look with **counter-depth design** that fits flush with surrounding cabinetry

Enjoy a cleaner appliance appearance with **internal water dispenser**

Display groceries like a gallery with **showcase LED lighting** positioned throughout the interior to spotlight your favorite foods and containers

Easily store your farmer's market veggies and fresh fruits in **two humidity-controlled drawers**, and place large items like party platters and sheet cakes in a **full-width, adjustable-temperature drawer**

Open the door as often as you need to while cooking or attending to guests and trust the **Turbo Cool setting** to make adjustments that will properly maintain the refrigerator's interior temperature

Spend less time looking for your favorite frozen foods thanks to **multi-level freezer baskets** that make organization easy

Choose your refrigerator's exact temperature using easily adjustable controls with a **digital actual temperature display**, stored in-the-door for a subtle, hidden appearance

Make room for tall items like milk and fruit juice with a **Quick Space shelf** that slides away usefully

Enjoy water and ice from the refrigerator with total peace of mind, thanks to an **advanced water filtration system** that uses RPWFE replacement filters to remove 98% of pharmaceuticals*

*Removes 98% of ibuprofen, atenolol, fluoxetine, progesterone and trimethoprim. These pharmaceuticals are not necessarily in all users' water.



Café™ Energy Star® 18.6 Cu. Ft. Counter-Depth French-Door Refrigerator


CWE19SP4NW2 / CWE19SP3ND1 / CWE19SP2NS1



WARRANTY

Parts warranty	Limited 1-year entire appliance
Labor warranty	Limited 1-year entire appliance
Warranty notes	See written warranty for full details

DIMENSIONS



OVERALL DIMENSIONS	Height to top of door (in.) A	69-7/8
	Height to top of hinge (in.) B	69-3/4
	Height to top of case (in.) C	68-5/8
	Case depth without door (in.) D	24-1/8
	Case depth less door handle (in.) E	29
	Case depth with door handle (in.) F	31
	Depth with fresh food door open 90° (in.) G	42
	Width (in.) H	32-3/4
	Width with door open 90° with door handle (in.) I	40-1/2
AIR CLEARANCES	Each side (in.)	1/8
	Top (in.)	1
	Back (in.)	2

ADDITIONAL ACCESSORIES



CXMA3H3PNBZ
Brushed Bronze
3 handles
(Standard on Matte White)



CXMA3H3PNSS
Brushed Stainless
3 handles
(Standard on Matte Black and Stainless Steel)



CXMA3H3PNBT
Brushed Black
3 handles



CXMA3H3PNCU
Brushed Copper
3 handles

3 ELECTRICAL REQUIREMENTS

⚠ WARNING

This appliance must be properly grounded.

⚠ WARNING

All new constructions, mobile homes, recreational vehicles and installations where local codes do not allow grounding through neutral, require a 4-conductor UL-listed range cord.

⚠ WARNING

To prevent fire or shock, do not use an extension cord with this appliance.

⚠ WARNING

To prevent shock, remove house fuse or open circuit breaker before beginning installation.

We recommend you have the electrical wiring and hookup of your range connected by a qualified electrician. After installation, have the electrician show you how to disconnect power from the range. You must use a single-phase, 120/208 VAC or 120/240 VAC, 60 hertz electrical system. If you connect to aluminum wiring, properly installed connectors approved for use with aluminum wiring must be used.

Effective January 1, 1996, the National Electrical Code requires that new construction (not existing) utilize a 4-conductor connection to an electric range. When installing an electric range in new construction, mobile home, recreational vehicle, or an area where local codes prohibit grounding through the neutral conductor, refer to the section on four-conductor branch circuit connections. Check with your local utilities for electrical codes which apply in your area. Failure to wire your oven according to governing codes could result in a hazardous condition, if there are no local codes, your oven must be wired and fused to meet the National Electrical Code, NFPA No. 70 – latest edition, available from the National Fire Protection Association.

This appliance must be supplied with the proper voltage and frequency, and connected to an individual, properly grounded, 40 amp (minimum) branch circuit protected by a circuit breaker or time-delay fuse.


Use only a 3-conductor or a 4-conductor UL-listed range cord. These cords may be provided with ring terminals on wire and a strain relief device.

A range cord rated at 40 amps with 125/250 minimum volt range is required. A 50 amp range cord is not recommended but if used, it should be marked for use with nominal 1 3/4" diameter connection openings. Care should be taken to center the cable and strain relief within the knockout hole to keep the edge from damaging the cable.

The rating plate is located on the oven frame or on the side of the drawer frame.

NOTE: Use of automatic, wireless or wired external switches that shut off power to the appliances, are not recommended for this product.

DOUBLE OVEN




4 POWER CORD AND CONDUIT INSTALLATION

Remove wire cover (on the back of range) by removing screws using a 1/4" nut driver. You can access the terminal block by either removing a terminal block cover (on some models) or the wire cover. Do not discard these screws.


A

Rear of Range



B


For power cord and 1" conduit only, remove the knockout ring (1 3/8") located on bracket directly below the terminal block. To remove the knockout, use a pair of pliers to bend the knockout ring away from the bracket and twist until ring is removed.



C


For power cord installations only (see the next step if using conduit), assemble the strain relief in the hole. Insert the power cord through the strain relief and tighten. Allow enough slack to easily attach the cord terminals to the terminal block. If tabs are present at the end of the winged strain relief, they can be removed for better fit.

NOTE: Do not install the power cord without a strain relief. The strain relief bracket **MUST** be installed before reinstalling the rear range wiring cover.



D


For 3/4" conduit installations only, purchase a squeeze connector matching the diameter of your conduit and assemble it in the hole. Insert the conduit through the squeeze connector and tighten. Allow enough slack to easily attach the wires to the terminal block. **NOTE:** Do not install the conduit without a squeeze connector. The squeeze connector **MUST** be installed before reinstalling the rear terminal block.



Proceed to step 6 or 7.

5 REAR TRIM INSTALLATION

For all installations, install the required rear trim to back of range with 4 screws provided.



6 3-WIRE INSTALLATION (GROUND IS THROUGH THE NEUTRAL WIRE)

⚠ WARNING Shock Hazard

The neutral wire and ground strap must be connected as shown below for the range to be properly grounded. Do not remove the ground strap. Failure follow this instruction may result in potential shock hazard.


⚠ WARNING Fire hazard

Terminal block screws must be securely tightened. Failure to do so may result in potential fire hazard.


FOR POWER CORD INSTALLATION

- A. Remove the 3 lower screws from the terminal block. Do not loosen the upper screws.
- B. Do not cut or remove the ground strap.
- C. Insert the 3 screws through each power cord terminal ring and back into the terminal block. Be certain the white wire is in the center. Securely tighten each screw (35 to 50 in-lbs.)

Power Cord



Conduit



FOR CONDUIT INSTALLATION


- A. Loosen the 3 lower screws on the terminal block. Do not loosen the upper screws.
 - B. Do not cut or remove the ground strap.
 - C. Insert the bare wire tip (insulation stripped 5/8") into the bottom terminal block openings. Be certain the white wire is in the center. On certain models, the wire must be inserted through an opening in the ground strap. Securely tighten each screw onto each wire (35 to 50 in-lbs.).
 - D. Reinstall terminal block cover.
- NOTE:** Aluminum building wire may be used but it must be rated for the correct amperage and voltage.

7 4-WIRE INSTALLATION (SEPARATE GROUND WIRE)

⚠ WARNING

The neutral wire of the supply circuit must be connected to the neutral terminal located in the lower center of the terminal block. The power leads must be connected to the lower left and the lower right terminals of the terminal block. The grounding lead must be connected to the frame of the range with the ground plate and the green ground screw.


Before—Power Cord and Conduit




FOR POWER CORD INSTALLATION

- A. Remove the 3 lower screws from the terminal block. Do not loosen the upper screws.
- B. Remove the ground screw and ground plate and retain them.
- C. Cut the ground strap below the terminal block and discard the lower section.
- D. Insert the ground screw through the ground plate (removed earlier) and back into the range frame. Tighten securely, but do not over-tighten (15 to 20 in-lbs.)
- E. Insert the 3 terminal screws through each power cord terminal ring and back into the terminal block. Be certain the white wire is in the center. Securely tighten each screw (35 to 50 in-lbs.)
- F. Reinstall terminal block cover.

After—Power Cord



After—Conduit



FOR CONDUIT INSTALLATION

- A. Remove the 3 lower screws from the terminal block. Do not loosen the upper screws.
 - B. Remove the ground screw and ground plate and retain them.
 - C. Cut the ground strap below the terminal block and discard the lower section.
 - D. Insert the bare ground bare wire tip (insulation stripped 5/8") between the range frame and the ground plate (removed earlier) and secure it in place with the ground screw. Tighten securely, but do not over-tighten (15 to 20 in-lbs.)
 - E. Insert the wire tips (insulation stripped 5/8") into the bottom terminal block openings. Be certain the white wire is in the center. On certain models, the wire must be inserted through an opening in the ground strap. Securely tighten each screw onto each wire (35 to 50 in-lbs.)
 - F. Reinstall terminal block cover.
- NOTE:** Aluminum building wire may be used but it must be rated for the correct amperage and voltage.

8 ANTI-TIP DEVICE INSTALLATION



A WARNING

Tip-Over Hazard

- A child or adult can tip the range and be killed.
- Install the anti-tip bracket to the wall or floor.
- Engage the range to the anti-tip bracket by sliding the range back such that the foot is engaged.
- Re-engage the anti-tip bracket if the range is moved.
- Failure to do so can result in death or serious burns to children or adults.



To reduce the risk of tipping the range, the range must be secured by a properly installed anti-tip bracket. See installation instructions shipped with the bracket for complete details before attempting to install.

To check if the bracket is installed and engaged properly, look underneath the range to see that the rear leveling leg is engaged in the bracket. On some models, the storage drawer or kick panel can be removed for easier inspection. If visual inspection is not possible, slide the range forward, confirm the anti-tip bracket is securely attached to the floor or wall, and slide the range back so the leveling leg is under the anti-tip bracket. If the range is pulled from the wall for any reason, always repeat this procedure to verify the range is properly secured by the anti-tip bracket. Never completely remove the leveling legs or the range will not be secured to the anti-tip bracket.


9 LEVEL THE RANGE

A WARNING Never completely remove the leveling leg as the range will not be secured to the anti-tip device properly.

- A. Plug in the unit.
- B. Measure the height of your countertop at the rear of the opening (X).
- C. Adjust two rear leveling legs so that the rear of cooktop is at the same height or higher than the counter (Y).
- D. Slide unit into place.
- E. Install oven shelves in the oven and position the range where it will be installed.
- F. Check for levelness by placing a spirit level on one of the oven shelves. Take two readings—with the level placed diagonally first in one direction and then the other.
- G. Adjust front leveling legs until the range is level.
- H. Look under the unit and verify that the rear leg is fully engaged with the anti-tip device. If not, remove the unit and adjust the height of the rear leg so that it is properly engaged.



NOTE: Cooktop must be at or above counter.



10 FINAL INSTALLATION CHECKLIST

- Check to make sure the circuit breaker is closed (RESET) or the circuit fuses are replaced.
- Be sure power is in service to the building.
- Check that all packing materials and tape have been removed. This will include tape on metal panel under control knobs (if applicable), adhesive tape, wire ties, cardboard and protective plastic. Failure to remove these materials could result in damage to the appliance once the appliance has been turned on and surfaces have heated.
- Check that the door and drawer are parallel to each other and that both operate smoothly. If they do not, see the Owner's Manual for proper replacement.
- Check to make sure that the rear leveling leg is fully inserted into the Anti-Tip bracket and that the bracket is securely installed.

OPERATION CHECKLIST

- Check that the oven control operates properly. If the oven control does not operate properly, recheck the wiring connections.
- Be sure all range controls are in the OFF position before leaving the range.

HOME APPLIANCES

LG LAUNDRY

WKEX200H_A / WKGX201H_A

Single Unit LG WashTower™ with Center Control™
4.5 cu. ft. Front Load Washer and 7.4 cu. ft. Dryer

KEY FEATURES

- Ultra Large Capacity 4.5 cu. ft. Washer and 7.4 cu. ft. Dryer
- Single Unit WashTower™ Design
- Full Touch Electronic Center Control™ Panel with LED Display
- Smart Pairing
- Advanced Drying - AI Sensor Dry™ and TurboSteam™
- Advanced AI DD™ Washing - TurboWash® 360 and Steam Technology
- AAFA Certified Washer with Allergiene™ Cycle
- Tempered Glass Door
- ENERGY STAR® Certified
- ThinQ® Technology with ThinQ Care

SMART APPLIANCE

ThinQ Care

- Preventative Alerts help you stay a step ahead of potential issues to find proactive solutions before problems arise.
- Avoid preventable repairs and service calls with real-time diagnostics for a hassle-free experience.
- Integrated within LG's ThinQ app—a smart home hub for managing your smart devices and appliances.

PRODUCT FEATURES

SUMMARY	Washer	Dryer
Type	Front Load Washer	Front Load Dryer
Capacity (cu.ft.)	4.5 cu. ft.	7.4 cu. ft.
Color	White (W), Black Steel (B), Nature Green (G), Candy Apple Red (R)	
APPEARANCE	Washer	Dryer
Touch Buttons		Yes
Full Touch Electronic Control Panel with LED Display	Yes	
Center Control™	Yes	
ENERGY	Washer	Dryer
ENERGY STAR® Certified	Yes	
CEE Tier	Tier 2	-
IMEF	2.92	-
IWF	2.9	-
CEF	-	Electric: 3.94 Gas: 3.49
PROGRAMS	Washer	Dryer
No. of Programs	6	6
	Normal, Bedding, Delicates, Heavy Duty, Speed Wash®, Downloaded	Normal, Bedding, Delicates, Heavy Duty, Small Load, Downloaded
OPTIONS	Washer	Dryer
No. of Options	10	9
	TurboWash®, Steam, Extra Rinse, Pre-wash, Sanitary*, Tub Clean*, Drum Light*, Control Lock*, Signal*, Wi-Fi* / Remote Start*	Wrinkle Care, Steam, Reduce Static, Energy Saver, Steam Fresh*, Drum Light*, Control Lock*, Signal*, Wi-Fi* / Remote Start*
DETAILS	Washer	Dryer
No. of Wash/Rinse Temps	5	-
Wash/Rinse Temps	Hot, Very Warm, Warm, Cool, Cold	-
No. of Spin Speeds	5	-
Spin Speeds	High, Medium/High, Medium, Low, No Spin	-
Max RPM	1300	-
Water Levels	Load Sensing	-
No. of Soil Levels	5	-
Temperature Settings	-	High, Medium/High, Medium, Low/ Medium, Low
Drying Levels	-	Very, More, Normal, Less, Damp
Manual Dry Times	-	60 min., 50 min., 40 min., 30 min., 20 min.

FABRIC CARE FEATURES	Washer	Dryer
AI DD™	Yes	-
TurboWash® 360 Technology	Yes	-
Steam Technology	Yes	-
Allergiene™ Cycle	Yes	-
Sanitary Cycle	Yes	-
AI Sensor Dry™	-	Yes
Sensor Dry	-	Yes
Precise Temperature Control with Variable Heater	-	Yes
Steam Technology	-	Yes (TurboSteam™)
CONVENIENCE FEATURES	Washer	Dryer
Vibration Sensing (Cabinet Vibration Sensor)	Yes	-
True Balance® Anti-Vibration System	Yes	-
4 Tray Dispenser	Prewash, Main Wash (with liquid detergent cup), Bleach, Fabric Softener	-
End of Cycle Signal	Yes	-
LoadSense	Yes	-
Control Lock		Yes
Auto Suds Removal	Yes	-
Leveling Legs		4 Adjustable Legs
Drum Light		Yes
Remaining Time Display/Status Indicator(s)		Yes
3 Minute Installation Check	-	Yes
End of Cycle Signal	-	Yes
FlowSense® Duct Clogging Indicator	-	Yes
Wrinkle Care Option	-	Yes
Venting Option	-	Electric: 3 Way Venting / Gas: 2 Way Venting
ThinQ® TECHNOLOGY	Washer	Dryer
SmartDiagnosis™ (v3.0)	Yes	
Wi-Fi	Yes	
Remote Start and Cycle Monitor		Yes
Energy Monitoring		Yes
Tub Clean Coach	Yes	-
MOTOR AND AGITATOR	Washer	Dryer
Motor Type	Inverter Direct Drive Motor	-
Axis	Horizontal	-

MATERIALS AND FINISHES	Washer	Dryer
NeveRust® Stainless Steel Drum		Yes
Cabinet		Painted Steel
Control Panel		Plastic
Top Plate		Steel
Door / Rim		Large Circle Chrome / Matte Black (Nature Green only)
Door Cover		Tinted Round Tempered Glass
All Available Colors		White (W), Black Steel (B), Nature Green (G), Candy Apple Red (R)
CERTIFICATION	Washer	Dryer
AAFA	Yes	-
POWER SOURCE	Washer	Dryer
Ratings		CSA Listed
Electrical Requirements	120V, 10 Amps	240V, 30 Amps (Electric) / 120V, 15 Amps (Gas)
Type	Electric	Electric / Gas
BTU Rating	-	Elec: N/A / Gas: 20,000
LP Conversion Kit	-	383EEL3002D
Side Venting Kit	-	3911EZ9131X
DIMENSIONS	Washer	Dryer
Product (WxHxD)		27" x 74 3/8" x 30 3/8"
Depth with Door Open		55" D with door open
Carton (WxHxD)		30 1/16" x 79 11/32" x 32"
Weight (Product/Carton)		311 lbs. / 346 lbs.
LIMITED WARRANTY	Washer	Dryer
Parts and Labor		1 Year
Direct Drive Motor	10 Years	-
Drum		3 Years
UPC CODES		
WKEX200HWA (White)		048231028462
WKGX201HWA (White)		048231029261
WKEX200HBA (Black Steel)		048231028486
WKGX201HBA (Black Steel)		048231029254
WKEX200HGA (Nature Green)		195174042687
WKGX201HGA (Nature Green)		195174042694
WKEX200HRA (Candy Apple Red)		195174043080
WKGX201HRA (Candy Apple Red)		195174043110



Café™ Beverage Center

CCP06BP4PW2 / CCP06BP3PD1 / CCP06BP2PS1



CCP06BP4PW2
Matte White with Brushed
Bronze handles

ALSO
AVAILABLE IN



CCP06BP2PS1
Stainless Steel with
Brushed Stainless
handles



CCP06BP3PD1
Matte Black with
Brushed Stainless
handles



FEATURES & BENEFITS

- Total Capacity: 5.1 Cu. Ft.
- Capacity: 126 Cans/14 Bottles
- ADA Compliant: Yes
- Energy Star: Yes
- BI capable: Yes
- Door Type: Glass
- Reversible Door: Yes
- Handle: Yes
- Shelf Type: 3 Spill Proof/3 Glass/2 Wine Racks
- Smart Capable: Yes
- Freezer: No
- Control Type: Electronic
- Internal Lighting: LED Light Wall

Triple Pane Glass Door: The triple pane glass door improves temperature stability, reduces condensation and enhances energy efficiency compared to a double pane glass door.

FEATURES

Control Type	Electronic
Interior Lighting	LED / LED Light Wall
Leveling System	Leveling Legs
Defrost Type	Automatic
Sabbath Mode	Yes

CAPACITY

Total Capacity (cubic feet)	5.1 cu ft
-----------------------------	-----------

WEIGHTS & DIMENSIONS

Approximate Shipping Weight	147 lb
Net Weight	137 lb
Depth Without Handle	23 3/8 in
Overall Depth	26 in
Overall Height	34 1/8 in
Overall Width	23 3/4 in



Café™ Beverage Center


CCP06BP4PW2 / CCP06BP3PD1 / CCP06BP2PS1



WARRANTY


Warranty notes	See written warranty for full details
Labor warranty	Limited 1-year entire appliance
Parts warranty	Limited 1-year entire appliance
Parts warranty	Limited 5-year sealed refrigerating system

DIMENSIONS



Overall Dimensions	Height (in.) A	34 1/8
	Width (in.) B	23 3/4
	Depth (in.) C	26
	Case Depth Without Door (in.) D	21 3/4
	Depth Without Handle (in.) E	23 3/8


ADDITIONAL ACCESSORIES



CXQW1H1PPBZ
Brushed Bronze
(Standard on Matte White)




CXQW1H1PPSS
Brushed Stainless
(Standard on Matte Black and Stainless Steel)




CXQW1H1PPBT
Brushed Black



CXQW1H1PPCU
Brushed Copper



CXQW1H1PPFB
Flat Black



CXQW1H1PPCG
Brushed Brass

BX212 - INSERT RANGE HOOD

The BX212 features a convenient underside three-speed control. It remains hidden at eye level, enabling seamless cabinet arrangement. Effective mesh filters purify the air, accompanied by bright halogen bulbs for ample illumination.

Green Features



3 Speed Push
Button Control
22" only



Long- lasting
LED lights



3 Speed Slide
Control Panel
28" & 34" only



Grease Cup



28"/34"
(34" includes 3 filters)



22"

Features


- Insert range hood
- 6" round duct adapter
- Non- stick Aluminium fan blades
- 3-speed push button control
- 3 speed slide control for 28" and 34"
- Quick-release Aluminium Mesh/ Stainless Steel Baffle filters
- 2 halogen light bulbs (2 x 25W E26)
- Plug-in connection

Specifications


- Air Flow Volume: 300 CFM
- Electrical Connection: 120 V/60 Hz
- Power Consumption: 300 Watts
- Current: 2.5 Amps
- Fan Speed: 1350 RPM
- Fan Type: Centrifugal Blower
- Finishes: Stainless Steel
- Ducting: 6" Round
- Noise Level: Min. 2 Sones Max. 4 Sones

Options

- Filters: Aluminium Mesh Filters
- Widths: 30", 36"
- Finish: Stainless Steel



ISOMETRIC



TOP

Model	Colour	Ducting	Filters	Size	CFM	Fits Cabinet
BX21222	Stainless Steel	6"	Mesh	22"	300	24"
BX21228	Stainless Steel	6"	Mesh	28"	300	30"
BX21234	Stainless Steel	6"	Mesh	34"	300	36"