

27" (68.6 cm) and 30" (76.2 cm) Electric Built-In Microwave/Oven Combination

KitchenAid®

PRODUCT MODEL NUMBERS

KEMS309E	KOCE500E	KOCE507E
ELECTRICAL CONNECTION		

If codes permit and a separate ground wire is used, it is recommended that a qualified electrical installer determine that the ground path and the wire gauge are in accordance with local codes.


Check with a qualified electrical installer if you are not sure the oven is properly grounded.

This oven must be connected to a grounded metal, permanent wiring system.

Be sure that the electrical connection and wire size are adequate and in conformance with the National Electrical Code, ANSI/NFPA 70-latest edition or CSA Standards C22.1-94, Canadian Electrical Code, Part 1 and C22.2 No. O-M91-latest edition, and all local codes and ordinances.

To properly install your oven, you must determine the type of electrical connection you will be using and follow the instructions provided for it here.

- Oven must be connected to the proper electrical voltage and frequency as specified on the model/serial/rating plate. See the following illustration.



A. Model/serial/rating plate

- Models rated from 7.3 to 9.6 kW at 240 volts (5.4 to 7.4 kW at 208 volts) require a separate 40-amp circuit. Models rated at 4.8 kW and below at 240 volts (3.6 kW and below at 208 volts) require a separate 30-amp circuit.
- A circuit breaker is recommended.
- Connect directly to the fused disconnect (or circuit breaker box) through flexible, armored or nonmetallic sheathed, copper cable (with grounding wire). See "Make Electrical Connection" section.
- Flexible conduit from the oven should be connected directly to the junction box.
- Do not cut the conduit. The length of conduit provided is for serviceability of the oven.
- A UL listed or CSA approved conduit connector must be provided.
- If the house has aluminum wiring, follow the procedure below:
  - Connect a section of solid copper wire to the pigtail leads.
  - Connect the aluminum wiring to the added section of copper wire using special connectors and/or tools designed and UL listed for joining copper to aluminum.

Follow the electrical connector manufacturer's recommended procedure. Aluminum/copper connection must conform with local codes and industry accepted wiring practices.

For power requirements, refer to the following table.

Model	Voltage	Amperage (L1)*	Amperage (L2)*	Rating (W)
KOCE507E/KOCE500E	120/240	32	30	8000
KOCE507E/KOCE500E	120/208	30	28	6600

\*Amperage values noted above are for information purposes only: the units are rated in watts.

PRODUCT DIMENSIONS

27" (68.6 cm) models

A. 42 9/16" (108.0 cm) overall height  
B. 25 1/8" (64.6 cm) recessed width  
C. 41" (104.1 cm) recessed height  
D. 23 1/4" (59.1 cm) max. recessed depth  
E. 27" (68.6 cm) overall width  
F. 48" (121.9 cm) flexible conduit length measured from the conduit clamp located at the rear of the oven. Do not remove the conduit clamp.

30" (76.2 cm) models  
A. 42 9/16" (108.0 cm) overall height  
B. 28 7/16" (72.3 cm) recessed width  
C. 41" (104.1 cm) recessed height  
D. 23 1/4" (59.1 cm) max. recessed depth  
E. 30" (76.2 cm) overall width  
F. 48" (121.9 cm) flexible conduit length measured from the conduit clamp located at the rear of the oven. Do not remove the conduit clamp.

Cabinet Dimensions

27" (68.6 cm) models  
A. 27" (68.6 cm) min. cabinet width  
B. 1" (2.5 cm) top of cutout to bottom of upper cabinet door  
C. 19 1/4" (48.9 cm) bottom of cutout to floor is recommended. 4"-19 1/4" (10.2-48.9 cm) bottom of cutout to floor is acceptable.  
D. 25 1/2" (64.8 cm) cutout width  
E. 1 1/8" (3.8 cm) min. bottom of cutout to top of cabinet door  
F. 41 1/16" (105 cm)\* recommended cutout height  
G. 24" (60.7 cm) cutout depth

30" (76.2 cm) models  
A. 30" (76.2 cm) min. cabinet width  
B. 1" (2.5 cm) top of cutout to bottom  
C. 19 1/4" (48.9 cm) bottom of cutout to floor is recommended. 4"-19 1/4" (10.2-48.9 cm) bottom of cutout to floor is acceptable.  
D. 28 1/2" (72.4 cm) cutout width  
E. 1 1/8" (3.8 cm) min. bottom of cutout  
F. 41 1/16" (105 cm)\* recommended cutout  
G. 24" (60.7 cm) cutout depth

\* NOTE: The cabinet height can be between 41" (104.1 cm) and 41 1/2" (105.6 cm) for microwave/oven combination.

Lot 90  
Aug 30, 2022

My Warehouse

Brampton

Open until 8:30 PM

Delivery Location

L5B 3Y1

Lists / Reorder

Home / Appliances / Refrigerators



+3



KitchenAid 36 in 26.8 cu ft. Stainless Steel French Door Refrigerator with Exterior Ice and Water Dispenser

Item 6660713 | Model KRFF507HPS

★★★★☆ 4.4 (2146) Write a review

Price \$3,949.99

Appliance Basic Installation & Haul Away Included

- Features:
- Through-the-door Ice and Water Dispenser
  - ExtendFresh™ Temperature Management System
  - Star-K certified
  - Metallic accents on shelf trim

Share Print

Delivery

Approximate Appointment Date  
Tuesday, November 29  
Delivery Postal Code: L5B 3Y1  
Change

Your delivery date is not secured until you complete your order. Dates may change based on delivery address, availability and if multiple items are shipped.

-

1

+

Add to Cart

Same-Day Delivery

This item is currently not available for Same-Day Delivery.

Add to List

Compare Product

Reviews

Product Details

Specifications

Warranty & Services

Shipping & Returns

Product Details

This 759 L (26.8 cu. ft.) French door refrigerator helps fresh produce stay that way with the ExtendFresh™ Temperature Management System. A pull-out tray accommodates large platters with ease, while a FRESH CHILL™ temperature-controlled full-width pantry lets you optimize temperature and airflow for the specific food you're storing. The refined interior design features LED lighting, and metallic accents add a touch of elegance.

**Through-the-door Ice and Water Dispenser**  
Provides quick and easy access to chilled water and ice.

**ExtendFresh™ Temperature Management System**  
Separately monitors the temperatures in the refrigerator and freezer through a sensor located in each, to help ensure fresh fruit juices don't become frozen and prawns avoid freezer burn.

- Features:
- PrintShield™ finish
  - Pull-out tray
  - FRESH CHILL™ temperature-controlled full-width pantry
  - In-Door-Ice® system
  - 2-tier freezer drawer with storage dividers
  - Metallic accents on shelf trim
  - SatinGlide® crispers and pantry
  - Humidity-controlled crispers
  - Measured water fill
  - Star-K certified
  - Slide-away split shelf
  - LED lighting
  - Light-touch controls
  - Max cool



Lot 90  
Aug 30, 2022

My Warehouse  
Brampton  
Open until 8:30 PM

Delivery Location  
LSB 3Y1

Lists / Reorder

Home / Appliances / Stoves, Cooktops & Range Hoods / Ranges



KitchenAid 30in 5.8 cu ft.Stainless Steel Gas Slide-In 5 Burner Convection Range

Item 6660724 | Model KSGG700ESS  
★★★★☆ 4.5 (1267) Write a review

Price \$2,799.99

In Home Delivery & Haul Away Included ⓘ

BUNDLE OFFER AVAILABLE

- Features:
- Even-Heat™ True Convection
  - 164 L (5.8 cu. ft.) oven capacity
  - Aqualift®

Share Print

Delivery

Approximate Appointment  
Date Tuesday, August 30  
Delivery Postal Code: LSB 3Y1 Change

Your delivery date is not secured until you complete your order. Dates may change based on delivery address, availability and if multiple items are shipped.

–

1

+

Add to Cart

Feedback

Same-Day Delivery

This item is currently not available for Same-Day Delivery.

Add to List

Compare Product

Product Details

Specifications

Warranty & Services

Shipping & Returns

Reviews

Product Details

BUNDLE OFFER:

Purchase multiple participating major appliances on the same order and receive additional savings.

- Purchase 2, save \$50
- Purchase 3, save \$150
- Purchase 4, save \$300
- Purchase 5, save \$400

Valid for orders placed 07/28/22 to 09/15/22.

Members also bought



GAS

\$1,649.99  
BUNDLE OFFER AVAILABLE  
Whirlpool 30in 5.8 cu ft. Stainless Steel Gas Freestanding Range with Frozen Bake Technology  
★★★★☆ (225)

Electrical connections must be made and fuel systems installed by qualified and licensed personnel. Improper installations present hazards, which can result in personal injury or property damage. Please contact a licensed residential electrician and your local natural gas or propane supplier for these services.

This beautiful gas range produces flawless cooking results thanks to Even-Heat™ True Convection; the unique bow-tie design and convection fan ensure the inside of the entire oven is heated to, and stays at, the perfect temperature. This range also features a steam rack that offers the ability to add additional moisture to the inside of the oven, enhancing cooking results. The oven is 164 L (5.8 cu. ft.), providing a large cooking capacity that's perfect for preparing multiple dishes at once.

Even-Heat™ True Convection

Produces flawless results. The unique bow-tie design and convection fan ensure the inside of the entire oven is heated to, and stays at, the perfect temperature.

Steam Rack

Offers the ability to provide additional moisture to the inside of the oven, enhancing cooking results.